Django Custom Models & Views Reference

Automated Architecture & Schema Export

1. Custom Models

crm.Customer

Primary entity for client accounts, billing metadata, and lifecycle status.

Field	Type	Constraints	Description / Help Text
id	BigAutoField	null=False, blank=False	Primary key identifier
name	CharField	null=False, blank=False	Legal company or individual name (max_length=150)
email	EmailField	null=False, blank=False	Unique primary contact email address
tier	CharField	null=False, blank=False	Subscription tier (choices: FREE, PRO, ENTERPRISE)
created_at	DateTimeField	null=False, blank=False	Auto-set timestamp on creation

• ***get_masked_email()****: Returns partially obfuscated email string for team displays.*

• ***is_enterprise_eligible()****: Evaluates contract revenue thresholds.*

orders.Invoice

Financial ledger record linked to customer transactions and payment status.

Field	Type	Constraints	Description / Help Text
id	BigAutoField	null=False, blank=False	Primary key identifier
customer	ForeignKey	null=False, blank=False	Relation to crm.Customer (on_delete=CASCADE)
amount_cents	IntegerField	null=False, blank=False	Total charge amount stored in minor units
status	CharField	null=False, blank=False	Invoice state (PENDING, PAID, VOID)
due_date	DateField	null=True, blank=True	Optional payment deadline

• ***total_dollars()****: Converts amount_cents to floating dollar representation.*

2. Custom Views

CustomerListView *(crm.views)*

Paginated staff dashboard listing active customers with tier badges.

Methods: *GET* | ***Template:*** *crm/customer_list.html* | ***Context:*** *object_list (QuerySet[Customer]), is_paginated (bool)*

InvoiceCreateView *(orders.views)*

Form-backed creation endpoint for manual billing generation by staff.

Methods: *GET, POST* | ***Template:*** *orders/invoice_form.html* | ***Context:*** *form (InvoiceForm)*

export_customer_csv *(crm.views)*

Function-based streaming response for exporting filtered customer records to CSV.

Methods: *GET (Function)* | ***Template:*** *None (HttpResponse)* | ***Context:*** *N/A*