KENWOOD

NEXEDGE®

NX-5200/5300/5400

NXDN™ DMR P25

NEXEDGE VHF/UHF/700-800 MHz
MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS

Gen2 Bluetooth® microSD HC GPS FleetSync® by KENWOOD 5-tone

Full Keypad Model

Limited Keypad Model

FEATURE HIGHLIGHTS

- **Multi-Digital** operation in NXDN, DMR and P25 (Phases 1 & 2) protocols
- **Any combination of two digital protocols** can be selected from NXDN, DMR, and P25
- **Mixed Digital & FM Analog Operation** allows intelligent migration in mixed sites and easy migration with digital radios in other sites
- **Large, Color 1.74" (240 x 180 pixels) Transflective TFT Display** for better interface even in direct sunlight and with use of polarized sunglasses.
- **Easy to follow GUI** for at-a-glance operational status checking and **Multi-line Text** to convey more information
- **4-way Directional-pad (D-pad) and 2-Position Lever Switch** for intuitive control and operation
- **Built-In GPS Receiver/Antenna** for effective fleet management
- **Bluetooth® Module built-in** for hands-free operation
- Renowned KENWOOD Audio Quality can be achieved with **Active Noise Reduction (ANR)** that utilizes built-in DSP with two microphones for suppression of ambient noise
- **Built-in 56-bit DES Encryption**
- Optional **256-bit AES Encryption**
- **Built-in Motion Sensor** for life-critical man down detection
- **microSD/microSDHC Memory Card Slot** for increased memory capacity for "Voice & Data"
- **IP67/68** and **MIL-STD-810 C/D/E/F/G**

GENERAL FEATURES

- 6 W (136-174 MHz) Model
- 5 W (380-470, 450-520 MHz) Models
- 3 W (700/800 MHz) Models
- Full Key Models (w/ numeric keypad) and Standard Key Models (w/o numeric keypad)
- Maximum of 4,000 CH/Radio capacity, 512 CH/Zone, 128 Zones
- AMBE+2™ Enhanced Vocoder
- 1 W Loud Speaker Audio

DIGITAL – NXDN MODE

- Gen2 & NXDN Type-C Trunked Operation
- NXDN Conventional Operation
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging
- Remote Stun/Kill
- Remote Check
- Short & Long Data Messages
- NXDN Digital Scrambler

DIGITAL – DMR MODE

- Complies with ETSI DMR Tier II standards
- Two-slot TDMA in 12.5kHz channels
- Call Interruption
- Dual-slot Direct Mode
- Energy Efficient

DIGITAL – P25 MODE

- P25 Phase 1 Conventional/Trunked Operation
- P25 Phase 2 Trunked Operation
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor/Remote Check
- Radio Inhibit
- Encryption Key Zeroize & Retention
- P25 Over-the-Air Re-keying
- P25 Over-the-Air Programming

ANALOG – FM MODE

- Conventional & LTR Zones
- FleetSync®/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, 2-Tone & 5-Tone
- Built-in Voice Inversion Scrambler

INTELLIGENT BATTERY SYSTEM

- System consists of a Li-ion or Ni-MH rechargeable battery (KNB-L1/L2/L3/N4), Rapid Charger (KSC-Y32), and Battery Reader (KAS-12/12PRO) software
- Up to 60 Rapid Chargers can be chain-connected to a PC
- KAS-12 Battery Reader software can display and manage information
- Up to 5,000 batteries can be managed at a time with the addition of optional KAS-12PRO license upgrade

OPTIONAL ACCESSORIES

- **KNB-L1** Li-ion BATTERY PACK, IP67/68 (7.4 V/2000 mAh)

- **KNB-L2** Li-ion BATTERY PACK, IP67/68 (7.4 V/2600 mAh)

- **KNB-L3** Li-ion BATTERY PACK, IP67/68 (7.4 V/3400 mAh)

- **KNB-N4** Ni-MH BATTERY PACK, IP67/68 (7.2 V/2500 mAh)

- **KSC-Y32** RAPID CHARGER

- **KSC-32/32S** RAPID CHARGER

- **KSC-326/326S** MULTIPLE CHARGER (6-unit Rapid Rate)

- **KBP-8** BATTERY CASE (12AA Alkaline Battery)

Intrinsically Safe Batteries are also available.

- **KRA-22** VHF HELICAL ANTENNA (Low Profile)

- **KRA-23** UHF HELICAL ANTENNA (Low Profile)

- **KRA-26** VHF HELICAL ANTENNA (Standard Length)

- **KRA-27** UHF WHIP ANTENNA (Standard Length)

- **KRA-41** VHF STUBBY ANTENNA

- **KRA-42** UHF STUBBY ANTENNA

- **KMC-54WD** SPEAKER MICROPHONE
  - 2-mic digital noise cancelling via the radio's DSP
  - 3.5mm-diameter earphone jack
  - Complies with MIL-STD 810C/D/E/F/G
  - IP65/67 Dust & Water*

*The earphone jack cap must be closed tightly

- **KMC-42WD** SPEAKER MICROPHONE (IP67)

- **KWD-AE31** SECURE CRYPTOGRAPHIC MODULE
- **KBH-11** BELT CLIP

- **KPG-180AP** OTAP MANAGER
- **KAS-12/12PRO** BATTERY READER (PC Software)

All accessories and options may not be available in all markets.
Contact an authorized KENWOOD dealer for details and complete list of all accessories and options.

SPECIFICATIONS

GENERAL		Portable Radios NX-5200	NX-5300	NX-5400
Frequency Range		136-174 MHz	Type 1: 450-520 MHz Type 2: 380-470 MHz	RX: 763-776, 851-870 MHz TX: 763-776, 793-806, 806-825, 851-870 MHz
Max. Channels Per Radio		1024 (Up to 4000 channels with option)		
Number of Zones		128		
Max. Channels Per Zone		512		
Channel Spacing	Analog	12.5/15/20/25/30 kHz	12.5/25 kHz	12.5/25 kHz
	Digital	6.25/12.5 kHz	6.25/12.5 kHz	12.5 kHz (6.25 kHz)
Power Supply		7.5 V DC ±20 %		
Battery Life (5-5-90/10-10-80 duty cycle)	KNB-L1 (2,000 mAh)	10 hours / 6.5 hours		
	KNB-L2 (2,600 mAh)	12.5 hours / 8.5 hours		
	KNB-L3 (3,400 mAh)	17 hours / 11 hours		
	KNB-N4 (2,500 mAh)	12 hours / 8.5 hours		
	KBP-8 (w/ AA x12)	High Power: 11 hours / 8 hours Low Power: 26 hours / 18.5 hours		
Operating Temperature		-30 °C to +60 °C		
Frequency Stability		±2.0 ppm	±1.0 ppm	±1.5 ppm
Dimensions (W x H x D) Radio w/ Battery, Projections Not Included	KNB-L1 (2,000 mAh)	58.0 x 138.9 x 36.5 mm		
	KNB-L2 (2,600 mAh)	58.0 x 138.9 x 39.5 mm		
	KNB-L3 (3,400 mAh)	58.0 x 138.9 x 44.9 mm		
	KNB-N4 (2,500 mAh)	58.0 x 166.4 x 45.2 mm		
	KBP-8 (w/ AA x 12)	67.0 x 218.3 x 53.9 mm		
Weight	KNB-L1 (2,000 mAh)	382 g		
	KNB-L2 (2,600 mAh)	406 g		
	KNB-L3 (3,400 mAh)	449 g		
	KNB-N4 (2,500 mAh)	579 g		
	KBP-8 (w/ AA x 12)	712 g		

RECEIVER		Portable Radios NX-5200	NX-5300	NX-5400
Sensitivity	NXDN 6.25 kHz Digital (3 % BER)	0.20 µV		
	NXDN 12.5 kHz Digital (3 % BER)	0.25 µV		
	DMR Digital (5 % BER)	0.25 µV		
	DMR Digital (1 % BER)	0.40 µV		
	P25 Digital (5 % BER)	0.25 µV		
	P25 Digital (1 % BER)	0.40 µV		
	Analog (12 dB SINAD)	0.25 µV		
Selectivity	Analog @ 12.5 kHz	67 dB		64 dB
	Analog @ 25 kHz	73 dB		
Intermodulation		73 dB	75 dB	
Spurious Rejection		80 dB	75 dB	
Audio Distortion		3 %		
Audio Output Power		500 mW/8 Ω (3 % Distortion)/1,000 mW/8 Ω (5 % Distortion)		
TRANSMITTER		**NX-5200**	**NX-5300**	**NX-5400**
RF Power Output Power		6 to 1 W	5 to 1 W	3 to 1 W
Spurious Emission		-70 dB		
FM Hum & Noise	Analog @ 12.5 kHz	40 dB		
	Analog @ 25 kHz	45 dB		
Audio Distortion		2 %		
Emission Designator		16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXE, 7K60FXD, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D		16K0F3E, 14K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXE, 7K60FXD, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D

Specifications are measured according to applicable standards, and subject to change without notice, due to advancements in technology.

APPLICABLE MIL-STD & IP

MIL Standard	810C Methods/ Procedures	810D Methods/ Procedures	810E Methods/ Procedures	810F Methods/ Procedures	810G Methods/ Procedures
Low Pressure	500.1/ I	500.2/ I, II	500.3/ I, II	500.4/ I, II	500.5/ I, II
High Temperature	501.1/ I, II	501.2/ I, II	501.3/ I, II	501.4/ I, II	501.5/ I, II
Low Temperature	502.1/ I	502.2/ I, II	502.3/ I, II	502.4/ I, II	502.5/ I, II
Temp. Shock	503.1/ I	503.2/ I	503.3/ I	503.4/ I, II	503.5/ I
Solar Radiation	505.1/ I	505.2/ I	505.3/ I	505.4/ I	505.5/ I
Rain	506.1/ I, II	506.2/ I, II	506.3/ I, II	506.4/ I, III	506.5/ I, III
Humidity	507.1/ I, II	507.2/ II, III	507.3/ II, III	507.4	507.5/ II
Salt Fog	509.1/ I	509.2/ I	509.3/ I	509.4	509.5
Dust	510.1/ I	510.2/ I	510.3/ I	510.4/ I, III	510.5/ I
Vibration	514.2/ VIII, X	514.3/ I	514.4/ I	514.5/ I	514.6/ I
Shock	516.2/ I, II, V	516.3/ I, IV	516.4/ I, IV	516.5/ I, IV	516.6/ I, IV
Immersion	—	—	—	512.4/I	512.5/I
International Protection Standard					
Dust & Water	IP54, IP55				
Immersion	IP67, IP68*				

*Conditions: Portable radio immersed for 2 hours at a depth of 1 meter

JVCKENWOOD Singapore Pte. Ltd.
1 Ang Mo Kio Street 63 Singapore 569110
comsales@sg.jvckenwood.com
www.kenwood.com/sg
http://comms.kenwood.com

JQA-1205 091
ISO9001 Registered
Communications Systems Business Unit
JVCKENWOOD Corporation

CL854M-E-2R