

✔ Congratulations! You passed!

Grade
received 100%

Latest Submission
Grade 100%

To pass 80% or
higher

[Go to next item](#)

1. What is a windowed dataset?

1 / 1 point

- ☐ The time series aligned to a fixed shape
- ☐ A consistent set of subsets of a time series
- ☐ There's no such thing
- ☒ A fixed-size subset of a time series

✔ Correct

2. What does 'drop_remainder=True' do?

1 / 1 point

- ☐ It ensures that all data is used
- ☐ It ensures that all rows in the data window are the same length by adding data
- ☒ It ensures that all rows in the data window are the same length by cropping data
- ☐ It ensures that the data is all the same shape

✔ Correct

3. What's the correct line of code to split an n column window into n-1 columns for features and 1 column for a label

1 / 1 point

- ☐ `dataset = dataset.map(lambda window: (window[n-1], window[1]))`
- ☒ `dataset = dataset.map(lambda window: (window[:-1], window[-1]))`
- ☐ `dataset = dataset.map(lambda window: (window[-1:], window[:-1]))`
- ☐ `dataset = dataset.map(lambda window: (window[n], window[1]))`

✔ Correct

4. What does MSE stand for?

1 / 1 point

- ☐ Mean Series error
- ☐ Mean Slight error
- ☐ Mean Second error
- ☒ Mean Squared error

✓ Correct

5. What does MAE stand for?

1 / 1 point

- ☐ Mean Average Error
- ☐ Mean Advanced Error
- ☒ Mean Absolute Error
- ☐ Mean Active Error

✓ Correct

6. If time values are in `time[]`, series values are in `series[]` and we want to split the series into training and validation at time `split_time`, what is the correct code?

1 / 1 point

- ☐

```
time_train = time[:split_time]
x_train = series[:split_time]
time_valid = time[split_time]
x_valid = series[split_time]
```
- ☐

```
time_train = time[split_time]
x_train = series[split_time]
time_valid = time[split_time:]
x_valid = series[split_time:]
```

☒ `time_train = time[:split_time]`
`x_train = series[:split_time]`
`time_valid = time[split_time:]`
`x_valid = series[split_time:]`

☐ `time_train = time[split_time]`
`x_train = series[split_time]`
`time_valid = time[split_time]`
`x_valid = series[split_time]`

 Correct

7. If you want to inspect the learned parameters in a layer after training, what's a good technique to use?

1 / 1 point

- ☒ Assign a variable to the layer and add it to the model using that variable. Inspect its properties after training.
- ☐ Run the model with unit data and inspect the output for that layer.
- ☐ Iterate through the layers dataset of the model to find the layer you want.
- ☐ Decompile the model and inspect the parameter set for that layer.

 Correct

8. How do you set the learning rate of the SGD optimizer?

1 / 1 point

- ☐ Use the `RateOfLearning` property
- ☒ Use the `learning_rate` property
- ☐ You can't set it
- ☐ Use the `Rate` property

 Correct

9. If you want to amend the learning rate of the optimizer on the fly, after each epoch. What do you do?

1 / 1 point

- ☐ Use a LearningRateScheduler and pass it as a parameter to a callback
- ☐ Callback to a custom function and change the SGD property
- ☒ Use a LearningRateScheduler object in the callbacks namespace and assign that to the callback
- ☐ You can't set it

✓ Correct