

A Methodology to Define QoS and SLA Requirements in Service Choreographies

Authors

Victoriano Alfonso Phocco Diaz
Daniel Macedo Batista

Department of Computer Science
University of Sao Paulo
`alfonso7@ime.usp.br`, `batista@ime.usp.br`

September 17, 2012

Agenda

- 1 Introduction
- 2 Problem
- 3 Methodology
- 4 Performance Evaluation
- 5 Conclusions and Future Works

- 1 Introduction
- 2 Problem
- 3 Methodology
- 4 Performance Evaluation
- 5 Conclusions and Future Works

SOC (Service Oriented Computing)

It is a new computing paradigm that utilizes services as the basic constructs to support the development of rapid, low-cost and easy composition of distributed applications even in heterogeneous environments. [Papazoglou et al., 2006].

Key elements:

- **Services** (mainly Web services).

SOC (Service Oriented Computing)

It is a new computing paradigm that utilizes services as the basic constructs to support the development of rapid, low-cost and easy composition of distributed applications even in heterogeneous environments. [Papazoglou et al., 2006].

Key elements:

- Services (mainly Web services).
- SOA .

SOC (Service Oriented Computing)

It is a new computing paradigm that utilizes services as the basic constructs to support the development of rapid, low-cost and easy composition of distributed applications even in heterogeneous environments. [Papazoglou et al., 2006].

Key elements:

- Services (mainly Web services).
- SOA .
- Service Composition .

SOC (Service Oriented Computing)

It is a new computing paradigm that utilizes services as the basic constructs to support the development of rapid, low-cost and easy composition of distributed applications even in heterogeneous environments. [Papazoglou et al., 2006].

Key elements:

- **Services** (mainly Web services).
- **SOA**.
- **Service Composition**.
 - ▶ **Service Orchestration**.

SOC (Service Oriented Computing)

It is a new computing paradigm that utilizes services as the basic constructs to support the development of rapid, low-cost and easy composition of distributed applications even in heterogeneous environments. [Papazoglou et al., 2006].

Key elements:

- **Services** (mainly Web services).
- **SOA**.
- **Service Composition**.
 - ▶ **Service Orchestration**.
 - ▶ **Service Choreography**.

SOC (Service Oriented Computing)

It is a new computing paradigm that utilizes services as the basic constructs to support the development of rapid, low-cost and easy composition of distributed applications even in heterogeneous environments. [Papazoglou et al., 2006].

Key elements:

- **Services** (mainly Web services).
- **SOA**.
- **Service Composition**.
 - ▶ **Service Orchestration**.
 - ▶ **Service Choreography**.
- ...

Service Orchestration




Figure: Service Orchestration

Service Choreography

- Allows service composition in a **collaborative** manner.
- Describes the **P2P interactions** of the externally **observable behavior of its participants**.
- Don't have a single point of control or coordination.




Figure: Service Choreography

Service Choreography




Figure: Service Choreography

- A Choreography is a type of process.
 - ▶ Differs in purpose and behavior from a standard BPMN Process (Process Orchestration).
 - ▶ Formalizes the way business **Participants** **coordinate** their **interactions**.

- A Choreography is a type of process.
 - ▶ Differs in purpose and behavior from a standard BPMN Process (Process Orchestration).
 - ▶ Formalizes the way business **Participants** **coordinate** their **interactions**.
- Focus on the exchange of information (**Messages**) between these Participants.

- A Choreography is a type of process.
 - ▶ Differs in purpose and behavior from a standard BPMN Process (Process Orchestration).
 - ▶ Formalizes the way business **Participants** **coordinate** their **interactions**.
- Focus on the exchange of information (**Messages**) between these Participants.
- Two approaches:


- A Choreography is a type of process.
 - ▶ Differs in purpose and behavior from a standard BPMN Process (Process Orchestration).
 - ▶ Formalizes the way business **Participants** **coordinate** their **interactions**.
- Focus on the exchange of information (**Messages**) between these Participants.
- Two approaches:
 - ▶ **Interconnection Model**: With collaborations diagrams.

BPMN and Choreography

- A Choreography is a type of process.
 - ▶ Differs in purpose and behavior from a standard BPMN Process (Process Orchestration).
 - ▶ Formalizes the way business **Participants** **coordinate** their **interactions**.
- Focus on the exchange of information (**Messages**) between these Participants.
- Two approaches:
 - ▶ **Interconnection Model**: With collaborations diagrams.
 - ▶ **Interaction Model**: BPMN Choreographies. using special activities (*Choreography Activity*).

Interaction Model

- Interactions **globally captured**.
- Basic building block: **atomic interaction** between two parties.
- “Choreography” in BPMN 2.0.



BPMN Choreography




Figure: BPMN elements for modeling choreographies (BPMN 2.0).

- 1 Introduction
- 2 Problem
- 3 Methodology
- 4 Performance Evaluation
- 5 Conclusions and Future Works

Problem to Solve

- Planning of resources before/during development of choreography.

Problem to Solve

- Planning of resources before/during development of choreography.
- Little approaches don't evaluate choreographies:
 - ▶ focusing on **QoS** or
 - ▶ in earlier stages of development.

Problem to Solve

- Planning of resources before/during development of choreography.
- Little approaches don't evaluate choreographies:
 - ▶ focusing on **QoS** or
 - ▶ in earlier stages of development.
- To guarantee QoS about communications (network) is important.

Objectives

- To assess the **impact of QoS** attributes in a **choreography interaction model**.
- To propose a novel methodology to establish **requirements for QoS and SLA** in **early stages of development**.
- To plan the capacity of the network elements in choreographies.
- To convert a interaction model to a GSPN including a QoS model.

- 1 Introduction
- 2 Problem
- 3 Methodology**
- 4 Performance Evaluation
- 5 Conclusions and Future Works

- ① **Mapping** of a choreography to a GSPN.
 - ▶ The choreography is specified according “interaction model”.
 - ▶ The choreography is specified in BPMN 2.0.
 - ▶ The resulting GSPN include a QoS model.

- ① **Mapping** of a choreography to a GSPN.
 - ▶ The choreography is specified according “interaction model”.
 - ▶ The choreography is specified in BPMN 2.0.
 - ▶ The resulting GSPN include a QoS model.
- ② **Configurations** of the resulting GSPN.

- ① **Mapping** of a choreography to a GSPN.
 - ▶ The choreography is specified according “interaction model”.
 - ▶ The choreography is specified in BPMN 2.0.
 - ▶ The resulting GSPN include a QoS model.
- ② **Configurations** of the resulting GSPN.
- ③ **Simulations** of scenarios.

- Defining the QoS attributes involved in **service**, **network** and **message** aspects.
- QoS attributes:

- Defining the QoS attributes involved in **service**, **network** and **message** aspects.
- QoS attributes:
 - ▶ In service operation: **time to complete the service**.

- Defining the QoS attributes involved in **service**, **network** and **message** aspects.
- QoS attributes:
 - ▶ **In service operation**: **time to complete the service**.
 - ▶ **In network**: delay and **communication errors**.

- Defining the QoS attributes involved in **service**, **network** and **message** aspects.
- QoS attributes:
 - ▶ In service operation : **time to complete the service**.
 - ▶ In network : delay and **communication errors**.
 - ▶ In message : **message format**.

Mapping BPMN to GSPN (I)






Figure: Mapping of events and gateways elements to modules of Petri nets


Mapping BPMN to GSPN (II)



A) Interaction in BPMN 2

B) GSPN Mapping with QoS


Mapping BPMN to GSPN (II)




A) Interaction in BPMN 2

B) GSPN Mapping with QoS


Mapping BPMN to GSPN (II)



Mapping BPMN to GSPN (II)




Mapping BPMN to GSPN (II)



A) Interaction in BPMN 2

B) GSPN Mapping with QoS

Mapping BPMN to GSPN (II)



Mapping of choreography in BPMN 2.0 to GSPN with QoS model

Input: **Process Choreography** $PC = (\mathcal{O}, \mathcal{A}, \mathcal{E}, \mathcal{G}, \mathcal{T}, \{e^S\}, \mathcal{E}^I, \{e^E\}, \mathcal{E}^{I_M}, \mathcal{E}^{I_T}, \mathcal{G}^F, \mathcal{G}^J, \mathcal{G}^X, \mathcal{G}^M, \mathcal{G}^V, \mathcal{F})$ in BPMN 2.0.

Mapping Algorithm

Mapping of choreography in BPMN 2.0 to GSPN with QoS model

Input: Process Choreography $PC = (\mathcal{O}, \mathcal{A}, \mathcal{E}, \mathcal{G}, \mathcal{T}, \{e^S\}, \mathcal{E}^I, \{e^E\}, \mathcal{E}^{I_M}, \mathcal{E}^{I_T}, \mathcal{G}^F, \mathcal{G}^J, \mathcal{G}^X, \mathcal{G}^M, \mathcal{G}^V, \mathcal{F})$ in BPMN 2.0.

Output: Generalized Stochastic Petri Net $GSPN_{QoS}$.

Mapping Algorithm

Mapping of choreography in BPMN 2.0 to GSPN with QoS model

Input: Process Choreography $PC = (\mathcal{O}, \mathcal{A}, \mathcal{E}, \mathcal{G}, \mathcal{T}, \{e^S\}, \mathcal{E}^I, \{e^E\}, \mathcal{E}^M, \mathcal{E}^T, \mathcal{G}^F, \mathcal{G}^J, \mathcal{G}^X, \mathcal{G}^M, \mathcal{G}^V, \mathcal{F})$ in BPMN 2.0.

Output: Generalized Stochastic Petri Net $GSPN_{QoS}$.

$CT_i \in \mathcal{T}$, $G_j \in \mathcal{G}$ and $E_k \in \mathcal{E}$. where $i, j, k \in \mathbb{N}$.

$PNQoS(CT_i)$, $PNQoS(G_j)$, $PNQoS(E_k)$ are functions return a GSPN according to mapping rules.

\oplus as the operator composition that returns other GSPN.

$GSPN_{QoS} \leftarrow$ Empty Petri Net

For $CT_i \in \mathcal{T}$ **Do**

$GSPN_{QoS} \leftarrow GSPN_{QoS} \oplus PNQoS(CT_i)$

Add a arrival **timed Transition** at beginning of the $GSPN_{QoS}$.

End

For $G_j \in \mathcal{G}$ **Do**

$GSPN_{QoS} \leftarrow GSPN_{QoS} \oplus PN(G_j)$

End

For $E_k \in \mathcal{E}$ **Do**

$GSPN_{QoS} \leftarrow GSPN_{QoS} \oplus PN(E_k)$

End







Add a starting Place and **immediate Transition** at the beginning of the $GSPN_{QoS}$.

Add a ending Place and **immediate Transition** at the end of the $GSPN_{QoS}$.

Return $GSPN_{QoS}$







Mapping Algorithm (II)

1) Mapping rules

BPMN Element		GSPN module
Choreography Activity		
Events		
Gateways		

Mapping Algorithm (II)


1) Mapping rules

BPMN Element		GSPN module
Choreography Activity		
Events		
Gateways		


2) Composition



Composition Operator




3) Replacing and composing




Mapping Algorithm (II)

3) Replacing and composing



4) Reducing and adding final elements



- 1 Introduction
- 2 Problem
- 3 Methodology
- 4 Performance Evaluation**
- 5 Conclusions and Future Works

Scenario




Figure: Choreography example using BPMN2 elements.

Scenario

Participant A: Financial Advisor

Participant B: Customer




Figure: Choreography example using BPMN2 elements.




Figure: GSPN obtained from the choreography.


Configuration (I)

Table: Weights of Scenario 1 and Scenario 2

Transition	Weights	
	Scenario 1	Scenario 2
$T_{latency1}, T_{latency2}, T_{latency3}$	0.99	0.94
$T_{cerr1}, T_{cerr2}, T_{cerr3}$	0.01	0.06
$T_{receive}, T_{receive2}, T_{receive3}$	99	97
$T_{merr1}, T_{merr2}, T_{merr3}$	1	3
$T_{arrival2}, T_{arrival3}$	0.5	0.5


Configuration (II)

Scenario 1:  (best case)
Scenario 2:  (worst case)



Configuration (II)


Scenario 1:  (best case)
Scenario 2:  (worst case)



Configuration (II)

Scenario 1:  (best case)


Scenario 2:  (worst case)



Configuration (II)

Scenario 1: █ (best case)

Scenario 2: █ (worst case)



- 1 **token** = 1 **choreography instance**.

- 1 **token** = 1 **choreography instance**.
- 100 **tokens** are considered to each scenario at the **place Start**.
- 100 **concurrent instances** were executed (**multiple-server semantic**).

- 1 **token** = 1 **choreography instance**.
- 100 **tokens** are considered to each scenario at the **place Start**.
- 100 **concurrent instances** were executed (**multiple-server semantic**).
- The **Pipe2** tool was used to **model** and **simulate** the **GSPN**.

- 1 **token** = 1 **choreography instance**.
- 100 **tokens** are considered to each scenario at the **place Start**.
- 100 **concurrent instances** were executed (**multiple-server semantic**).
- The **Pipe2** tool was used to **model** and **simulate** the **GSPN**.
- 1500 fires and 10 replications.
- Confidence level of 95%.

Results (I)

Table: Simulation results

Place	Average number of tokens (%)		95% Confidence interval (+/- %)	
	Scenario 1	Scenario 2	Scenario 1	Scenario 2
<i>Start</i>	35.28	40.15	5.83	6.23
<i>End</i>	41.95	38.78	2.53	3.82
M_{err1}	0.39	0.91	0.95	1.92
M_{err2}	0.00	0.93	0.63	0.64
M_{err3}	0.00	0.66	0.87	0.74
C_{err1}	0.74	2.94	0.82	2.02
C_{err2}	0.00	0.00	0.67	1.75
C_{err3}	0.78	0.16	0.92	1.52
C_{i1}	8.32	8.90	5.33	7.48
C_{i2}	0.63	0.69	0.23	0.52
C_{i3}	0.75	8.90	0.39	0.21

Results (I)

Table: Simulation results

Place	Average number of tokens (%)		95% Confidence interval (+/- %)	
	Scenario 1	Scenario 2	Scenario 1	Scenario 2
<i>Start</i>	35.28	40.15	5.83	6.23
<i>End</i>	41.95	38.78	2.53	3.82
M_{err1}	0.39	0.91	0.95	1.92
M_{err2}	0.00	0.93	0.63	0.64
M_{err3}	0.00	0.66	0.87	0.74
C_{err1}	0.74	2.94	0.82	2.02
C_{err2}	0.00	0.00	0.67	1.75
C_{err3}	0.78	0.16	0.92	1.52
C_{i1}	8.32	8.90	5.33	7.48
C_{i2}	0.63	0.69	0.23	0.52
C_{i3}	0.75	8.90	0.39	0.21

Results (II)

- **Communication errors:** An average of $C_{err1} + C_{err2} + C_{err3}$ of instances **didn't finish the process**.
 - ▶ Scenario 1: 1.52% .
 - ▶ Scenario 2: 3.10% (more errors).

Results (II)

- **Communication errors:** An average of $C_{err1} + C_{err2} + C_{err3}$ of instances **didn't finish the process**.
 - ▶ Scenario 1: 1.52% .
 - ▶ Scenario 2: 3.10% (more errors).
- **Invalid format message:** An average of $M_{err1} + M_{err2} + M_{err3}$ of instances **didn't finish the process**.
 - ▶ Scenario 1: 0.39% .
 - ▶ Scenario 2: 2.50% (more invalid messages).

Results (II)

- **Communication errors:** An average of $C_{err1} + C_{err2} + C_{err3}$ of instances **didn't finish the process**.
 - ▶ Scenario 1: 1.52% .
 - ▶ Scenario 2: 3.10% (more errors).
- **Invalid format message:** An average of $M_{err1} + M_{err2} + M_{err3}$ of instances **didn't finish the process**.
 - ▶ Scenario 1: 0.39% .
 - ▶ Scenario 2: 2.50% (more invalid messages).
- **Bottleneck:** It was found a communication bottleneck in the first interaction (C_i place).
 - ▶ Scenario 1: 8.32% .
 - ▶ Scenario 2: 8.90% .

- 1 Introduction
- 2 Problem
- 3 Methodology
- 4 Performance Evaluation
- 5 Conclusions and Future Works

Conclusions

- We have proposed a Novel methodology to define QoS and SLA requirements in service Choreography.

Conclusions

- We have proposed a Novel methodology to define QoS and SLA requirements in service Choreography.
- It's a initial approach using the “interaction model” (supported by BPMN 2.0).

Conclusions

- We have proposed a Novel methodology to define QoS and SLA requirements in service Choreography.
- It's a initial approach using the “interaction model” (supported by BPMN 2.0).
- The GSPN is good to model and analyze several aspects involved into service choreography.

Conclusions

- We have proposed a Novel methodology to define QoS and SLA requirements in service Choreography.
- It's a initial approach using the “interaction model” (supported by BPMN 2.0).
- The GSPN is good to model and analyze several aspects involved into service choreography.
- The simulation is needed for supporting analysis of complex process (e.g. process choreography).

- We have proposed a Novel methodology to define QoS and SLA requirements in service Choreography.
- It's a initial approach using the “interaction model” (supported by BPMN 2.0).
- The GSPN is good to model and analyze several aspects involved into service choreography.
- The simulation is needed for supporting analysis of complex process (e.g. process choreography).
- The simulation results can be used to establish early QoS and SLA constraints.
 - ▶ Integration is expensive, then early detections are needed.
 - ▶ Establishing SLAs according to resources.
 - ▶ Planning in order to reduce failures.

- To extend the mapping to support more choreography BPMN elements.

- To extend the mapping to support more choreography BPMN elements.
- To expand our methodology to support generic probability distributions in the decision points. Use of Colored Petri Nets (CPNs) can be a alternative.

- To extend the mapping to support more choreography BPMN elements.
- To expand our methodology to support generic probability distributions in the decision points. Use of Colored Petri Nets (CPNs) can be a alternative.
- To make more analysis and to use complex scenarios, where correlation problems could happen.

- To extend the mapping to support more choreography BPMN elements.
- To expand our methodology to support generic probability distributions in the decision points. Use of Colored Petri Nets (CPNs) can be a alternative.
- To make more analysis and to use complex scenarios, where correlation problems could happen.
- To include more QoS attributes.



Baile Project
Enabling Scalable Cloud Service Choreographies

Thanks!