



roadmaster
menembus batas getarkan jiwa

PRODUCT CATALOGUE

SPEKIFICATION



Power source	: AC 100 - 240V ~ 50Hz & DC 13.5V, 3A
Power (No-signal)	: 14 W
Power consumption (Max)	: 70 W
Power output	: 70 W (RMS)
Speaker system	: 2-way speaker
Drivers - Woofer	: 15.2 cm (6"), 4 Ohm, 30 W
- Midrange	: 7.5 cm (3"), 4 Ohm 30 W
Frequency response	: 40 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : Volume, Treble, Bass, X-Bass, Mic Priority
Microphone control	: Rotary Knob: MIC VOLUME, Echo, Mic Priority
Inputs	: Guitar & 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	264 x 240 x 319.5 mm
Content on the box	1 set PA 61 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless 2 pc Handle Mic 1 pc Charger



SPEKIFICATION

Power source	: AC 100 - 240V ~ 50Hz & DC 13.5V, 3A
Power (No-signal)	: 14 W
Power consumption (Max)	: 70 W
Power output	: 70 W (RMS)
Speaker system	: 2-way speaker
Drivers - Woofer	: 20.3 cm (8"), 4 Ohm, 35 W
- Midrange	: 7.5 cm (3"), 4 Ohm 30 W
Frequency response	: 40 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : Volume, Treble, Bass, X-Bass, Mic Priority
Microphone control	: Rotary Knob: MIC VOLUME, Echo, Mic Priority
Inputs	: Guitar & 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 304 x 250 x 370 mm
Content on the box	1 set PA 81 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless 2 pc Handle Mic 1 pc Charger



SPEKIFICATION

Power source	: AC 100 - 240V ~ 50Hz & DC 13.5V, 3A
Power (No-signal)	: 14 W
Power consumption (Max)	: 70 W
Power output	: 70 W (RMS)
Speaker system	: 2-way speaker
Drivers - Woofer	: 25.4 cm (10"), 4 Ohm, 30 W
- Midrange	: 7.5 cm (3"), 4 Ohm 30 W
Frequency response	: 40 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : Volume, Treble, Bass, X-Bass, Mic Priority
Microphone control	: Rotary Knob: MIC VOLUME, Echo, Mic Priority
Inputs	: Guitar & 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 380 x 298 x 551 mm
Content on the box	1 set PA 101 Gen 2 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless 2 pc Handle Mic 1 pc Charger



SPEIFICATION

Power source	: AC 100 - 240V ~ 50Hz & DC 13.5V, 3A
Power (No-signal)	: 14 W
Power consumption (Max)	: 70 W
Power output	: 70 W (RMS)
Speaker system	: 2-way speaker
Drivers - Woofer	: 30.5 cm (12"), 4 Ohm, 30 W
- Midrange	: 7.5 cm (3"), 4 Ohm 30 W
Frequency response	: 40 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : Volume, Treble, Bass, X-Bass, Mic Priority
Microphone control	: Rotary Knob: MIC VOLUME, Echo, Mic Priority
Inputs	: Guitar & 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 380 x 298 x 611 mm
Content on the box	1 set PA 121 Gen 2 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless 2 pc Handle Mic 1 pc Charger



SPEIFICATION

Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 17 W
Power consumption (Max)	: 240 W
Power output	: 80 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 15.2 cm (6"), 4 Ohm, 50 W
- Midrange	: 7.6 cm (3"), 4 Ohm 30 W
- Piezo	: 2.5 cm (1"), 25 W
Frequency response	: 25 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: Sliding : Volume, Treble, Bass, X-Bass
Microphone control	: Sliding & Rotary : Mic Priority, Volume, Echo, Reverb
Inputs	: Guitar / Keyboard & 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type), HDMI, OPTICAL
Dimension (WxDxH)	: 280 x 290 x 700 mm
Content on the box	1 pc Bass BX 6020 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless 2 pc Handle Mic



SPEKIFICATION

Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 17 W
Power consumption (Max)	: 240 W
Power output	: 80 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 20.3 cm (8"), 4 Ohm, 50 W
- Midrange	: 7.6 cm (3"), 4 Ohm 30 W
- Piezo	: 2.5 cm (1"), 25 W
Frequency response	: 25 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: Sliding : Volume, Treble, Bass, X-Bass
Microphone control	: Sliding & Rotary : Mic Priority, Volume, Echo, Reverb
Inputs	: Guitar / Keyboard & 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type), HDMI, OPTICAL
Dimension (WxDxH)	: 310 x 300 x 800 mm
Content on the box	1 pc Bass BX 8020 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless 2 pc Handle Mic



SPEKIFICATION

Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 22 W
Power consumption (Max)	: 75 W
Power output	: 40 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 20.3 cm (8"), 4 Ohm, 80 W
- Midrange	: 7.6 cm (3"), 4 Ohm 30 W
- Piezo	: 2.5 cm (1"), 25 W
Frequency response	: 25 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : Volume, Treble, Bass, X-Bass
Microphone control	: ROTARY KNOB : MIC VOLUME, Echo
Inputs	: 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 330 x 330 x 760 mm
Content on the box	1 pc Party 8 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless



SPEKIFICATION

Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 22 W
Power consumption (Max)	: 75 W
Power output	: 40 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 25.4 cm (10"), 4 Ohm, 80 W
- Midrange	: 7.6 cm (3"), 4 Ohm 30 W
- Piezo	: 2.5 cm (1"), 25 W
Frequency response	: 25 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : Volume, Treble, Bass, X-Bass
Microphone control	: ROTARY KNOB : MIC VOLUME, Echo
Inputs	: 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 370 x 340 x 880 mm
Content on the box	1 pc Party 10 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless



PARTY FLASH 28

SPEKIFICATION

Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 22 W
Power consumption (Max)	: 75 W
Power output	: 40 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 20.3 cm (8"), 4 Ohm, 80 W
- Midrange	: 7.6 cm (3"), 4 Ohm 30 W
- Piezo	: 2.5 cm (1"), 25 W
Frequency response	: 25 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : Volume, Treble, Bass, X-Bass
Microphone control	: ROTARY KNOB : MIC VOLUME, Echo
Inputs	: 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 340 x 320 x 730 mm
Content on the box	1 pc Party Flash 28 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless



PARTY FLASH 10

SPEKIFICATION

Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 22 W
Power consumption (Max)	: 75 W
Power output	: 40 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 25.4 cm (10"), 4 Ohm, 80 W
- Midrange	: 7.6 cm (3"), 4 Ohm 30 W
- Piezo	: 2.5 cm (1"), 25 W
Frequency response	: 25 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : Volume, Treble, Bass, X-Bass
Microphone control	: ROTARY KNOB : MIC VOLUME, Echo
Inputs	: 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 360 x 340 x 880 mm
Content on the box	1 pc Party Flash 10 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless

BASS 16 GEN 2

SPEKIFICATION



Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 22 W
Power consumption (Max)	: 100 W
Power output	: 2 x 45 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 15.3 cm (6"), 6 Ohm, 60 W
- Midrange	: 7.5 cm (3"), 4 Ohm, 25 W
- Piezzo	: 2.5 cm (1"), 4 Ohm, 25 W
Frequency response	: 20 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : X-BASS, BASS, TREBLE, VOLUME
Microphone control	: ROTARY KNOB : MIC Volume, Echo
Inputs	: 2 x MIC Input (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 271.4 x 203.5 x 548 mm
Content on the box	1 set Bass 16 Reborn Gen2 1 pc Owners manual 1 pc Warranty card 1 pc Remote control

BASS 26 GEN 2

SPEKIFICATION



Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 22 W
Power consumption (Max)	: 135 W
Power output	: 2 x 45 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 15.3 cm (6"), 6 Ohm, 60 W
- Midrange	: 7.5 cm (3"), 4 Ohm, 25 W
- Piezzo	: 2.5 cm (1"), 4 Ohm, 25 W
Frequency response	: 20 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : X-BASS, BASS, TREBLE, VOLUME
Microphone control	: ROTARY KNOB : MIC Volume, Echo
Inputs	: 2 x MIC Input (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 276.4 x 247 x 744 mm
Content on the box	1 set Bass 26 Reborn Gen2 1 pc Owners manual 1 pc Warranty card 1 pc Remote control

BASS 28 GEN 2

SPEKIFICATION



Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 22 W
Power consumption (Max)	: 150 W
Power output	: 2 x 45 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 20.3 cm (8"), 6 Ohm, 60 W
- Midrange	: 7.5 cm (3"), 4 Ohm, 25 W
- Piezzo	: 2.5 cm (1"), 4 Ohm, 25 W
Frequency response	: 20 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: ROTARY KNOB : X-BASS, BASS, TREBLE, VOLUME
Microphone control	: ROTARY KNOB : MIC Volume, Echo
Inputs	: 2 x MIC Input (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 289.3 x 247 x 900 mm
Content on the box	1 set Bass 28 Reborn Gen2 1 pc Owners manual 1 pc Warranty card 1 pc Remote control

KD PRO 212 GEN 2

SPEKIFICATION



Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 22 W
Power consumption (Max)	: 280 W
Power output	: 2 x 150 W (RMS)
Speaker system	: 2-way speaker
Drivers - Woofer	: 2 x 30.5 cm (12"), 6 Ohm, 60 W
- Compression Driver	: 2.5 cm (1"), 4 Ohm, 25 W
Frequency response	: 20 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: MIXER : X-Bass, High, Mid, Low, Volume, Master, Music, Guitar & Keyboard
Microphone control	: MIXER : MIC VOLUME, Echo, Wireless Volume, Repeat, Delay
Inputs	: 2 x MIC, Keyboard & Guitar Input (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 406 x 426 x 984 mm
Content on the box	1 set KD Pro 212 Reborn Gen2 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless 2 pc Mic Wireless Battery 1 pc Mic Charger

KD PRO 215 GEN 2

SPEKIFICATION



Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 22 W
Power consumption (Max)	: 280 W
Power output	: 2 x 150 W (RMS)
Speaker system	: 2-way speaker
Drivers - Woofer	: 2 x 38.1 cm (15"), 6 Ohm, 60 W
- Compression Driver	: 2.5 cm (1"), 4 Ohm, 25 W
Frequency response	: 20 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: MIXER : X-Bass, High, Mid, Low, Volume, Master, Music, Guitar & Keyboard
Microphone control	: MIXER : MIC VOLUME, Echo, Wireless Volume, Repeat, Delay
Inputs	: 2 x MIC, Keyboard & Guitar Input (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type)
Dimension (WxDxH)	: 466 x 425 x 1078 mm
Content on the box	1 set KD Pro 215 Reborn Gen2 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless 2 pc Mic Wireless Battery 1 pc Mic Charger

MONSTER 210 GEN 2

SPECIFICATION



Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 14 W
Power consumption (Max)	: 220 W
Power output	: 2 x 50 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 25.4 cm (10"), 6 Ohm, 60 W
- Midrange	: 7.6 cm (3"), 4 Ohm, 30 W
- Piezzo	: 2.5 cm (1"), 25 W
Frequency response	: 20 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: Sliding : Volume, Treble, Bass, X-Bass
Microphone control	: Sliding & Rotary : Mic Priority, Volume, Echo, Reverb
Inputs	: Guitar / Keyboard & 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type), HDMI, OPTICAL
Dimension (WxDxH)	: 298 x 296 x 1052 mm
Content on the box	1 set Monster 210 Reborn Gen2 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless

MONSTER 212 GEN 2

SPECIFICATION



Power source	: AC 220 V - 50 Hz
Power (No-signal)	: 14 W
Power consumption (Max)	: 240 W
Power output	: 2 x 70 W (RMS)
Speaker system	: 3-way speaker
Drivers - Woofer	: 2 x 30 cm (12"), 6 Ohm, 60 W
- Midrange	: 7.6 cm (3"), 4 Ohm, 30 W
- Piezzo	: 2.5 cm (1"), 25 W
Frequency response	: 20 Hz - 20 KHz
Input impedance	: 50K Ohms
Controls	: Sliding : Volume, Treble, Bass, X-Bass
Microphone control	: Sliding & Rotary : Mic Priority, Volume, Echo, Reverb
Inputs	: Guitar / Keyboard & 2 x MIC inputs (6.35 mm)
Connectivity	- BLUETOOTH 5.3, Freq. Band : 2.4 GHz (2.4000 GHz - 2.4835 GHz) - TWS (True Wireless Stereo) *BT connection between 2 units - FM RADIO (Freq. Range : 87.50 MHz - 108.00 MHz) - USB (MP3 Playback) - SD/MMC (MP3 Playback) - LINE (RCA 2-pin L/R type), HDMI, OPTICAL
Dimension (WxDxH)	: 353 x 310 x 1115 mm
Content on the box	1 set Monster 212 Reborn Gen2 1 pc Owners manual 1 pc Warranty card 1 pc Remote control 2 pc Mic Wireless