






FEATURES

- Soft low damping rubber surround for improved transient response
- Geometrically reinforced aluminium cone for improved break-up control
- Shorting ring in motor system for reduced distortion
- Vented pole piece for reduced compression
- Vented cast aluminium chassis for optimum strength and low compression
- Shallow design
- Non-conducting fibre glass voice coil former for minimum damping
- CCAW voice coil for reduced moving mass
- Long life silver lead wires

Specs :

Nominal Impedance	8 Ω	Free air resonance, Fs	25 Hz
DC resistance, Re	5.7 Ω	Sensitivity (2.83 V / 1 m)	87.5 dB
Voice coil inductance, Le	0.37 mH	Mechanical Q-factor, Qms	5.54
Effective piston area, Sd	216 cm ²	Electrical Q-factor, Qes	0.43
Voice coil diameter	45.5 mm	Total Q-factor, Qts	0.40
Voice coil height	19 mm	Moving mass incl.air, Mms	31.2 g
Air gap height	6 mm	Force factor, Bl	7.9 Tm
Linear coil travel (p-p)	13 mm	Equivalent volume, Vas	93.4 liters
Magnetic flux density	0.9 T	Compliance, Cms	1.43 mm/N
Magnet weight	0.8 kg	Mechanical loss, Rms	0.8 kg/s
Net weight	2.7 kg	Rated power handling*	60 W

* IEC 268-5, T/S parameters measured on drive units that are broken in.



Response Curve :

— (Blue) : on axis

— (Green) : 30° off-axis

— (Red) : 60° off-axis

REV.1 (04.05.2026)