

BIANCO-15W200

15" - Woofer - 600W - 100dB

AUDIENCE

- Proprietary cone paper material with silk cotton tree and manila pulp
- 3" voice coil with APC (Advanced Polymer Coating)
- Minimum damping fiber glass voice coil former
- Vented pole piece for reduced compression
- Long life silver lead wires
- Weather-proof coated cone paper



Dimensions & Weight

Overall Diameter	385.5 mm (15.17 in)
Bolt Circle Diameter	369.5 mm (14.54 in)
Baffle Cutout Diameter	354 mm (13.93 in)
Mounting Depth	153.5 mm (6.04 in)
Flange and Gasket Thickness	8.85 mm (0.35 in)
Net Weight	7.24 Kg (15.96 lb)
Shipping Box	428 x 428 x 209 mm (16.8 x 16.8 x 8.22 in)
Gross Weight	9 Kg (19.84 lb)

Recone Kit

1P0000PSB013

NOTES :

- (1) AES standard, test mode with continuous pink noise signal (6 dB crest factor; 2 hours) within the Fo to 10Fo power calculated on rated nominal impedance. Loudspeaker in free air
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) $X_{max} = ((\text{Winding depth} - \text{magnetic gap depth})/2) + (\text{magnetic gap depth}/3)$
- (4) Maximum excursion (p-p) before permanent damage
- (5) T/S parameters measured on drive units that are broken in using Klippel LPM Measurement System.

Specs :

Nominal Impedance	8 Ohm
Minimum Impedance	5.2 Ohm
AES Power Handling (1)	300 W
Maximum Power Handling (2)	600 W
Sensitivity (1W/1m)	100 dB
Frequency Range	47 - 4700 Hz
Voice Coil Diameter	75.5 mm (3 in)
Winding Material	Copper clad aluminium
Former Material	Till
Winding Depth	20.4 mm
Magnetic Gap Depth	10 mm (0.39 in)
Flux Density	1.21 T
Magnet	Ferrite
Basket Material	Stamped steel
Demodulation	-
Cone Surround	Double half roll
NET Air Volume filled by driver	4.10 liters
Spider Profile	Constant height waves
Weather Resistant	Yes

Thiele Small Parameters

Fs	47 Hz
Re	5.2 Ohm
Qes	0.57
Qms	10.62
Qts	0.54
Vas	123.5 liters
Sd	907.9 cm ²
Xmax (3)	8.53 mm
Xdamage (4)	20 mm
Mms	107.1 g
Bl	17 Tm
Le	0.85 mH
Cms	0.11 mm/N
Rms	3 Kg/s
Eta Zero	2.2 %
EBP	82

