

BIANCO-18SW450

18" - Subwoofer - 900W - 99dB

AUDIENCE

- Proprietary cone paper material with silk cotton tree
- 3" voice coil with APC (Advanced Polymer Coating)
- Minimum damping fiber glass voice coil former
- Cast aluminium chassis
- Vented pole piece for reduced compression
- Weather-proof coated cone paper
- Triple roll surround allows long excursion



Dimensions & Weight

Overall Diameter	470 mm (18.5 in)
Bolt Circle Diameter	455 mm (17.9 in)
Baffle Cutout Diameter	426 mm (16.77 in)
Mounting Depth	189.5 mm (7.46 in)
Flange and Gasket Thickness	13.5 mm (0.6 in)
Net Weight	9.05 Kg (25.52 lb)
Shipping Box	504 x 504 x 248 mm (19.84 x 19.84 x 9.76 in)
Gross Weight	11.4 Kg (31.30 lb)

Recone Kit

1P000OPSB020

NOTES :

- (1) AES standard, test mode with continuous pink noise signal (6 dB crest factor; 2 hours) within the F_0 to $10F_0$ power calculated on rated nominal impedance. Loudspeaker in free air
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) $X_{max} = ((\text{Winding depth} - \text{magnetic gap depth})/2) + (\text{magnetic gap depth}/3)$
- (4) Maximum excursion (p-p) before permanent damage
- (5) T/S parameters measured on drive units that are broken in using Klippel LPM Measurement System.

Specs :

Nominal Impedance	8 Ohm
Minimum Impedance	5 Ohm
AES Power Handling (1)	450 W
Maximum Power Handling (2)	900 W
Sensitivity (1W/1m)	99 dB
Frequency Range	28 - 3000 Hz
Voice Coil Diameter	75.5 mm (3 in)
Winding Material	Copper
Former Material	Till
Winding Depth	25.2 mm
Magnetic Gap Depth	10 mm (0.39 in)
Flux Density	1.24 T
Magnet	Ferrite
Basket Material	Aluminium die cast
Demodulation	-
Cone Surround	Triple roll
NET Air Volume filled by driver	7.32
Spider Profile	Single constant height waves
Weather Resistant	Yes

Thiele Small Parameters

Fs	28 Hz
Re	5 Ohm
Qes	0.47
Qms	8.39
Qts	0.45
Vas	370.4 liters
Sd	1244.1 cm ²
Xmax (3)	10.93 mm
Xdamage (4)	34 mm
Mms	190.3 g
Bl	18.8 Tm
Le	1.37 mH
Cms	0.17 mm/N
Rms	4 Kg/s
Eta Zero	1.66 %
EBP	60

