

# BIANCO-75CD-T

1.4" - 200W - 109dB - 8Ohm - VC 75mm



- Titanium composite diaphragm with kapton surround
- Extended lower frequency range
- High SPL and power handling
- Crisp sound
- Black kapton VC former for improved power handling
- Voice coil from light weight flat aluminium winding material

### Dimensions & Weight

|                                    |                                           |
|------------------------------------|-------------------------------------------|
| Nominal Throat Diameter            | 35.6 mm (1.4 in)                          |
| Overall Diameter                   | 170 mm (6.7 in)                           |
| 90° Mounting Holes Diameter (4xM6) | 102 mm (4.0 in)                           |
| Depth                              | 65.4 mm (2.6 in)                          |
| Net Weight                         | 4.4 kg (9.7 lb)                           |
| Shipping Box                       | 196 x 179 x 74 mm<br>(7.7 x 7.0 x 2.9 in) |
| Gross Weight                       | 4.5 Kg (10 lb)                            |

### Replacement Diaphragm

|              |
|--------------|
| 1P000OPSB007 |
|--------------|

### Specs :

|                                    |                    |
|------------------------------------|--------------------|
| Nominal Impedance                  | 8 Ohm              |
| RDC                                | 7 Ohm              |
| AES Power Handling (1)             | 100 W              |
| Maximum Power Handling (2)         | 200 W              |
| Sensitivity (1W/1m)(3)             | 109 dB             |
| Frequency Range                    | 500 - 20000 Hz     |
| Recommended Crossover Frequency    | 1 kHz              |
| Voice Coil Diameter                | 75 mm (3 in)       |
| Winding Material                   | Flat aluminium     |
| Former Material                    | Black Kapton       |
| Winding Depth                      | 2.45 mm (0.1 in)   |
| Magnetic Gap Depth                 | 3 mm (0.12 in)     |
| Diaphragm Material                 | Composite Titanium |
| Flux Density                       | 1.65 T             |
| Magnet                             | Ferrite            |
| Demodulation                       | Copper cap         |
| Phase Plug Design                  | Annular            |
| Total Exit Angle                   | 5.1° conical       |
| NET Air Volume filled by HF Driver | 1.16 liters        |

### NOTES :

Driver mounted on Horn H280

- (1) 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20kHz.
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Averaged within the frequency range (1kHz - 18kHz)

