

# BIANCO-8MW125

8" - Midwoofer - 250W - 97dB

AUDIENCE

- Proprietary cone paper material made in-house
- 2" voice coil with APC (Advanced Polymer Coating)
- Vented pole piece for reduced compression
- CCAW voice coil wire for reduced moving mass
- Minimum damping fiber glass voice coil former
- Long life silver lead wires



### Dimensions & Weight

|                             |                                               |
|-----------------------------|-----------------------------------------------|
| Overall Diameter            | 205.6 mm (8.09 in)                            |
| Bolt Circle Diameter        | 195.0 mm (7.68 in)                            |
| Baffle Cutout Diameter      | 179.6 mm (7.07 in)                            |
| Mounting Depth              | 99 mm (3.89 in)                               |
| Flange and Gasket Thickness | 9.15 mm (0.36 in)                             |
| Net Weight                  | 3.47 Kg (7.65 lb)                             |
| Shipping Box                | 233 x 233 x 140 mm<br>(9.17 x 9.17 x 5.51 in) |
| Gross Weight                | 3.92 Kg (8.64 lb)                             |

### Recone Kit

|     |
|-----|
| N/A |
|-----|

### NOTES :

- (1) AES standard, test mode with continuous pink noise signal (6 dB crest factor; 2 hours) within the Fo to 10Fo power calculated on rated nominal impedance. Loudspeaker in free air
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3)  $X_{max} = ((\text{Winding depth} - \text{magnetic gap depth})/2) + (\text{magnetic gap depth}/3)$
- (4) Maximum excursion (p-p) before permanent damage
- (5) T/S parameters measured on drive units that are broken in using Klippel LPM Measurement System.

### Specs :

|                                 |                                    |
|---------------------------------|------------------------------------|
| Nominal Impedance               | 8 Ohm                              |
| Minimum Impedance               | 5.6 Ohm                            |
| AES Power Handling (1)          | 125 W                              |
| Maximum Power Handling (2)      | 250 W                              |
| Sensitivity (1W/1m)             | 97 dB                              |
| Frequency Range                 | 89 - 7400 Hz                       |
| Voice Coil Diameter             | 49.5 mm (2 in)                     |
| Winding Material                | Copper clad aluminium              |
| Former Material                 | Till                               |
| Winding Depth                   | 15.5 mm                            |
| Magnetic Gap Depth              | 8 mm (0.31 in)                     |
| Flux Density                    | 1.23 T                             |
| Magnet                          | Ferrite                            |
| Basket Material                 | Stamped steel                      |
| Demodulation                    | -                                  |
| Cone Surround                   | Double half roll with damping glue |
| NET Air Volume filled by driver | 1.54 liters                        |
| Spider Profile                  | Single constant height waves       |
| Weather Resistant               | Yes                                |

### Thiele Small Parameters

|             |                       |
|-------------|-----------------------|
| Fs          | 89 Hz                 |
| Re          | 5.8 Ohm               |
| Qes         | 0.57                  |
| Qms         | 14.63                 |
| Qts         | 0.55                  |
| Vas         | 10.1 liters           |
| Sd          | 224.3 cm <sup>2</sup> |
| Xmax (3)    | 6.42 mm               |
| Xdamage (4) | 16 mm                 |
| Mms         | 22.8 g                |
| BI          | 11.3 Tm               |
| Le          | 0.5 mH                |
| Cms         | 0.14 mm/N             |
| Rms         | 0.87 Kg/s             |
| Eta Zero    | 1.19 %                |
| EBP         | 156                   |

