

# ROSSO-65CD-T

1.4" - 140W - 108dB - 8Ohm - VC 65mm

AUDIENCE



- Titanium diaphragm
- Copper cap for reduced distortion and extended HF response
- Extended upper frequency response
- Advanced ferrite motor assembly
- High sensitivity and linear frequency response
- Advanced voice coil with flat copper clad aluminum wire

### Dimensions & Weight

|                                    |                                           |
|------------------------------------|-------------------------------------------|
| Nominal Throat Diameter            | 35.6 mm (1.4 in)                          |
| Overall Diameter                   | 156 mm (6.1 in)                           |
| 90° Mounting Holes Diameter (4xM6) | 102 mm (4.0 in)                           |
| Depth                              | 65.9 mm (2.6 in)                          |
| Net Weight                         | 3.76 kg (8.3 lb)                          |
| Shipping Box                       | 196 x 179 x 74 mm<br>(7.7 x 7.0 x 2.9 in) |
| Gross Weight                       | 4.06 Kg (8.95 lb)                         |

### Replacement Diaphragm

|              |
|--------------|
| 1P0000PSB008 |
|--------------|

### Specs :

|                                    |                            |
|------------------------------------|----------------------------|
| Nominal Impedance                  | 8 Ohm                      |
| RDC                                | 6.2 Ohm                    |
| AES Power Handling (1)             | 70 W                       |
| Maximum Power Handling (2)         | 140 W                      |
| Sensitivity (1W/1m)(3)             | 108 dB                     |
| Frequency Range                    | 500 - 20000 Hz             |
| Recommended Crossover Frequency    | 1 kHz                      |
| Voice Coil Diameter                | 65 mm (2.56 in)            |
| Winding Material                   | Flat copper clad aluminium |
| Former Material                    | Kapton                     |
| Winding Depth                      | 1.8 mm (0.07 in)           |
| Magnetic Gap Depth                 | 2.5 mm (0.1 in)            |
| Diaphragm Material                 | Titanium                   |
| Flux Density                       | 1.6 T                      |
| Magnet                             | Ferrite                    |
| Demodulation                       | Copper cap                 |
| Phase Plug Design                  | Annular                    |
| Total Exit Angle                   | 18.4° conical              |
| NET Air Volume filled by HF Driver | 0.71 liters                |

### NOTES :

Driver mounted on Horn H280

- (1) 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20kHz.  
(2) Maximum power is defined as 3dB greater than nominal power.  
(3) Averaged within the frequency range (1kHz - 18kHz)

