

ROSSO-65CDN-T

1.4" - 140W - 109dB - 8Ohm - VC 65mm



- Titanium diaphragm
- Neodymium motor assembly
- Copper cap for reduced distortion and extended HF response
- Smooth yet detailed and dynamic character
- High sensitivity and linear frequency response
- Advanced voice coil with flat copper clad aluminum wire

Dimensions & Weight

Nominal Throat Diameter	35.6 mm (1.4 in)
Overall Diameter	120 mm (4.7 in)
90° Mounting Holes Diameter (4xM6)	102 mm (4.0 in)
Depth	54 mm (2.1 in)
Net Weight	2 kg (4.4 lb)
Shipping Box	267 x 150 x 170 mm (10.5 x 5.9 x 6.7 in)
Gross Weight	2.1 Kg (4.6 lb)

Replacement Diaphragm

1P000OPSB008

Specs :

Nominal Impedance	8 Ohm
RDC	6.2 Ohm
AES Power Handling (1)	70 W
Maximum Power Handling (2)	140 W
Sensitivity (1W/1m)(3)	109 dB
Frequency Range	500 - 20000 Hz
Recommended Crossover Frequency	1 kHz
Voice Coil Diameter	65 mm (2.5 in)
Winding Material	Flat copper clad aluminium
Former Material	Kapton
Winding Depth	1.8 mm (0.07 in)
Magnetic Gap Depth	2 mm (0.08 in)
Diaphragm Material	Titanium
Flux Density	1.9 T
Magnet	Neodymium
Demodulation	Copper cap
Phase Plug Design	Annular
Total Exit Angle	33.1° conical
NET Air Volume filled by HF Driver	0.33 liters

NOTES :

- Driver mounted on Horn H280
- (1) 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20kHz.
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Averaged within the frequency range (1kHz - 18kHz)

