12" 127150 DLX

Deluxe Series By ACR | 12 Inch - Woofer







1. Tahan panas dan minimum kompresi

- Motor dan chassis didesain dengan ventilasi sehingga tidak ada kompresi udara dan memberikan sirkulasi udara yang baik serta berfungsi sebagai pendingin

2. Weatherproof


- Conepaper yang kokoh dilapisi dengan black coating menjadikan tahan terhadap segala cuaca

3. Kokoh

- Chassis memiliki konstruksi yang kuat dan terbuat dari aluminium diecast

4. Daya Magnet Optimal

- Daya motor magnet speaker yang optimal karena didesain dengan menggunakan teknologi FEA (Finite Element Analysis)



Spesifikasi


Diameter Speaker (inch/mm)	12 inch / 305 mm
Impedansi (Ω)	4 Ω
Nominal power handling (Watt) ¹	200 Watt
Program power (Watt) ²	400 Watt
Lebar daerah frekuensi (Hz)	58 Hz - 5000 Hz
SPL (2.83 V / 1 m) (dB)	98 dB
Diameter cone efektif (mm)	255.5 mm
Medan magnet (T)	0.91 T
Berat magnet (Kg/Oz)	1.56 kg / 54.7 Oz
Voice coil diameter (mm)	49.5 mm
Voice coil material	Kapton

^{- (1)} AES standard, test mode with continuous pink noise signal (6 dB crest factor; 2 hours)


Parameter "Thiele-Small"

Frekuensi Resonansi / Fs (Hz)	58 Hz
DCR (Ω)	3.2 Ω
Qts	0.26
Qes	0.27
Qms	9.71
Mms (g)	58.2 g
Cms (mm/N)	0.13 mm/N
BL Product (Tm)	15.8 Tm
Vas (liters)	48.4 liters
No (%)	3.32 %
Sd (cm ²)	514.7 cm ²
Xmax (mm)	5.0 mm

Respon Frekuensi




Impedansi




within the Fo to 10Fo power calculated on rated nominal impedance. Loudspeaker in free air - (?) Power on continous program is defined as 3dB greater than nominal power handling.

Respon Bass



Referensi Box Speaker

Dimensi luar 64.8 Lt pada Fb 60 Hz Tebal material 15 mm



Showroom

Surabaya: Jl. Margomulyo No. 5, Tandes - Surabaya

Telp. +62-81 231833504

Jakarta : Ruko Glodok Plaza Blok F no. 97

Jl. Pinangsia Raya, Mangga Besar - Jakarta Barat, Telp. +62-21 6493139