12" PA-12880-MK II EXCEL

Excellent Series By ACR | 12 Inch - Woofer





1. Daya Magnet Optimal

- Daya motor magnet speaker yang optimal karena didesain dengan menggunakan teknologi FEA (Finite Element Analysis)

2. Weatherproof

- Conepaper yang kokoh dilapisi dengan black coating menjadikan tahan terhadap segala cuaca

Spesifikasi

Diameter Speaker (inch/mm)	12 inch / 305 mm
Impedansi (Ω)	8 Ω
Nominal power handling (Watt) ¹	300 Watt
Program power (Watt) ²	600 Watt
Lebar daerah frekuensi (Hz)	40 Hz - 6100 Hz
SPL (2.83 V / 1 m) (dB)	98 dB
Diameter cone efektif (mm)	263 mm
Medan magnet (T)	1.24 T
Berat magnet (Kg/Oz)	1.77 kg /61.95 Oz
Voice coil diameter (mm)	60.55 mm
Voice coil material	Kapton


^{- (1)} AES standard, test mode with continuous pink noise signal (6 dB crest factor; 2 hours)

Parameter "Thiele-Small"


Frekuensi Resonansi / Fs (Hz)	40 Hz
DCR (Ω)	5.2 Ω
Qts	0.30
Qes	0.35
Qms	2.01
Mms (g)	45.6 g
Cms (mm/N)	0.37 mm/N
BL Product (Tm)	12.8 Tm
Vas (liters)	150.8 liters
No (%)	2.45 %
Sd (cm ²)	543.3 cm ²
Xmax (mm)	6.6 mm

Ø 306.0 Ø 280.0

Respon Frekuensi




Impedansi




within the Fo to 10Fo power calculated on rated nominal impedance. Loudspeaker in free air - (2) Power on continous program is defined as 3dB greater than nominal power handling.

Respon Bass



Referensi Box Speaker

Dimensi luar 68.4 Lt pada Fb 49 Hz Tebal material 15 mm



Showroom

Surabaya : Jl. Margomulyo No. 5, Tandes - Surabaya.

Telp. +62-81 231833504

Jakarta : Ruko Glodok Plaza Blok F no. 97 RT 06/RW 06 Mangga Besar - Jakarta Barat

Telp.: +62-21 30525443, 6493139, Fax.: +62-21 6493171