

## **Assignment 11: Exploring the Integration of Multivariate Analysis and Machine Learning**

A. Sepúlveda-Jiménez

Data Science Dept., SoTE, CoBET, National University

DDS-8515: Multivariate Analysis

Course Instructor: Y. Karahan, PhD

November 18, 2025

## Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>Core Analysis I: Canonical Correlation Analysis (CCA)</b>	<b>3</b>
2.1	Foundations and assumptions . . . . .	3
2.2	Modern extensions: kernel and deep CCA . . . . .	4
2.3	Implications . . . . .	4
<b>3</b>	<b>Core Analysis II: Partial Least Squares (PLS)</b>	<b>4</b>
3.1	Foundations and assumptions . . . . .	4
3.2	Modern extensions . . . . .	5
3.3	Implications . . . . .	5
<b>4</b>	<b>Applied Example: Exercise Physiology (Linnerud)</b>	<b>5</b>
4.1	Integrated workflow . . . . .	5
<b>5</b>	<b>Results and Discussion</b>	<b>6</b>
<b>6</b>	<b>Future Outlook: Interface of Multivariate Stats and ML</b>	<b>6</b>
<b>7</b>	<b>Conclusion</b>	<b>6</b>

## List of Figures

1	Block correlation heatmap for Linnerud variables (exercise vs. physiology). . .	11
2	CCA: first canonical variates $U_1$ (exercise) vs $V_1$ (physiology). . . . .	12
3	Held-out canonical correlations by component (mean over CV folds). . . . .	13
4	PLS: cross-validated mean $R^2$ by number of components; per-target and average. .	14
5	Test $R^2$ : PLS vs. Gradient Boosting (wrapped in MultiOutputRegressor). . .	15

## 1 Introduction

Multivariate statistical analysis studies joint variation across multiple variables measured on the same observational units, modeling covariance structure to infer latent constructs or relations among variable blocks (Bollen, 1989; Hastie et al., 2009). Machine learning focuses on algorithms that learn patterns from data to make predictions, with emphasis on generalization and scalable optimization (James et al., 2021; Murphy, 2012). Integrating these paradigms matters because modern data sets are both high-dimensional and semantically structured: scientists need models that both predict well and reveal mechanisms (Hardoon et al., 2004; Rudin, 2019).

This paper asks: *How can classical multivariate reasoning complement, enhance, or constrain modern ML in practice?* I analyze two pillars—CCA and PLS—covering their assumptions, ML extensions, and implications for inference, prediction, and interpretability. A reproducible Python case study demonstrates an integrated workflow and quantifies trade-offs Sections 4–5.

## 2 Core Analysis I: Canonical Correlation Analysis (CCA)

### 2.1 Foundations and assumptions

Let  $\mathbf{X} \in \mathbb{R}^{n \times p}$  and  $\mathbf{Y} \in \mathbb{R}^{n \times q}$  be centered matrices (two “views” of the same  $n$  units). CCA finds weight vectors  $(\mathbf{a}_k, \mathbf{b}_k)$  that maximize correlation between the  $k$ -th canonical variates  $u_k = \mathbf{X}\mathbf{a}_k$  and  $v_k = \mathbf{Y}\mathbf{b}_k$  subject to unit-variance and orthogonality constraints (Hotelling, 1936; Thompson, 2005):

$$\begin{aligned} (\hat{\mathbf{a}}_1, \hat{\mathbf{b}}_1) &= \arg \max_{\mathbf{a}, \mathbf{b}} \text{corr}(\mathbf{X}\mathbf{a}, \mathbf{Y}\mathbf{b}) \\ \text{s.t. } \mathbf{a}^\top \Sigma_{XX} \mathbf{a} &= 1, \quad \mathbf{b}^\top \Sigma_{YY} \mathbf{b} = 1, \end{aligned} \tag{1}$$

with  $(\hat{\mathbf{a}}_k, \hat{\mathbf{b}}_k)$  for  $k \geq 2$  subject to additional orthogonality constraints in the induced inner products. Under mild conditions, (1) reduces to a generalized eigenproblem involving blocks of the sample covariance  $\Sigma$  (Hardoon et al., 2004). CCA assumes linear relations and is sensitive to scaling; standardization of features in each view is routine.

## 2.2 Modern extensions: kernel and deep CCA

**Kernel CCA (KCCA)** replaces inner products with kernel functions, allowing non-linear relations in reproducing kernel Hilbert spaces (Hardoon et al., 2004). **Deep CCA (DCCA)** learns non-linear transformations  $f_\theta(\mathbf{X}), g_\phi(\mathbf{Y})$  via neural networks to maximize the sum of correlations of corresponding components, trained with stochastic optimization (Andrew et al., 2013). Both approaches trade closed-form solutions for powerful representation learning. Regularization (e.g., ridge penalties) is crucial for stability (Hardoon et al., 2004).

## 2.3 Implications

For *inference*, linear CCA yields interpretable canonical loadings and redundancy indices; KCCA/DCCA emphasize *prediction/extraction* of shared structure but require post-hoc interpretation (e.g., saliency maps). For *interpretability*, linear CCA’s weights are transparent; deep variants are blacker boxes but can be probed with attribution methods. For *generalization*, cross-validation on the number of components and regularization strength is essential in all variants.

# 3 Core Analysis II: Partial Least Squares (PLS)

## 3.1 Foundations and assumptions

With centered  $\mathbf{X} \in \mathbb{R}^{n \times p}$  and response matrix  $\mathbf{Y} \in \mathbb{R}^{n \times r}$ , **PLS2** iteratively extracts latent scores  $\mathbf{t}_k = \mathbf{X}\mathbf{w}_k$  and  $\mathbf{u}_k = \mathbf{Y}\mathbf{c}_k$  to maximize covariance:

$$(\hat{\mathbf{w}}_k, \hat{\mathbf{c}}_k) = \arg \max_{\mathbf{w}, \mathbf{c}} \text{cov}(\mathbf{X}\mathbf{w}, \mathbf{Y}\mathbf{c}) \quad \text{with normalization/deflation,} \quad (2)$$

and regresses  $\mathbf{Y}$  on the latent  $\mathbf{T} = [\mathbf{t}_1, \dots, \mathbf{t}_K]$  (Abdi & Williams, 2010; Rosipal & Kramer, 2006; Wold, 1975). Unlike OLS, PLS is stable when  $p \gg n$  and collinearity is high. It assumes (approximately) linear relations; sparsity (sPLS) adds interpretability by selecting variables (Cao, Rossell, et al., 2008; Witten et al., 2009).

### 3.2 Modern extensions

**Sparse/penalized PLS** induces variable selection via  $\ell_1$  or group penalties (Cao, Rossell, et al., 2008; Witten et al., 2009). **Kernel PLS** parallels KCCA by lifting to RKHS (Rosipal & Kramer, 2006). PLS ideas permeate ML as supervised dimension reduction feeding flexible learners (e.g., tree ensembles), improving stability in the presence of collinearity.

### 3.3 Implications

For *prediction*, PLS often rivals ridge/elastic net when predictors are many and correlated, with clearer component structure. For *interpretability*, loadings/weights and VIP scores help rank features; sparsity improves parsimony. For *inference*, bootstrap CIs are common; strict classical inference is less emphasized than in SEM but more structured than typical black-box ML.

## 4 Applied Example: Exercise Physiology (Linnerud)

We analyze the Linnerud dataset (3 exercise measures vs. 3 physiological measures) included in scikit-learn. Let  $\mathbf{X} \in \mathbb{R}^{n \times 3}$  be *exercise* (Chins, Situps, Jumps) and  $\mathbf{Y} \in \mathbb{R}^{n \times 3}$  be *physiology* (Weight, Waist, Pulse).

### 4.1 Integrated workflow

1. **EDA & scaling.** Standardize each block; inspect block correlation (Figure 1).
2. **CCA for structure discovery.** Select  $K$  via CV maximizing mean held-out canonical correlation; plot  $U_1$  vs  $V_1$  (Figure 2) and barplot correlations by component (Figure 3).
3. **PLS for prediction.** Tune components via CV to predict  $\mathbf{Y}$  from  $\mathbf{X}$ ; report multioutput  $R^2$  per target and mean (Figure 4).
4. **Benchmark vs ensemble ML.** Compare PLS to a tuned Gradient Boosting multioutput regressor; report test  $R^2$  (Figure 5).

## 5 Results and Discussion

**CCA.** The first canonical pair exhibits a strong linear association ( $\hat{\rho}_1$  high in CV), aligning higher exercise performance with lower weight/waist and modest changes in pulse—consistent with physiology. Linear CCA suffices; DCCA would be overkill here (risking overfitting) yet becomes attractive for large non-linear multi-modal data (Andrew et al., 2013).

**PLS.** With 1–2 components, PLS attains competitive multioutput  $R^2$  and clear component interpretations (e.g., a “fitness” axis). Gradient boosting can match or slightly exceed  $R^2$  but sacrifices transparency; feature attributions (e.g., SHAP) help but add complexity (Lundberg & Lee, 2017).

**Trade-offs.** The integrated approach pairs *CCA for structure* (interpretable relationships between views) with *PLS for prediction* (parsimonious supervised compression). Ensembles add incremental accuracy at the cost of simplicity.

## 6 Future Outlook: Interface of Multivariate Stats and ML

Methodological directions include: **(i)** scalable & regularized multiview learning (sparse CCA/PLS with stability selection) (Cao, Rossell, et al., 2008; Witten et al., 2009); **(ii)** deep multiview models with causally informed inductive biases (e.g., disentangling content vs. nuisance); **(iii)** probabilistic interpretability layers (post-hoc explanations aligned with linear subspaces). Ethical/practical concerns: *black-box risk*, *data transparency*, and *computational cost*. When decisions affect people, prefer interpretable models unless accuracy gaps are substantial and justified (Rudin, 2019).

## 7 Conclusion

Classical multivariate tools remain essential: they encode structure, deliver stable low-dimensional representations, and enable principled interpretation. Modern ML contributes flexible function classes, robust pipelines, and powerful optimization. The sweet spot is an *integrated workflow* that uses multivariate structure (CCA/PLS) to guide representation and feature compression, with ML layers for residual complexity—monitored

via cross-validation and documented with clear interpretability artifacts. Use integrated approaches when: (a) variables naturally split into views (CCA), (b) predictors are many and collinear (PLS), and (c) stakeholders require both insight and performance.


## References

- Abdi, H., & Williams, L. J. (2010). Partial least squares methods: Partial least squares correlation and partial least squares regression. *Wiley Interdisciplinary Reviews: Computational Statistics*, 2(1), 97–106.
- Andrew, G., Arora, R., Bilmes, J. A., & Livescu, K. (2013). Deep canonical correlation analysis. *Proceedings of the 30th International Conference on Machine Learning*, 1247–1255.
- Bollen, K. A. (1989). *Structural equations with latent variables*. Wiley.
- Cao, K.-A. L., Rossell, D., et al. (2008). Sparse pls: Variable selection in multivariate regression. *BMC Bioinformatics*, 9, 558.
- Hardoon, D. R., Szedmak, S., & Shawe-Taylor, J. (2004). Canonical correlation analysis: An overview with application to learning methods. *Neural Computation*, 16(12), 2639–2664.
- Hastie, T., Tibshirani, R., & Friedman, J. (2009). *The elements of statistical learning: Data mining, inference, and prediction* (2nd ed.). Springer.
- Hotelling, H. (1936). Relations between two sets of variates. *Biometrika*, 28(3/4), 321–377.
- James, G., Witten, D., Hastie, T., & Tibshirani, R. (2021). *An introduction to statistical learning: With applications in r* (2nd ed.). Springer.
- Lundberg, S. M., & Lee, S.-I. (2017). A unified approach to interpreting model predictions. *Advances in Neural Information Processing Systems*, 30.
- Murphy, K. P. (2012). *Machine learning: A probabilistic perspective*. MIT Press.
- Rosipal, R., & Kramer, N. (2006). Overview and recent advances in partial least squares. *Subspace, Latent Structure and Feature Selection*, 34–51.
- Rudin, C. (2019). Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 1(5), 206–215.




- Thompson, B. (2005). Canonical correlation analysis. In *Encyclopedia of statistics in behavioral science*. Wiley.
- Witten, D. M., Tibshirani, R., & Hastie, T. (2009). A penalized matrix decomposition, with applications to sparse principal components and canonical correlation analysis. *Biostatistics*, 10(3), 515–534.
- Wold, H. (1975). Soft modelling by latent variables: The non-linear iterative partial least squares (nipals) approach. In *Perspectives in probability and statistics*. Academic Press.

## Figures




**Figure 1**

*Block correlation heatmap for Linnerud variables (exercise vs. physiology).*




**Figure 2**

*CCA: first canonical variates  $U_1$  (exercise) vs  $V_1$  (physiology).*




**Figure 3**

*Held-out canonical correlations by component (mean over CV folds).*



**Figure 4**

*PLS: cross-validated mean  $R^2$  by number of components; per-target and average.*



**Figure 5**

*Test R<sup>2</sup>: PLS vs. Gradient Boosting (wrapped in MultiOutputRegressor).*