

Lab 3: Types

Your software team has been hard at work making code to support Bill and Sally's big store merger. The engineering team presents their design and needs you to review it and ok the logic with the client.

1. Engineering progress report

Eugene the engineer tells us the following function fetchs points from clients at Billy's Bats-&-Balls, and also one for Sally's Shoes-&-Socks.

```
def points(client: BillyClient): Int
def tier(client: SallyClient): Color
```

1. Write the possible logic of this function using $A \xrightarrow{f} B$ notation (like a flowchart) and then in words.


2. Engineering proposal

The engineering team suggests this interface for joining the two loyalty programs.

```
def loyalty(client: (BillyClient | SallyClient)) : (Int | Color)
```

Realizing everyone is scared of this code he quickly says $(A|B)$ just means "data from A or B".

- 2 Starting from the input, draw a commutative diagram (flow chart) of the information in and out. Remember the logic of OR tells you the introductions (constructor/"setters") and elimination rules "getter(s)" you should expect. [Here is a start.]



3. Filling in the missing pieces.

3. In the syntax given, write the signatures of the functions which are missing from the engineering proposal. [Here is a start]

```

def left(x:Int) : (Int | Color)
def from_Sally( c:SallyClient) : (BillyClient | SallyClient)

```

4. Write a test you can do of this design that leverages the fact that composing two paths should be equal ("commutative diagram").

4. Revamp.

5. With this interface can a customer from Billy's use loyalty at Sally's? Explain why not.

Realizing there are gaps, Eugene remarks there is a data type (A, B) which means "a pair of data from A and B ".

6. Redesign your program so that `loyalty` outputs $(Int, Color)$ where a client from a different store is automatically given a comparable value to the other store.

5. A demo.

```
import Billy.{BillyClient, points}
import Sally.{SallyClient, tier, Blue, Red}

def loyalty( client : BillyClient | SallyClient ) : (Int,Color) =
  client match
    BillyClient => {
      p = points(client)
      if p > 5
        (10, Red )
      else
        (5, Blue )
    }
    SallyClient => {
      c = tier(client)
      if c == Blue
        (5,c)
      else
        (10,c)
    }
  }
```