

TAG. NO	605-E-103	
SERVICE	CONDENSATE STRIPPER REBOILER	
TYPE/SURFACE	BKU	/ 438 M2
HEAT DUTY	1.39 E+07	BTU/HR
	SHELL	TUBE
DESIGN PRESS.	300 / FV PSIG	200 / FV PSIG
DESIGN TEMP.	411 / 73 ° F	450 / 73 ° F
INSULATION	HOT 62 MM	HOT 75 MM
MATERIAL	CS+CA 6 MM	CS+CA 1.5 MM

TAG NO.	605-C-101	
SERVICE	CONDENSATE STRIPPER	
ID x TT	1700 x 18750	MM
DESIGN PRESS.	300 / FV	PSIG
DESIGN TEMP.	411 / 40	° F
INSULATION	HOT 62	MM
MATERIAL	CS + SS 316L CLAD (TOP)	
	CS + CA 6 MM (BOTTOM)	

NOTES

- VESSEL SKIRT HEIGHT / TAN LINE ELEVATION SET BY REQUIREMENT TO MAINTAIN SINGLE PHASE INLET TO RUNDOWN COOLER 615-E-104.
- TOP OF REBOILER WEIR TO BE ABOVE CONDENSATE STRIPPER BOTTOM TAN LINE.
- FLASHING FEED DISTRIBUTOR.
- NO POCKETS.
- 605-TV-104 IS AUTOMATICALLY CLOSED BY EMERGENCY SIGNAL (605-HY-102).
OUTPUT : 4 mA
MODE : MANUAL

