

R | Basic Text Analysis

Presented by Aviv Lo

Table of Contents



Topic 1

What is R?



Topic 2

AI/ML/NLP Explained



Topic 3

Text Analysis



Topic 4

R Basics

1

What exactly is R?



1. Developed by Ross Ihaka and Robert Gentleman in 1991
2. Hence the name "R"
3. Maintained by The R Foundation for Statistical Computing
4. Difficult for beginners + Steep learning curve
5. Rich and powerful visualization libraries
6. Support matrix / vectorized operations
7. It's born for stats

```
example.R (/tmp) - VIM
numbers <- 1:3
words <- c("word1", "word2", "word3")
categories <- as.factor(words)
dtfrm <- data.frame(numbers, words)

attr(numbers, "label") <- "A numeric vector"
attr(words, "label") <- "A character vector"
attr(categories, "label") <- "A factor vector"

list1 <- list(dtfrm = dtfrm, y = numbers)
list2 <- list(list1 = list1, abc = words)
list2$name with space <- 1:10
list2$`2` <- c("one", "two")
list3 <- list(abc = categories, list1 = list1)
rm(list1)

> list1 <- list(dtfrm = dtfrm, y = numbers)
> list2 <- list(list1 = list1, abc = words)
> list2$name with space <- 1:10
> list2$`2` <- c("one", "two")
> list3 <- list(abc = categories, list1 = list1)
> rm(list1)
> source('/home/jakson/src/Vim-R-plugin/r-plugin/vimbrowser.R') ; .vim.browser()
>
```

.GlobalEnv | Libraries

- categories A factor vector
- dtfrm
 - numbers
 - words
- list2
 - list1
 - dtfrm
 - numbers
 - words
 - y A numeric vector
 - abc A character vector
 - name with space
 - 2

example.R [+] 1,1 All Object_Browser 8,1 Top

RStudio

The screenshot displays the RStudio environment with four panels, each highlighted by a red box and a label:

- 1- Code Editor:** The top-left panel shows an R script file named `diamondPricing.R`. The code includes loading the `ggplot2` library, viewing the `diamonds` dataset, summarizing its structure, and creating a ggplot of carat vs price, colored by clarity. The plot is titled "Diamond Pricing".
- 2- R Console:** The bottom-left panel shows the output of the code. It displays summary statistics for the `diamonds` dataset (min, 1st Qu., Median, Mean, 3rd Q., Max.) for variables `x`, `y`, and `z`. It also shows the execution of `aveSize` and `clarity` assignments, and the creation of the plot object `p`.
- 3- Workspace and History:** The top-right panel shows the `Workspace` and `History` tabs. The `Workspace` tab lists the `diamonds` dataset (53940 obs. of 10 variables) and the `aveSize` variable (0.7979).
- 4 - Plots and files:** The bottom-right panel shows the `Plots` and `Files` tabs. The `Plots` tab displays the "Diamond Pricing" plot, which is a scatter plot of Price vs Carat, colored by clarity. The legend indicates clarity levels: VS2, VS1, VVS2, VVS1, and IF.


R vs. Python

	Python	R
General	Python is a general-purpose programming language for data analysis and scientific computing.	R is a functional programming environment and language for statistical computing and graphics.
Objective	Data Science, Web Development, Embedded Systems	Data Science & Statistical Modeling
IDE	iPython, Pycharm, Jupyter Notebook, Spyder	Rstudio, R GUI, R KWARD
Data Collection	Supports CSV files, SQL , JSON , and webscraping with BeautifulSoup .	Can also import csv files with built-in readr library. R's library RCurl provides a simple way to make API requests, similar to Python's requests package.
Data Analysis	Organize dataframes with Pandas filtering, sorting. Python takes a more streamlined approach for data science projects.	Complex data visualization tools make the exploratory data analysis (EDA) process much more complex than Python.
Essential Packages & Libraries	Numpy , Pandas , matplotlib , scipy , scikit-learn , TensorFlow	caret , stringr , ggplot2 , knitr , tidyverse , markdown , shiny , forcats , haven
Database Handling Capacity	Can easily handle large data because there are less constraints for memory usage	R computes everything in memory, so its capabilities are limited by RAM size. A major downfall of R is the inability to handle massive amounts of data
Data Visualization	Despite the capabilities of data visualization tools like Matplotlib and Seaborn , Python fails to measure up to data visualization features of R.	Developed by and for statisticians, R has complex data visualization features.
Syntax	The 'zen of python' is that there's a proper way to write code.	R doesn't have this set of rules. Also indexing starts at 1, which can be considered unconventional for general programmers.
Learning Curve	Simple and readable code structure makes it easier for beginners to learn. It also allows for object-oriented programming. It also offers a wide range of data structures that you wouldn't expect from a general-purpose language.	R's functional syntax isn't easy for beginners, but not too challenging for those well versed in programming. It also offers a few data structures, but fails to handle large amounts of data.

2


AI/ML/NLP Explained

AI Domains




Machine Learning Family Tree


Machine Learning Types



Machine Learning Family Tree




Types of NLP




3

Text Analysis

Process & Techniques



Process & Techniques



Goals

KEY DIFFERENCE BETWEEN TEXT ANALYSIS & NLP? THEIR GOALS.


TEXT ANALYSIS GOAL

Derive insights solely
from the text itself,
without consideration of
the semantics.


NLP GOAL

Understand the linguistic
use and context behind text,
with consideration of
semantics and grammatical
structures.


Example: Word Cloud & Word Frequency



Example: Word Frequency



Example: Tweet Sentiment




Examples: Covid Sentiment Map

Data Points Displayed: 8432

Gradient Scale: Green 😊 > Yellow 😐 > Red 😞

You can click on each point to see the actual tweets

The site updates every 13 seconds



4

R Basics

R Basics

- **Data Types**

- Character & Double & Integer & Logical & Complex

- **Data Structures**

- Matrix & Data Frame
- List & Vector
- Factor

- **Variable Assignment**

- `x ← 1`
- `y ← c("apple", "orange")`
- `car_speeds <- read.csv(file = './car-speeds.csv')`

- **Accessing Data Frame**

- `Data_Frame[row, col]`
- `Data_Frame$Column_Name`

R Basics: Data Structure Examples

List

```
> x
[[1]]
[1] 1

[[2]]
[1] "a"

[[3]]
[1] TRUE

[[4]]
[1] 1+4i

> |
```

Data Frame

```
> df
  id  x  y
1  a  1 11
2  b  2 12
3  c  3 13
4  d  4 14
5  e  5 15
6  f  6 16
7  g  7 17
8  h  8 18
9  i  9 19
10 j 10 20
> |
```

Vector

```
> z
[1] "Sarah" "Tracy" "Jon"
> y
[1] 1 2 3
> |
```

Matrix

```
> m
      [,1] [,2] [,3]
[1,]    1    2    3
[2,]   11   12   13
> |
```


R Basics: Exploring Your Data

- **nrow() & ncol()**

- Gives you the number of rows of the dataset
- Gives you the number of columns of the data set

- **head() & tail()**

- Gives you the top 6 rows of the data set
- Gives you the bottom 6 rows of the data set

- **str()**

- Gives you the structure of the data set

- **dim()**

- Gives you the dimension (row, col) of the data set

- **summary()**

- Gives you a summary of your data set
- Ex: min, max, mean, IQR, number of categorical variables ...etc.



R

Let's Code



Thank You