```
class PktbsUser {
//
final String id;
final DateTime created;
DateTime? updated;
final String collectionId;
final String collectionName;
//
String name;
final String username;
final String email;
bool emailVisibility;
bool verified;
String? avatar;

}
```

```
1 class PktbsEmployee {
2 //
    final String id;
4
    final DateTime created;
     DateTime? updated;
    final PktbsUser creator;
    PktbsUser? updator;
     final String collectionId;
     final String collectionName;
     //
11 String name;
12 String phone;
13 String? email;
double salary;
  String address;
     String description;
17 }
```

```
1 class PktbsVendor {
2 //
     final String id;
4
    final DateTime created;
     DateTime? updated;
    final PktbsUser creator;
    PktbsUser? updator;
     final String collectionId;
     final String collectionName;
    //
11 String name;
12 String phone;
13 String? email;
14 String address;
15 String description;
16 }
```

```
1 class PktbsInventory {
     final String id;
4
     final DateTime created;
     DateTime? updated;
    final PktbsUser creator;
    PktbsUser? updator;
     final String collectionId;
     final String collectionName;
     //
     String title;
12 int quantity;
   Measurement unit;
double amount;
    PktbsVendor from;
16 String? description;
17 }
19 class Measurement {
20 //
21 final String name;
22 final String symbol;
23 final String unitOf;
24 final String system;
25 }
```

```
1 class PktbsOrder {
     final String id;
     DateTime created;
     DateTime? updated;
     PktbsUser creator;
     PktbsUser? updator;
     String collectionId;
     String collectionName;
     String customerName;
     String? customerEmail;
     String customerPhone;
     String? customerAddress;
     String? customerNote;
     String? measurement;
     String? plate;
     String? sleeve;
     String? colar;
     String? pocket;
     String? button;
     String? measurementNote;
     int quantity;
     PktbsEmployee tailorEmployee;
     // double tailorCharge; -> only add a column in trx table for tailor.
     String? tailorNote;
     PktbsInventory? inventory;
     int? inventoryQuantity;
     String? inventoryUnit;
     // double? inventoryPrice; -> only add a column in trx table for inventory.
     String? inventoryNote;
     PktbsEmployee? deliveryEmployee;
     String? deliveryAddress;
     // double? deliveryCharge; -> only add a column in trx table for delivery.
     String? deliveryNote;
     PaymentMethod paymentMethod; // enum PaymentMethod { cash, mfs, card, cheque, others }
     String? paymentNote;
     double amount; // total amount = tailorCharge + inventoryPrice + deliveryCharge
     DateTime deliveryTime;
     String? description;
     OrderStatus status; // enum OrderStatus { pending, processing, ready, shipping, completed, cancelled }
```

```
1 class PktbsTrx {
     //
     final String id;
     final DateTime created;
     DateTime? updated;
     final PktbsUser creator;
    PktbsUser? updator;
     final String collectionId;
     final String collectionName;
     //
     String fromId;
     GLType fromType; // enum GLType { vendor, inventory, employee, order, user }
     Map<String, dynamic> from;
     //
     String toId;
     GLType toType; // enum GLType { vendor, inventory, employee, order, user }
     Map<String, dynamic> to;
     //
     double amount;
     Measurement? unit;
     bool isGoods;
     TrxType trxType; // enum TrxType { debit, credit }
     String voucher;
     bool isSystemGenerated;
    String? description;
27 }
```