

# Foundations of Machine Learning — Homework Assignment 1

Anirudhan J Rajagopalan  
N18824115  
ajr619

October 11, 2015

## C. Randomized Halving

### 1. Psuedo code

---

**Algorithm 1** Randomized Halving

---

```

1:  $H_1 \leftarrow H$ 
2: for  $t \leftarrow 1$  to  $T$  do
3:    $RECEIVE(x_t)$ 
4:    $r_t \leftarrow \frac{\sum_{i: y_{t,i}=1} 1}{|H_t|}$ 
5:    $p_t \leftarrow 1$ 
6:   if  $r_t \leq \frac{3}{4}$  then
7:      $p_t \leftarrow \lceil \frac{1}{2} \log_2 \frac{1}{1-r_t} \rceil$ 
8:    $\hat{y}_t \leftarrow GetRandomNumberWithProbability([1, 0], [p_t, 1 - p_t])$ 
9:    $RECEIVE(y_t)$ 
10:  if  $\hat{y}_t \neq y_t$  then
11:     $H_{t+1} \leftarrow \{C \in H_t : C(x_t) = y_t\}$ 
return  $H_{T+1}$ 

```

---

### 2. Prove $\forall t \geq 1, E[\mu] \leq \frac{\phi_t - \phi_{t+1}}{2}$

Given: Potential function:  $\phi_t = \log_2 |H_t|$  and  $\mu_t = 1_{y_t \neq \hat{y}_t}$

Proof:

We are only considering the case when the predicted value  $\hat{y}_t$  is not equal to the received value  $y_t$ . The value of expectation can be written as

$$\begin{aligned} E[\mu_t] &= p_t * 1 + (1 - p_t) * 0 \\ &= p_t * 1 \end{aligned}$$

The probability of predicting 1 by the randomized algorithm is the probability of making a mistake since we are only considering the cases in which we make mistakes ( $\mu_t = 1_{y_t \neq \hat{y}_t}$ )

Therefore,

$$\begin{aligned} E[\mu_t] &= p_t \\ &= \lceil \frac{1}{2} \log_2 \frac{1}{1-r_t} \rceil 1_{r_t \leq \frac{3}{4}} + 1_{r_t > \frac{3}{4}} \\ &\leq \lceil \frac{1}{2} \log_2 \frac{1}{1-r_t} \rceil \end{aligned}$$

Since, the Expectation will be 1 when  $r_t > \frac{3}{4}$  which corresponds to the maximum expectation here, we can upper bound the expectation by using  $r_t \leq \frac{3}{4}$  as  $\lceil \frac{1}{2} \log_2 \frac{1}{1-r_t} \rceil$  equals 1 when  $r_t = \frac{3}{4}$

$$\begin{aligned}
 E[\mu_t] &\leq \left\lfloor \frac{1}{2} \log_2 \frac{1}{1-r_t} \right\rfloor \\
 &= \left\lfloor \frac{\log_2 \frac{1}{1-r_t}}{2} \right\rfloor \\
 &= \left\lfloor \frac{\log_2 \frac{1}{1-r_t}}{2} \right\rfloor \\
 &= \left\lfloor \frac{\log_2 \frac{1}{1-\frac{|H_1|}{|H_t|}}}{2} \right\rfloor \\
 &= \left\lfloor \frac{\log_2 \frac{|H_t|}{|H_t|-|H_1|}}{2} \right\rfloor \\
 &= \left\lfloor \frac{\log_2 \frac{|H_t|}{|H_0|}}{2} \right\rfloor \\
 &= \left\lfloor \frac{\log_2 |H_t| - \log_2 |H_0|}{2} \right\rfloor \\
 &= \left\lfloor \frac{\log_2 |H_t| - \log_2 |H_{t+1}|}{2} \right\rfloor \\
 &= \left\lfloor \frac{\phi_t - \phi_{t+1}}{2} \right\rfloor \\
 \therefore E[\mu_t] &\leq \frac{\phi_t - \phi_{t+1}}{2}
 \end{aligned}$$

**3. Expected number of mistakes.**

**4. [Bonus Question]**