

KMP Algorithm for Pattern Searching

Difficulty Level : Hard • Last Updated : 28 Sep, 2020

Given a text $txt[0..n-1]$ and a pattern $pat[0..m-1]$, write a function $search(char pat[], char txt[])$ that prints all occurrences of $pat[]$ in $txt[]$. You may assume that $n > m$.

Examples:

Input: `txt[] = "THIS IS A TEST TEXT"`

`pat[] = "TEST"`

Output: Pattern found at index 10

Input: `txt[] = "AABAACAADAABAABA"`

`pat[] = "AABA"`

Output: Pattern found at index 0

Pattern found at index 9

Pattern found at index 12

Text : A A B A A C A A D A A B A A B A

Pattern : A A B A

```

      A A B A           A A B A
    A A B A A C A A D A A B A A B A
      0  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15
                          A A B A
  
```

Pattern Found at 0, 9 and 12

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

Recommended: Please solve it on "**PRACTICE**" first, before moving on to the solution.



Related Articles

We have discussed Naive pattern searching algorithm in the [previous post](#). The worst case complexity of the Naive algorithm is $O(m(n-m+1))$. The time complexity of KMP algorithm is $O(n)$ in the worst case.

KMP (Knuth Morris Pratt) Pattern Searching

The [Naive pattern searching algorithm](#) doesn't work well in cases where we see many matching characters followed by a mismatching character. Following are some examples.

```
txt[ ] = "AAAAAAAAAAAAAAAAAAB"  
pat[ ] = "AAAAB"
```

```
txt[ ] = "ABABABCABABABCABABABC"
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

The KMP matching algorithm uses degenerating property (pattern having same sub-patterns appearing more than once in the pattern) of the pattern and improves the worst case complexity to $O(n)$. The basic idea behind KMP's algorithm is: whenever we detect a mismatch (after some matches), we already know some of the characters in the text of the next window. We take advantage of this information to avoid matching the characters that we know will anyway match. Let us consider below example to understand this.

Matching Overview

```
txt = "AAAAABAAABA"  
pat = "AAAA"
```

We compare first window of **txt** with **pat**

```
txt = "AAAAABAAABA"  
pat = "AAAA" [Initial position]
```

We find a match. This is same as [Naive String Matching](#).

In the next step, we compare next window of **txt** with **pat**.

```
txt = "AAAAABAAABA"  
pat = "AAAA" [Pattern shifted one position]
```

This is where KMP does optimization over Naive. In this second window, we only compare fourth **A** of pattern with fourth character of current window of text to decide whether current window matches or not. Since we know first three characters will anyway match, we skipped matching first three characters.

Need of Preprocessing?

An important question arises from the above explanation, how to know how many characters to be skipped. To know this, we pre-process pattern and prepare an integer array `lps[]` that tells us the count of characters to be skipped.

Preprocessing Overview:

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

- **name lps indicates longest proper prefix which is also suffix..** A proper prefix is prefix with whole string **not** allowed. For example, prefixes of "ABC" are "", "A", "AB" and "ABC". Proper prefixes are "", "A" and "AB". Suffixes of the string are "", "C", "BC" and "ABC".
- We search for lps in sub-patterns. More clearly we focus on sub-strings of patterns that are either prefix and suffix.
- For each sub-pattern $pat[0..i]$ where $i = 0$ to $m-1$, $lps[i]$ stores length of the maximum matching proper prefix which is also a suffix of the sub-pattern $pat[0..i]$.

$lps[i]$ = the longest proper prefix of $pat[0..i]$
which is also a suffix of $pat[0..i]$.

Note : $lps[i]$ could also be defined as longest prefix which is also proper suffix. We need to use properly at one place to make sure that the whole substring is not considered.

Examples of $lps[]$ construction:

For the pattern "AAAA",
 $lps[]$ is [0, 1, 2, 3]

For the pattern "ABCDE",
 $lps[]$ is [0, 0, 0, 0, 0]

For the pattern "AABAACAABAA",
 $lps[]$ is [0, 1, 0, 1, 2, 0, 1, 2, 3, 4, 5]

For the pattern "AAACAAAAAC",
 $lps[]$ is [0, 1, 2, 0, 1, 2, 3, 3, 3, 4]

For the pattern "AAABAAA",
 $lps[]$ is [0, 1, 2, 0, 1, 2, 3]

Searching Algorithm:

Unlike [Naive algorithm](#), where we slide the pattern by one and compare all characters at each shift, we use a value from $lps[]$ to decide the next characters to be matched. The

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

How to use `lps[]` to decide next positions (or to know a number of characters to be skipped)?

- We start comparison of `pat[j]` with `j = 0` with characters of current window of text.
- We keep matching characters `txt[i]` and `pat[j]` and keep incrementing `i` and `j` while `pat[j]` and `txt[i]` keep **matching**.
- When we see a **mismatch**
 - We know that characters `pat[0..j-1]` match with `txt[i-j...i-1]` (Note that `j` starts with 0 and increment it only when there is a match).
 - We also know (from above definition) that `lps[j-1]` is count of characters of `pat[0..j-1]` that are both proper prefix and suffix.
 - From above two points, we can conclude that we do not need to match these `lps[j-1]` characters with `txt[i-j...i-1]` because we know that these characters will anyway match. Let us consider above example to understand this.

```
txt[] = "AAAAABAAABA"
```

```
pat[] = "AAAA"
```

```
lps[] = {0, 1, 2, 3}
```

```
i = 0, j = 0
```

```
txt[] = "AAAAABAAABA"
```

```
pat[] = "AAAA"
```

```
txt[i] and pat[j] match, do i++, j++
```

```
i = 1, j = 1
```

```
txt[] = "AAAAABAAABA"
```

```
pat[] = "AAAA"
```

```
txt[i] and pat[j] match, do i++, j++
```

```
i = 2, j = 2
```

```
txt[] = "AAAAABAAABA"
```

```
pat[] = "AAAA"
```

```
pat[i] and pat[j] match, do i++, j++
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```
txt[] = "AAAABAAABA"
pat[] = "AAA"
txt[i] and pat[j] match, do i++, j++
```

```
i = 4, j = 4
Since j == M, print pattern found and reset j,
j = lps[j-1] = lps[3] = 3
```

Here unlike Naive algorithm, we do not match first three characters of this window. Value of lps[j-1] (in above step) gave us index of next character to match.

```
i = 4, j = 3
txt[] = "AAAABAAABA"
pat[] = "AAA"
txt[i] and pat[j] match, do i++, j++
```

```
i = 5, j = 4
Since j == M, print pattern found and reset j,
j = lps[j-1] = lps[3] = 3
```

Again unlike Naive algorithm, we do not match first three characters of this window. Value of lps[j-1] (in above step) gave us index of next character to match.

```
i = 5, j = 3
txt[] = "AAAAABAAABA"
pat[] = "AAA"
txt[i] and pat[j] do NOT match and j > 0, change only j
j = lps[j-1] = lps[2] = 2
```

```
i = 5, j = 2
txt[] = "AAAAABAAABA"
pat[] = "AAA"
txt[i] and pat[j] do NOT match and j > 0, change only j
j = lps[j-1] = lps[1] = 1
```

```
pat[] =      "AAAA"
txt[i] and pat[j] do NOT match and j > 0, change only j
j = lps[j-1] = lps[0] = 0
```

```
i = 5, j = 0
txt[] = "AAAAABAAABA"
pat[] =      "AAAA"
txt[i] and pat[j] do NOT match and j is 0, we do i++.
```

```
i = 6, j = 0
txt[] = "AAAAABAAABA"
pat[] =      "AAAA"
txt[i] and pat[j] match, do i++ and j++
```

```
i = 7, j = 1
txt[] = "AAAAABAAABA"
pat[] =      "AAAA"
txt[i] and pat[j] match, do i++ and j++
```

We continue this way...

C++

```
// C++ program for implementation of KMP pattern searching
// algorithm
#include <bits/stdc++.h>

void computeLPSArray(char* pat, int M, int* lps);

// Prints occurrences of txt[] in pat[]
void KMPSearch(char* pat, char* txt)
{
    int M = strlen(pat);
    int N = strlen(txt);
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

// Preprocess the pattern (calculate lps[] array)
computeLPSArray(pat, M, lps);

int i = 0; // index for txt[]
int j = 0; // index for pat[]
while (i < N) {
    if (pat[j] == txt[i]) {
        j++;
        i++;
    }

    if (j == M) {
        printf("Found pattern at index %d ", i - j);
        j = lps[j - 1];
    }

    // mismatch after j matches
    else if (i < N && pat[j] != txt[i]) {
        // Do not match lps[0..lps[j-1]] characters,
        // they will match anyway
        if (j != 0)
            j = lps[j - 1];
        else
            i = i + 1;
    }
}

// Fills lps[] for given pattern pat[0..M-1]
void computeLPSArray(char* pat, int M, int* lps)
{
    // length of the previous longest prefix suffix
    int len = 0;

    lps[0] = 0; // lps[0] is always 0

    // the loop calculates lps[i] for i = 1 to M-1
    int i = 1;
    while (i < M) {
        if (pat[i] == pat[len]) {
            len++;
            lps[i] = len;
            i++;
        }
        else // (pat[i] != pat[len])
        {
            // mismatch after len matches
            if (len != 0)
                len = lps[len - 1];
            else
                i++;
        }
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !


```

        len = lps[len - 1];

        // Also, note that we do not increment
        // i here
    }
    else // if (len == 0)
    {
        lps[i] = 0;
        i++;
    }
}
}

// Driver program to test above function
int main()
{
    char txt[] = "ABABDABACDABABCABAB";
    char pat[] = "ABABCABAB";
    KMPSearch(pat, txt);
    return 0;
}

```

Java

```

// JAVA program for implementation of KMP pattern
// searching algorithm

class KMP_String_Matching {
    void KMPSearch(String pat, String txt)
    {
        int M = pat.length();
        int N = txt.length();

        // create lps[] that will hold the longest
        // prefix suffix values for pattern
        int lps[] = new int[M];
        int j = 0; // index for pat[]

        // Preprocess the pattern (calculate lps[]
        // array)
        computeLPSArray(pat, M, lps);

        int i = 0; // index for txt[]
        while (i < N) {
            if (pat.charAt(j) == txt.charAt(i)) {

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

        System.out.println("Found pattern "
                           + "at index " + (i - j));
        j = lps[j - 1];
    }

    // mismatch after j matches
    else if (i < N && pat.charAt(j) != txt.charAt(i)) {
        // Do not match lps[0..lps[j-1]] characters,
        // they will match anyway
        if (j != 0)
            j = lps[j - 1];
        else
            i = i + 1;
    }
}

}

void computeLPSArray(String pat, int M, int lps[])
{
    // length of the previous longest prefix suffix
    int len = 0;
    int i = 1;
    lps[0] = 0; // lps[0] is always 0

    // the loop calculates lps[i] for i = 1 to M-1
    while (i < M) {
        if (pat.charAt(i) == pat.charAt(len)) {
            len++;
            lps[i] = len;
            i++;
        }
        else // (pat[i] != pat[len])
        {
            // This is tricky. Consider the example.
            // AAACAAAA and i = 7. The idea is similar
            // to search step.
            if (len != 0) {
                len = lps[len - 1];

                // Also, note that we do not increment
                // i here
            }
            else // if (len == 0)
            {
                lps[i] = len;
                i++;
            }
        }
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```
// Driver program to test above function
public static void main(String args[])
{
    String txt = "ABABDABACDABABCABAB";
    String pat = "ABABCABAB";
    new KMP_String_Matching().KMPSearch(pat, txt);
}
// This code has been contributed by Amit Khandelwal.
```

Python

```
# Python program for KMP Algorithm
def KMPSearch(pat, txt):
    M = len(pat)
    N = len(txt)

    # create lps[] that will hold the longest prefix suffix
    # values for pattern
    lps = [0]*M
    j = 0 # index for pat[]

    # Preprocess the pattern (calculate lps[] array)
    computeLPSArray(pat, M, lps)

    i = 0 # index for txt[]
    while i < N:
        if pat[j] == txt[i]:
            i += 1
            j += 1

        if j == M:
            print ("Found pattern at index " + str(i-j))
            j = lps[j-1]

        # mismatch after j matches
        elif i < N and pat[j] != txt[i]:
            # Do not match lps[0..lps[j-1]] characters,
            # they will match anyway
            if j != 0:
                j = lps[j-1]
            else:
                i += 1

    def computeLPSArray(pat, M, lps):
        len = 0 # length of the previous longest prefix suffix
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

# the loop calculates lps[i] for i = 1 to M-1
while i < M:
    if pat[i]== pat[len]:
        len += 1
        lps[i] = len
        i += 1
    else:
        # This is tricky. Consider the example.
        # AAACAAAA and i = 7. The idea is similar
        # to search step.
        if len != 0:
            len = lps[len-1]

            # Also, note that we do not increment i here
        else:
            lps[i] = 0
            i += 1

txt = "ABABDABACDABABCABAB"
pat = "ABABCABAB"
KMPSearch(pat, txt)

# This code is contributed by Bhavya Jain

```

C#

```

// C# program for implementation of KMP pattern
// searching algorithm
using System;

class GFG {

    void KMPSearch(string pat, string txt)
    {
        int M = pat.Length;
        int N = txt.Length;

        // create lps[] that will hold the longest
        // prefix suffix values for pattern
        int[] lps = new int[M];
        int j = 0; // index for pat[]

        // Preprocess the pattern (calculate lps[]
        // array)
        computeLPSArray(pat, M, lps);
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

        i++;
    }
    if (j == M) {
        Console.WriteLine("Found pattern "
                           + "at index " + (i - j));
        j = lps[j - 1];
    }

    // mismatch after j matches
    else if (i < N && pat[j] != txt[i]) {
        // Do not match lps[0..lps[j-1]] characters,
        // they will match anyway
        if (j != 0)
            j = lps[j - 1];
        else
            i = i + 1;
    }
}

}

void computeLPSArray(string pat, int M, int[] lps)
{
    // length of the previous longest prefix suffix
    int len = 0;
    int i = 1;
    lps[0] = 0; // lps[0] is always 0

    // the loop calculates lps[i] for i = 1 to M-1
    while (i < M) {
        if (pat[i] == pat[len]) {
            len++;
            lps[i] = len;
            i++;
        }
        else // (pat[i] != pat[len])
        {
            // This is tricky. Consider the example.
            // AAACAAAA and i = 7. The idea is similar
            // to search step.
            if (len != 0) {
                len = lps[len - 1];

                // Also, note that we do not increment
                // i here
            }
            else // if (len == 0)
            {
                // ...
            }
        }
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

    }
}

// Driver program to test above function
public static void Main()
{
    string txt = "ABABDABACDABABCABAB";
    string pat = "ABABCABAB";
    new GFG().KMPSearch(pat, txt);
}

// This code has been contributed by Amit Khandelwal.

```

PHP

```

<?php
// PHP program for implementation of KMP pattern searching
// algorithm

// Prints occurrences of txt[] in pat[]
function KMPSearch($pat, $txt)
{
    $M = strlen($pat);
    $N = strlen($txt);

    // create lps[] that will hold the longest prefix suffix
    // values for pattern
    $lps=array_fill(0,$M,0);

    // Preprocess the pattern (calculate lps[] array)
    computeLPSArray($pat, $M, $lps);

    $i = 0; // index for txt[]
    $j = 0; // index for pat[]
    while ($i < $N) {
        if ($pat[$j] == $txt[$i]) {
            $j++;
            $i++;
        }

        if ($j == $M) {
            printf("Found pattern at index " . ($i - $j));
            $j = $lps[$j - 1];
        }
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

        // they will match anyway
        if ($j != 0)
            $j = $lps[$j - 1];
        else
            $i = $i + 1;
    }
}

// Fills lps[] for given pattern pat[0..M-1]
function computeLPSArray($pat, $M, &$lps)
{
    // length of the previous longest prefix suffix
    $len = 0;

    $lps[0] = 0; // lps[0] is always 0

    // the loop calculates lps[i] for i = 1 to M-1
    $i = 1;
    while ($i < $M) {
        if ($pat[$i] == $pat[$len]) {
            $len++;
            $lps[$i] = $len;
            $i++;
        }
        else // (pat[i] != pat[len])
        {
            // This is tricky. Consider the example.
            // AAACAAA and i = 7. The idea is similar
            // to search step.
            if ($len != 0) {
                $len = $lps[$len - 1];

                // Also, note that we do not increment
                // i here
            }
            else // if (len == 0)
            {
                $lps[$i] = 0;
                $i++;
            }
        }
    }
}

// Driver program to test above function

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```
// This code is contributed by chandan_jnu
?>
```

Output:

Found pattern at index 10

Preprocessing Algorithm:

In the preprocessing part, we calculate values in `lps[]`. To do that, we keep track of the length of the longest prefix suffix value (we use `len` variable for this purpose) for the previous index. We initialize `lps[0]` and `len` as 0. If `pat[len]` and `pat[i]` match, we increment `len` by 1 and assign the incremented value to `lps[i]`. If `pat[i]` and `pat[len]` do not match and `len` is not 0, we update `len` to `lps[len-1]`. See `computeLPSArray()` in the below code for details.

Illustration of preprocessing (or construction of `lps[]`)

```
pat[] = "AAACAAAA"
```

```
len = 0, i = 0.
```

```
lps[0] is always 0, we move  
to i = 1
```

```
len = 0, i = 1.
```

```
Since pat[len] and pat[i] match, do len++,  
store it in lps[i] and do i++.
```

```
len = 1, lps[1] = 1, i = 2
```

```
len = 1, i = 2.
```

```
Since pat[len] and pat[i] match, do len++,  
store it in lps[i] and do i++.
```

```
len = 2, lps[2] = 2, i = 3
```

```
len = 2. i = 3.
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

len = 1, i = 3.

Since pat[len] and pat[i] do not match and len > 0,

len = lps[len-1] = lps[0] = 0

len = 0, i = 3.

Since pat[len] and pat[i] do not match and len = 0,

Set **lps[3] = 0** and i = 4.

We know that characters pat

len = 0, i = 4.

Since pat[len] and pat[i] match, do len++,

store it in lps[i] and do i++.

len = 1, **lps[4] = 1**, i = 5

len = 1, i = 5.

Since pat[len] and pat[i] match, do len++,

store it in lps[i] and do i++.

len = 2, **lps[5] = 2**, i = 6

len = 2, i = 6.

Since pat[len] and pat[i] match, do len++,

store it in lps[i] and do i++.

len = 3, **lps[6] = 3**, i = 7

len = 3, i = 7.

Since pat[len] and pat[i] do not match and len > 0,

set len = lps[len-1] = lps[2] = 2

len = 2, i = 7.

Since pat[len] and pat[i] match, do len++,

store it in lps[i] and do i++.

len = 3, **lps[7] = 3**, i = 8

We stop here as we have constructed the whole lps[].