

Functional Pearl: Do-it-yourself module types

ANONYMOUS AUTHOR(S)

Can parameterised records and algebraic datatypes be derived from one pragmatic declaration?

Record types give a universe of discourse, parameterised record types fix parts of that universe ahead of time, and algebraic datatypes give us first-class syntax, whence evaluators and optimisers.

The answer is in the affirmative. Besides a practical shared declaration interface, which is extensible in the language, we also find that common data structures correspond to simple theories.

1 INTRODUCTION

All too often, when we program, we write the same information two or more times in our code, in different guises. For example, in Haskell, we may write a class, a record to reify that class, and an algebraic type to give us a syntax for programs written using that class. In proof assistants, this tends to get worse rather than better, as parametrized records give us a means to “stage” information. From here on, we will use Agda~Norell [2007] for our examples.

Concretely, suppose we have two monoids $(M_1, _ \circ_1 -, Id_1)$ and $(M_2, _ \circ_2 -, Id_2)$, if we know¹ that $ceq : M_1 \equiv M_2$ then it is “obvious” that $Id_2 \circ_2 (x \circ_1 Id_1) \equiv x$ for all $x : M_1$. However, as written, this does not type-check. This is because $_ \circ_2 -$ expects elements of M_2 but has been given an element of M_1 . Because we have ceq in hand, we can use $subst$ to transport things around. The resulting formula, shown as the type of $claim$ below, then typechecks, but is hideous. “subst hell” only gets worse. Below, we use pointed magmas for brevity, as the problem is the same.

```
record Magma0 : Set1 where
  field
    Carrier : Set
    _o_      : Carrier → Carrier → Carrier
    Id       : Carrier

module Awkward-Formulation (A B : Magma0)
  (ceq : Magma0.Carrier A ≡ Magma0.Carrier B)
  where
    open Magma0 A renaming (Id to Id1; _o_ to _o1_)
    open Magma0 B renaming (Id to Id2; _o_ to _o2_)

    claim : ∀ x → Id2 o2 subst id ceq (x o1 Id1) ≡ subst id ceq x
    claim = {!!}
    {- “{!!}” stands for a “hole” in Agda,
       needing replacement by an expression -}
```

It should not be this difficult to state a trivial fact. We could make things artificially prettier by defining coe to be $subst \ id \ ceq$ without changing the heart of the matter. But if $Magma_0$ is the definition used in the library we are using, we are stuck with it, if we want to be compatible with other work.

¹ The propositional equality $M_1 \equiv M_2$ means the M_i are convertible with each other when all free variables occurring in the M_i are instantiated, and otherwise are not necessarily identical. A stronger equality operator cannot be expressed in Agda.

Ideally, we would prefer to be able to express that the carriers are shared “on the nose”, which can be done as follows:

```

50 record Magma1 (Carrier : Set) : Set where
51   field
52     _%_      : Carrier → Carrier → Carrier
53     Id       : Carrier
54
55 module Nicer
56   (M : Set)    {- The shared carrier -}
57   (A B : Magma1 M)
58   where
59     open Magma1 A renaming (Id to Id1; _%_ to _%1_ )
60     open Magma1 B renaming (Id to Id2; _%_ to _%2_ )
61
62     claim : ∀ x → Id2 %2 (x %1 Id1) ≡ x
63     claim = {!!}
64
65
66

```

This is the formaluation we expected, without noise. Thus it seems that it would be better to expose the carrier. But, before long, we’d find a different concept, such as homomorphism, which is awkward in this way, and cleaner using the first approach. These two approaches are called *bundled* and *unbundled* respectively ?.

The definitions of homomorphism themselves (see below) is not so different, but the definition of composition already starts to be quite unwieldly.

```

70 record Hom0 (A B : Magma0) : Set where ...
71 record Hom1 {M1 M2 : Set} (A : Magma1 M1) (B : Magma1 M2) : Set where ...
72
73 composition0 : ∀ {A B C} → Hom0 A B → Hom0 B C → Hom0 A C
74 composition0 = {!!}
75
76 composition1 : ∀ {M1 M2 M3} {A : Magma1 M1} {B : Magma1 M2} {C : Magma1 M3}
77   → Hom1 A B → Hom1 B C → Hom1 A C
78 composition1 = {!!}
79
80
81

```

So not only are there no general rules for when to bundle or not, it is in fact guaranteed that any given choice will be sub-optimal for certain applications. Furthermore, these types are equivalent, as we can “pack away” an exposed piece, e.g., $\text{Monoid}_0 \cong \sum M : \text{Set} \bullet \text{Monoid}_1 M$. The developers of the Agda standard library [agd 2020] have chosen to expose all types and function symbols while bundling up the proof obligations at one level, and also provide a fully bundled form as a wrapper. This is also the method chosen in Lean [Hales 2018], and in Coq [Spitters and van der Weegen 2011].

While such a choice is workable, it is still not optimal. There are bundling variants that are unavailable, and would be more convenient for certain application.

We will show an automatic technique for unbundling data at will; thereby resulting in *bundling-independent representations* and in *delayed unbundling*. Our contributions are to show:

- (1) Languages with sufficiently powerful type systems and meta-programming can conflate record and term datatype declarations into one practical interface. In addition, the contents of these grouping mechanisms may be function symbols as well as propositional invariants—an example is shown at the end of Section 3. We identify the problem and the subtleties in shifting between representations in Section 2.

- (2) Parameterised records can be obtained on-demand from non-parameterised records (Section 3).
- As with Magma_0 , the traditional approach [Gross et al. 2014] to unbundling a record requires the use of transport along propositional equalities, with trivial refl -exivity proofs. In Section 3, we develop a combinator, $_:\text{waist}_$, which removes the boilerplate necessary at the type specialisation location as well as at the instance declaration location.
- (3) Programming with fixed-points of unary type constructors can be made as simple as programming with term datatypes (Section 4).

As an application, in Section 5 we show that the resulting setup applies as a semantics for a declarative pre-processing tool that accomplishes the above tasks.

For brevity, and accessibility, a number of definitions are elided and only [dashed pseudo-code] is presented in the paper, with the understanding that such functions need to be extended homomorphically over all possible term constructors of the host language. Enough is shown to communicate the techniques and ideas, as well as to make the resulting library usable. The details, which users do not need to bother with, can be found in the appendices.

2 THE PROBLEMS

There are a number of problems, with the number of parameters being exposed being the pivotal concern. To exemplify the distinctions at the type level as more parameters are exposed, consider the following approaches to formalising a dynamical system—a collection of states, a designated start state, and a transition function.

```

record DynamicSystem0 : Set1 where
  field
    State : Set
    start  : State
    next   : State → State

record DynamicSystem1 (State : Set) : Set where
  field
    start : State
    next  : State → State

record DynamicSystem2 (State : Set) (start : State) : Set where
  field
    next : State → State

```

Each DynamicSystem_i is a type constructor of i -many arguments; but it is the types of these constructors that provide insight into the sort of data they contain:

Type	Kind
DynamicSystem_0	Set_1
DynamicSystem_1	$\Pi X : \text{Set} \bullet \text{Set}$
DynamicSystem_2	$\Pi X : \text{Set} \bullet \Pi x : X \bullet \text{Set}$

We shall refer to the concern of moving from a record to a parameterised record as **the unbundling problem** [Garillot et al. 2009]. For example, moving from the *type* Set_1 to the *function type* $\Pi X : \text{Set} \bullet \text{Set}$ gets us from DynamicSystem_0 to something resembling DynamicSystem_1 , which we arrive at if we can obtain a *type constructor* $\lambda X : \text{Set} \bullet \dots$. We shall refer to the latter change as *reification* since the result is more concrete: It can be applied. This transformation will be denoted by $\Pi \rightarrow \lambda$. To clarify this subtlety, consider the following forms of the polymorphic

identity function. Notice that id_i exposes i -many details at the type level to indicate the sort it consists of. However, notice that id_0 is a type of functions whereas id_1 is a function on types. Indeed, the latter two are derived from the first one: $\text{id}_{i+1} = \Pi \rightarrow \lambda \text{id}_i$. The latter identity is proven by reflexivity in the appendices.

```

id0 : Set1
id0 =  $\Pi X : \text{Set} \bullet \Pi e : X \bullet X$ 

id1 :  $\Pi X : \text{Set} \bullet \text{Set}$ 
id1 =  $\lambda (X : \text{Set}) \rightarrow \Pi e : X \bullet X$ 

id2 :  $\Pi X : \text{Set} \bullet \Pi e : X \bullet \text{Set}$ 
id2 =  $\lambda (X : \text{Set}) (e : X) \rightarrow X$ 

```

Of course, there is also the need for descriptions of values, which leads to term datatypes. We shall refer to the shift from record types to algebraic data types as **the termtype problem**. Our aim is to obtain all of these notions —of ways to group data together— from a single user-friendly context declaration, using monadic notation.

3 MONADIC NOTATION

There is little use in an idea that is difficult to use in practice. As such, we conflate records and termtypes by starting with an ideal syntax they would share, then derive the necessary artefacts that permit it. Our choice of syntax is monadic do-notation [Moggi 1991; ?]:

```

DynamicSystem : Context  $\ell_1$ 
DynamicSystem = do State  $\leftarrow \text{Set}$ 
                  start  $\leftarrow \text{State}$ 
                  next  $\leftarrow (\text{State} \rightarrow \text{State})$ 
                  End

```

Here Context , End , and the underlying monadic bind operator are unknown. Since we want to be able to *expose* a number of fields at will, we may take Context to be types indexed by a number denoting exposure. Moreover, since records are product types, we expect there to be a recursive definition whose base case will be the identity of products, the unit type $\mathbb{1}$ —which corresponds to \top in the Agda standard library and to $()$ in Haskell.

Table 1. Elaborations of DynamicSystem at various exposure levels

Exposure	Elaboration
0	$\Sigma \text{State} : \text{Set} \bullet \Sigma \text{start} : X \bullet \Sigma \text{next} : \text{State} \rightarrow \text{State} \bullet \mathbb{1}$
1	$\Pi \text{State} : \text{Set} \bullet \Sigma \text{start} : X \bullet \Sigma \text{next} : \text{State} \rightarrow \text{State} \bullet \mathbb{1}$
2	$\Pi \text{State} : \text{Set} \bullet \Pi \text{start} : X \bullet \Sigma \text{next} : \text{State} \rightarrow \text{State} \bullet \mathbb{1}$
3	$\Pi \text{State} : \text{Set} \bullet \Pi \text{start} : X \bullet \Pi \text{next} : \text{State} \rightarrow \text{State} \bullet \mathbb{1}$

With these elaborations of DynamicSystem to guide the way, we resolve two of our unknowns.

```

{- “Contexts” are exposure-indexed types -}
Context =  $\lambda \ell \rightarrow \mathbb{N} \rightarrow \text{Set } \ell$ 

{- Every type can be used as a context -}

```

```

197   ' _ : ∀ {ℓ} → Set ℓ → Context ℓ
198   ' S = λ _ → S
199
200   {- The “empty context” is the unit type -}
201   End : ∀ {ℓ} → Context ℓ
202   End = ' 1

```

It remains to identify the definition of the underlying bind operation $\gg=$. Usually, for a type constructor m , bind is typed $\forall \{X \ Y : \text{Set}\} \rightarrow m \ X \rightarrow (X \rightarrow m \ Y) \rightarrow m \ Y$. It allows one to “extract an X -value for later use” in the $m \ Y$ context. Since our $m = \text{Context}$ is from levels to types, we need to slightly alter bind’s typing.

```

207   _>>= : ∀ {a b}
208         → (Γ : Context a)
209         → (∀ {n} → Γ n → Context b)
210         → Context (a ⊔ b)
211   (Γ >>= f) zero    = Σ γ : Γ 0 • f γ 0
212   (Γ >>= f) (suc n) = Π γ : Γ n • f γ n

```

The definition here accounts for the current exposure index: If zero, we have *record types*, otherwise *function types*. Using this definition, the above dynamical system context would need to be expressed using the lifting quote operation.

```

217   ' Set >>= λ State → ' State >>= λ start → ' (State → State) >>= λ next → End
218   {- or -}
219   do State ← ' Set
220     start ← ' State
221     next ← ' (State → State)
222   End

```

Interestingly [Bird 2009; Hudak et al. 2007], use of *do*-notation in preference to bind, $\gg=$, was suggested by John Launchbury in 1993 and was first implemented by Mark Jones in Gofer. Anyhow, with our goal of practicality in mind, we shall “build the lifting quote into the definition” of bind:

```

227   _>>= : ∀ {a b}
228         → (Γ : Set a) -- Main difference
229         → (Γ → Context b)
230         → Context (a ⊔ b)
231   (Γ >>= f) zero    = Σ γ : Γ • f γ 0
232   (Γ >>= f) (suc n) = Π γ : Γ • f γ n

```

Listing 1. Semantics: Context *do*-syntax is interpreted as Π - Σ -types

With this definition, the above declaration `DynamicSystem` typechecks. However, `DynamicSystem i` $\not\cong$ `DynamicSystemi`, instead `DynamicSystem i` are “factories”: Given i -many arguments, a product value is formed. What if we want to *instantiate* some of the factory arguments ahead of time?

```

240   N0 : DynamicSystem 0 {- See the elaborations in Table 1 -}
241   N0 = λ , 0 , suc , tt
242
243   N1 : DynamicSystem 1
244   N1 = λ State → ??? {- Impossible to complete if “State” is empty! -}

```

```

246 {- "Instantiaing" X to be N in "DynamicSystem 1" -}
247 N1' : let State = N in Σ start : State • Σ s : (State → State) • 1
248 N1' = 0 , suc , tt

```

It seems what we need is a method, say $\Pi \rightarrow \lambda$, that takes a Π -type and transforms it into a λ -expression. One could use a universe, an algebraic type of codes denoting types, to define $\Pi \rightarrow \lambda$. However, one can no longer then easily use existing types since they are not formed from the universe's constructors, thereby resulting in duplication of existing types via the universe encoding. This is neither practical nor pragmatic.

As such, we are left with pattern matching on the language's type formation primitives as the only reasonable approach. The method $\Pi \rightarrow \lambda$ is thus a macro² that acts on the syntactic term representations of types. Below is main transformation —the details can be found in Appendix A.7.

$$\boxed{\Pi \rightarrow \lambda (\Pi a : A \bullet \tau) = (\lambda a : A \bullet \tau)}$$

That is, we walk along the term tree replacing occurrences of Π with λ . For example,

```

249 Π → λ (Π → λ (DynamicSystem 2))
250 ≡ {- Definition of DynamicSystem at exposure level 2 -}
251 Π → λ (Π → λ (Π X : Set • Π s : X • Σ n : X → X • 1))
252 ≡ {- Definition of Π → λ -}
253 Π → λ (λ X : Set • Π s : X • Σ n : X → X • 1)
254 ≡ {- Homomorphism of Π → λ -}
255 λ X : Set • Π → λ (Π s : X • Σ n : X → X • 1)
256 ≡ {- Definition of Π → λ -}
257 λ X : Set • λ s : X • Σ n : X → X • 1

```

For practicality, `_:waist_` is a macro (defined in Appendix A.8) acting on contexts that repeats $\Pi \rightarrow \lambda$ a number of times in order to lift a number of field components to the parameter level.

$$\boxed{\begin{array}{l} \tau : \text{waist } n = \Pi \rightarrow \lambda^n (\tau \text{ n}) \\ \text{-----} \\ f^0 x = x \\ \text{-----} \\ f^{n+1} x = f^n (f x) \end{array}}$$

We can now “fix arguments ahead of time”. Before such demonstration, we need to be mindful of our practicality goals: One declares a grouping mechanism with `do . . . End`, which in turn has its instance values constructed with `< . . . >`.

```

258 -- Expressions of the form "... , tt" may now be written "< ... >"
259 infixr 5 < _>
260 < : ∀ {ℓ} → 1 {ℓ}
261 < = tt
262
263 < : ∀ {ℓ} {S : Set ℓ} → S → S
264 < s = s
265
266 < : ∀ {ℓ} {S : Set ℓ} → S → S × (1 {ℓ})
267 < s = s , tt

```

²A *macro* is a function that manipulates the abstract syntax trees of the host language. In particular, it may take an arbitrary term, shuffle its syntax to provide possibly meaningless terms or terms that could not be formed without pattern matching on the possible syntactic constructions. An up to date and gentle introduction to reflection in Agda can be found at [Al-hassy 2019b]

The following instances of grouping types demonstrate how information moves from the body level to the parameter level.

```

 $\mathcal{N}^0$  : DynamicSystem :waist 0
 $\mathcal{N}^0$  = <  $\mathbb{N}$  , 0 , suc >

 $\mathcal{N}^1$  : (DynamicSystem :waist 1)  $\mathbb{N}$ 
 $\mathcal{N}^1$  = < 0 , suc >

 $\mathcal{N}^2$  : (DynamicSystem :waist 2)  $\mathbb{N}$  0
 $\mathcal{N}^2$  = < suc >

 $\mathcal{N}^3$  : (DynamicSystem :waist 3)  $\mathbb{N}$  0 suc
 $\mathcal{N}^3$  = < >

```

Using `:waist i` we may fix the first i -parameters ahead of time. Indeed, the type `(DynamicSystem :waist 1) \mathbb{N}` is the type of dynamic systems over carrier \mathbb{N} , whereas `(DynamicSystem :waist 2) \mathbb{N} 0` is the type of dynamic systems over carrier \mathbb{N} and start state 0.

Examples of the need for such on-the-fly unbundling can be found in numerous places in the Haskell standard library. For instance, the standard libraries [dat 2020] have two isomorphic copies of the integers, called `Sum` and `Product`, whose reason for being is to distinguish two common monoids: The former is for *integers with addition* whereas the latter is for *integers with multiplication*. An orthogonal solution would be to use contexts:

```

Monoid :  $\forall \ell \rightarrow$  Context ( $\ell$  suc  $\ell$ )
Monoid  $\ell$  = do Carrier  $\leftarrow$  Set  $\ell$ 
            _ $\oplus$ _  $\leftarrow$  (Carrier  $\rightarrow$  Carrier  $\rightarrow$  Carrier)
            Id  $\leftarrow$  Carrier
            leftId  $\leftarrow \forall \{x : \text{Carrier}\} \rightarrow x \oplus \text{Id} \equiv x$ 
            rightId  $\leftarrow \forall \{x : \text{Carrier}\} \rightarrow \text{Id} \oplus x \equiv x$ 
            assoc  $\leftarrow \forall \{x y z\} \rightarrow (x \oplus y) \oplus z \equiv x \oplus (y \oplus z)$ 
            End { $\ell$ }

```

With this context, `(Monoid ℓ_0 :waist 2) M \oplus` is the type of monoids over *particular* types M and *particular* operations \oplus . Of-course, this is orthogonal, since traditionally unification on the carrier type M is what makes typeclasses and canonical structures [Mahboubi and Tassi 2013] useful for ad-hoc polymorphism.

4 TERMTYPES AS FIXED-POINTS

We have a practical monadic syntax for possibly parameterised record types that we would like to extend to termtypes. Algebraic data types are a means to declare concrete representations of the least fixed-point of a functor; see [Swierstra 2008] for more on this idea. for more on this idea. In particular, the description language \mathbb{D} for dynamical systems, below, declares concrete constructors for a fixpoint of a certain functor F ; i.e., $\mathbb{D} \cong \text{Fix } F$ where:

```

data  $\mathbb{D}$  : Set where
  startD :  $\mathbb{D}$ 
  nextD :  $\mathbb{D} \rightarrow \mathbb{D}$ 

F : Set  $\rightarrow$  Set
F =  $\lambda (D : \text{Set}) \rightarrow 1 \uplus D$ 

```

```

344 data Fix (F : Set → Set) : Set where
345   μ : F (Fix F) → Fix F

```

The problem is whether we can derive F from DynamicSystem . Let us attempt a quick calculation sketching the necessary transformation steps (informally expressed via “ \Rightarrow ”):

```

348   do X ← Set; z ← X; s ← (X → X); End
349   ⇒ {- Use existing interpretation to obtain a record. -}
350     Σ X : Set • Σ z : X • Σ s : (X → X) • 1
351   ⇒ {- Pull out the carrier, “:waist 1”,
352        to obtain a type constructor using “Π→λ”. -}
353     λ X : Set • Σ z : X • Σ s : (X → X) • 1
354   ⇒ {- Termtypes constructors target the declared type,
355        so only their sources matter. E.g., ‘z : X’ is a
356        nullary constructor targeting the carrier ‘X’.
357        This introduces 1 types, so any existing
358        occurrences are dropped via 0. -}
359     λ X : Set • Σ z : 1 • Σ s : X • 0
360   ⇒ {- Termtypes are sums of products. -}
361     λ X : Set • 1 ⊔ X ⊔ 0
362   ⇒ {- Termtypes are fixpoints of type constructors. -}
363     Fix (λ X • 1 ⊔ X) -- i.e., D

```

Since we may view an algebraic data-type as a fixed-point of the functor obtained from the union of the sources of its constructors, it suffices to treat the fields of a record as constructors, then obtain their sources, then union them. That is, since algebraic-datatype constructors necessarily target the declared type, they are determined by their sources. For example, considered as a unary constructor $\text{op} : A \rightarrow B$ targets the type termtype B and so its source is A . The details on the operations \Downarrow , $\Sigma \rightarrow \uplus$, and sources characterised by the pseudocode below can be found in appendices A.3.4, A.11.4, and A.11.3, respectively. It suffices to know that $\Sigma \rightarrow \uplus$ rewrites dependent-sums into sums, which requires the second argument to lose its reference to the first argument which is accomplished by \Downarrow ; further details can be found in the appendix.

```

374  ⌞⌋ τ = “reduce all de Bruijn indices within τ by 1”
375
376  Σ → ⊔ (Σ a : A • Ba) = A ⊔ Σ → ⊔ (⌋ Ba)
377
378  sources (λ x : (Π a : A • Ba) • τ) = (λ x : A • sources τ)
379  sources (λ x : A • τ) = (λ x : 1 • sources τ)
380
381  termtype τ = Fix (Σ → ⊔ (sources τ))

```

It is instructive to work through the process of how \mathbb{D} is obtained from termtype in order to demonstrate that this approach to algebraic data types is practical.

```

385   D = termtype (DynamicSystem :waist 1)
386
387   -- Pattern synonyms for more compact presentation
388   pattern startD = μ (inj1 tt) -- : D
389   pattern nextD e = μ (inj2 (inj1 e)) -- : D → D

```

With these pattern declarations, we can actually use the more meaningful names startD and nextD when pattern matching, instead of the seemingly daunting μ -inj-jections. For instance,

we can immediately see that the natural numbers act as the description language for dynamical systems:

```

to :  $\mathbb{D} \rightarrow \mathbb{N}$ 
to startD = 0
to (nextD x) = suc (to x)

from :  $\mathbb{N} \rightarrow \mathbb{D}$ 
from zero = startD
from (suc n) = nextD (from n)

```

Readers whose language does not have **pattern** clauses need not despair. With the macro

$$\text{Inj } n \ x = \mu (\text{inj}_2^n (\text{inj}_1 \ x))$$

we may define `startD = Inj 0 tt` and `nextD e = Inj 1 e`—that is, constructors of termtypes are particular injections into the possible summands that the termtype consists of. Details on this macro may be found in appendix A.11.6.

5 RELATED WORKS

Surprisingly, conflating parameterised and non-parameterised record types with termtypes *within a language in a practical fashion* has not been done before.

The PackageFormer [Al-hassy 2019a; Al-hassy et al. 2019] editor extension reads contexts—in nearly the same notation as ours—enclosed in dedicated comments, then generates and imports Agda code from them seamlessly in the background whenever typechecking happens. The framework provides a fixed number of meta-primitives for producing arbitrary notions of grouping mechanisms, and allows arbitrary Emacs Lisp [Graham 1995] to be invoked in the construction of complex grouping mechanisms.

Table 2. Comparing the in-language Context mechanism with the PackageFormer editor extension

	PackageFormer	Contexts
Type of Entity	Preprocessing Tool	Language Library
Specification Language	Lisp + Agda	Agda
Well-formedness Checking	✗	✓
Termination Checking	✓	✓
Elaboration Tooltips	✓	✗
Rapid Prototyping	✓	✓ (Slower)
Usability Barrier	None	None
Extensibility Barrier	Lisp	Weak Metaprogramming

The PackageFormer paper [Al-hassy et al. 2019] provided the syntax necessary to form useful grouping mechanisms but was shy on the semantics of such constructs. We have chosen the names of our combinators to closely match those of PackageFormer’s with an aim of furnishing the mechanism with semantics by construing the syntax as semantics-functions; i.e., we have a shallow embedding of PackageFormer’s constructs as Agda entities:

PackageFormer’s `_:kind_` meta-primitive dictates how an abstract grouping mechanism should be viewed in terms of existing Agda syntax. However, unlike PackageFormer, all of our syntax consists of legitimate Agda terms. Since language syntax is being manipulated, we are forced to implement the `_:kind_` meta-primitive as a macro—further details can be found in Appendix A.13.

Table 3. Contexts as a semantics for PackageFormer constructs

Syntax	Semantics
PackageFormer	Context
:waist	:waist
$\oplus \rightarrow$	Forward function application
:kind	:kind, see below
:level	Agda built-in
:alter-elements	Agda macros

```

data Kind : Set where
  'record   : Kind
  'typeclass : Kind
  'data     : Kind

```

```

-----
C :kind 'record = C 0
-----
C :kind 'typeclass = C :waist 1
-----
C :kind 'data = termtype (C :waist 1)
-----

```

We did not expect to be able to define a full Agda implementation of the semantics of PackageFormer’s syntactic constructs due to Agda’s rather constrained metaprogramming mechanism. However, it is important to note that PackageFormer’s Lisp extensibility expedites the process of trying out arbitrary grouping mechanisms —such as partial-choices of pushouts and pullbacks along user-provided assignment functions— since it is all either string or symbolic list manipulation. On the Agda side, using contexts, it would require substantially more effort due to the limited reflection mechanism and the intrusion of the stringent type system.

6 CONCLUSION

Starting from the insight that related grouping mechanisms could be unified, we showed how related structures can be obtained from a single declaration using a practical interface. The resulting framework, based on contexts, still captures the familiar record declaration syntax as well as the expressivity of usual algebraic datatype declarations —at the minimal cost of using pattern declarations to aide as user-chosen constructor names. We believe that our approach to using contexts as general grouping mechanisms *with* a practical interface are interesting contributions.

We used the focus on practicality to guide the design of our context interface, and provided interpretations both for the rather intuitive “contexts are name-type records” view, and for the novel “contexts are fixed-points” view for termtypes. In addition, to obtain parameterised variants, we needed to explicitly form “contexts whose contents are over a given ambient context” —e.g., contexts of vector spaces are usually discussed with the understanding that there is a context of fields that can be referenced— which we did using the name binding mechanism of do-notation. These relationships are summarised in the following table.

Table 4. Contexts embody all kinds of grouping mechanisms

Concept	Concrete Syntax	Description
Context	$\text{do } S \leftarrow \text{Set}; s \leftarrow S; n \leftarrow (S \rightarrow S); \text{End}$	“name-type pairs”
Record Type	$\Sigma S : \text{Set} \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet \mathbb{1}$	“bundled-up data”
Function Type	$\Pi S \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet \mathbb{1}$	“a type of functions”
Type constructor	$\lambda S \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet \mathbb{1}$	“a function on types”
Algebraic datatype	$\text{data } \mathbb{D} : \text{Set} \text{ where } s : \mathbb{D}; n : \mathbb{D} \rightarrow \mathbb{D}$	“a descriptive syntax”

To those interested in exotic ways to group data together —such as, mechanically deriving product types and homomorphism types of theories— we offer an interface that is extensible using Agda’s reflection mechanism. In comparison with, for example, special-purpose preprocessing tools, this has obvious advantages in accessibility and semantics.

To Agda programmers, this offers a standard interface for grouping mechanisms that had been sorely missing, with an interface that is so familiar that there would be little barrier to its use. In particular, as we have shown, it acts as an in-language library for exploiting relationships between free theories and data structures. As we have only presented the high-level definitions of the core combinators, leaving the Agda-specific details to the appendices, it is also straightforward to translate the library into other dependently-typed languages.

7 VECTOR SPACES

Consider the signature of vector spaces V over a field F .

```

VecSpcSig : Context  $\ell_1$ 
VecSpcSig = do F  ← Set
              V  ← Set
              0   ← F
              1   ← F
              _+_ ← (F → F → F)
              o   ← V
              _*_ ← (F → V → V)
              _·_ ← (V → V → F)
              End0

```

We can expose V and F so that they can be varied.

```

VSInterface : (Field Vectors : Set) → Set
VSInterface F V = (VecSpcSig :waist 2) F V

```

We conjecture that the terms over such vector space signatures are similar to lists (vectors) consisting of elements (field scalars), but we also have two additional nullary constructors, a pairing constructor, and a branching constructor. That is, we have a structure amalgamating both lists and binary trees.

```

data Ring (Scalar : Set) : Set where
  zeros : Ring Scalar
  ones  : Ring Scalar
  pluss : Scalar → Scalar → Ring Scalar
  zerov : Ring Scalar
  prod  : Scalar → Ring Scalar → Ring Scalar
  dot   : Ring Scalar → Ring Scalar → Ring Scalar

```

We confirm this claim by relying on the mechanical approach to forming term types, then witnessing a view between the two.

```

VSTerm : (Field : Set) → Set
VSTerm = λ F → termtype ((VecSpcSig :waist 2) F)
{- ≅ Fix (λ X → 1
    ⊕ 1      -- Representation of additive unit, zero
    ⊕ F × F  -- Representation of multiplicative unit, one
    ⊕ F × F  -- Pair of scalars to be summed
    ⊕ 1      -- Representation of the zero vector
    ⊕ F × X  -- Pair of arguments to be scalar-producted
    ⊕ X × X  -- Pair of vectors to be dot-producted
-}

-- Convenience synonyms for more compact presentation & meaningful names
pattern 0s      = μ (inj1 tt)
pattern 1s      = μ (inj2 (inj1 tt))
pattern +s x y   = μ (inj2 (inj2 (inj1 (x , (y , tt)))))
pattern 0v      = μ (inj2 (inj2 (inj2 (inj1 tt))))
pattern *v x xs  = μ (inj2 (inj2 (inj2 (inj2 (inj1 (x , (xs , tt)))))
pattern ·v xs ys = μ (inj2 (inj2 (inj2 (inj2 (inj2 (inj1 (xs , (ys , tt)))))

```

Now the view: It simply associated constructors of the same shape, recursively.

```

view : ∀ {F} → VSTerm F → Ring F
view 0s      = zeros
view 1s      = ones
view (x +s y) = pluss x y
view 0v      = zerov
view (x *v xs) = prod x (view xs)
view (xs ·v ys) = dot (view xs) (view ys)

```

Neato.

REFERENCES

2020. Agda Standard Library. <https://github.com/agda/agda-stdlib>
2020. Haskell Basic Libraries — Data.Monoid. <http://hackage.haskell.org/package/base-4.12.0.0/docs/Data-Monoid.html>
- Musa Al-hassy. 2019a. The Next 700 Module Systems: Extending Dependently-Typed Languages to Implement Module System Features In The Core Language. <https://alhassy.github.io/next-700-module-systems-proposal/thesis-proposal.pdf>
- Musa Al-hassy. 2019b. A slow-paced introduction to reflection in Agda —Tactics! <https://github.com/alhassy/gentle-intro-to-reflection>
- Musa Al-hassy, Jacques Carette, and Wolfram Kahl. 2019. A language feature to unbundle data at will (short paper). In *Proceedings of the 18th ACM SIGPLAN International Conference on Generative Programming: Concepts and Experiences, GPCE 2019, Athens, Greece, October 21-22, 2019*, Ina Schaefer, Christoph Reichenbach, and Tijs van der Storm (Eds.). ACM, 14–19. <https://doi.org/10.1145/3357765.3359523>
- Richard Bird. 2009. Thinking Functionally with Haskell. (2009). <https://doi.org/10.1017/cbo9781316092415>
- François Garillot, Georges Gonthier, Assia Mahboubi, and Laurence Rideau. 2009. Packaging Mathematical Structures. In *Theorem Proving in Higher Order Logics (Lecture Notes in Computer Science)*, Tobias Nipkow and Christian Urban (Eds.), Vol. 5674. Springer, Munich, Germany. <https://hal.inria.fr/inria-00368403>
- Paul Graham. 1995. *ANSI Common Lisp*. Prentice Hall Press, USA.
- Jason Gross, Adam Chlipala, and David I. Spivak. 2014. Experience Implementing a Performant Category-Theory Library in Coq. *arXiv:math.CT/1401.7694v2*
- Tom Hales. 2018. A Review of the Lean Theorem Prover. <https://jiggerwit.wordpress.com/2018/09/18/a-review-of-the-lean-theorem-prover/>

- Paul Hudak, John Hughes, Simon L. Peyton Jones, and Philip Wadler. 2007. A history of Haskell: being lazy with class. In *Proceedings of the Third ACM SIGPLAN History of Programming Languages Conference (HOPL-III)*, San Diego, California, USA, 9-10 June 2007, Barbara G. Ryder and Brent Hailpern (Eds.). ACM, 1–55. <https://doi.org/10.1145/1238844.1238856>
- Assia Mahboubi and Enrico Tassi. 2013. Canonical Structures for the working Coq user. In *ITP 2013, 4th Conference on Interactive Theorem Proving (LNCS)*, Sandrine Blazy, Christine Paulin, and David Pichardie (Eds.), Vol. 7998. Springer, Rennes, France, 19–34. https://doi.org/10.1007/978-3-642-39634-2_5
- Eugenio Moggi. 1991. Notions of Computation and Monads. *Inf. Comput.* 93, 1 (1991), 55–92. [https://doi.org/10.1016/0890-5401\(91\)90052-4](https://doi.org/10.1016/0890-5401(91)90052-4)
- Ulf Norell. 2007. *Towards a Practical Programming Language Based on Dependent Type Theory*. Ph.D. Dissertation. Dept. Comp. Sci. and Eng., Chalmers Univ. of Technology.
- Bas Spitters and Eelis van der Weegen. 2011. Type classes for mathematics in type theory. *Mathematical Structures in Computer Science* 21, 4 (2011), 795–825. <https://doi.org/10.1017/S0960129511000119>
- Wouter Swierstra. 2008. Data types à la carte. *J. Funct. Program.* 18, 4 (2008), 423–436. <https://doi.org/10.1017/S0956796808006758>
- Jim Woodcock and Jim Davies. 1996. *Using Z: Specification, Refinement, and Proof*. Prentice-Hall, Inc., USA.

A APPENDICES

Below is the entirety of the Context library discussed in the paper proper.

```
module Context where
```

A.1 Imports

```
open import Level renaming (_⊔_ to _⊔_; suc to ℓsuc; zero to ℓ₀)
open import Relation.Binary.PropositionalEquality
open import Relation.Nullary

open import Data.Nat
open import Data.Fin as Fin using (Fin)
open import Data.Maybe hiding (<=>=)

open import Data.Bool using (Bool ; true ; false)
open import Data.List as List using (List ; [] ; _::_ ; _::ʳ_; sum)

ℓ₁ = Level.suc ℓ₀
```

A.2 Quantifiers $\Pi\bullet/\Sigma\bullet$ and Products/Sums

We shall use Z-style quantifier notation [Woodcock and Davies 1996] in which the quantifier dummy variables are separated from the body by a large bullet.

In Agda, we use \backslash : to obtain the “ghost colon” since standard colon $:$ is an Agda operator.

Even though Agda provides $\forall (x : \tau) \rightarrow fx$ as a built-in syntax for Π -types, we have chosen the Z-style one below to mirror the notation for Σ -types, which Agda provides as **record** declarations. In the paper proper, in the definition of **bind**, the subtle shift between Σ -types and Π -types is easier to notice when the notations are so similar that only the quantifier symbol changes.

```
open import Data.Empty using (⊥)
open import Data.Sum
open import Data.Product
open import Function using (_o_)

Σ• : ∀ {a b} (A : Set a) (B : A → Set b) → Set _
Σ• = Σ

infix -666 Σ•
syntax Σ• A (λ x → B) = Σ x : A • B

Π• : ∀ {a b} (A : Set a) (B : A → Set b) → Set _
```

```

638  II:• A B = (x : A) → B x
639
640  infix -666 II:•
641  syntax II:• A (λ x → B) = II x : A • B
642
643  record T {ℓ} : Set ℓ where
644    constructor tt
645
646  1 = T {ℓ0}
647  0 = ⊥

```

A.3 Reflection

We form a few metaprogramming utilities we would have expected to be in the standard library.

```

650  import Data.Unit as Unit
651  open import Reflection hiding (name; Type) renaming (>=>_ to >=>_m_)

```

A.3.1 Single argument application.

```

652  _app_ : Term → Term → Term
653  (def f args) app arg' = def f (args ::r arg (arg-info visible relevant) arg')
654  (con f args) app arg' = con f (args ::r arg (arg-info visible relevant) arg')
655  {-# CATCHALL #-}
656  tm app arg' = tm

```

Notice that we maintain existing applications:

```

657  quoteTerm (f x) app quoteTerm y ≈ quoteTerm (f x y)

```

A.3.2 Reify \mathbb{N} term encodings as \mathbb{N} values.

```

658  toN : Term → ℕ
659  toN (lit (nat n)) = n
660  {-# CATCHALL #-}
661  toN _ = 0

```

A.3.3 The Length of a Term.

```

662  arg-term : ∀ {ℓ} {A : Set ℓ} → (Term → A) → Arg Term → A
663  arg-term f (arg i x) = f x
664
665  {-# TERMINATING #-}
666  lengtht : Term → ℕ
667  lengtht (var x args) = 1 + sum (List.map (arg-term lengtht) args)
668  lengtht (con c args) = 1 + sum (List.map (arg-term lengtht) args)
669  lengtht (def f args) = 1 + sum (List.map (arg-term lengtht) args)
670  lengtht (lam v (abs s x)) = 1 + lengtht x
671  lengtht (pat-lam cs args) = 1 + sum (List.map (arg-term lengtht) args)
672  lengtht (II[ x : A ] Bx) = 1 + lengtht Bx
673  {-# CATCHALL #-}
674  -- sort, lit, meta, unknown
675  lengtht t = 0

```

Here is an example use:

```

676  _ : lengtht (quoteTerm (Σ x : ℕ • x ≡ x)) ≡ 10
677  _ = refl

```

A.3.4 Decreasing de Bruijn Indices. Given a quantification $(\oplus x : \tau \bullet fx)$, its body fx may refer to a free variable x . If we decrement all de Bruijn indices fx contains, then there would be no reference to x .

```

687 var-dec0 : (fuel : ℕ) → Term → Term
688 var-dec0 zero t = t
689 -- Let's use an "impossible" term.
690 var-dec0 (suc n) (var zero args) = def (quote ⊥) []
691 var-dec0 (suc n) (var (suc x) args) = var x args
692 var-dec0 (suc n) (con c args) = con c (map-Args (var-dec0 n) args)
693 var-dec0 (suc n) (def f args) = def f (map-Args (var-dec0 n) args)
694 var-dec0 (suc n) (lam v (abs s x)) = lam v (abs s (var-dec0 n x))
695 var-dec0 (suc n) (pat-lam cs args) = pat-lam cs (map-Args (var-dec0 n) args)
696 var-dec0 (suc n) (Π[ s : arg i A ] B) = Π[ s : arg i (var-dec0 n A) ] var-dec0 n B
697 {-# CATCHALL #-}
698 -- sort, lit, meta, unknown
699 var-dec0 n t = t

```

In the paper proper, var-dec was mentioned once under the name \Downarrow .

```

700 var-dec : Term → Term
701 var-dec t = var-dec0 (lengtht t) t

```

Notice that we made the decision that x , the body of $(\oplus x \bullet x)$, will reduce to \emptyset , the empty type. Indeed, in such a situation the only Debrujin index cannot be reduced further. Here is an example:

```

702 _ : ∀ {x : ℕ} → var-dec (quoteTerm x) ≡ quoteTerm ⊥
703 _ = refl

```

A.4 Context Monad

```

704 Context = λ ℓ → ℕ → Set ℓ
705
706 infix -1000 ' _
707 ' _ : ∀ {ℓ} → Set ℓ → Context ℓ
708 ' S = λ _ → S
709
710 End : ∀ {ℓ} → Context ℓ
711 End = ' ⊤
712
713 End0 = End {ℓ0}
714
715 _>=>_ : ∀ {a b}
716   → (Γ : Set a) -- Main difference
717   → (Γ → Context b)
718   → Context (a ⊔ b)
719 (Γ >=> f) N.zero = Σ γ : Γ • f γ ∅
720 (Γ >=> f) (suc n) = (γ : Γ) → f γ n
721
722

```

A.5 $\langle \rangle$ Notation

As mentioned, grouping mechanisms are declared with `do . . . End`, and instances of them are constructed using $\langle \dots \rangle$.

```

723 -- Expressions of the form "... , tt" may now be written "< ... >"
724
725 infixr 5 < _>
726 < _ : ∀ {ℓ} → T {ℓ}
727 < _ = tt
728
729 < : ∀ {ℓ} {S : Set ℓ} → S → S
730 < s = s
731
732 _> : ∀ {ℓ} {S : Set ℓ} → S → S × T {ℓ}
733 s > = s , tt
734
735

```

A.6 DynamicSystem Context

```

DynamicSystem : Context (ℓsuc Level.zero)
DynamicSystem = do X ← Set
                z ← X
                s ← (X → X)
                End {Level.zero}

-- Records with n-Parameters, n : 0..3
A B C D : Set1
A = DynamicSystem 0 -- ∑ X : Set • ∑ z : X • ∑ s : X → X • T
B = DynamicSystem 1 -- (X : Set) → ∑ z : X • ∑ s : X → X • T
C = DynamicSystem 2 -- (X : Set) (z : X) → ∑ s : X → X • T
D = DynamicSystem 3 -- (X : Set) (z : X) → (s : X → X) → T

_ : A ≡ (∑ X : Set • ∑ z : X • ∑ s : (X → X) • T) ; _ = refl
_ : B ≡ (∏ X : Set • ∑ z : X • ∑ s : (X → X) • T) ; _ = refl
_ : C ≡ (∏ X : Set • ∏ z : X • ∑ s : (X → X) • T) ; _ = refl
_ : D ≡ (∏ X : Set • ∏ z : X • ∏ s : (X → X) • T) ; _ = refl

stability : ∀ {n} → DynamicSystem (3 + n)
              ≡ DynamicSystem 3
stability = refl

B-is-empty : ¬ B
B-is-empty b = proj1( b ⊥ )

N0 : DynamicSystem 0
N0 = N , 0 , suc , tt

N : DynamicSystem 0
N = ⟨ N , 0 , suc ⟩

B-on-N : Set
B-on-N = let X = N in ∑ z : X • ∑ s : (X → X) • T

ex : B-on-N
ex = ⟨ 0 , suc ⟩

```

A.7 $\Pi \rightarrow \lambda$

```

Π→λ-helper : Term → Term
Π→λ-helper (pi a b)      = lam visible b
Π→λ-helper (lam a (abs x y)) = lam a (abs x (Π→λ-helper y))
{-# CATCHALL #-}
Π→λ-helper x = x

macro
  Π→λ : Term → Term → TC Unit.T
  Π→λ tm goal = normalise tm >=>m λ tm' → unify (Π→λ-helper tm') goal

```

A.8 $_:\text{waist}__$

```

waist-helper : N → Term → Term
waist-helper zero t      = t
waist-helper (suc n) t = waist-helper n (Π→λ-helper t)

macro
  _:\waist_ : Term → Term → Term → TC Unit.T

```



```

785     _ : waist_ t n goal =      normalise (t app n)
786                               >>=  $m$   $\lambda$  t'  $\rightarrow$  unify (waist-helper (toN n) t') goal

```

A.9 DynamicSystem :waist i

```

789  A' : Set1
790  B' :  $\forall$  (X : Set)  $\rightarrow$  Set
791  C' :  $\forall$  (X : Set) (x : X)  $\rightarrow$  Set
792  D' :  $\forall$  (X : Set) (x : X) (s : X  $\rightarrow$  X)  $\rightarrow$  Set

793  A' = DynamicSystem :waist 0
794  B' = DynamicSystem :waist 1
795  C' = DynamicSystem :waist 2
796  D' = DynamicSystem :waist 3

797  N0 : A'
798  N0 =  $\langle$  N , 0 , suc  $\rangle$ 

799
800  N1 : B' N
801  N1 =  $\langle$  0 , suc  $\rangle$ 

802
803  N2 : C' N 0
804  N2 =  $\langle$  suc  $\rangle$ 

805
806  N3 : D' N 0 suc
807  N3 =  $\langle$ 

```

It may be the case that $\Gamma \ 0 \equiv \Gamma \text{ :waist } 0$ for every context Γ .

```

808  _ : DynamicSystem 0  $\equiv$  DynamicSystem :waist 0
809  _ = refl

```

A.10 Field projections

```

812  Field0 : N  $\rightarrow$  Term  $\rightarrow$  Term
813  Field0 zero c    = def (quote proj1) (arg (arg-info visible relevant) c :: [])
814  Field0 (suc n) c = Field0 n (def (quote proj2) (arg (arg-info visible relevant) c :: []))

815  macro
816    Field : N  $\rightarrow$  Term  $\rightarrow$  Term  $\rightarrow$  TC Unit.T
817    Field n t goal = unify goal (Field0 n t)

```

A.11 Termtypes

Using the guide, ??, outlined in the paper proper we shall form D_i for each stage in the calculation.

A.11.1 Stage 1: Records.

```

822  D1 = DynamicSystem 0

824  1-records : D1  $\equiv$  ( $\Sigma$  X : Set •  $\Sigma$  z : X •  $\Sigma$  s : (X  $\rightarrow$  X) • T)
825  1-records = refl

```

A.11.2 Stage 2: Parameterised Records.

```

828  D2 = DynamicSystem :waist 1

829  2-funcs : D2  $\equiv$  ( $\lambda$  (X : Set)  $\rightarrow$   $\Sigma$  z : X •  $\Sigma$  s : (X  $\rightarrow$  X) • T)
830  2-funcs = refl

```

A.11.3 Stage 3: Sources. Let's begin with an example to motivate the definition of sources.

```

834   _ : quoteTerm (V {x : N} → N)
835   ≡ pi (arg (arg-info hidden relevant) (quoteTerm N)) (abs "x" (quoteTerm N))
836   _ = refl

```

We now form two sources-helper utilities, although we suspect they could be combined into one function.

```

839 sources0 : Term → Term
840 -- Otherwise:
841 sources0 (Π[ a : arg i A ] (Π[ b : arg _ Ba ] Cab)) =
842   def (quote _X_) (vArg A
843     :: vArg (def (quote _X_)
844       (vArg (var-dec Ba) :: vArg (var-dec (var-dec (sources0 Cab))) :: []))
845     :: [])
846 sources0 (Π[ a : arg (arg-info hidden _) A ] Ba) = quoteTerm 0
847 sources0 (Π[ x : arg i A ] Bx) = A
848 {-# CATCHALL #-}
849 -- sort, lit, meta, unknown
850 sources0 t = quoteTerm 1
851
852 {-# TERMINATING #-}
853 sources1 : Term → Term
854 sources1 (Π[ a : arg (arg-info hidden _) A ] Ba) = quoteTerm 0
855 sources1 (Π[ a : arg i A ] (Π[ b : arg _ Ba ] Cab)) = def (quote _X_) (vArg A ::
856   vArg (def (quote _X_) (vArg (var-dec Ba) :: vArg (var-dec (var-dec (sources0 Cab))) :: [])) :: [])
857 sources1 (Π[ x : arg i A ] Bx) = A
858 sources1 (def (quote Σ) (ℓ1 :: ℓ2 :: τ :: body))
859   = def (quote Σ) (ℓ1 :: ℓ2 :: map-Arg sources0 τ :: List.map (map-Arg sources1) body)
860 -- This function introduces 1s, so let's drop any old occurrences a la 0.
861 sources1 (def (quote T) _) = def (quote 0) []
862 sources1 (lam v (abs s x)) = lam v (abs s (sources1 x))
863 sources1 (var x args) = var x (List.map (map-Arg sources1) args)
864 sources1 (con c args) = con c (List.map (map-Arg sources1) args)
865 sources1 (def f args) = def f (List.map (map-Arg sources1) args)
866 sources1 (pat-lam cs args) = pat-lam cs (List.map (map-Arg sources1) args)
867 {-# CATCHALL #-}
868 -- sort, lit, meta, unknown
869 sources1 t = t

```

We now form the macro and some unit tests.

```

867 macro
868   sources : Term → Term → TC Unit.T
869   sources tm goal = normalise tm >>= m λ tm' → unify (sources1 tm') goal
870
871 _ : sources (N → Set) ≡ N
872 _ = refl
873
874 _ : sources (Σ x : (N → Fin 3) • N) ≡ (Σ x : N • N)
875 _ = refl
876
877 _ : ∀ {ℓ : Level} {A B C : Set}
878   → sources (Σ x : (A → B) • C) ≡ (Σ x : A • C)
879 _ = refl
880
881 _ : sources (Fin 1 → Fin 2 → Fin 3) ≡ (Σ _ : Fin 1 • Fin 2 × 1)
882 _ = refl
883
884 _ : sources (Σ f : (Fin 1 → Fin 2 → Fin 3 → Fin 4) • Fin 5)

```

```

883     ≡ (Σ f : (Fin 1 × Fin 2 × Fin 3) • Fin 5)
884   _ = refl

885
886   _ : ∀ {A B C : Set} → sources (A → B → C) ≡ (A × B × 1)
887   _ = refl

888   _ : ∀ {A B C D E : Set} → sources (A → B → C → D → E)
889                                     ≡ Σ A (λ _ → Σ B (λ _ → Σ C (λ _ → Σ D (λ _ → T))))
890   _ = refl

```

Design decision: Types starting with implicit arguments are *invariants*, not *constructors*.

```

892   -- one implicit
893   _ : sources (∀ {x : N} → x ≡ x) ≡ 0
894   _ = refl

895   -- multiple implicits
896   _ : sources (∀ {x y z : N} → x ≡ y) ≡ 0
897   _ = refl

```

The third stage can now be formed.

```

899   D3 = sources D2

900
901   3-sources : D3 ≡ λ (X : Set) → Σ z : 1 • Σ s : X • 0
902   3-sources = refl

```

A.11.4 Stage 4: $\Sigma \rightarrow \cup$ –Replacing Products with Sums.

```

904   {-# TERMINATING #-}
905   Σ→∪0 : Term → Term
906   Σ→∪0 (def (quote Σ) (h1 :: h0 :: arg i A :: arg i1 (lam v (abs s x)) :: []))
907     = def (quote _∪_) (h1 :: h0 :: arg i A :: vArg (Σ→∪0 (var-dec x)) :: [])
908   -- Interpret “End” in do-notation to be an empty, impossible, constructor.
909   Σ→∪0 (def (quote T) _) = def (quote ⊥) []
910   -- Walk under λ's and Π's.
911   Σ→∪0 (lam v (abs s x)) = lam v (abs s (Σ→∪0 x))
912   Σ→∪0 (Π[ x : A ] Bx) = Π[ x : A ] Σ→∪0 Bx
913   {-# CATCHALL #-}
914   Σ→∪0 t = t

915   macro
916     Σ→∪ : Term → Term → TC Unit.T
917     Σ→∪ tm goal = normalise tm >>= m λ tm' → unify (Σ→∪0 tm') goal

918   -- Unit tests
919   _ : Σ→∪ (Π X : Set • (X → X)) ≡ (Π X : Set • (X → X)); _ = refl
920   _ : Σ→∪ (Π X : Set • Σ s : X • X) ≡ (Π X : Set • X ∪ X) ; _ = refl
921   _ : Σ→∪ (Π X : Set • Σ s : (X → X) • X) ≡ (Π X : Set • (X → X) ∪ X) ; _ = refl
922   _ : Σ→∪ (Π X : Set • Σ z : X • Σ s : (X → X) • T {ℓ0}) ≡ (Π X : Set • X ∪ (X → X) ∪ ⊥) ; _ = refl

923   D4 = Σ→∪ D3

924   4-unions : D4 ≡ λ X → 1 ∪ X ∪ 0
925   4-unions = refl

```

A.11.5 Stage 5: Fixpoint and proof that $\mathbb{D} \cong \mathbb{N}$.

```

927   {-# NO_POSITIVITY_CHECK #-}
928   data Fix {ℓ} (F : Set ℓ → Set ℓ) : Set ℓ where
929     μ : F (Fix F) → Fix F
930
931

```

```

932   $\mathbb{D}$  = Fix  $D_4$ 
933
934  -- Pattern synonyms for more compact presentation
935  pattern zeroD =  $\mu$  (inj1 tt)      -- :  $\mathbb{D}$ 
936  pattern sucD e =  $\mu$  (inj2 (inj1 e)) -- :  $\mathbb{D} \rightarrow \mathbb{D}$ 
937
938  to :  $\mathbb{D} \rightarrow \mathbb{N}$ 
939  to zeroD    = 0
940  to (sucD x) = suc (to x)
941
942  from :  $\mathbb{N} \rightarrow \mathbb{D}$ 
943  from zero   = zeroD
944  from (suc n) = sucD (from n)
945
946  toofrom :  $\forall n \rightarrow \text{to (from n)} \equiv n$ 
947  toofrom zero   = refl
948  toofrom (suc n) = cong suc (toofrom n)
949
950  fromto :  $\forall d \rightarrow \text{from (to d)} \equiv d$ 
951  fromto zeroD   = refl
952  fromto (sucD x) = cong sucD (fromto x)

```

A.11.6 *termtypes and Inj macros*. We summarise the stages together into one macro: “termtypes : UnaryFunction \rightarrow Type”.

```

952  macro
953    termtypes : Term  $\rightarrow$  Term  $\rightarrow$  TC Unit.T
954    termtypes tm goal =
955      normalise tm
956      >>=  $\lambda$  tm'  $\rightarrow$  unify goal (def (quote Fix) ((vArg ( $\Sigma \rightarrow \mathbb{U}_0$  (sources1 tm')))) :: []))

```

It is interesting to note that in place of pattern clauses, say for languages that do not support them, we would resort to “fancy injections”.

```

957  Inj0 :  $\mathbb{N} \rightarrow \text{Term} \rightarrow \text{Term}$ 
958  Inj0 zero c = con (quote inj1) (arg (arg-info visible relevant) c :: [])
959  Inj0 (suc n) c = con (quote inj2) (vArg (Inj0 n c) :: [])
960
961  -- Duality!
962  -- i-th projection: proj1  $\circ$  (proj2  $\circ$  ...  $\circ$  proj2)
963  -- i-th injection: (inj2  $\circ$  ...  $\circ$  inj2)  $\circ$  inj1
964
965  macro
966    Inj :  $\mathbb{N} \rightarrow \text{Term} \rightarrow \text{Term} \rightarrow \text{TC Unit.T}$ 
967    Inj n t goal = unify goal ((con (quote  $\mu$ ) []) app (Inj0 n t))

```

With this alternative, we regain the “user chosen constructor names” for \mathbb{D} :

```

970  startD :  $\mathbb{D}$ 
971  startD = Inj 0 (tt { $\ell_0$ })
972
973  nextD' :  $\mathbb{D} \rightarrow \mathbb{D}$ 
974  nextD' d = Inj 1 d

```

A.12 Monoids

A.12.1 Context.

```

975  Monoid :  $\forall \ell \rightarrow \text{Context } (\ell \text{ suc } \ell)$ 
976  Monoid  $\ell$  = do Carrier  $\leftarrow$  Set  $\ell$ 
977  Id  $\leftarrow$  Carrier

```

```

981      _⊕_      ← (Carrier → Carrier → Carrier)
982      leftId  ← ∀ {x : Carrier} → x ⊕ Id ≡ x
983      rightId ← ∀ {x : Carrier} → Id ⊕ x ≡ x
984      assoc   ← ∀ {x y z} → (x ⊕ y) ⊕ z ≡ x ⊕ (y ⊕ z)
985      End {ℓ}

```

A.12.2 Termtypes.

```

986  M : Set
987  M = termtype (Monoid ℓ0 :waist 1)
988  {- ie Fix (λ X → 1
989      ⊔ X × X × 1 -- _⊕_, branch
990      ⊔ 0         -- src of leftId
991      ⊔ 0         -- src of rightId
992      ⊔ X × X × 0 -- src of assoc
993      ⊔ 0)       -- the “End {ℓ}”
994  -}
995
996  -- Pattern synonyms for more compact presentation
997  pattern emptyM      = μ (inj1 tt)          -- : M
998  pattern branchM l r = μ (inj2 (inj1 (l , r , tt))) -- : M → M → M
999  pattern absurdM a   = μ (inj2 (inj2 (inj2 (inj2 a)))) -- absurd values of 0
1000
1001  data TreeSkeleton : Set where
1002    empty : TreeSkeleton
1003    branch : TreeSkeleton → TreeSkeleton → TreeSkeleton

```

A.12.3 $M \cong \text{TreeSkeleton}$.

```

1004  M→Tree : M → TreeSkeleton
1005  M→Tree emptyM = empty
1006  M→Tree (branchM l r) = branch (M→Tree l) (M→Tree r)
1007  M→Tree (absurdM (inj1 ()))
1008  M→Tree (absurdM (inj2 ()))
1009
1010  M←Tree : TreeSkeleton → M
1011  M←Tree empty = emptyM
1012  M←Tree (branch l r) = branchM (M←Tree l) (M←Tree r)
1013
1014  M←Tree◦M→Tree : ∀ m → M←Tree (M→Tree m) ≡ m
1015  M←Tree◦M→Tree emptyM = refl
1016  M←Tree◦M→Tree (branchM l r) = cong2 branchM (M←Tree◦M→Tree l) (M←Tree◦M→Tree r)
1017  M←Tree◦M→Tree (absurdM (inj1 ()))
1018  M←Tree◦M→Tree (absurdM (inj2 ()))
1019
1020  M→Tree◦M←Tree : ∀ t → M→Tree (M←Tree t) ≡ t
1021  M→Tree◦M←Tree empty = refl
1022  M→Tree◦M←Tree (branch l r) = cong2 branch (M→Tree◦M←Tree l) (M→Tree◦M←Tree r)

```

A.13 :kind

```

1023  data Kind : Set where
1024    ‘record   : Kind
1025    ‘typeclass : Kind
1026    ‘data     : Kind
1027
1028  macro
1029    _:kind_ : Term → Term → Term → TC Unit.⊤
1030    _:kind_ t (con (quote ‘record) _) goal = normalise (t app (quoteTerm 0))
1031    >>= m λ t' → unify (waist-helper 0 t') goal

```

```

1030   _:kind_ t (con (quote 'typeclass) _) goal = normalise (t app (quoteTerm 1))
1031   >>=m λ t' → unify (waist-helper 1 t') goal
1032   _:kind_ t (con (quote 'data) _) goal = normalise (t app (quoteTerm 1))
1033   >>=m λ t' → normalise (waist-helper 1 t')
1034   >>=m λ t'' → unify goal (def (quote Fix) ((vArg (Σ→ℳ₀ (sources₁ t'')))) :: []))
1035   _:kind_ t _ goal = unify t goal

```

Informally, `_:kind_` behaves as follows:

```

1036   C :kind 'record   = C :waist 0
1037   C :kind 'typeclass = C :waist 1
1038   C :kind 'data     = termtype (C :waist 1)
1039

```

A.14 termtype PointedSet $\cong \mathbb{1}$

```

1041   -- termtype (PointedSet)  $\cong \top$  !
1042   One : Context (ℓsuc ℓ₀)
1043   One  = do Carrier ← Set ℓ₀
1044         point  ← Carrier
1045         End {ℓ₀}

1046   One : Set
1047   One = termtype (One :waist 1)

1048
1049   view₁ : One → 1
1050   view₁ emptyM = tt

```

A.15 The Termtype of Graphs is Vertex Pairs

From simple graphs (relations) to a syntax about them: One describes a simple graph by presenting edges as pairs of vertices!

```

1055   PointedOver₂ : Set → Context (ℓsuc ℓ₀)
1056   PointedOver₂  $\Xi$  = do Carrier ← Set ℓ₀
1057                   relation ← ( $\Xi \rightarrow \Xi \rightarrow$  Carrier)
1058                   End {ℓ₀}

1059   P₂ : Set → Set
1060   P₂ X = termtype (PointedOver₂ X :waist 1)

1061   pattern _ $\rightleftharpoons$ _ x y =  $\mu$  (inj₁ (x , y , tt))

1062
1063   view₂ :  $\forall \{X\} \rightarrow P₂ X \rightarrow X \times X$ 
1064   view₂ (x  $\rightleftharpoons$  y) = x , y

```

A.16 No ‘constants’, whence a type of infinitely branching terms

```

1067   PointedOver₃ : Set → Context (ℓ₀)
1068   PointedOver₃  $\Xi$  = do relation ← ( $\Xi \rightarrow \Xi \rightarrow \Xi$ )
1069                   End {ℓ₀}

1070   P₃ : Set
1071   P₃ = termtype (λ X → PointedOver₃ X 0)

```

A.17 $P₂$ again!

```

1074   PointedOver₄ : Context (ℓsuc ℓ₀)
1075   PointedOver₄ = do  $\Xi \leftarrow$  Set
1076                   Carrier ← Set ℓ₀
1077                   relation ← ( $\Xi \rightarrow \Xi \rightarrow$  Carrier)
1078                   End {ℓ₀}

```

```

1079
1080 -- The current implementation of “termtyping” only allows for one “Set” in the body.
1081 -- So we lift both out; thereby regaining  $\mathbb{P}_2$ !
1082
1083  $\mathbb{P}_4 : \text{Set} \rightarrow \text{Set}$ 
1084  $\mathbb{P}_4 X = \text{termtyping } ((\text{PointedOver}_4 : \text{waist } 2) X)$ 
1085
1086 pattern  $\_ \Leftarrow \_ x y = \mu (\text{inj}_1 (x, y, \text{tt}))$ 
1087
1088  $\text{case}_4 : \forall \{X\} \rightarrow \mathbb{P}_4 X \rightarrow \text{Set}_1$ 
1089  $\text{case}_4 (x \Leftarrow y) = \text{Set}$ 
1090
1091 -- Claim: Mention in paper.
1092 --
1093 --  $P_1 : \text{Set} \rightarrow \text{Context} = \lambda \Xi \rightarrow \text{do } \dots \text{ End}$ 
1094 --  $\cong P_2 : \text{waist } 1$ 
1095 -- where  $P_2 : \text{Context} = \text{do } \Xi \leftarrow \text{Set}; \dots \text{ End}$ 

```

A.18 \mathbb{P}_4 again – indexed unary algebras; i.e., “actions”

```

1095  $\text{PointedOver}_8 : \text{Context } (\ell\text{suc } \ell_0)$ 
1096  $\text{PointedOver}_8 = \text{do Index} \leftarrow \text{Set}$ 
1097  $\text{Carrier} \leftarrow \text{Set}$ 
1098  $\text{Operation} \leftarrow (\text{Index} \rightarrow \text{Carrier} \rightarrow \text{Carrier})$ 
1099  $\text{End } \{\ell_0\}$ 
1100
1101  $\mathbb{P}_8 : \text{Set} \rightarrow \text{Set}$ 
1102  $\mathbb{P}_8 X = \text{termtyping } ((\text{PointedOver}_8 : \text{waist } 2) X)$ 
1103
1104 pattern  $\_ \cdot \_ x y = \mu (\text{inj}_1 (x, y, \text{tt}))$ 
1105
1106  $\text{view}_8 : \forall \{I\} \rightarrow \mathbb{P}_8 I \rightarrow \text{Set}_1$ 
1107  $\text{view}_8 (i \cdot e) = \text{Set}$ 

```

**COMMENT Other experiments

```

1107 {- Yellow:
1108
1109  $\text{PointedOver}_5 : \text{Context } (\ell\text{suc } \ell_0)$ 
1110  $\text{PointedOver}_5 = \text{do One} \leftarrow \text{Set}$ 
1111  $\text{Two} \leftarrow \text{Set}$ 
1112  $\text{Three} \leftarrow (\text{One} \rightarrow \text{Two} \rightarrow \text{Set})$ 
1113  $\text{End } \{\ell_0\}$ 
1114
1115  $\mathbb{P}_5 : \text{Set} \rightarrow \text{Set}_1$ 
1116  $\mathbb{P}_5 X = \text{termtyping } ((\text{PointedOver}_5 : \text{waist } 2) X)$ 
1117 -- Fix  $(\lambda \text{Two} \rightarrow \text{One} \times \text{Two})$ 
1118
1119 pattern  $\_ ::_5 \_ x y = \mu (\text{inj}_1 (x, y, \text{tt}))$ 
1120
1121  $\text{case}_5 : \forall \{X\} \rightarrow \mathbb{P}_5 X \rightarrow \text{Set}_1$ 
1122  $\text{case}_5 (x ::_5 xs) = \text{Set}$ 
1123
1124 -}
1125
1126 -----
1127 {- Dependent sums

```

```

1128   PointedOver6 : Context  $\ell_1$ 
1129   PointedOver6 = do Sort  $\leftarrow$  Set
1130                   Carrier  $\leftarrow$  (Sort  $\rightarrow$  Set)
1131                   End { $\ell_0$ }
1132
1132    $\mathbb{P}_6$  : Set1
1133    $\mathbb{P}_6$  = termtype ((PointedOver6 :waist 1) )
1134   -- Fix ( $\lambda X \rightarrow X$ )
1135
1136   -}
1137
1138   -----
1139
1139   -- Distinuighed subset algebra
1140
1140   open import Data.Bool renaming (Bool to  $\mathbb{B}$ )
1141
1142   {-
1143   PointedOver7 : Context ( $\ell_{\text{suc}} \ell_0$ )
1144   PointedOver7 = do Index  $\leftarrow$  Set
1145                   Is  $\leftarrow$  (Index  $\rightarrow \mathbb{B}$ )
1146                   End { $\ell_0$ }
1147
1147   -- The current implementation of “termtype” only allows for one “Set” in the body.
1148   -- So we lift both out; thereby regaining  $\mathbb{P}_2$ !
1149
1149    $\mathbb{P}_7$  : Set  $\rightarrow$  Set
1150    $\mathbb{P}_7$  X = termtype ( $\lambda (\_ : \text{Set}) \rightarrow (\text{PointedOver}_7 : \text{waist } 1) X$ )
1151   --  $\mathbb{P}_1 X \cong X$ 
1152
1153   pattern  $\_ \rightleftharpoons \_$  x y =  $\mu$  (inj1 (x , y , tt))
1154
1155   case7 :  $\forall \{X\} \rightarrow \mathbb{P}_7 X \rightarrow \text{Set}$ 
1156   case7 {X} ( $\mu$  (inj1 x)) = X
1157
1158   -}
1159
1160   -----
1161
1161   {-
1162   PointedOver9 : Context  $\ell_1$ 
1163   PointedOver9 = do Carrier  $\leftarrow$  Set
1164                   End { $\ell_0$ }
1165
1165   -- The current implementation of “termtype” only allows for one “Set” in the body.
1166   -- So we lift both out; thereby regaining  $\mathbb{P}_2$ !
1167
1167    $\mathbb{P}_9$  : Set
1168    $\mathbb{P}_9$  = termtype ( $\lambda (X : \text{Set}) \rightarrow (\text{PointedOver}_9 : \text{waist } 1) X$ )
1169   --  $\cong 0 \cong \text{Fix } (\lambda X \rightarrow 0)$ 
1170   -}
1171
1171   A.19 Fix Id
1172
1172   PointedOver10 : Context  $\ell_1$ 
1173   PointedOver10 = do Carrier  $\leftarrow$  Set
1174                   next  $\leftarrow$  (Carrier  $\rightarrow$  Carrier)
1175                   End { $\ell_0$ }
1176

```



```

1177
1178     -- The current implementation of “termttype” only allows for one “Set” in the body.
1179     -- So we lift both out; thereby regaining  $\mathbb{P}_2$ !
1180
1181      $\mathbb{P}_{10}$  : Set
1182      $\mathbb{P}_{10}$  = termttype ( $\lambda$  (X : Set)  $\rightarrow$  (PointedOver10 :waist 1) X)
1183     -- Fix ( $\lambda$  X  $\rightarrow$  X), which does not exist.
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225

```