

# Do-it-yourself Module Systems

Extending Dependently-Typed Languages to Implement \ Module System Features In The Core Language

---

Musa Al-hassy

April 28, 2021

McMaster University, Hamilton, Ontario, Canada  
alhassy@gmail.com

# What is the problem?

---

# Overview

With a bit of reflection, we can obtain

1. a uniform, and **practical**, syntax for both *records* (semantics) and *termtypes* (syntax)
2. on-the-fly unbundling; and,
3. **mechanically** obtain data structures from theories

# Overview

With a bit of reflection, we can obtain

1. a uniform, and **practical**, syntax for both *records* (semantics) and *termtypes* (syntax)
2. on-the-fly unbundling; and,
3. **mechanically** obtain data structures from theories

'theory' $\tau$	'data structure' termtype $\tau$
pointed set	$\mathbb{1}$
dynamic system	$\mathbb{N}$
monoid	tree skeletons
collections	lists
graphs	(homogeneous) pairs
actions	infinite streams

# Overview

With a bit of reflection, we can obtain

1. a uniform, and **practical**, syntax for both *records* (semantics) and

2 The combinators presented in the thesis were guided  
3 *not* by theoretical concerns on the algebraic nature  
of containers but rather on the *mon theories*

**practical needs of actual users working in DTLs**

pointed set	$\mathbb{I}$
dynamic system	$\mathbb{N}$
monoid	tree skeletons
collections	lists
graphs	(homogeneous) pairs
actions	infinite streams

# What is *in a* monoid?

People work with monoids at various levels of exposure ...

# What is *in* a monoid?

People work with monoids at various levels of exposure ...

- “Let  $M$  be a monoid, ...”

# What is *in* a monoid?

People work with monoids at various levels of exposure ...

- “Let  $M$  be a monoid, ...”
- “Given a monoid over  $\mathbb{N}$ , ...”



# What is *in* a monoid?

People work with monoids at various levels of exposure ...

- “Let  $M$  be a monoid, ...”
- “Given a monoid over  $\mathbb{N}$ , ...”
- “Consider *the* monoid  $(\mathbb{N}, +)$ , ...”
  - (Unique viz proof irrelevance.)

# What is *in* a monoid?

People work with monoids at various levels of exposure ...

- “Let  $M$  be a monoid, ...”
- “Given a monoid over  $\mathbb{N}$ , ...”
- “Consider *the* monoid  $(\mathbb{N}, +)$ , ...”
  - (Unique viz proof irrelevance.)
- “Consider *the* monoid  $(\mathbb{N}, +, 0)$ , ...”

“A monoid consists of a collection Carrier, an operation, ...”?

```
record Monoid0 : Set1 where
  field Carrier : Set
        _◊_      : Carrier → Carrier → Carrier
        Id       : Carrier
        lid      : ∀ {x} → Id ◊ x ≡ x
        rid      : ∀ {x} → x ◊ Id ≡ x
        assoc    : ∀ {x y z} → (x ◊ y) ◊ z ≡ x ◊ (y ◊ z)
```

Use-case: The category of monoids.

“A monoid over a given collection `Carrier` and operation `_∘_` is given by ensuring there is a selected point ...”?

```
record Monoid1
  (Carrier : Set)      : Set  where
  field
    _∘_      : Carrier → Carrier → Carrier
    Id       : Carrier
    lid      : ∀ {x} → Id ∘ x ≡ x
    rid      : ∀ {x} → x ∘ Id ≡ x
    assoc    : ∀ {x y z} → (x ∘ y) ∘ z ≡ x ∘ (y ∘ z)
```

Use-case: Sharing the carrier type

## Or ... ?

```
record Monoid2
  (Carrier : Set)
  (_◊_      : Carrier → Carrier → Carrier) : Set where
  field
    Id      : Carrier
    lid     : ∀ {x} → Id ◊ x ≡ x
    rid     : ∀ {x} → x ◊ Id ≡ x
    assoc   : ∀ {x y z} → (x ◊ y) ◊ z ≡ x ◊ (y ◊ z)
```

Use-case: The additive monoid on the Natural numbers

## Or ... ?

```
record Monoid3
  (Carrier : Set)
  (_⋄_      : Carrier → Carrier → Carrier)
  (Id      : Carrier)      : Set where
  field
    lid      : ∀ {x} → Id ⋄ x ≡ x
    rid      : ∀ {x} → x ⋄ Id ≡ x
    assoc    : ∀ {x y z} → (x ⋄ y) ⋄ z ≡ x ⋄ (y ⋄ z)
```

Notice that the keyword *field* is “going down” the *waist* each time.

*Structures are meaninglessly parameterized from a mathematical perspective. [...] That is, what is bundled cannot be later opened up as a parameter. [...] This means that library designers are forced to take a conservative approach and expose as a parameter anything that any user might reasonably want exposed, because once it is bundled, it is not coming back.*

*—A Review of the Lean Theorem Prover, 2018-09-18*

⇒ This is a problem we are solving!

*Structures are meaninglessly parameterized from a mathematical perspective. [...] That is, what is bundled cannot be later opened up as a parameter. [...] This means that library designers are forced to take a conservative approach and expose as a parameter anything that any user might reasonably want exposed, because once it is bundled, it is not coming back.*

*—A Review of the Lean Theorem Prover, 2018-09-18*



⇒ This is a problem we are solving!

⇒ A recent problem

*Structural design is characterized from a mathematical perspective. [...] That is, what is bundled cannot be later opened up as a parameter. [...] This means that library designers are forced to take a conservative approach and expose as a parameter anything that any user might reasonably want exposed, because once it is bundled, it is not coming back.*

—A Review of the Lean Theorem Prover, 2018-09-18

⇒ This is a problem we are solving!

⇒ A recent problem

⇒ ***“The Unbundling Problem”***

*Structural perspective characterized from a mathematical perspective. [...] This means that library designers are forced to take a conservative approach and expose as a parameter anything that any user might reasonably want exposed, because once it is bundled, it is not coming back.*

—A Review of the Lean Theorem Prover, 2018-09-18

Does this *actually* happen?

Does this *actually* happen?

Yes!

## Does this *actually* happen?

Yes!

Examples:

- Agda's Standard Library,
- RATH-Agda,
- agda-categories

It's not just dependently-typed languages. . .

# Does this *actually* happen?

Yes!

Examples:

- Agda's Standard Library,
- RATH-Agda,
- agda-categories

It's not just dependently-typed languages. . .

- Arend
- Haskell's Standard Library

## What are the adjacent problems?

Maintenance of relationships when we “bring down the waist” —the position of the `field` keyword.

## What are the adjacent problems?

Maintenance of relationships when we “bring down the waist” —the position of the `field` keyword.

$$\mathbf{Monoid}_0 \cong \sum C : \mathbf{Set} \bullet \mathbf{Monoid}_1 C$$



## What are the adjacent problems?

Maintenance of relationships when we “bring down the waist” —the position of the `field` keyword.

$$\mathsf{Monoid}_0 \cong \sum C : \mathsf{Set} \bullet \mathsf{Monoid}_1 C$$

$$\mathsf{Monoid}_1 C \cong \sum M : \mathsf{Monoid}_0 \bullet \mathsf{Monoid}_0.\mathsf{Carrier} M \equiv C$$

## What are the adjacent problems?

Maintenance of relationships when we “bring down the waist” —the position of the `field` keyword.

$$\mathsf{Monoid}_0 \cong \sum C : \mathsf{Set} \bullet \mathsf{Monoid}_1 C$$

$$\mathsf{Monoid}_1 C \cong \sum M : \mathsf{Monoid}_0 \bullet \mathsf{Monoid}_0.\mathsf{Carrier} M \equiv C$$

These coercions can be derived **mechanically**

## What are the adjacent problems?

Maintenance of relationships when we “bring down the waist” —the position of the `field` keyword.

$$\mathsf{Monoid}_0 \cong \sum C : \mathsf{Set} \bullet \mathsf{Monoid}_1 C$$

$$\mathsf{Monoid}_1 C \cong \sum M : \mathsf{Monoid}_0 \bullet \mathsf{Monoid}_0.\mathsf{Carrier} M \equiv C$$

These coercions can be derived **mechanically**

What about other *natural constructions* on mathematical theories (and the associated relationships)?

- Extensions? —“A group is a monoid with an extra...”

# What are the adjacent problems?

Maintenance of relationships when we “bring down the waist” —the position of the `field` keyword.

$$\mathsf{Monoid}_0 \cong \sum C : \mathsf{Set} \bullet \mathsf{Monoid}_1 C$$

$$\mathsf{Monoid}_1 C \cong \sum M : \mathsf{Monoid}_0 \bullet \mathsf{Monoid}_0.\mathsf{Carrier} M \equiv C$$

These coercions can be derived **mechanically**

What about other *natural constructions* on mathematical theories (and the associated relationships)?

- Extensions? —“A group is a monoid with an extra...”
- Exclusions? —“A semigroup is a non-unital monoid.”

# What are the adjacent problems?

Maintenance of relationships when we “bring down the waist” —the position of the `field` keyword.

$$\mathsf{Monoid}_0 \cong \sum C : \mathsf{Set} \bullet \mathsf{Monoid}_1 C$$

$$\mathsf{Monoid}_1 C \cong \sum M : \mathsf{Monoid}_0 \bullet \mathsf{Monoid}_0.\mathsf{Carrier} M \equiv C$$

These coercions can be derived **mechanically**

What about other *natural constructions* on mathematical theories (and the associated relationships)?

- Extensions? —“A group is a monoid with an extra...”
- Exclusions? —“A semigroup is a non-unital monoid.”
- Termtypes? —“Lists are just the free *monoid* over a given type.”

# What are the adjacent problems?

Maintenance of relationships when we “bring down the waist” —the position of the `field` keyword.

$$\mathbf{Monoid}_0 \cong \Sigma C : \mathbf{Set} \bullet \mathbf{Monoid}_1 C$$

$$\mathbf{Monoid}_1 C \cong \Sigma M : \mathbf{Monoid}_0 \bullet \mathbf{Monoid}_0.\mathbf{Carrier} M \equiv C$$

These coercions can be derived **mechanically**

What about other *natural constructions* on mathematical theories (and the associated relationships)?

- Extensions? —“A group is a monoid with an extra...”
- Exclusions? —“A semigroup is a non-unital monoid.”
- Termtypes? —“Lists are just the free *monoid* over a given type.”
- Pushouts: Name-relevant unions? —“A monoid is a pointed set along with a semigroup **such that** they share the same carrier.”

# What are the adjacent problems?

Maintenance of relationships when we “bring down the waist” —the position of the `field` keyword.

$$\mathbf{Monoid}_0 \cong \Sigma C : \mathbf{Set} \bullet \mathbf{Monoid}_1 C$$

$$\mathbf{Monoid}_1 C \cong \Sigma M : \mathbf{Monoid}_0 \bullet \mathbf{Monoid}_0.\mathbf{Carrier} M \equiv C$$

These coercions can be derived **mechanically**

What about other *natural constructions* on mathematical theories (and the associated relationships)?

- Extensions? —“A group is a monoid with an extra...”
- Exclusions? —“A semigroup is a non-unital monoid.”
- Termtypes? —“Lists are just the free *monoid* over a given type.”
- Pushouts: Name-relevant unions? —“A monoid is a pointed set along with a semigroup **such that** they share the same carrier.”
- Numerous other constructions from Category Theory

## Which items should be fields, which parameters?

- The `Monoid` family showed some combinations of items selected as parameters.



## Which items should be fields, which parameters?

- The `Monoid` family showed some combinations of items selected as parameters.
- There are other combinations of what is to be exposed and hidden, for applications that we might never think of.

## Which items should be fields, which parameters?

- The `Monoid` family showed some combinations of items selected as parameters.
- There are other combinations of what is to be exposed and hidden, for applications that we might never think of.
- Providing always the most-general parameterisation produces awkward library interfaces!

# Which items should be fields, which parameters?

- The `Monoid` family showed some combinations of items selected as parameters.
- There are other combinations of what is to be exposed and hidden, for applications that we might never think of.
- Providing always the most-general parameterisation produces awkward library interfaces!

## Proposed Solution:

- Commit to no particular formulation and allow on-the-fly “unbundling”
  - This is the *converse* of instantiation

# Which items should be fields, which parameters?

- The `Monoid` family showed some combinations of items selected as parameters.
- There are other combinations of what is to be exposed and hidden, for applications that we might never think of.
- Providing always the most-general parameterisation produces awkward library interfaces!

## Proposed Solution:

- Commit to no particular formulation and allow on-the-fly “unbundling”
  - This is the *converse* of instantiation
- The “Emacs editor tactic” `PackageFormer`
- The “Agda library” `Context`

## The PackageFormer Prototype: A useful experimentation tool

---

# Evidence that the theory 'actually works'

Prototype with an editor extension *then* incorporate lessons learned into a DTL library!

```
{-700
PackageFormer M-Set : Set₁ where
  Scalar   : Set
  Vector   : Set
  _'_      : Scalar → Vector → Vector
  1         : Scalar
  _x_      : Scalar → Scalar → Scalar
  leftId   : {v : Vector} → 1 · v ≡ v
  assoc    : ∀ {a b v} → (a × b) · v ≡ a · (b · v)

NearRing = M-Set record ⊕ single-sorted "Scalar"
-}
```

```
{- NearRing = M-Set record ⊕ single-sorted "Scalar" -}
record NearRing : Set₁ where
  field Scalar       : Set
  field _'_          : Scalar → Scalar → Scalar
  field 1            : Scalar
  field _x_          : Scalar → Scalar → Scalar
  field leftId       : {v : Scalar} → 1 · v ≡ v
  field assoc        : ∀ {a b v} → (a × b) · v ≡ a · (b · v)
```

Generated code displayed on hover

# A Language Feature to Unbundle Data at Will (GPCE '19)

But perhaps Haskell's type system does not give the programmer sufficient tools to adequately express such ideas. As such, for the rest of this paper we will illustrate our ideas in Agda [2, 7]. For the monoid example, it seems that there are three contenders for the monoid interface:

```
record Monoid0 : Set1 where
  field
    Carrier : Set
    _[-]_    : Carrier → Carrier → Carrier
    Id      : Carrier
    assoc   : ∀ {x y z}
              → (x § y) § z ≡ x § (y § z)
    leftId  : ∀ {x} → Id § x ≡ x
    rightId : ∀ {x} → x § Id ≡ x

record Monoid1 (Carrier : Set) : Set where
  field
    _[-]_    : Carrier → Carrier → Carrier
    Id      : Carrier
    assoc   : ∀ {x y z}
              → (x § y) § z ≡ x § (y § z)
    leftId  : ∀ {x} → Id § x ≡ x
    rightId : ∀ {x} → x § Id ≡ x

record Monoid2
  (Carrier : Set)
  (_[-]_ : Carrier → Carrier → Carrier)
  : Set where
  field
    Id      : Carrier
    assoc   : ∀ {x y z}
              → (x § y) § z ≡ x § (y § z)
    leftId  : ∀ {x} → Id § x ≡ x
    rightId : ∀ {x} → x § Id ≡ x
```

In Monoid<sub>0</sub>, we will call Carrier “bundled up”, while we call it “exposed” in Monoid<sub>1</sub> and Monoid<sub>2</sub>. The bundled-up version allows us to speak of a monoid, rather than a *monoid on a given type* which is captured by Monoid<sub>1</sub>. While Monoid<sub>2</sub> exposes both the carrier and the composition operation, we

automation, may want to use the associated datatype for syntax. For example, the syntax of closed monoid terms can be expressed, using trees, as follows.

```
data Monoid3 : Set where
  _[-]_ : Monoid3 → Monoid3 → Monoid3
  Id   : Monoid3
```

We can see that this can be obtained from Monoid<sub>0</sub> by discarding the fields denoting equations, then turning the remaining fields into constructors.

We show how these different presentations can be derived from a *single* PackageFormer declaration via a generative meta-program integrated into the most widely-used Agda “IDE”, the Emacs mode for Agda. In particular, if one were to explicitly write  $M$  different bundlings of a package with  $N$  constants then one would write nearly  $N \times M$  lines of code, yet this quadratic count becomes linear  $N + M$  by having a single package declaration of  $N$  constituents with  $M$  subsequent instantiations. We hope that reducing such duplication of effort, and of potential maintenance burden, will be beneficial to the software engineering of large libraries of formal code — and consider it the main contribution of our work.

## 2 PackageFormers — Being Non-committal as Much as Possible

We claim that the above monoid-related pieces of Agda code can be unified as a single declaration which does not distinguish between parameters and fields, where PackageFormer is a keyword with similar syntax as record:

```
PackageFormer MonoidP : Set1 where
  Carrier : Set
  _[-]_    : Carrier → Carrier → Carrier
  Id      : Carrier
  assoc   : ∀ {x y z}
            → (x § y) § z ≡ x § (y § z)
  leftId  : ∀ {x} → Id § x ≡ x
  rightId : ∀ {x} → x § Id ≡ x
```

(For clarity, this and other non-native Agda syntax is left uncoloured.)

# A Language Feature to Unbundle Data at Will (GPCE '19)

But perhaps Haskell's type system does not give the programmer sufficient tools to adequately express such ideas. As such, for the rest of this paper we will illustrate our ideas in Agda [2, 7]. For the monoid example, it seems that there are three contenders for the monoid interface:

```
record Monoid0 : Set1 where
  field
    Carrier : Set
    _|-_      : Carrier → Carrier → Carrier
    Id       : Carrier
    assoc    : ∀ {x y z}
              → (x § y) § z ≡ x § (y § z)
    leftId   : ∀ {x} → Id § x ≡ x
    rightId  : ∀ {x} → x § Id ≡ x

record Monoid1 (Carrier : Set) : Set where
  field
    _|-_      : Carrier → Carrier → Carrier
    Id       : Carrier
    assoc    : ∀ {x y z}
```

⇒ Influenced Agda's Standard Library

```
record Monoid2
  (Carrier : Set)
  (_|-_ : Carrier → Carrier → Carrier)
  : Set where
  field
    Id       : Carrier
    assoc    : ∀ {x y z}
              → (x § y) § z ≡ x § (y § z)
    leftId   : ∀ {x} → Id § x ≡ x
    rightId  : ∀ {x} → x § Id ≡ x
```

In Monoid<sub>0</sub>, we will call Carrier "bundled up", while we call it "exposed" in Monoid<sub>1</sub> and Monoid<sub>2</sub>. The bundled-up version allows us to speak of a monoid, rather than a *monoid on a given type* which is captured by Monoid<sub>1</sub>. While Monoid<sub>2</sub> exposes both the carrier and the composition operation, we

automation, may want to use the associated datatype for syntax. For example, the syntax of closed monoid terms can be expressed, using trees, as follows.

```
data Monoid3 : Set where
  _|-_ : Monoid3 → Monoid3 → Monoid3
  Id   : Monoid3
```

We can see that this can be obtained from Monoid<sub>0</sub> by discarding the fields denoting equations, then turning the remaining fields into constructors.

We show how these different presentations can be derived from a *single* PackageFormer declaration via a generative meta-program integrated into the most widely-used Agda "IDE", the Emacs mode for Agda. In particular, if one were to explicitly write  $M$  different bundlings of a package with  $N$  constants then one would write nearly  $N \times M$  lines of code, yet this quadratic count becomes linear  $N + M$  by having a single package declaration of  $N$  constituents with  $M$  subsequent instantiations. We hope that reducing such duplication of effort, and of potential maintenance burden, will be beneficial to the software engineering of large libraries of

## as Much as Possible

We claim that the above monoid-related pieces of Agda code can be unified as a single declaration which does not distinguish between parameters and fields, where PackageFormer is a keyword with similar syntax as record:

```
PackageFormer MonoidP : Set1 where
  Carrier : Set
  _|-_      : Carrier → Carrier → Carrier
  Id       : Carrier
  assoc    : ∀ {x y z}
            → (x § y) § z ≡ x § (y § z)
  leftId   : ∀ {x} → Id § x ≡ x
  rightId  : ∀ {x} → x § Id ≡ x
```

(For clarity, this and other non-native Agda syntax is left uncoloured.)



# The Definition of a Monoid

```
PackageFormer MonoidP : Set1 where
  Carrier : Set
  _⋄_      : Carrier → Carrier → Carrier
  Id       : Carrier
  assoc    : ∀ {x y z} → (x ⋄ y) ⋄ z ≡ x ⋄ (y ⋄ z)
  leftId   : ∀ {x} → Id ⋄ x ≡ x
  rightId  : ∀ {x} → x ⋄ Id ≡ x
```

# The Definition of a Monoid

```
PackageFormer MonoidP : Set1 where
  Carrier : Set
  _∘_      : Carrier → Carrier → Carrier
  Id       : Carrier
  assoc    : ∀ {x y z} → (x ∘ y) ∘ z ≡ x ∘ (y ∘ z)
  leftId   : ∀ {x} → Id ∘ x ≡ x
  rightId  : ∀ {x} → x ∘ Id ≡ x
```

We regain the different candidates by applying **variational**s.

```
Monoid0 = MonoidP record
Monoid1 = MonoidP record ⊕→ unbundled 1
Monoid2 = MonoidP record ⊕→ unbundled 2
Monoid3 = Monoid0' exposing "Carrier; _∘_; Id"
```

...and we can do more

# The Definition of a Monoid

```
PackageFormer MonoidP : Set1 where
  Carrier : Set
  _◊_      : Carrier → Carrier → Carrier
  Id       : Carrier
  assoc    : ∀ {x y z} → (x ◊ y) ◊ z ≡ x ◊ (y ◊ z)
  leftId   : ∀ {x} → Id ◊ x ≡ x
  rightId  : ∀ {x} → x ◊ Id ≡ x
```

We regain the different candidates by applying **variational**s.

```
Monoid0 = MonoidP record
Monoid1 = MonoidP record ⊕→ unbundled 1
Monoid2 = MonoidP record ⊕→ unbundled 2
Monoid3 = Monoid0' exposing "Carrier; _◊_; Id"
```

...and we can do more

## Monoid syntax!

```
Tree = MonoidP termtype-with-variables "Carrier"
≅
data Tree (Var : Set) : Set where
  inj : Var → Tree Var
  _◊_  : Tree Var → Tree Var → Tree Var
  Id  : Tree Var
```

# The Definition of a Monoid

```
PackageFormer MonoidP : Set1 where
  Carrier : Set
  _∘_      : Carrier → Carrier → Carrier
  Id       : Carrier
  assoc    : ∀ {x y z} → (x ∘ y) ∘ z ≡ x ∘ (y ∘ z)
  leftId   : ∀ {x} → Id ∘ x ≡ x
  rightId  : ∀ {x} → x ∘ Id ≡ x
```

We regain the different candidates by applying **variational**s.

```
Monoid0 = MonoidP record
Monoid1 = MonoidP record ⊕→ unbundled 1
Monoid2 = MonoidP record ⊕→ unbundled 2
Monoid3 = Monoid0' exposing "Carrier; _∘_; Id"
```

...and we can do more

## Monoid syntax!

```
Tree = MonoidP termtype-with-variables "Carrier"
≃
data Tree (Var : Set) : Set where
  inj : Var → Tree Var
  _∘_  : Tree Var → Tree Var → Tree Var
  Id  : Tree Var
```

Linear effort in number of variations

## Pushout unions, intersections, extensions, views, ...

```
(V union pf (renaming1 "") (renaming2 "") (adjoin-retract1 t) (adjoin-retract2 t)
= "Union the elements of the parent PackageFormer with those of
  the provided PF symbolic name, then adorn the result with two views:
  One to the parent and one to the provided PF.

If an identifier is shared but has different types, then crash."
:alter-elements (λ es →
  (let* ((p (symbol-name 'pf))
    (es1 (alter-elements es renaming renaming1 :adjoin-retract nil))
    (es2 (alter-elements ($elements-of p) renaming renaming2 :adjoin-retract nil))
    (es' (-concat es1 es2)))

;; Ensure no name clashes!
(loop for n in (find-duplicates (mapcar #'element-name es'))
  for e = (--filter (equal n (element-name it)) es')
  unless (--all-p (equal (car e) it)) e)
do (-let [debug-on-error nil]
  (error "%s = %s union %s \n\n\t\t → Error: Elements “%s” conflict!\n\n\t\t\t%s"
    $name $parent p (element-name (car e)) (s-join "\n\t\t\t" (mapcar #'show-element e)))))

;; return value
(-concat
  es'
  (when adjoin-retract1 (list (element-retract $parent es :new es1 :name adjoin-retract1)))
  (when adjoin-retract2 (list (element-retract p ($elements-of p) :new es2 :name
    ↪ adjoin-retract2))))))
```

Combinators are motivated from existing, real-world, DTL libraries!

# Pushout unions, intersections, extensions, views, ...

```
(V union pf (renaming1 "") (renaming2 "") (adjoin-retract1 t) (adjoin-retract2 t))
= "Union the elements of the parent PackageFormer with those of
  the provided PF symbolic name, then adorn the result with two views:
  One to the parent and one to the provided PF."
```

If an identifier is shared but has different types, then crash."

```
:alter-elements (λ es →
```

Framework built around **5 metaprimitives**

⇒ Lisp Metaprogramming, untyped string manipulation,

⇒ Macro DSL, Agda generation

```
(loop for n in (find-duplicates (mapcar #'element-name es))
  for e = (--filter (equal n (element-name it)) es')
  unless (--all-p (equal (car e) it) e)
  do (-let [debug-on-error nil]
      (error "%s = %s union %s \n\n\t\t → Error: Elements “%s” conflict!\n\n\t\t\t%s"
              $name $parent p (element-name (car e)) (s-join "\n\t\t\t" (mapcar #'show-element e)))))

;; return value
(-concat
  es'
  (when adjoin-retract1 (list (element-retract $parent es :new es1 :name adjoin-retract1)))
  (when adjoin-retract2 (list (element-retract p ($elements-of p) :new es2 :name
    ↪ adjoin-retract2))))))
```

Combinators are motivated from existing, real-world, DTL libraries!



# Generated 200+ theories using the Lisp metaprogramming framework —the MathScheme library

```
AdditiveMagma           = Magma renaming' "_*_ to _+_"
LeftDivisionMagma       = Magma renaming' "_*_ to _\_"
RightDivisionMagma      = Magma renaming' "_*_ to _/__"
LeftOperation           = MultiCarrier extended-by' "_>>_ : U → S → S"
RightOperation          = MultiCarrier extended-by' "_<<_ : S → U → S"
IdempotentMagma         = Magma extended-by' "*-idempotent : ∀ (x : U) → (x * x) ≡ x"
IdempotentAdditiveMagma = IdempotentMagma renaming' "_*_ to _+_"
SelectiveMagma          = Magma extended-by' "*-selective : ∀ (x y : U) → (x * y ≡ x) ⊔ (x * y ≡ y)"
SelectiveAdditiveMagma  = SelectiveMagma renaming' "_*_ to _+_"
PointedMagma            = Magma union' PointedCarrier
PointedOMagma           = PointedMagma renaming' "e to 0"
AdditivePointed1Magma   = PointedMagma renaming' "_*_ to _+_; e to 1"
LeftPointAction         = PointedMagma extended-by' "pointactLeft : U → U; pointactLeft x = e * x"
RightPointAction        = PointedMagma extended-by' "pointactRight : U → U; pointactRight x = x * e"
CommutativeMagma        = Magma extended-by' "*-commutative : ∀ (x y : U) → (x * y) ≡ (y * x)"
CommutativeAdditiveMagma = CommutativeMagma renaming' "_*_ to _+_"
PointedCommutativeMagma = PointedMagma union' CommutativeMagma ⊕→ :remark "over Magma"
AntiAbsorbent           = Magma extended-by' "*-anti-self-absorbent : ∀ (x y : U) → (x * (x * y)) ≡ y"
SteinerMagma            = CommutativeMagma union' AntiAbsorbent ⊕→ :remark "over Magma"
Squag                   = SteinerMagma union' IdempotentMagma ⊕→ :remark "over Magma"
PointedSteinerMagma     = PointedMagma union' SteinerMagma ⊕→ :remark "over Magma"
UnipotentPointedMagma   = PointedMagma extended-by' "unipotent : ∀ (x : U) → (x * x) ≡ e"
Sloop                   = PointedSteinerMagma union' UnipotentPointedMagma
```



# Generated 200+ theories using the Lisp metaprogramming framework —the MathScheme library

AdditiveMagma	= Magma renaming' "_*_ to _+_"
LeftDivisionMagma	= Magma renaming' "_*_ to _\_"
RightDivisionMagma	= Magma renaming' "_*_ to _/"
LeftOperation	
RightOperation	
IdempotentMagma	
IdempotentAdditive	
SelectiveMagma	= Magma extended-by' "*-selective : $\forall (x\ y : U) \rightarrow (x * y \equiv x) \sqcup (x * y \equiv y)$ "
SelectiveAdditiveMagma	= SelectiveMagma renaming' "_*_ to _+_"
PointedMagma	= Magma union' PointedCarrier
PointedOMagma	= PointedMagma renaming' "e to 0"
AdditivePointed1Magma	= PointedMagma renaming' "_*_ to _+_; e to 1"
LeftPointAction	= PointedMagma extended-by' "pointactLeft : $U \rightarrow U$ ; pointactLeft $x = e * x$ "
RightPointAction	= PointedMagma extended-by' "pointactRight : $U \rightarrow U$ ; pointactRight $x = x * e$ "
CommutativeMagma	= Magma extended-by' "*-commutative : $\forall (x\ y : U) \rightarrow (x * y) \equiv (y * x)$ "
CommutativeAdditiveMagma	= CommutativeMagma renaming' "_*_ to _+_"
PointedCommutativeMagma	= PointedMagma union' CommutativeMagma $\oplus$ :remark "over Magma"
AntiAbsorbent	= Magma extended-by' "*-anti-self-absorbent : $\forall (x\ y : U) \rightarrow (x * (x * y)) \equiv y$ "
SteinerMagma	= CommutativeMagma union' AntiAbsorbent $\oplus$ :remark "over Magma"
Squag	= SteinerMagma union' IdempotentMagma $\oplus$ :remark "over Magma"
PointedSteinerMagma	= PointedMagma union' SteinerMagma $\oplus$ :remark "over Magma"
UnipotentPointedMagma	= PointedMagma extended-by' "unipotent : $\forall (x : U) \rightarrow (x * x) \equiv e$ "
Sloop	= PointedSteinerMagma union' UnipotentPointedMagma

Terse, readable, specifications

→ Useful, typecheckable, dauntingly large code

# Generated 200+ theories using the Lisp metaprogramming framework —the MathScheme library

```
AdditiveMagma           = Magma renaming' "_*_ to _+_"
LeftDivisionMagma       = Magma renaming' "_*_ to _\_"
RightDivisionMagma      = Magma renaming' "_*_ to _/"
LeftOperation
RightOperation
IdempotentMagma
IdempotentAdditive
SelectiveMagma           = Magma extended-by' "*-selective :  $\forall (x\ y : U) \rightarrow (x * y \equiv x) \sqcup (x * y \equiv y)$ "
SelectiveAdditiveMagma  = SelectiveMagma renaming' "_*_ to _+_"
PointedMagma             = Magma union' PointedCarrier
PointedOMagma            = Magma union' PointedCarrier
AdditivePointedMagma     = Magma union' PointedCarrier
LeftPointAction          = Magma union' PointedCarrier
RightPointAction         = Magma union' PointedCarrier
CommutativeMagma         = Magma extended-by' "*-commutative :  $\forall (x\ y : U) \rightarrow (x * y) \equiv (y * x)$ "
CommutativeAdditiveMagma = CommutativeMagma renaming' "_*_ to _+_"
PointedCommutativeMagma  = PointedMagma union' CommutativeMagma  $\oplus$  :remark "over Magma"
AntiAbsorbent            = Magma extended-by' "*-anti-self-absorbent :  $\forall (x\ y : U) \rightarrow (x * (x * y)) \equiv y$ "
SteinerMagma             = CommutativeMagma union' AntiAbsorbent  $\oplus$  :remark "over Magma"
Squag                   = SteinerMagma union' IdempotentMagma  $\oplus$  :remark "over Magma"
PointedSteinerMagma      = PointedMagma union' SteinerMagma  $\oplus$  :remark "over Magma"
UnipotentPointedMagma    = PointedMagma extended-by' "unipotent :  $\forall (x : U) \rightarrow (x * x) \equiv e$ "
Sloop                   = PointedSteinerMagma union' UnipotentPointedMagma
```

Terse, readable, specifications  
→ Useful, typecheckable, dauntingly large code

200+ one-line specs  
→ 1500+ lines of typechecked Agda

# Generated 200+ theories using the Lisp metaprogramming framework —the MathScheme library

```
AdditiveMagma           = Magma renaming' "_*_ to _+_"
LeftDivisionMagma       = Magma renaming' "_*_ to _\_"
RightDivisionMagma      = Magma renaming' "_*_ to _/"
LeftOperation
RightOperation
IdempotentMagma
IdempotentAdditive
SelectiveMagma           = Magma extended-by' "*-selective :  $\forall (x\ y : U) \rightarrow (x * y \equiv x) \sqcup (x * y \equiv y)$ "
SelectiveAdditiveMagma  = SelectiveMagma renaming' "_*_ to _+_"
PointedMagma             = Magma union' PointedCarrier
PointedOMagma            = Magma union' PointedCarrier
AdditivePointedMagma     = Magma union' PointedCarrier
LeftPointAction          = Magma union' PointedCarrier
RightPointAction         = Magma union' PointedCarrier
CommutativeMagma         = Magma union' PointedCarrier
CommutativeAdditiveMagma = Magma union' PointedCarrier
PointedCommutativeMagma  = Magma union' PointedCarrier
AntiAbsorbent            = Magma union' PointedCarrier
SteinerMagma             = Magma union' PointedCarrier
Squag                    = Magma union' PointedCarrier
PointedSteinerMagma      = Magma union' PointedCarrier
UnipotentPointedMagma    = Magma union' PointedCarrier
Sloop                    = Magma union' PointedCarrier
```

Terse, readable, specifications  
⇒ Useful, typecheckable, dauntingly large code

200+ **one-line specs**  
⇒ 1500+ lines of typechecked Agda  
⇒ 750% efficiency savings

Useful engineering result

## Primary Lessons Learned

## Primary Lessons Learned

**Waist** The difference between **field** and **parameter** is an illusion —as is that of **input** and **output** when one considers relations rather than deterministic functions.

## Primary Lessons Learned

**Waist** The difference between **field** and **parameter** is an illusion —as is that of **input** and **output** when one considers relations rather than deterministic functions.

**Termtypes** Record types ( $\Sigma$ ), type classes ( $\Pi^1\Sigma$ ), and algebraic data types ( $\mathcal{W}$ ) are all valid **semantics of contexts** —which are “name : type = optional-definition” tuples.

# Primary Lessons Learned

**Waist** The difference between **field** and **parameter** is an illusion —as is that of **input** and **output** when one considers relations rather than deterministic functions.

**Termtypes** Record types ( $\Sigma$ ), type classes ( $\Pi^1\Sigma$ ), and algebraic data types ( $\mathcal{W}$ ) are all valid **semantics of contexts** —which are “name : type = optional-definition” tuples.

**Pragmatic** We have an extendable,

## Primary Lessons Learned

**Waist** The difference between **field** and **parameter** is an illusion —as is that of **input** and **output** when one considers relations rather than deterministic functions.

**Termtypes** Record types ( $\Sigma$ ), type classes ( $\Pi^1\Sigma$ ), and algebraic data types ( $\mathcal{W}$ ) are all valid **semantics of contexts** —which are “name : type = optional-definition” tuples.

**Pragmatic** We have an extendable, expressive,



# Primary Lessons Learned

**Waist** The difference between **field** and **parameter** is an illusion —as is that of **input** and **output** when one considers relations rather than deterministic functions.

**Termtypes** Record types ( $\Sigma$ ), type classes ( $\Pi^1\Sigma$ ), and algebraic data types ( $\mathcal{W}$ ) are all valid **semantics of contexts** —which are “name : type = optional-definition” tuples.

**Pragmatic** We have an extendable, expressive, and efficient interface based on a small kernel,

# Primary Lessons Learned

**Waist** The difference between **field** and **parameter** is an illusion —as is that of **input** and **output** when one considers relations rather than deterministic functions.

**Termtypes** Record types ( $\Sigma$ ), type classes ( $\Pi^1\Sigma$ ), and algebraic data types ( $\mathcal{W}$ ) are all valid **semantics of contexts** —which are “name : type = optional-definition” tuples.

**Pragmatic** We have an extendable, expressive, and efficient interface based on a small kernel, that is immediately usable,

# Primary Lessons Learned

**Waist** The difference between **field** and **parameter** is an illusion —as is that of **input** and **output** when one considers relations rather than deterministic functions.

**Termtypes** Record types ( $\Sigma$ ), type classes ( $\Pi^1\Sigma$ ), and algebraic data types ( $\mathcal{W}$ ) are all valid **semantics of contexts** —which are “name : type = optional-definition” tuples.

**Pragmatic** We have an extendable, expressive, and efficient interface based on a small kernel, that is immediately usable, as an editor extension;

# Primary Lessons Learned

**Waist** The difference between **field** and **parameter** is an illusion —as is that of **input** and **output** when one considers relations rather than deterministic functions.

**Termtypes** Record types ( $\Sigma$ ), type classes ( $\Pi^1\Sigma$ ), and algebraic data types ( $\mathcal{W}$ ) are all valid **semantics of contexts** —which are “name : type = optional-definition” tuples.

**Pragmatic** We have an extendable, expressive, and efficient interface based on a small kernel, that is immediately usable, as an editor extension; what about an in-language (DTL) library?

# The Unbundling Problem —in Agda

---

# What is “the” monoid on the natural numbers?

Haskell’s solution is to make **two isomorphic copies** of numbers since typeclass instance search relies on *unique* instances for the typeclass parameters.

*Some types can be viewed as a monoid in more than one way, e.g. both addition and multiplication on numbers. In such cases we often define newtypes and make those instances of Monoid, e.g. Sum and Product. —Hackage Data.Monoid*

$$\text{Sum } \alpha \cong \alpha \quad \{- \text{ and } -\} \quad \text{Product } \alpha \cong \alpha$$

For **Num**  $\alpha$  they have different monoid instances.

# Alternate Solution to Multiple Monoid Instance Problem

# Alternate Solution to Multiple Monoid Instance Problem

Start with *fully bundled* Monoid



## Alternate Solution to Multiple Monoid Instance Problem

Start with *fully bundled* `Monoid` then *expose fields as parameters on the fly*.

## Alternate Solution to Multiple Monoid Instance Problem

Start with *fully bundled* `Monoid` then *expose fields as parameters on the fly*.

How?

# Alternate Solution to Multiple Monoid Instance Problem

Start with *fully bundled* `Monoid` then *expose fields as parameters on the fly*.

How?

Reflection!

# Alternate Solution to Multiple Monoid Instance Problem

Start with *fully bundled* `Monoid` then *expose fields as parameters on the fly*.

How?

Reflection!

- Unfortunately, current mechanism cannot touch `record-s` *directly*.
- But every record is a  $\Sigma$ -type...

# Records as $\Pi^w \Sigma$ -types — Partitioned Contexts

- Instead of the nice *syntactic sugar*

```
record R ( $\varepsilon^1 : \tau^1$ )  $\cdots$  ( $\varepsilon^w : \tau^w$ ) : Set
```

```
  where
```

```
    field
```

```
       $\varepsilon^{w+1} : \tau^{w+1}$ 
```

```
       $\vdots$ 
```

```
       $\varepsilon^{w+k} : \tau^{w+k}$ 
```

# Records as $\Pi^w \Sigma$ -types —Partitioned Contexts

- Instead of the nice *syntactic sugar*

**record**  $\mathbf{R}$   $(\varepsilon^1 : \tau^1) \cdots (\varepsilon^w : \tau^w) : \mathbf{Set}$

**where**

**field**

$\varepsilon^{w+1} : \tau^{w+1}$

$\vdots$

$\varepsilon^{w+k} : \tau^{w+k}$

- Use a more raw form —*EEK!*

$\mathbf{R} : \Pi \varepsilon^1 : \tau^1 \bullet \cdots \bullet \Pi \varepsilon^w : \tau^w \bullet \mathbf{Set}$

$\mathbf{R} \cong \lambda \varepsilon^1 : \tau^1 \bullet \cdots \bullet \lambda \varepsilon^w : \tau^w$

$\bullet \Sigma \varepsilon^{w+1} : \tau^{w+1} \bullet \cdots \bullet \Sigma \varepsilon^{w+k} : \tau^{w+k}$

$\bullet \mathbb{1}$

# Records as $\Pi^w \Sigma$ -types — Partitioned Contexts

- Instead of the nice *syntactic sugar*

**record**  $\mathbf{R}$   $(\varepsilon^1 : \tau^1) \cdots (\varepsilon^w : \tau^w) : \mathbf{Set}$

**where**

**field**

$\varepsilon^{w+1} : \tau^{w+1}$

$\vdots$

$\varepsilon^{w+k} : \tau^{w+k}$

- Use a more raw form —*EEK!*

$\mathbf{R} : \Pi \varepsilon^1 : \tau^1 \bullet \cdots \bullet \Pi \varepsilon^w : \tau^w \bullet \mathbf{Set}$

$\mathbf{R} \cong \lambda \varepsilon^1 : \tau^1 \bullet \cdots \bullet \lambda \varepsilon^w : \tau^w$

$\bullet \Sigma \varepsilon^{w+1} : \tau^{w+1} \bullet \cdots \bullet \Sigma \varepsilon^{w+k} : \tau^{w+k}$

$\bullet \mathbb{1}$

$\Leftarrow$  “parameters”

# Records as $\Pi^w \Sigma$ -types — Partitioned Contexts

- Instead of the nice *syntactic sugar*

**record** **R** ( $\varepsilon^1 : \tau^1$ )  $\dots$  ( $\varepsilon^w : \tau^w$ ) : **Set**

**where**

**field**

$\varepsilon^{w+1} : \tau^{w+1}$

$\vdots$

$\varepsilon^{w+k} : \tau^{w+k}$

- Use a more raw form —*EEK!*

**R** :  $\Pi \varepsilon^1 : \tau^1 \bullet \dots \bullet \Pi \varepsilon^w : \tau^w \bullet \mathbf{Set}$

**R**  $\cong \lambda \varepsilon^1 : \tau^1 \bullet \dots \bullet \lambda \varepsilon^w : \tau^w$

$\bullet \Sigma \varepsilon^{w+1} : \tau^{w+1} \bullet \dots \bullet \Sigma \varepsilon^{w+k} : \tau^{w+k}$

$\bullet \mathbb{1}$

$\Leftarrow$  “parameters”

$\Leftarrow$  “fields”



# Records as $\Pi^w \Sigma$ -types — Partitioned Contexts

- Instead of the nice *syntactic sugar*

**record**  $\mathbf{R}$   $(\varepsilon^1 : \tau^1) \cdots (\varepsilon^w : \tau^w) : \mathbf{Set}$

**where**

**field**

$\varepsilon^{w+1} : \tau^{w+1}$

$\vdots$

$\varepsilon^{w+k} : \tau^{w+k}$

- Use a more raw form —*EEK!*

$\mathbf{R} : \Pi \varepsilon^1 : \tau^1 \bullet \cdots \bullet \Pi \varepsilon^w : \tau^w \bullet \mathbf{Set}$

$\mathbf{R} \cong \lambda \varepsilon^1 : \tau^1 \bullet \cdots \bullet \lambda \varepsilon^w : \tau^w$

$\bullet \Sigma \varepsilon^{w+1} : \tau^{w+1} \bullet \cdots \bullet \Sigma \varepsilon^{w+k} : \tau^{w+k}$

$\bullet \mathbb{1}$

$\Leftarrow$  “parameters”

$\Leftarrow$  “fields”

We say  $w$  is the “**waist**”

## A Pragmatic Notation —Contexts

1. “Contexts” are exposure-indexed types

`Context` =  $\lambda \ell \rightarrow (\text{waist} : \mathbb{N}) \rightarrow \text{Set } \ell$

## A Pragmatic Notation —Contexts

1. “Contexts” are exposure-indexed types

$$\text{Context} = \lambda \ell \rightarrow (\text{waist} : \mathbb{N}) \rightarrow \text{Set } \ell$$

2. The “empty context” is the unit type

$$\text{End} : \forall \{\ell\} \rightarrow \text{Context } \ell$$
$$\text{End } \{\ell\} = \lambda \_ \rightarrow \mathbb{1} \{\ell\}$$

## A Pragmatic Notation —Contexts

1. “Contexts” are exposure-indexed types

$$\text{Context} = \lambda \ell \rightarrow (\text{waist} : \mathbb{N}) \rightarrow \text{Set } \ell$$

2. The “empty context” is the unit type

$$\text{End} : \forall \{\ell\} \rightarrow \text{Context } \ell$$
$$\text{End } \{\ell\} = \lambda \_ \rightarrow \mathbb{1} \{\ell\}$$

3. **do**-notation!

$$\_ >=> \_ : \forall \{a \ b\}$$
$$\rightarrow (\Gamma : \text{Context } a)$$
$$\rightarrow (\forall \{n\} \rightarrow \Gamma \ n \rightarrow \text{Context } b)$$
$$\rightarrow \text{Context } (a \uplus b)$$
$$(\Gamma >=> f) \text{ zero} = \sum \gamma : \Gamma \ 0 \bullet f \ \gamma \ 0$$
$$(\Gamma >=> f) (\text{suc } n) = \prod \gamma : \Gamma \ n \bullet f \ \gamma \ n$$

## A Pragmatic Notation —Contexts

1. “Contexts” are exposure-indexed types

$$\mathbf{Context} = \lambda \ell \rightarrow (\mathbf{waist} : \mathbb{N}) \rightarrow \mathbf{Set} \ell$$

2. The “empty context” is the unit type

$$\mathbf{End} : \forall \{\ell\} \rightarrow \mathbf{Context} \ell$$
$$\mathbf{End} \{\ell\} = \lambda \_ \rightarrow \mathbb{1} \{\ell\}$$

3. **do**-notation!

$$\_ \gg= \_ : \forall \{a \ b\}$$
$$\rightarrow (\Gamma : \mathbf{Context} \ a)$$
$$\rightarrow (\forall \{n\} \rightarrow \Gamma \ n \rightarrow \mathbf{Context} \ b)$$
$$\rightarrow \mathbf{Context} \ (a \uplus b)$$
$$(\Gamma \gg= f) \ \mathbf{zero} \quad = \ \Sigma \ \gamma : \Gamma \ 0 \bullet f \ \gamma \ 0$$
$$(\Gamma \gg= f) \ (\mathbf{suc} \ n) = \Pi \ \gamma : \Gamma \ n \bullet f \ \gamma \ n$$

The “DIY” lies at  $\gg=$ , permitting  $\Sigma$ ,  $\Pi$ ,  $\mathcal{W}$ ,  $\mathbf{let}$ , ... !

## Example Context —Monoids

```
Monoid : Context  $\ell_1$ 
Monoid = do Carrier  $\leftarrow$  Set
           _ $\circ$ _       $\leftarrow$  (Carrier  $\rightarrow$  Carrier  $\rightarrow$  Carrier)
           Id        $\leftarrow$  Carrier
           leftId    $\leftarrow$   $\forall$  (x : Carrier)  $\rightarrow$  x  $\circ$  Id  $\equiv$  x
           rightId   $\leftarrow$   $\forall$  (x : Carrier)  $\rightarrow$  Id  $\circ$  x  $\equiv$  x
           assoc     $\leftarrow$   $\forall$  (x y z)  $\rightarrow$  (x  $\circ$  y)  $\circ$  z  $\equiv$  x  $\circ$  (y  $\circ$  z)
           End { $\ell$ }
```

- If  $C : \text{Context } \ell_0$  then  $C_w$  has the type  $\Pi^w x \bullet \tau$ —consisting of  $w$ -many  $\Pi$ 's—

## Using Contexts —*reification*

- If  $C : \text{Context } \ell_0$  then  $C_w$  has the type  $\Pi^w x \bullet \tau$ —consisting of  $w$ -many  $\Pi$ 's— but we want to **apply**  $C_w$  to  $w$ -many *parameters*. . .



## Using Contexts —*reification*

- If  $C : \text{Context } \ell_0$  then  $C_w$  has the type  $\Pi^w x \bullet \tau$ —consisting of  $w$ -many  $\Pi$ 's— but we want to **apply**  $C_w$  to  $w$ -many *parameters*. . .
- So we need a combinator. . .

$$\Pi \rightarrow \lambda \quad “\Pi^w x \bullet \tau” \quad = \quad “\lambda^w x \bullet \tau”$$

## Using Contexts —*reification*

- If  $C : \text{Context } \ell_0$  then  $C_w$  has the type  $\Pi^w x \bullet \tau$ —consisting of  $w$ -many  $\Pi$ 's— but we want to **apply**  $C_w$  to  $w$ -many *parameters*...

- So we need a combinator...

$$\Pi \rightarrow \lambda \text{ “}\Pi^w x \bullet \tau\text{”} = \text{“}\lambda^w x \bullet \tau\text{”}$$

- with an infix form for contexts in particular ...

$$C : \text{waist } w = \Pi \rightarrow \lambda (C_w)$$

## Characterising `:waist` as $\Pi \rightarrow \lambda$

$$\begin{aligned}\Pi \rightarrow \lambda \ (\Pi \ a : A \bullet \tau) &= (\lambda \ a : A \bullet \tau) \\ C : \text{waist } w &= \Pi \rightarrow \lambda \ (C \ w)\end{aligned}$$

## Characterising `:waist` as $\Pi \rightarrow \lambda$

$$\begin{aligned}\Pi \rightarrow \lambda \ (\Pi \ a : A \bullet \tau) &= (\lambda \ a : A \bullet \tau) \\ C : \text{waist } w &= \Pi \rightarrow \lambda \ (C \ w)\end{aligned}$$

---

`id0 : Set1`

`id0 =  $\Pi \ X : \text{Set} \bullet \Pi \ e : X \bullet X$`

## Characterising $\text{:waist}$ as $\Pi \rightarrow \lambda$

$$\begin{aligned}\Pi \rightarrow \lambda \ (\Pi \ a : A \bullet \tau) &= (\lambda \ a : A \bullet \tau) \\ C \text{:waist } w &= \Pi \rightarrow \lambda \ (C \ w)\end{aligned}$$

---

$\text{id}_0 : \text{Set}_1$

$\text{id}_0 = \Pi \ X : \text{Set} \bullet \Pi \ e : X \bullet X$

$\text{id}_1 : \Pi \ X : \text{Set} \bullet \text{Set}$

$\text{id}_1 = \lambda \ (X : \text{Set}) \rightarrow \Pi \ e : X \bullet X$

## Characterising $\text{:waist}$ as $\Pi \rightarrow \lambda$

$$\begin{aligned}\Pi \rightarrow \lambda \ (\Pi \ a : A \bullet \tau) &= (\lambda \ a : A \bullet \tau) \\ C \text{:waist } w &= \Pi \rightarrow \lambda \ (C \ w)\end{aligned}$$

---

$\text{id}_0 : \text{Set}_1$

$\text{id}_0 = \Pi \ X : \text{Set} \bullet \Pi \ e : X \bullet X$

$\text{id}_1 : \Pi \ X : \text{Set} \bullet \text{Set}$

$\text{id}_1 = \lambda \ (X : \text{Set}) \rightarrow \Pi \ e : X \bullet X$

$\text{id}_2 : \Pi \ X : \text{Set} \bullet \Pi \ e : X \bullet \text{Set}$

$\text{id}_2 = \lambda \ (X : \text{Set}) \ (e : X) \rightarrow X$

## Characterising $\text{waist}$ as $\Pi \rightarrow \lambda$

$$\begin{aligned}\Pi \rightarrow \lambda (\Pi a : A \bullet \tau) &= (\lambda a : A \bullet \tau) \\ C : \text{waist } w &= \Pi \rightarrow \lambda (C w)\end{aligned}$$

---

```
id0 : Set1
id0 =  $\Pi X : \text{Set} \bullet \Pi e : X \bullet X$ 

id1 :  $\Pi X : \text{Set} \bullet \text{Set}$ 
id1 =  $\lambda (X : \text{Set}) \rightarrow \Pi e : X \bullet X$ 

id2 :  $\Pi X : \text{Set} \bullet \Pi e : X \bullet \text{Set}$ 
id2 =  $\lambda (X : \text{Set}) (e : X) \rightarrow X$ 
```

- $\text{id}_{i+1} \approx \Pi \rightarrow \lambda \text{id}_i$
- $\text{id}_0$  is a *type of functions*
- $\text{id}_1$  is a *function on types*

# Monoid<sub>i</sub>

Monoid : Context

Monoid = do C ← Set;  $\_ \circ \_$  : C → C → C; Id ← C; ...



# Monoid<sub>i</sub>

```
Monoid : Context
```

```
Monoid = do C ← Set; _◦_ : C → C → C; Id ← C; ...
```

With no parameters, we have a  $\Pi^0\Sigma$ -type (a **record**)

```
Monoid :waist 0 : Set1
```

```
Monoid :waist 0 ≡  $\Sigma C : \text{Set} \bullet \Sigma \_ \circ \_ : C \rightarrow C \rightarrow C \bullet \Sigma \text{Id} : C \bullet \dots$ 
```

# Monoid<sub>i</sub>

```
Monoid : Context
```

```
Monoid = do C ← Set; _◦_ : C → C → C; Id ← C; ...
```

With no parameters, we have a  $\Pi^0\Sigma$ -type (a **record**)

```
Monoid :waist 0 : Set1
```

```
Monoid :waist 0 ≡  $\Sigma C : \text{Set} \bullet \Sigma \_◦\_ : C \rightarrow C \rightarrow C \bullet \Sigma \text{Id} : C \bullet \dots$ 
```

With **one** parameter, we have a **typeclass**

```
Monoid :waist 1 :  $\Pi C : \text{Set} \bullet \text{Set}$ 
```

```
Monoid :waist 1 =  $\lambda C : \text{Set} \bullet \Sigma \_◦\_ : C \rightarrow C \rightarrow C \bullet \Sigma \text{Id} : C \bullet \dots$ 
```

# Monoid<sub>i</sub>

```
Monoid : Context
```

```
Monoid = do C ← Set; _∘_ : C → C → C; Id ← C; ...
```

With no parameters, we have a  $\Pi^0\Sigma$ -type (a **record**)

```
Monoid :waist 0 : Set1
```

```
Monoid :waist 0 ≡  $\Sigma C : \text{Set} \bullet \Sigma \_ \circ \_ : C \rightarrow C \rightarrow C \bullet \Sigma \text{Id} : C \bullet \dots$ 
```

With **one** parameter, we have a **typeclass**

```
Monoid :waist 1 :  $\Pi C : \text{Set} \bullet \text{Set}$ 
```

```
Monoid :waist 1 =  $\lambda C : \text{Set} \bullet \Sigma \_ \circ \_ : C \rightarrow C \rightarrow C \bullet \Sigma \text{Id} : C \bullet \dots$ 
```

With **two** parameters, we have a ‘*solution*’ to the additive-or-multiplicative-monoid-problem!

```
Monoid :waist 2 :  $\Pi C : \text{Set}) \bullet \Pi \_ \circ \_ : C \rightarrow C \rightarrow C \bullet \text{Set}$ 
```

```
Monoid :waist 2 =  $\lambda C : \text{Set} \bullet \lambda \_ \circ \_ : C \rightarrow C \rightarrow C \bullet \Sigma \text{Id} : C \bullet \dots$ 
```

## Example Instance —Additive Naturals

```
 $\mathbb{N}_+$  : (Monoid  $\ell_0$  :waist 1)  $\mathbb{N}$   
 $\mathbb{N}_+$  = <  $_{-}+_{-}$  --  $_{-}\circ_{-}$   
      , 0 --  $Id$   
      , +-identity'  
      , +-identityr  
      , +-assoc  
      >
```

On-the-fly unbundling can be implemented as an in-language library in a dependently-typed language with sufficient reflection capabilities :-)

★ ★ ★

The **Context** approach *inherits* the strengths and limitations of the host language.

## Comparing PackageFormer and Context

	PackageFormer	Contexts
Type of Entity	Preprocessing Tool	Language Library
Specification Language	Lisp + Agda	Agda
Well-formedness Checking	×	✓
Termination Checking	✓	✓
Elaboration Tooltips	✓	×
Rapid Prototyping	✓	✓ (Slower)
Usability Barrier	None	None
Extensibility Barrier	Lisp	Weak Metaprogramming

**GADTs are Contexts too!**

---

# From Contexts to GADTS

Monoid



# From Contexts to GADTS

Monoid

$\rightsquigarrow$

```
do C ← Set;  $\circ$  : C → C → C; Id : C; ...
```

# From Contexts to GADTS

Monoid

$\rightsquigarrow$

`do C ← Set;  $\circ$  : C → C → C; Id : C; ...`

$\rightsquigarrow$

`λ C : Set •  $\Sigma$   $\circ$  : C → C → C •  $\Sigma$  Id : C • ...`

# From Contexts to GADTS

Monoid

$\rightsquigarrow$

`do C ← Set;  $\circ_{-}$  : C → C → C; Id : C; ...`

$\rightsquigarrow$

`λ C : Set •  $\Sigma$   $\circ_{-}$  : C → C → C •  $\Sigma$  Id : C • ...`

$\rightsquigarrow$

`λ C : Set •  $\Sigma$   $\circ_{-}$  : C → C → C •  $\Sigma$  Id : C •  $\mathbb{1}$`

# From Contexts to GADTS

Monoid

$\rightsquigarrow$

`do C ← Set;  $\circ$  : C → C → C; Id : C; ...`

$\rightsquigarrow$

`λ C : Set • Σ  $\circ$  : C → C → C • Σ Id : C • ...`

$\rightsquigarrow$

`λ C : Set • Σ  $\circ$  : C → C → C • Σ Id : C • 1`

$\rightsquigarrow$

`λ C : Set • C × C ⊔ C ⊔ 1`

# From Contexts to GADTS

Monoid

$\rightsquigarrow$

`do C ← Set;  $\_ \circ \_$  : C → C → C; Id : C; ...`

$\rightsquigarrow$

`λ C : Set • Σ  $\_ \circ \_$  : C → C → C • Σ Id : C • ...`

$\rightsquigarrow$

`λ C : Set •  
 termtree : UnaryFunctor → Type  
 termtree τ = Fix (Σ → ⊔ (sources τ))`

$\rightsquigarrow$

`λ C : Set •  
 C × C ⊔ C ⊔ 1`

$\rightsquigarrow$

`μ C : Set •  
 C × C ⊔ C ⊔ 1`

# Monoids give rise to tree skeletons / Context

```
Monoid :  $\forall \ell \rightarrow$  Context (lsuc  $\ell$ )  
Monoid  $\ell$  = do Carrier  $\leftarrow$  Set  $\ell$   
             _ $\circ$ _       $\leftarrow$  (Carrier  $\rightarrow$  Carrier  $\rightarrow$  Carrier)  
             Id        $\leftarrow$  Carrier  
             leftId    $\leftarrow$   $\forall \{x : \text{Carrier}\} \rightarrow \text{Id} \circ x \equiv x$   
             rightId   $\leftarrow$   $\forall \{x : \text{Carrier}\} \rightarrow x \circ \text{Id} \equiv x$   
             assoc     $\leftarrow$   $\forall \{x\ y\ z\} \rightarrow (x \circ y) \circ z \equiv x \circ (y \circ z)$   
             End { $\ell$ }
```

# Monoids give rise to tree skeletons / Termtree

```
 $\mathbb{M} : \text{Set}$   
 $\mathbb{M} = \text{termtree } (\text{Monoid } \ell_0 : \text{waist } 1)$   
  
that-is :  $\mathbb{M}$   
   $\equiv \text{Fix } (\lambda X \rightarrow$   
    --  $\oplus$ , branch  
     $X \times X \times \mathbb{1}$   
    -- Id, nil leaf  
     $\oplus \mathbb{1}$   
    -- invariant leftId  
     $\oplus \mathbb{0}$   
    -- invariant rightId  
     $\oplus \mathbb{0}$   
    -- invariant assoc  
     $\oplus \mathbb{0}$   
    -- the “End  $\{\ell\}$ ”  
     $\oplus \mathbb{0})$   
that-is = refl
```

## Monoids give rise to tree skeletons / Readability

```
-- : M
pattern emptyM
    =  $\mu$  (inj2 (inj1 tt))

-- : M → M → M
pattern branchM l r
    =  $\mu$  (inj1 (l , r , tt))

-- absurd 0-values
pattern absurdM a
    =  $\mu$  (inj2 (inj2 (inj2 (inj2 a))))
```



# Monoids give rise to tree skeletons / $\text{termtype Monoid} \cong \text{TreeSkeleton}$

```
data TreeSkeleton : Set where
  empty   : TreeSkeleton
  branch  : TreeSkeleton → TreeSkeleton → TreeSkeleton
```

- “doing nothing”

```
to : M → TreeSkeleton
to emptyM          = empty
to (branchM l r) = branch (to l) (to r)
to (absurdM (inj1 ()))
to (absurdM (inj2 ()))
```

- “doing nothing”

```
from : TreeSkeleton → M
from empty          = emptyM
from (branch l r) = branchM (from l) (from r)
```

# Summary

'theory' $\tau$	'data structure' termtype $\tau$
pointed set	$\mathbb{1}$
dynamic system	$\mathbb{N}$
monoid	tree skeletons
collections	lists
graphs	(homogeneous) pairs
actions	infinite streams

*Many more theories  $\tau$  to explore and see what data structures arise!*

# Contributions

---

0. Identify the **module design patterns** used by DTL practitioners

# Module Systems for DTLs

0. Identify the **module design patterns** used by DTL practitioners
1. The ability to *implement* module systems **for DTLs within DTLs**

# Module Systems for DTLs

0. Identify the **module design patterns** used by DTL practitioners
1. The ability to *implement* module systems **for DTLs within DTLs**
2. The ability to arbitrarily **extend** such systems by users at a high-level

# Module Systems for DTLs

0. Identify the **module design patterns** used by DTL practitioners
1. The ability to *implement* module systems **for DTLs within DTLs**
2. The ability to arbitrarily **extend** such systems by users at a high-level
3. Demonstrate that there is an expressive yet minimal set of **module meta-primitives** which allow common module constructions to be defined

# Module Systems for DTLs

0. Identify the **module design patterns** used by DTL practitioners
1. The ability to *implement* module systems **for DTLs within DTLs**
2. The ability to arbitrarily **extend** such systems by users at a high-level
3. Demonstrate that there is an expressive yet minimal set of **module meta-primitives** which allow common module constructions to be defined
4. Demonstrate that relationships between modules can also be **mechanically** generated.



# Termtypes as Modules

5. Bring **algebraic data types** under the umbrella of grouping mechanisms: An ADT is just a context whose symbols target the ADT 'carrier' and are not otherwise interpreted.
  - In particular, both an ADT and a record can be obtained **practically** from a **single** context declaration.

# Termtypes as Modules

5. Bring **algebraic data types** under the umbrella of grouping mechanisms: An ADT is just a context whose symbols target the ADT 'carrier' and are not otherwise interpreted.
- In particular, both an ADT and a record can be obtained **practically** from a **single** context declaration.

```
DynamicSystem : Context  $\ell_1$ 
```

```
DynamicSystem
```

```
= do State  $\leftarrow$  Set  
    start  $\leftarrow$  State  
    next  $\leftarrow$  (State  $\rightarrow$  State)  
End
```

# Termtypes as Modules

5. Bring **algebraic data types** under the umbrella of grouping mechanisms: An ADT is just a context whose symbols target the ADT 'carrier' and are not otherwise interpreted.
- In particular, both an ADT and a record can be obtained **practically** from a **single** context declaration.

```
DynamicSystem : Context  $\ell_1$                                 data  $\mathbb{D}$  : Set where
DynamicSystem                                           startD :  $\mathbb{D}$ 
= do State  $\leftarrow$  Set                                   nextD  :  $\mathbb{D} \rightarrow \mathbb{D}$ 
    start  $\leftarrow$  State
    next   $\leftarrow$  (State  $\rightarrow$  State)
End
```

# Termtypes as Modules

5. Bring **algebraic data types** under the umbrella of grouping mechanisms: An ADT is just a context whose symbols target the ADT 'carrier' and are not otherwise interpreted.
- In particular, both an ADT and a record can be obtained **practically** from a **single** context declaration.

```
DynamicSystem : Context  $\ell_1$                                 data  $\mathbb{D}$  : Set where
DynamicSystem                                           startD :  $\mathbb{D}$ 
= do State  $\leftarrow$  Set                                nextD  :  $\mathbb{D} \rightarrow \mathbb{D}$ 
    start  $\leftarrow$  State
    next   $\leftarrow$  (State  $\rightarrow$  State)
End
```

---

```
 $\mathbb{D}$  = termtype (DynamicSystem :waist 1)
```

```
-- Pattern synonyms for more compact presentation
pattern startD =  $\mu$  (inj1 tt)      -- :  $\mathbb{D}$ 
pattern nextD e =  $\mu$  (inj2 (inj1 e)) -- :  $\mathbb{D} \rightarrow \mathbb{D}$ 
trivial :  $\mathbb{D} \cong \mathbb{N}$ 
```

## Common data-structures as free termtypes

6. Show that common data-structures are mechanically the (free) termtypes of common modules.

# Common data-structures as free termtypes

6. Show that common data-structures are mechanically the (free) termtypes of common modules.

Module System	Termtyp
Dynamical Structures	Naturals
Collection Structures	Lists
Pointed Structures	Maybe

# Common data-structures as free termtypes

6. Show that common data-structures are mechanically the (free) termtypes of common modules.

Module System	Termtype
Dynamical Structures	Naturals
Collection Structures	Lists
Pointed Structures	Maybe

```
Collection :  $\forall \ell \rightarrow \text{Context } (\text{lsuc } \ell)$ 
```

```
Collection  $\ell = \text{do Elem} \leftarrow \text{Set } \ell$ 
```

```
Carrier  $\leftarrow \text{Set } \ell$ 
```

```
insert  $\leftarrow (\text{Elem} \rightarrow \text{Carrier} \rightarrow \text{Carrier})$ 
```

```
 $\emptyset \leftarrow \text{Carrier}$ 
```

```
End  $\{\ell\}$ 
```

```
List : Set  $\rightarrow$  Set
```

```
List ElemType = termtype ((Collection  $\ell_0$  :waist 2) ElemType)
```

```
pattern _::_ x xs =  $\mu$  (inj1 (x , xs , tt))
```

```
pattern  $\emptyset$  =  $\mu$  (inj2 (inj1 tt))
```

## Solve the unbundling problem —all in Agda!

7. The ability to ‘unbundle’ module fields as if they were parameters ‘on the fly’



# Solve the unbundling problem —all in Agda!

7. The ability to ‘unbundle’ module fields as if they were parameters ‘on the fly’
- 

```
DynamicSystem : Context  $\ell_1$   
DynamicSystem  
  = do State  $\leftarrow$  Set  
      start  $\leftarrow$  State  
      next  $\leftarrow$  (State  $\rightarrow$  State)  
      End
```

# Solve the unbundling problem —all in Agda!

7. The ability to ‘unbundle’ module fields as if they were parameters ‘on the fly’

---

<code>DynamicSystem : Context <math>\ell_1</math></code>	<code><math>\mathcal{N}^1</math> : (DynamicSystem :waist 1) <math>\mathbb{N}</math></code>
<code>DynamicSystem</code>	<code><math>\mathcal{N}^1</math> = <math>\langle 0 , \text{ suc } \rangle</math></code>
<code>  = do State <math>\leftarrow</math> Set</code>	
<code>    start <math>\leftarrow</math> State</code>	<code><math>\mathcal{N}^2</math> : (DynamicSystem :waist 2) <math>\mathbb{N}</math> 0</code>
<code>    next <math>\leftarrow</math> (State <math>\rightarrow</math> State)</code>	<code><math>\mathcal{N}^2</math> = <math>\langle \text{ suc } \rangle</math></code>
<code>  End</code>	
<code><math>\mathcal{N}^0</math> : DynamicSystem :waist 0</code>	<code><math>\mathcal{N}^3</math> : (DynamicSystem :waist 3) <math>\mathbb{N}</math> 0</code>
<code><math>\mathcal{N}^0</math> = <math>\langle \mathbb{N} , 0 , \text{ suc } \rangle</math></code>	<code><math>\hookrightarrow \text{ suc}</math></code>
	<code><math>\mathcal{N}^3</math> = <math>\langle \rangle</math></code>

Without redefining `DynamicSystem`, we are able to **fix** some of its *fields* by making them into *parameters*!

8. Demonstrate that there is a **practical implementation** of such a framework
  - ☒ The Context framework is implemented in Agda and we've seen practical examples of its use.

8. Demonstrate that there is a **practical implementation** of such a framework
  - ☒ The Context framework is implemented in Agda and we've seen practical examples of its use.
9. Finally, the resulting framework is *mostly* **type-theory agnostic**: The target setting is DTLs but we only assume the barebones; if users drop parts of that theory, then *only* some parts of the framework will no longer apply.
  - ☒ There are various forms of semantics presented in the thesis: Abstract semantics via signatures, concrete semantics via Agda functions, denotational semantics via  $\Pi\Sigma\mathcal{W}$ , as well as a guide for forming the **Context** library in other languages.

“All” module constructions are born from Context

## “All” module constructions are born from Context

- Context: “name-type pairs”

```
do S ← Set; s ← S; n ← (S → S); End
```

## “All” module constructions are born from Context

- Context: “name-type pairs”

```
do S ← Set; s ← S; n ← (S → S); End
```

- Record Type: “bundled-up data”

```
 $\Sigma S : \text{Set} \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$ 
```

## “All” module constructions are born from Context

- Context: “name-type pairs”

`do S ← Set; s ← S; n ← (S → S); End`

- Record Type: “bundled-up data”

$\Sigma S : \text{Set} \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet \mathbb{1}$

- Function Type: “a type of functions”

$\Pi S \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet \mathbb{1}$



# “All” module constructions are born from Context

- Context: “name-type pairs”

$\text{do } S \leftarrow \text{Set}; s \leftarrow S; n \leftarrow (S \rightarrow S); \text{End}$

- Record Type: “bundled-up data”

$\Sigma S : \text{Set} \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$

- Function Type: “a type of functions”

$\Pi S \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$

- Type constructor: “a function on types”

$\lambda S \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$

# “All” module constructions are born from Context

- Context: “name-type pairs”

`do S ← Set; s ← S; n ← (S → S); End`

- Record Type: “bundled-up data”

$\Sigma S : \text{Set} \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$

- Function Type: “a type of functions”

$\Pi S \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$

- Type constructor: “a function on types”

$\lambda S \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$

- Algebraic datatype: “a descriptive syntax”

`data D : Set where s : D; n : D → D`

# “All” module constructions are born from Context

- Context: “name-type pairs”

`do S ← Set; s ← S; n ← (S → S); End`

- Record Type: “bundled-up data”

$\Sigma S : \text{Set} \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$

- Function Type: “a type of functions”

$\Pi S \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$

- Type constructor: “a function on types”

$\lambda S \bullet \Sigma s : S \bullet \Sigma n : S \rightarrow S \bullet 1$

- Algebraic datatype: “a descriptive syntax”

`data D : Set where s : D; n : D → D`

⇒ Thank-you  
for

your time! ⇐