

# **GENERAL SPECIFICATIONS**









### PHYSICAL CHARACTERISITICS

113mm x 52.5mm x 24.5mm Dimension 4.44inch x 2.06inch x 0.96inch

Weight 176g

חוי	$\sim$		NTAL
V 11 - 2		1/4/12/1	VI I A I
 <i>y</i> 1100			

**Dust And Water Intrusion IP54 Drop Test** 1.5m -20°C to + 60°C (-4°F to 140°F) **Working Temperature** Storage Temperature  $-30^{\circ}$ C to +  $70^{\circ}$ C ( $-22^{\circ}$ F to  $158^{\circ}$ F)

## **INTERACTION & DISPLAY**

Diagonal dimension: 1.77 inch Resolution: 160\*128 Display Type: TFT **Power Button Emergency Button** PTT Button **Buttons and Keyboards** Navigation Button Volume+&Volume- Buttons Programmable Button Tri-color LED: Red, Blue, Green Indication Text to speech: Pre-installed TTS Engine

## **HARDWARE**

Processor	Quad-core ARM Cortex-A53; up to 1.5GHz; 64 bit processor
Battery	4000 mAh. Li-Polymer. Removable

	512MB RAM
Memory	4GB Internal Storage
Wellory	Storage is expandable with external 128 GB microSD $^{\mbox{\scriptsize M}}$ card
Sensor Platform	Acceleration Sensor

INTERNATIONAL:

#### CONNECTIVITY

Cellular Network	WCDMA: B1/B2/B5/B8 TD-SCDMA(B34/39) FDD-LTE: B1/3/5/7/8/20/26/28a/28b TDD-LTE: B34/B38/B39/B40/B41
LTE	LTE FDD R9 Cat.4 150Mbps/50Mbps
WiFi	IEEE 802.11 b/g/n/ 2.4/5GHz
WiFi Hotspot	IEEE 802.11 b/g/n/ 2.4GHz
Bluetooth	V4.2+LE+HS+EDR
Location	GPS, GLONASS, BEIDOU and AGPS
NFC	Optional

### **INTERFACE**

Card Slot	Nano-SIM Card Slot * 2	
Card Slot	Micro-SD Card Slot * 1	
3.5mm audio interface	Support PTT Earphone, Remote Speaker Microphone, External Speaker	
USB	Type-C, USB 2.0	

### **PLATFORM**

Operating System	Android 8.1
Preloaded Applications	Push-to-Talk APP (Please check with your service provider)

#### **AUDIO**

Speaker 3 Watt Radio-grade Speaker

#### STANDARD ACCESSORIES

USB Cable	*1	
Travel Charger	*1	
Battery	*1	
Belt Clip	*1	
Quick Start Guide	*1	

### **OPTIONAL ACCESSORIES**

Power	Desktop Charger MT100-DC	
Power	Multi-unit Charger MUC-MT100	
External Audio	PTT Earphone TSR1-T100	

# Telo Communication (Shenzhen) Co.,Ltd



















