

Model No.(Subject): EM-T50C

6 views



Tech Spec

Product Form 5 inch Rugged Handheld

Material -

Dimension 157.4*74.6*24.2mm

Weight 260g

Product Color Black

CPU MT6765/Mediatek Helio P35

GPU IMG PowerVR GE8320

Memory **RAM** LPDDR4X up to 4GB(dual channels with 16-bit data bus width) **ROM** 64GB EMMC

Operating System Andriod14

Display Type: IPS
Size: 5 inch 16:9
Resolution: 720*1280
Brightness: 350 Nit

Touch Pannel 5 points Capacitive, G+FF

Camera **Front** 5MP
Rear 13.0MP, automatic focusing with astigmatism, PDAF support

Buttons	Power *1 Volume Adjustment Key (+) *1 Volume Adjustment Key (-) *1 Home Key *1 Bar code scanning (left and right)*2 Menu*1 Back*1 Custom*2
Speaker	Embedded 8Ω/1W speaker x 1
Microphone	Sensitivity: -42db, Output Impedance 2.2kΩ
Sensors	G_sensor *1 Geomagnetic sensor *1 Ggyroscope *1 light Sensor *1
Battery	Built-in Removable Lithium-ion polymer battery 3.8V/4000mAh 10hrs(default volume and brightness to play video)
WIFI	WIFI 802.11(a/b/g/n/ac) frequency 2.4G+5G dual band WIFI,Support AP seamless roaming
Bluetooth	BT5.0(BLE)
4G	GSM(B2/3/5/8)+WCDMA(B1/B2/5/8)+TDS(B34/B39)+FDD(B1/2/3/4/5/7/8/13/17/20/28AB)+TDD(B38/39/40/41)
GPS	Support GPS、Glionass、beidou(G+G+B)
NFC	NFC 13.56MHz Support ISO/IEC 下14443A/14443B/15693/18092/mifare 协议
I/O Interface	Type-c 2.0*1 OTG (Data transmission) ϕ3.5mm standard earphone jack x1 SIM card *1 TF card *1 (SDHC/SDXC supported), Max: 128GB Pogo Pin (Base Charge) *1
Adapter	AC100V ~ 240V, 50Hz/60Hz, DC 5V/2A US EU

USB cable	Type-C USB cable 5p l=1.2m 4-core with aluminum foil and screen
Rugged Features	Drop height: 1.2m Composite wood floor working
	Working temperature: -10 °C to 50 °C
	Storage temperature: -20 °C to 60 °C
	Humidity: 95% Non-Condensing
Certification	<p>IP65</p> <p>IP65 Report: Water resistance: IP-X5, Dust resistance: IP-6X Report ID no.: SET2015-07677</p> <p>a.Inner Nozzle diameter: 6.3mm; b. water speed: 12.5±0.625L/min;</p> <p>c. Water Pressure: adjust according to water volumn;</p> <p>d.Central part of water volumn</p> <p>e.Spray time in surface of panel: about 1min; f.test time: at least 3min;</p> <p>g.distance between nozzle and panel surface: 2.5 ~ 3m。</p> <p>After test, there is no water leakage in sample.</p>
Data Collection	<p>2D Barcode Scanner</p> <p>Zebra4710</p>

Hand-strap (Standard)



5V2A Adapter (Standard)



Docking Charger (Optional)



Accessories

Vehicle Mount (Optional)



Removable Battery (Optional)

