

---

# **Association Rule Mining**

Dr. Faisal Kamiran

# FP-growth Algorithm

---


- Use a compressed representation of the database using an **FP-tree**
  
- Once an FP-tree has been constructed, it uses a recursive divide-and-conquer approach to mine the frequent itemsets
  
- Steps:
  - FP tree construction
  - Conditional pattern base construction
  - Conditional FP-trees
  - Frequent pattern generation

# FP-Tree Construction

<i>TID</i>	<i>Items bought</i>	<i>(ordered) frequent items</i>
100	{f, a, c, d, g, i, m, p}	{f, c, a, m, p}
200	{a, b, c, f, l, m, o}	{f, c, a, b, m}
300	{b, f, h, j, o, w}	{f, b}
400	{b, c, k, s, p}	{c, b, p}
500	{a, f, c, e, l, p, m, n}	{f, c, a, m, p}

*min\_support* = 3

**F-list = f-c-a-b-m-p**



# FP-Tree Construction

<i>TID</i>	<i>Items bought</i>	<i>(ordered) frequent items</i>
100	{f, a, c, d, g, i, m, p}	{f, c, a, m, p}
200	{a, b, c, f, l, m, o}	{f, c, a, b, m}
300	{b, f, h, j, o, w}	{f, b}
400	{b, c, k, s, p}	{c, b, p}
500	{a, f, c, e, l, p, m, n}	{f, c, a, m, p}


*min\_support* = 3

1. Scan DB once, find frequent 1-itemset (single item pattern)
2. Sort frequent items in frequency descending order, f-list
3. Scan DB again, construct FP-tree

Header Table

<i>Item</i>	<i>frequency</i>	<i>head</i>
<i>f</i>	4	
<i>c</i>	4	
<i>a</i>	3	
<i>b</i>	3	
<i>m</i>	3	
<i>p</i>	3	

**F-list = f-c-a-b-m-p**




# Partition Patterns and Databases

---

- Frequent patterns can be partitioned into subsets according to f-list
  - F-list = f-c-a-b-m-p
  - Patterns containing p
  - Patterns having m but no p
  - ...
  - Patterns having c but no a nor b, m, p
  - Pattern f
- Completeness and non-redundancy


# Conditional Pattern Base Construction

- Conditional Pattern Base is a sub-database which consists of the set of prefix paths in the FP tree co-occurring with the suffix pattern or item. For example *prefix paths (fcam, cb)* of item *p* to form *p*'s conditional pattern base.




# From Conditional Pattern-bases to Conditional FP-trees

- For each pattern-base
  - Accumulate the count for each item in the base
  - Construct the FP-tree for the frequent items of the pattern base



*m*-conditional pattern base:  
*fca:2, fcab:1*




# FP Growth: Example

Min supp=2

Data:

TID	List of item_IDs
T100	I1, I2, I5
T200	I2, I4
T300	I2, I3
T400	I1, I2, I4
T500	I1, I3
T600	I2, I3
T700	I1, I3
T800	I1, I2, I3, I5
T900	I1, I2, I3

FP Tree:



Mining the FP-Tree

Item	Conditional Pattern Base	Conditional FP-tree	Frequent Patterns Generated
I5	{ {I2, I1: 1}, {I2, I1, I3: 1} }	$\langle I2: 2, I1: 2 \rangle$	{I2, I5: 2}, {I1, I5: 2}, {I2, I1, I5: 2}
I4			
I3			
I1			



# Benefits of the FP-tree Structure

---

## □ Completeness

- Preserve complete information for frequent pattern mining
- Never break a long pattern of any transaction

## □ Compactness

- Reduce irrelevant info—infrequent items are gone
- Items in frequency descending order: the more frequently occurring, the more likely to be shared
- Never be larger than the original database (not count node-links and the *count* field)

# ECLAT

- For each item, store a list of transaction ids (tids)

Horizontal  
Data Layout

TID	Items
1	A,B,E
2	B,C,D
3	C,E
4	A,C,D
5	A,B,C,D
6	A,E
7	A,B
8	A,B,C
9	A,C,D
10	B

Vertical Data Layout


A	B	C	D	E
1	1	2	2	1
4	2	3	4	3
5	5	4	5	6
6	7	8	9	
7	8	9		
8	10			
9				



**TID-list**

# ECLAT

- Determine support of any k-itemset by intersecting tid-lists of two of its (k-1) subsets.



- 3 traversal approaches:
  - top-down, bottom-up and hybrid
- Advantage: very fast support counting
- Disadvantage: intermediate tid-lists may become too large for memory

# Rule Generation

- Given a frequent itemset  $L$ , find all non-empty subsets  $f \subset L$  such that  $f \rightarrow L - f$  satisfies the minimum confidence requirement

- If  $\{A,B,C,D\}$  is a frequent itemset, candidate rules:

$ABC \rightarrow D,$	$ABD \rightarrow C,$	$ACD \rightarrow B,$	$BCD \rightarrow A,$
$A \rightarrow BCD,$	$B \rightarrow ACD,$	$C \rightarrow ABD,$	$D \rightarrow ABC$
$AB \rightarrow CD,$	$AC \rightarrow BD,$	$AD \rightarrow BC,$	$BC \rightarrow AD,$
$BD \rightarrow AC,$	$CD \rightarrow AB,$		

- If  $|L| = k$ , then there are  $2^k - 2$  candidate association rules (ignoring  $L \rightarrow \emptyset$  and  $\emptyset \rightarrow L$ )

# Rule Generation

---

## □ How to efficiently generate rules from frequent itemsets?

- In general, confidence does not have an anti-monotone property


$c(ABC \rightarrow D)$  can be larger or smaller than  $c(AB \rightarrow D)$

- But confidence of rules generated from the same itemset has an anti-monotone property
- e.g.,  $L = \{A, B, C, D\}$ :

$$c(ABC \rightarrow D) \geq c(AB \rightarrow CD) \geq c(A \rightarrow BCD)$$


# Rule Generation for Apriori Algorithm

## Lattice of rules



# Rule Generation for Apriori Algorithm

- Candidate rule is generated by merging two rules that share the same prefix in the rule consequent
- $\text{join}(\text{CD} \Rightarrow \text{AB}, \text{BD} \Rightarrow \text{AC})$  would produce the candidate rule  $\text{D} \Rightarrow \text{ABC}$
- Prune rule  $\text{D} \Rightarrow \text{ABC}$  if its subset  $\text{CD} \Rightarrow \text{AB}$  does not have high confidence



# Pattern Evaluation

---

- Association rule algorithms tend to produce too many rules
  - many of them are uninteresting or redundant
  - Redundant if  $\{A,B,C\} \rightarrow \{D\}$  and  $\{A,B\} \rightarrow \{D\}$  have same support & confidence
- Interestingness measures can be used to prune/rank the derived patterns
- In the original formulation of association rules, support & confidence are the only measures used



# Computing Interestingness Measure

- Given a rule  $X \rightarrow Y$ , information needed to compute rule interestingness can be obtained from a contingency table

Contingency table for  $X \rightarrow Y$

	Y	$\overline{Y}$	
X	$f_{11}$	$f_{10}$	$f_{1+}$
$\overline{X}$	$f_{01}$	$f_{00}$	$f_{0+}$
	$f_{+1}$	$f_{+0}$	$ T $

$f_{11}$ : support of X and Y

$f_{10}$ : support of X and  $\overline{Y}$

$f_{01}$ : support of  $\overline{X}$  and Y

$f_{00}$ : support of  $\overline{X}$  and  $\overline{Y}$

Used to define various measures

- support, confidence, lift, Gini, J-measure, etc.

# Drawback of Confidence

	Coffee	<u>Coffee</u>	
Tea	15	5	20
<u>Tea</u>	75	5	80
	90	10	100

Association Rule: Tea  $\rightarrow$  Coffee

- Confidence =  $P(\text{Coffee}|\text{Tea}) = 0.75$
- but  $P(\text{Coffee}) = 0.9$
- Although confidence is high, rule is misleading
- $P(\text{Coffee}|\overline{\text{Tea}}) = 0.9375$

# Statistical-based Measures

---

- Measures that take into account statistical dependence

$$Lift = \frac{P(Y | X)}{P(Y)}$$

# Example: Lift/Interest

	Coffee	<u>Coffee</u>	
Tea	15	5	20
<u>Tea</u>	75	5	80
	90	10	100

Association Rule: Tea  $\rightarrow$  Coffee

Confidence=  $P(\text{Coffee}|\text{Tea}) = 0.75$

but  $P(\text{Coffee}) = 0.9$

$\Rightarrow \text{Lift} = 0.75/0.9 = 0.8333 (< 1, \text{ therefore is negatively associated})$