


# **Text Retrieval & Search Engines**


## **Evaluation of Text Retrieval Systems: Basic Measures**

**Dr. Iqra Safder**


# Evaluation of Text Retrieval Systems



# Test Collection Evaluation



# Test Collection Evaluation



# Evaluating a Set of Retrieved Docs: Precision and Recall

Action Doc	Retrieved	Not Retrieved
Relevant	Relevant Retrieved <b>a</b>	Relevant Rejected <b>b</b>
Not relevant	Irrelevant Retrieved <b>c</b>	Irrelevant Rejected <b>d</b>

$$\text{Precision} = \frac{a}{a + c}$$

$$\text{Recall} = \frac{a}{a + b}$$

Ideal results: Precision=Recall=1.0

In reality, high recall tends to be associated with low precision

Set can be defined by a cutoff (e.g., precision @ 10 docs)

# Combine Precision and Recall: F-Measure

$$F_{\beta} = \frac{1}{\frac{\beta^2}{\beta^2 + 1} \frac{1}{R} + \frac{1}{\beta^2 + 1} \frac{1}{P}} = \frac{(\beta^2 + 1)P * R}{\beta^2 P + R}$$

$$F_1 = \frac{2PR}{P + R}$$

Why not  $0.5 * P + 0.5 * R$ ?

**P**: precision

**R**: recall

**$\beta$** : parameter (often set to 1)

# Combine Precision and Recall: F-Measure

$$F_{\beta} = \frac{1}{\frac{\beta^2}{\beta^2 + 1} \frac{1}{R} + \frac{1}{\beta^2 + 1} \frac{1}{P}} = \frac{(\beta^2 + 1)P * R}{\beta^2 P + R}$$

$$F_1 = \frac{2PR}{P + R}$$

**P**: precision

**R**: recall

**β**: parameter (often set to 1)

Why not  $0.5 * P + 0.5 * R$ ?

Sum will be dominated by the higher value in arithmetic mean.

# Summary

- Precision: are the retrieved results all relevant?
- Recall: have all the relevant documents been retrieved?
- F measure combines Precision and Recall
- Tradeoff between Precision and Recall depends on the user's search task