

SAFE-BREAK™ MP

SAFE-BREAK MP is an internal filtercake breaker for use in polymer-base reservoir drilling and completion fluids and lost circulation pills used during a workover or completion operation. SAFE-BREAK MP is initially deposited as an inert particle within the filtercake. However when activated by lower pH, SAFE-BREAK MP greatly increases the degradation rate of the filter cake, thereby aiding in cleanup.

TYPICAL PHYSICAL PROPERTIES

Physical appearance Yellow to white powder
Bulk density 37.5-50.0 lb/ft²
Solubility insoluble in water

APPLICATIONS

SAFE-BREAK MP aids in filtercake clean-up when used in polymer-based reservoir drilling and completion fluids and in lost circulation pills during workover and completion operations. SAFE-BREAK MP is deposited as an inert particle in the filtercake. During the completion/cleanup phase, a mild acidic solution activates the SAFE-BREAK MP, resulting in a more improved digestion of the filter cake. This process increases overall cleanup efficiently. Treatment levels are normally 0.5 – 1.0 lb/bbl for reservoir drilling fluid applications and 3.0 to 4.0 lb/bbl for lost-circulation pill applications.



ADVANTAGES

- When compared to a plain acid soak, SAFE-BREAK MP reduces by as much as 60% the time required for filtercake removal.
- Can be used in any polymer-based drilling fluid with pH>9.
- Most effective at temperatures <190°F.
- Weak acid, such as 1% HCl, can activate decomposition process.

LIMITATIONS

- Exposure of dry material to the atmosphere will reduce the activity level of the product.
- Do not apply in base brines with a below neutral pH.

TOXICITY AND HANDLING

Bioassay information is available upon request.

Handle as an industrial chemical, wearing protective equipment and observing the precautions as described on the Material Safety Data Sheet (MSDS).

Also observe the health hazard information and emergency and first aid procedures described on the MSDS.

Keep container closed until use.

PACKAGING AND STORAGE

SAFE-BREAK MP is available in 100-lb (45.4 kg) drums.

No claim of personal safety is intended nor implied by the use of the name SAFE in this product. Personnel handling this material should read and follow all safety and handling procedures set forth on the Material Safety Data Sheet.

This material is supplied solely for informational purposes and M-I L.L.C. makes no guarantees or warranties, either expressed or implied, with respect to the accuracy or use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale.

©2000 M-I L.L.C. All rights reserved.
™ SAFE-BREAK is a trademark of M-I L.L.C.
MIC-11916 4/00



M-I L.L.C.
A Smith/Schlumberger Company
P.O. Box 721110 Tel: 281-561-1300
Houston, Texas 77272-1110 Fax: 281-561-7240
<http://www.midf.com> E-mail: mimud@midf.com