Analysis Plan for Kepler Data

Hamamah Hasan

```
Warning Note:
```

```
## Loading required package: foreign
## Loading required package: ggplot2
## Loading required package: tidyverse
## Loading required package: dplyr
## Loading required package: purrr
## Loading required package: tibble
## Loading required package: MASS
## Loading required package: tidyverse
## Attaching packages ------------------------------------ tidyverse 1.3.0 ##
## ggplot2 3.3.2     readr   1.3.1
## tibble  3.0.3     stringr 1.4.0
## tidyr   1.1.2     forcats 0.5.0
## purrr   0.3.4
## Conflicts ---------------------------------------- tidyverse_conflicts() ##
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()    masks stats::lag()
## x MASS::select()  masks dplyr::select()
```

```
Modeling Warning Note:
```

```
## Loading required package: rstanarm
## This is rstanarm version 2.21.1
## - See https://mc-stan.org/rstanarm/articles/priors for changes to default priors!
## - Default priors may change, so it's safest to specify priors, even if equivalent to the defaults.
## - For execution on a local, multicore CPU with excess RAM we recommend calling
##   options(mc.cores = parallel::detectCores())
```

```
Data Import:
```

name	bindyRep_tc	value	period	semimajorAxis	eccentricity	periastron
character	character	numeric	numeric	numeric	numeric	numeric
2 Kepler-1625 b	0	1	0.167	0.0617	---	---
3 KIC 10489718	0	0.04	0.8	0.0033333	1.181	0.46
4 KIC 10489718	0	0.08	0.8	0.0033333	1.181	0.46
5 Kepler-1625 b	0	0.999	1.2	0.0033333	1.181	0.46
7 Kepler-1625 b	0	0.04	1.2	0.0033333	---	---
8 Kepler-1625 b	0	0.04	1.2	0.0033333	---	---

```
## Rows: 2,418 Columns: 7
```

```
Visualization:
```

```
Visualization:
```


Kepler_Name
Kepler_Name
Kepler_Name

```
## NUTS: Done
## NUTS: Elapsed 1s Warmup 0s Sample 1s.
## NUTS: Chain 1
## NUTS: Mean Accept 0.9 Mean Step Size 0.2
## NUTS: Mean Tree Size 511.5 Num Diverging 0
## NUTS: Mean Energy -1.1e+03
## NUTS: Mean Energy Change 0.2
## NUTS: Mean Abs Dynamics 1.1e+03
## NUTS: Mean Max Dynamics 1.1e+03
## NUTS: Mean Accept Ratio 0.9
```

```
## NSGA2 done
## Best fit: Poisson in Device Type
##
## NSGA2 begin
## Best fit: Poisson in Device Type
## Best fit: Poisson in Device Type
## Best fit: Poisson in Device Type
```

```
##   [7]  380.70720  612.72366  691.23858  785.32710  815.56827 1295.96335
## [13] 1237.11414 1369.06269 1499.75321 1400.73334 1400.42406 1587.82787
## [19] 1587.82787 1536.86076 1587.82787 1587.82787 1587.82787 1584.82012
## [25] 1587.82787 1578.22416 1587.82787 1586.82329 1587.82787 1555.13494
## [31] 1587.82787 1556.29956 1587.82787 1547.25869 1587.82787 1587.82787
## [37] 1587.82787 1587.82787 1587.82787 1587.82787
##
## Slower
##   [1] -882.38169 -882.38169 -882.38169 -863.73210 -933.57060 -788.60073
##   [7] -796.10473 -831.36361 -594.54006 -533.49497 -518.49214 -45.20614
##  [13]   41.82059  463.82388  521.32829  593.69662  651.32162  957.76237
##  [19]  959.03066  995.47285 1148.45299 1234.64285 1347.69440 1390.54378
##  [25] 1422.69446 1432.25457 1476.71577 1556.69277 1557.60735 1521.47936
##  [31] 1568.55433 1531.54206 1563.08038 1516.24794 1556.48116 1556.48116
##  [37] 1555.84788 1555.84788 1555.55456 1555.55456
##
## Supper
##   [1] -882.3817 -882.3817 -882.3817  962.2495 1108.2607 1492.4373 1557.5191
##   [8] 1856.8109 1937.0172 2104.1492 2149.8287 2627.1328 2432.4317 2276.8019
##  [15] 2298.1783 2207.8101 2149.5265 2267.8936 2216.6251 2076.6487 2027.2017
##  [22] 1861.0329 1827.9613 1773.1165 1752.9611 1724.0937 1698.9480 1615.8438
##  [29] 1618.0484 1588.7905 1607.1014 1581.0370 1612.5754 1578.2534 1619.1746
##  [36] 1619.1746 1619.8079 1619.8079 1620.1012 1620.1012
```

Median probability model

```
confint(lm(semmajoraxis ~ 1 +I(troot(period*period*hoststar_mass)),data = data.train))
```

```
##                                                 2.5 %      97.5 %
## (Intercept)                                -0.000739221 0.002264746
## I(troot(period * period * hoststar_mass)) 0.019537438# 0.019560654
```

```
preds.train.bgnlm <- predict(bgnlm, data.train[,-1])
preds.test.bgnlm <- predict(bgnlm, data.test[,-1])
r.bgnlm <- round((cor(data.train[,1],preds.train.bgnlm$aggr$mean)^2,cor(data.test[,1],preds.test.bgnlm$aggr$mean)^2),3)
plot(x = data.train[, 1], preds.train.bgnlm$aggr$mean, xlab = "data", ylab = "prediction", main = "Title of the Plot", col = "blue", pch = 16)
points(x = data.test[, 1], preds.test.bgnlm$aggr$mean, col = "red", pch = 17)
legend("topright", legend = c(paste0("Training Data, R.sqr = ",r.bgnlm[1]), paste0("Test Data, R.sqr = ",r.bgnlm[2])), col = c("blue", "red"), pch = c(16, 17))
```



In the Bayesian Generalized Nonlinear Model (BGNLM) analysis, you obtained the following results:

Predictor: `troot(((period*hoststar_mass)*period))` Inclusion Probability: 1.000000

This result indicates a perfect inclusion probability (1.0) for the predictor `troot(((period*hoststar_mass)*period))`, suggesting that this complex non-linear interaction term is crucial for predicting the semimajor axis.

Interpretation

1. Complex Interaction Term:

- The predictor `troot(((period*hoststar_mass)*period))` combines `period` and `hoststar_mass` in a multiplicative form, followed by a transformation.
- `troot` likely represents a specific non-linear transformation, such as a root function, which means the predictor is a transformed version of the product of `period`, `hoststar_mass`, and `period` again.

Discussion with Relation to Kepler's Third Law

1. Kepler's Third Law

Kepler's Third Law states that the square of the orbital period of a planet is proportional to the cube of the semimajor axis of its orbit.

2. Implications and Interpretation

- **Alignment with Physical Laws**: The inclusion of `troot(((period*hoststar_mass)*period))` in the BGNLM model supports Kepler's Third Law by explicitly incorporating the cubic root transformation of the complicated interaction. This suggests that the model correctly captures the underlying Known in this case as Kepler's Third Law) physical relationship between the orbital period and the semimajor axis.
- **Predictive Power and Physical Meaning**: The perfect inclusion probability of this term indicates that the model effectively leverages the cubic root relationship to predict the semimajor axis. This reinforces the physical validity of the model and emphasizes the importance of incorporating both the period and the host star's mass in a non-linear fashion.

2. Comparison with Previous Models:

- **Linear and Log-Transformed Models**: These simpler models highlighted the importance of `period` and `hoststar_mass` individually, but the BGNLM model shows that their interaction, particularly in a non-linear form, is even more crucial.
- **Fractional Polynomials**: The fractional polynomial model also indicated non-linear relationships but did not capture this specific interaction and it also missed the solar mass in its functional form, highlighting the added value of BGNLM in uncovering complex dependencies.

Predictions

```
preds.train.bgnlm <- predict(bgnlm, data.train[,-1])
preds.test.bgnlm <- predict(bgnlm, data.test[,-1])
r.bgnlm <- round((cor(data.train[,1],preds.train.bgnlm$aggr$mean)^2,cor(data.test[,1],preds.test.bgnlm$aggr$mean)^2),3)
plot(x = data.train[, 1], preds.train.bgnlm$aggr$mean, xlab = "data", ylab = "prediction", main = "Title of the Plot", col = "blue", pch = 16)
points(x = data.test[, 1], preds.test.bgnlm$aggr$mean, col = "red", pch = 17)
legend("topright", legend = c(paste0("Training Data, R.sqr = ",r.bgnlm[1]), paste0("Test Data, R.sqr = ",r.bgnlm[2])), col = c("blue", "red"), pch = c(16, 17))
```



The predictions are expectedly perfect on both training and testing sets, as inclusion of `troot(((period*hoststar_mass)*period))` in the BGNLM model effectively captures the essence of Kepler's Third Law, incorporating the orbital period and the host star's mass in a cubic root transformation. This predictor reflects the key physical relationship between these variables, demonstrating that the model is not only statistically sound but also physically meaningful. The high inclusion probability underscores the importance of this non-linear interaction in accurately predicting the semimajor axis.

And use the g prior and redo the inference.

```
set.seed(1)
bgnlm <- FBMS::fbms(semmajoraxis ~ ., data = data.train,method = 'gmjmcmc.parallel',beta_prior = list(type = 'g-prior', g = nrow(data.train)),transforms = transforms,runs = 64,cores = 8,P = 40,probs = probs, params = params)
plot(bgnlm)
```




```
summary(bgnlm,labels = names(data.train)[-1])
```

feats.strings <chr>	marg.probs <dbl>
troot((((period*hoststar_mass)*period))	0.999998774
(hoststar_mass*period)	0.000173347

2 rows

Here we perfectly recover the true law! Also good convergence for g - prior.

```
diags_plot(bgnlm,window = 10,FUN = median)
```




```
## $stat
##   [1]  898.2229  897.1210  898.4530  898.6731  898.6731  898.6731  909.1390
##   [8] 1129.0970 1238.8356 1276.4673 1276.5973 1270.5401 1282.2995 1289.1977
##  [15] 1300.6592 1298.6657 1289.9745 1286.2103 1289.6226 1288.4389 1314.4966
##  [22] 1309.8131 1310.6536 1312.7699 1310.8936 1312.8077 1306.9176 1314.7034
##  [29] 1314.6228 1307.4979 1318.7803 1319.1866 1320.9995 1315.5996 1316.8580
##  [36] 1322.5425 1311.4218 1317.0231 1319.7607 1314.6869
##
## Slower
##   [1]  898.2229  895.5801  897.0536  897.3211  897.4059  897.4856  901.0399
##   [8]  970.0645  986.9912  970.2130  937.3096  917.2263  921.1179  933.1128
##  [15]  962.4488  999.9810 1059.6222 1190.7652 1255.4991 1286.6599 1287.0899
##  [22] 1283.9335 1288.4575 1291.4667 1290.5471 1291.7250 1286.0839 1295.5609
##  [29] 1306.6921 1302.1599 1312.0201 1311.3235 1311.9782 1306.7350 1307.8984
##  [36] 1312.7579 1301.4571 1308.7073 1311.2853 1306.2177
##
## Supper
##   [1]  898.2229  898.6620  899.8525  900.0251  899.9404  899.8606  917.2380
##   [8] 1288.1295 1689.0800 1582.7216 1603.8850 1623.8708 1643.4811 1645.2826
##  [15] 1637.8698 1597.2283 1520.3267 1381.4755 1323.7462 1332.2180 1341.7233
##  [22] 1335.6927 1332.8497 1332.8731 1331.2401 1233.8904 1327.7514 1333.8459
##  [29] 1328.5535 1313.2259 1325.5405 1327.0496 1330.0208 1326.4641 1325.8175
##  [36] 1332.3271 1321.3866 1325.3389 1328.2361 1323.1562
```

```
diags_plot(bgnlm,window = 10,FUN = max)
```



```
## $stat
##   [1]  898.6731  898.6731  921.6583 1085.1515 1240.8263 1270.5937 1330.8985
##   [8] 1331.2467 1332.1172 1367.6588 1367.6588 1357.3973 1367.6588 1367.6588
##  [15] 1383.6693 1382.6693 1367.6588 1367.6588 1367.6588 1367.6588 1367.6588
##  [22] 1367.6588 1370.7495 1370.7495 1367.6588 1367.6588 1370.7495 1367.6588
##  [29] 1370.7495 1370.7495 1370.7495 1367.6588 1370.7495 1370.7495 1370.7495
##  [36] 1361.6201 1368.5465 1370.7495 1370.7495 1370.7495
##
## Slower
##   [1]  898.6731  898.6731  895.6486  908.6323  944.3674  932.7711  959.9434
##   [8]  949.9901  956.0324  982.0154  983.2045 1010.9078 1087.7685 1199.2737
##  [15] 1295.8936 1318.9557 1329.0952 1333.8339 1340.9083 1352.7975 1352.7975
##  [22] 1352.7975 1358.1973 1358.3675 1355.2767 1361.4137 1364.8292 1367.6932
##  [29] 1367.5860 1367.5860 1367.6932 1364.6025 1367.9200 1367.9200 1367.9200
##  [36] 1356.0371 1363.0230 1365.2462 1365.2462 1365.2462
##
## Supper
##   [1]  898.6731  898.6731  947.6680 1261.6708 1537.2852 1608.4164 1701.8536
##   [8] 1712.4914 1716.2020 1753.3022 1752.1130 1703.8865 1647.5490 1536.0438
##  [15] 1471.5351 1448.3830 1406.2223 1401.4837 1394.4173 1382.5201 1382.5201
##  [22] 1382.5201 1383.3018 1383.1316 1380.0408 1380.0853 1370.4884 1373.8058
##  [29] 1373.9131 1373.9131 1373.8058 1370.7151 1373.5791 1373.5791 1373.5791
##  [36] 1367.2031 1374.0700 1376.2528 1376.2528 1376.2528
```

And as expected perfect predictions

```
preds.train.bgnlm <- predict(bgnlm, data.train[,-1])
preds.test.bgnlm <- predict(bgnlm, data.test[,-1])
r.bgnlm <- round((cor(data.train[,1],preds.train.bgnlm$aggr$mean)^2,cor(data.test[,1],preds.test.bgnlm$aggr$mean)^2),3)
plot(x = data.train[, 1], preds.train.bgnlm$aggr$mean, xlab = "data", ylab = "prediction", main = "Title of the Plot", col = "blue", pch = 16)
points(x = data.test[, 1], preds.test.bgnlm$aggr$mean, col = "red", pch = 17)
legend("topright", legend = c(paste0("Training Data, R.sqr = ",r.bgnlm[1]), paste0("Test Data, R.sqr = ",r.bgnlm[2])), col = c("blue", "red"), pch = c(16, 17))
```


We see that variation is possible in the results and that ideally maximal possible compute resources should be used to reduce the variation. But given enough resources GMJMCMC converges to being able to recover the true underlying physical law.