

Building a sophisticated stream topology


Creating Kafka Streams Application


- Create Configurations.
- Create Streams Topology.
- Start the Stream.
- Add shutdown hook.


What is Streams Topology?

Step-by-step computational logic of a stream processing application.

Topology DAG







KStream

Abstraction of a stream of Kafka message records.

`filter()`

`map()`

`flatMap()`

`foreach()`

`to()`

KStream

Abstraction of a stream of Kafka message records.

filter()	}	KStream
map()		
flatMap()		
foreach()	}	Void
to()		

The void method performs some actions or operations but does not produce a result that can be used or accessed by the caller.

Problem Statement

- Use the POS Simulator Application to generate a continuous stream of Invoices.
- Create a stream processing application for the following

Business Requirement

XYZ is a Home Furniture and Kitchen utensils retailer. They have twenty retail stores spread all over the country. XYZ management decided to transform themselves into a real-time data-driven organization. As a first step towards that goal, they started sending their invoices to a Kafka cluster in real-time. The POS machines in all their stores are now sending invoices to a Kafka topic – POS. As a next step, they want to create the following automated services.

1. Shipment Service
2. Loyalty Management Service
3. Trend Analytics

While other teams are working on the implementation details of these three services, you are asked to create a Kafka Streams application that does following.

1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.

Problem Statement

- Use the POS Simulator Application to generate a continuous stream of Invoices.
- Create a stream processing application for the following

Business Requirement

XYZ is a Home Furniture and Kitchen utensils retailer. They have twenty retail management decided to transform themselves into a real-time data-driven organization. They started sending their invoices to a Kafka cluster in real-time. The POS machines in all stores send data to a Kafka topic – POS. As a next step, they want to create the following automated services:

1. Shipment Service
2. Loyalty Management Service
3. Trend Analytics

While other teams are working on the implementation details of these three services, you are asked to create a Kafka Streams application that does the following.

1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.

```
{  
  "InvoiceNumber": "xx",  
  "CustomerCardNo": "xx",  
  "TotalAmount": "xx",  
  "EarnedLoyaltyPoints": "xx"  
}
```


Problem Statement

- Use the POS Simulator Application to generate a continuous stream of Invoice
- Create a stream processing application for the following

Business Requirement

XYZ is a Home Furniture and Kitchen utensils retailer. They have twenty retail store management decided to transform themselves into a real-time data-driven organization started sending their invoices to a Kafka cluster in real-time. The POS machines in all the Kafka topic – POS. As a next step, they want to create the following automated services.

1. Shipment Service
2. Loyalty Management Service
3. Trend Analytics

While other teams are working on the implementation details of these three services, you application that does following.

1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment
2. Select Invoices where CustomerType = "PRIME" and create a notification event for format for the new notification event is given here.

3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.

```
{  
  "InvoiceNumber": "xx",  
  "CreatedTime": "xx",  
  "StoreID": "xx",  
  "PosID": "xx",  
  "CustomerType": "xx",  
  "PaymentMethod": "xx",  
  "DeliveryType": "xx",  
  "City": "xx",  
  "State": "xx",  
  "PinCode": "xx",  
  "ItemCode": "xx",  
  "ItemDescription": "xx",  
  "ItemPrice": "xx",  
  "ItemQty": "xx",  
  "TotalValue": "xx"  
}
```

Requirement Extract

1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.

Kafka Topics

POS

Kafka Topics

POS

Source
Processor

```
graph TD; subgraph Kafka_Topics [Kafka Topics]; POS[POS]; end; POS --> SP((Source Processor));
```

The diagram illustrates a data flow process. A green rectangular box labeled 'POS' is located inside a dashed-line container labeled 'Kafka Topics'. A vertical arrow points from the 'POS' box to a gray circular node labeled 'Source Processor' located outside the container.

Kafka Topics

POS

Source
Processor


KSO


```
graph TD; subgraph Kafka_Topics [Kafka Topics]; POS[POS]; end; POS --> SP((Source Processor)); SP -- KSO --> Kafka_Topics;
```

The diagram illustrates a data processing pipeline. A green rectangular box labeled 'POS' is located inside a dashed-line container labeled 'Kafka Topics'. A vertical arrow points from the 'POS' box to a gray circular node labeled 'Source Processor'. From the 'Source Processor', a horizontal arrow points to the right, labeled with the text 'KSO' in red, indicating the output to the Kafka Topics.

Requirement Extract


1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.






Requirement Extract


1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.




Requirement Extract

1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.










```
{
  "type": "object",
  "javaType": "ir.mfozouni.types.Notification",
  "properties": {
    "InvoiceNumber": {
      "type": "string"
    },
    "CustomerCardNo": {
      "type": "string"
    },
    "TotalAmount": {
      "type": "number"
    },
    "EarnedLoyaltyPoints": {
      "type": "number"
    }
  }
}
```

```
{
  "InvoiceNumber": "xx",
  "CustomerCardNo": "xx",
  "TotalAmount": "xx",
  "EarnedLoyaltyPoints": "xx"
}
```


Kafka Topics






Requirement Extract


1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.



Requirement Extract

1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.





Requirement Extract

1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.

```
{  
  "InvoiceNumber": "xx",  
  "CreatedTime": "xx",  
  "StoreID": "xx",  
  "PosID": "xx",  
  "CustomerType": "xx",  
  "PaymentMethod": "xx",  
  "DeliveryType": "xx",  
  "City": "xx",  
  "State": "xx",  
  "PinCode": "xx",  
  "ItemCode": "xx",  
  "ItemDescription": "xx",  
  "ItemPrice": "xx",  
  "ItemQty": "xx",  
  "TotalValue": "xx"  
}
```


Sample Invoice

```
{  "InvoiceNumber": "2798495",
    "CreatedTime": 1552393659955,
    "StoreID": "STR7188",
    "PosID": "POS825",
    "CashierID": "OAS329",
    "CustomerType": "PRIME",
    "CustomerCardNo": "7051101351",
    "TotalAmount": 3529.0,
    "NumberOfItems": 2,
    "PaymentMethod": "CASH",
    "TaxableAmount": 3529.0,
    "CGST": 88.22500000000001,
    "SGST": 88.22500000000001,
    "CESS": 4.41125,
    "DeliveryType": "HOME-DELIVERY",
    "DeliveryAddress": {
        "AddressLine": "House No 727, 9696 Ullamcorper, Road",
        "City": "Dabgram",
        "State": "West Bengal",
        "PinCode": "953658",
        "ContactNumber": "4166559042"
    },
    "InvoiceLineItems": [
        {
            "ItemCode": "213",
            "ItemDescription": "Infant bed",
            "ItemPrice": 1755.0,
            "ItemQty": 1,
            "TotalValue": 1755.0
        },
        {
            "ItemCode": "628",
            "ItemDescription": "Window Scarf",
            "ItemPrice": 1774.0,
            "ItemQty": 1,
            "TotalValue": 1774.0
        }
    ]
}
```


Sample Invoice

```
{  "InvoiceNumber": "2798495",
    "CreatedTime": 1552393659955,
    "StoreID": "STR7188",
    "PosID": "POS825",
    "CashierID": "OAS329",
    "CustomerType": "PRIME",
    "CustomerCardNo": "7051101351",
    "TotalAmount": 3529.0,
    "NumberOfItems": 2,
    "PaymentMethod": "CASH",
    "TaxableAmount": 3529.0,
    "CGST": 88.22500000000001,
    "SGST": 88.22500000000001,
    "CESS": 4.41125,
    "DeliveryType": "HOME-DELIVERY",
    "DeliveryAddress": {
        "AddressLine": "House No 727, 9696 Ullamcorper, Road",
        "City": "Dabgram",
        "State": "West Bengal",
        "PinCode": "953658",
        "ContactNumber": "4166559042"
    },
    "InvoiceLineItems": [
        {
            "ItemCode": "213",
            "ItemDescription": "Infant bed",
            "ItemPrice": 1755.0,
            "ItemQty": 1,
            "TotalValue": 1755.0
        },
        {
            "ItemCode": "628",
            "ItemDescription": "Window Scarf",
            "ItemPrice": 1774.0,
            "ItemQty": 1,
            "TotalValue": 1774.0
        }
    ]
}
```

```
{
  "InvoiceNumber": "xx",
  "CreatedTime": "xx",
  "StoreID": "xx",
  "PosID": "xx",
  "CustomerType": "xx",
  "PaymentMethod": "xx",
  "DeliveryType": "xx",
  "City": "xx",
  "State": "xx",
  "PinCode": "xx",
  "ItemCode": "xx",
  "ItemDescription": "xx",
  "ItemPrice": "xx",
  "ItemQty": "xx",
  "TotalValue": "xx"
}
```





Kafka Topics



Requirement Extract

1. Select Invoices where DeliveryType = "HOME-DELIVERY" and push them to the shipment service queue.
2. Select Invoices where CustomerType = "PRIME" and create a notification event for the Loyalty Management Service. The format for the new notification event is given here.
3. Select all Invoices, mask the personal information, and create records for Trend Analytics. When the records are ready, persist them to Hadoop storage for batch analytics. The format for the new Hadoop record is also given.



Topologies:

Sub-topology: 0

Source: KSTREAM-SOURCE-0000000000 (topics: [pos])

--> KSTREAM-FILTER-0000000003, KSTREAM-MAPVALUES-0000000006, KSTREAM-FILTER-0000000001

Processor: KSTREAM-FILTER-0000000003 (stores: [])

--> KSTREAM-MAPVALUES-0000000004

<-- KSTREAM-SOURCE-0000000000

Processor: KSTREAM-MAPVALUES-0000000006 (stores: [])

--> KSTREAM-FLATMAPVALUES-0000000007

<-- KSTREAM-SOURCE-0000000000

Processor: KSTREAM-FILTER-0000000001 (stores: [])

--> KSTREAM-SINK-0000000002

<-- KSTREAM-SOURCE-0000000000

Processor: KSTREAM-FLATMAPVALUES-0000000007 (stores: [])

--> KSTREAM-SINK-0000000008

<-- KSTREAM-MAPVALUES-0000000006

Processor: KSTREAM-MAPVALUES-0000000004 (stores: [])

--> KSTREAM-SINK-0000000005

<-- KSTREAM-FILTER-0000000003

Sink: KSTREAM-SINK-0000000002 (topic: shipment)

<-- KSTREAM-FILTER-0000000001

Sink: KSTREAM-SINK-0000000005 (topic: loyalty)

<-- KSTREAM-MAPVALUES-0000000004

Sink: KSTREAM-SINK-0000000008 (topic: hadoop-sink)

<-- KSTREAM-FLATMAPVALUES-0000000007

State stores in Kafka Streams are used to maintain and store local state information for stream processing tasks. They allow processors to store and access intermediate results, aggregate data, or perform join operations efficiently.