```
#include<stdio.h>
#include<stdlib.h>
#include<ctype.h>
#include<string.h>
#define SIZE 100
char stack[SIZE];
int top = -1;
void push(char item){
if(top >= SIZE-1)
printf("\n Stack Overflow.");
else
top = top+1;
stack[top] = item;
}
char pop(){
char item;
if(top < 0)
printf("stack under flow: invalid infix expression");
getchar();
exit(1);
}
else
item = stack[top];
top = top-1;
return(item);
}
}
int is_operator(char symbol){
if(symbol == '^' || symbol == '*' || symbol == '-')
return 1;
}
else
return 0;
}
```

```
int precedence(char symbol){
if(symbol == ' \land ')
return(3);
else if(symbol == '*' || symbol == '/')
return(2);
else if(symbol == '+' || symbol == '-')
return(1);
}
else
return(0);
}
void InfixToPostfix(char infix_exp[], char postfix_exp[]){
int i, j;
char item;
char x;
push('(');
strcat(infix_exp,")");
i=0;
j=0;
item=infix_exp[i];
while(item != '\0'){
if(item == '(')
push(item);
else if( isdigit(item) || isalpha(item))
postfix_exp[j] = item;
j++;
else if(is_operator(item) == 1)
x = pop();
while(is_operator(x) == 1 && precedence(x)>= precedence(item))
postfix_exp[j] = x;
j++;
x = pop();
}
push(x);
push(item);
```

```
else if(item == ')')
x = pop();
while(x != '(')
postfix_exp[j] = x;
j++;
x = pop();
}
else
printf("\nInvalid infix Expression.\n");
getchar();
exit(1);
}
i++;
item = infix_exp[i];
if(top>0)
printf("\nInvalid infix Expression.\n");
getchar();
exit(1);
postfix_exp[j] = '\0';
}
int main(){
char infix[SIZE], postfix[SIZE];
printf("\n Enter Infix expression : ");
scanf("%s",infix);
InfixToPostfix(infix,postfix);
printf(" Postfix Expression: ");
printf("%s",postfix);
return 0;
}
```

```
itl4@22DL407:~/Desktop$ gedit yug.c
itl4@22DL407:~/Desktop$ gcc yug.c
itl4@22DL407:~/Desktop$ ./a.out yug.c

Enter Infix expression : a+b*c-(d/(e*f))
Postfix Expression: abc*+def*/-itl4@22DL407:~/Desktop$
```