ALI AYDIN 2093326 11.12.18

EE447 EXPERIMENT #4

PRELIMINARY REPORT

Question 1-)

In pulse.s, timer0a is used periodic, count down mode and 16 bit.

```
My_Timer0A_Handler      PROC
                                LDR     R1,=TIMER0_ICR; Clear the Flag
                                MOV     R0,#0x01;
                                STR     R0,[R1]; Time Out Interrupt clearead
                                LDR R1,=GPIO_PORTF_DATA;
                                LDR     R2,[R1];
                                CMP     R2,#0;
                                BNE     MakeItLow;
                                MOV     R2,#4;
                                STR     R2,[R1];
                                LDR     R1,=TIMER0_TAILR;
                                LDR     R2,=HIGH;
                                STR     R2,[R1];
                                BX      LR;
MakeItLow               MOV     R2,#0;
                                STR     R2,[R1];
                                LDR     R1,=TIMER0_TAILR;
                                LDR     R2,=LOW;
                                STR     R2,[R1];
                                BX      LR
                                ENDP
```

Question 2-)

READ.S

```
; 16/32 Timer Registers
TIMER1_CFG              EQU 0x40031000 ; Configuration Register
TIMER1_TAMR             EQU 0x40031004 ; Mode Register
TIMER1_CTL              EQU 0x4003100C ; Control Register
TIMER1_RIS              EQU 0x4003101C ; Raw interrupt Status
TIMER1_ICR              EQU 0x40031024 ; Interrupt Clear Register
TIMER1_TAILR            EQU 0x40031028 ; Interval Load Register
TIMER1_TAMATCHR EQU 0x40031030 ; Match Register
TIMER1_TAPR  EQU 0x40031038 ; Prescaling Divider
TIMER1_TAR              EQU 0x40031048 ; Counter Register
TIMER1_IMR              EQU     0x40031018 ; Defining Interrupt
TIMER1_TAV              EQU 0x40031050 ; To set the timer initial value

;GPIO Registers
;Port B base 0x40005000
GPIO_PORTB_IM                   EQU 0x40005010 ; Interrupt Mask
GPIO_PORTB_DIR                  EQU 0x40005400 ; Port Direction
GPIO_PORTB_AFSEL        EQU 0x40005420 ; Alt Function enable
GPIO_PORTB_DEN                  EQU 0x4000551C ; Digital Enable
GPIO_PORTB_AMSEL        EQU 0x40005528 ; Analog enable
```

```
GPIO_PORTB_PCTL       EQU 0x4000552C ; Alternate Functions
GPIO_PORTB_PDR                  EQU      0x40005514 ; Pull down
;System Registers
SYSCTL_RCGCGPIO       EQU 0x400FE608 ; GPIO Gate Control
SYSCTL_RCGCTIMER      EQU 0x400FE604 ; GPTM Gate Control

            AREA    routines, CODE, READONLY
                        THUMB
                        EXPORT          READ_INIT

READ_INIT       PROC
            LDR R1, =SYSCTL_RCGCGPIO ; start GPIO clock
            LDR R0, [R1]
            ORR R0, R0, #0x02 ; set bit 2 for port B
            STR R0, [R1]
            NOP ; allow clock to settle
            NOP
            NOP
            LDR R1, =GPIO_PORTB_DIR
            LDR R0, [R1]
            BIC R0, R0, #0x10 ; clear bit 4 for input
            STR R0, [R1]
; enable alternate function
            LDR R1, =GPIO_PORTB_AFSEL
            LDR R0, [R1]
            ORR R0, R0, #0x10 ; set bit4 for alternate fuction on PB4
            STR R0, [R1]
; set alternate function to T1CCP0 (7)
            LDR R1, =GPIO_PORTB_PCTL
            LDR R0, [R1]
            ORR R0, R0, #0x00070000 ; set bits 27:24 of PCTL to 7
            STR R0, [R1] ; to enable T1CCP0 on PB4
; disable analog
            LDR R1, =GPIO_PORTB_AMSEL
            MOV R0, #0 ; clear AMSEL to diable analog
            STR R0, [R1]
            LDR R1, =GPIO_PORTB_DEN ; enable port digital
            LDR R0, [R1]
            ORR R0, R0, #0x10
            STR R0, [R1]
; Set pull down
;           LDR     R1, =GPIO_PORTB_PDR
;           MOV     R0, #0x10; set PB4 as pull down
;           STR     R0, [R1];

;Timer1,A initialization
            LDR R1, =SYSCTL_RCGCTIMER
            LDR R2, [R1] ; Start timer 1
            ORR R2, R2, #0x02 ; Timer module = bit position (1)
            STR R2, [R1]
            NOP
            NOP
```

```
        NOP ; allow clock to settle
; disable timer during setup
        LDR R1, =TIMER1_CTL
        LDR R2, [R1]
        BIC R2, R2, #0x01 ; clear bit 0 to disable Timer 0
        STR R2, [R1]
; set to 16bit Timer Mode
        LDR R1, =TIMER1_CFG
        MOV R2, #0x04 ; set bits 2:0 to 0x04 for 16bit timer
        STR R2, [R1]
; set for edge time and capture mode
        LDR R1, =TIMER1_TAMR; set bit 4 to 0x01 for up counting
        MOV R2, #0x07 ; set bit2 to 0x01 for Edge Time Mode,
        STR R2, [R1] ; set bits 1:0 to 0x03 for Capture Mode
; set edge detection to both
        LDR R1, =TIMER1_CTL
        LDR R2, [R1]
        ORR R2, R2, #0x0C ; set bits 3:2 to 0x03
        STR R2, [R1]
; set start value
        LDR R1, =TIMER1_TAILR ; counter counts down,
        MOV R0, #0xFFFFFFFF ; so start counter at max value
        ;MOV R0, #0x00000000 ; so start counter at min value
        STR R0, [R1]
; Enable timer
        LDR R1, =TIMER1_CTL ;
        LDR R2, [R1] ;
        ORR R2, R2, #0x01 ; set bit 0 to enable
        STR R2, [R1]
        BX      LR
                        ENDP
                        END
```

__main.s

```
FIRST                   EQU     0x20000480
FREQ                    EQU     0x00F42400 ; Freq 16M
                                AREA sdata , DATA, READONLY
                                THUMB
MSG                     DCB "PULSE WIDTH "
                                DCB 0x0D
                                DCB 0x04
MSG1                    DCB "PERIOD "
                                DCB 0x0D
                                DCB 0x04
MSG2                    DCB "DUTY CYCLE % "
                                DCB 0x0D
                                DCB 0x04
;LABEL          DIRECTIVE       VALUE           COMMENT
                        AREA            main, READONLY, CODE
                        THUMB
                        EXTERN                  PULSE_INIT              ; Pulse initialization
                        EXTERN                  READ_INIT
                        EXTERN                  OutStr
                        EXTERN                  CONVRT
                        EXPORT          __main  ; Make available

__main
                        BL              READ_INIT;      initialize read
                        BL              PULSE_INIT; initialize pulse
START
                        MOV             R0,#0; R0 is turn counter
                        MOV     R10, #0
                        MOV     R8, #0
                        MOV             R6, #0
                        PUSH    {R0}

loop            LDR     R1, =TIMER1_RIS
                        LDR     R2, [R1]
                        ANDS    R2, #04 ; isolate CAERIS bit
                        BEQ     loop ; if no capture, then loop

                        LDR     R1, =TIMER1_ICR;
                        ORR             R2, #0x04; by setting CAECINT bit to 1, CAERIS bir is cleared
                        STR             R2, [R1]
                        LDR             R1, =GPIO_PORTB_DATA
                        LDR             R2, [R1]
                        LDR     R1, =TIMER1_TAR ; address of timer register
                        LDR     R0, [R1] ; Get timer register value
                        CMP             R6, #0
                        BEQ             FIRST_NUMBER
                        CMP             R8, #0
                        BEQ     SECOND_NUMBER
                        CMP             R10, #0
                        BEQ             THIRD_NUMBER

FIRST_NUMBER
                        CMP             R2, #0x10 ;IF sees positive edge, contunie
                        BNE             loop  ;if not, go begin
                        MOV             R6, R0
                        B               loop
SECOND_NUMBER
                        MOV             R8, R0
                        B               loop
THIRD_NUMBER
                        MOV             R10, R0
                        B               CONTINUE

CONTINUE                PUSH    {R5, R6, R7, R8}
                        LDR     R5,=MSG
                        BL              OutStr;to write string above definition
                        POP     {R5, R6, R7, R8}
                        MOV             R2, #16
                        UDIV    R6, R6, R2  ; r6 to microsec(us)
                        UDIV    R8,     R8, R2   ;r8 to us
                        UDIV    R10, R10, R2 ;r10 to us
                        SUB             R4, R6, R8          ;to find pulse width
                        PUSH    {R5, R6, R7, R8}
                        LDR             R5,=FIRST;
                        BL              CONVRT
                        LDR             R5,=FIRST;
                        BL      OutStr    ; write pulse width
                        POP     {R5, R6, R7, R8}
                        PUSH    {R5, R6, R7, R8}
                        LDR     R5,=MSG1
                        BL              OutStr ;write string
                        POP     {R5, R6, R7, R8}
                        MOV             R4, #0
                        SUB             R4, R6, R10 ;to find period
                        PUSH    {R5, R6, R7, R8}
                        LDR             R5,=FIRST;
                        BL              CONVRT
                        LDR             R5,=FIRST;
                        BL              OutStr ;write period
                        POP     {R5, R6, R7, R8}
                        PUSH    {R5, R6, R7, R8}
                        LDR     R5,=MSG2
                        BL              OutStr ;write string
                        POP     {R5, R6, R7, R8}
                        SUB             R4, R6, R10         ;period
                        MOV             R11, #100
                        SUB             R6, R6, R8          ;pulse width
                        MUL             R6, R6, R11
                        UDIV    R4,     R6, R4 ;duty cycle
                        PUSH    {R5, R6, R7, R8}
                        LDR             R5,=FIRST;
                        BL              CONVRT
                        LDR             R5,=FIRST;
                        BL              OutStr   ;write duty cycle
                        POP     {R5, R6, R7, R8}
                        B               START
                        ALIGN
                        END
```



```
PULSE WIDTH
33
PERIOD
56
DUTY CYCLE %
58
PULSE WIDTH
33
PERIOD
56
DUTY CYCLE %
58
```