

# WEEK 9 challenge and code along

alicia tan

2023-10-18

Code along (slides 8, 11, 12, 14, 18 and 19)

```
library(tidyverse)
```

```
## — Attaching core tidyverse packages — tidyverse 2.0.0 —
## ✓ dplyr      1.1.2      ✓ readr      2.1.4
## ✓ forcats    1.0.0      ✓ stringr    1.5.0
## ✓ ggplot2     3.4.3      ✓ tibble     3.2.1
## ✓ lubridate  1.9.2      ✓ tidyr      1.3.0
## ✓ purrr      1.0.2
## — Conflicts — tidyverse_conflicts() —
## * dplyr::filter() masks stats::filter()
## * dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
tidydata <- tribble(
  ~country, ~year, ~cases, ~population,
  "Afghanistan", 1999, 745, 19987071,
  "Afghanistan", 2000, 2666, 20595360,
  "Brazil", 1999, 37737, 172006362,
  "Brazil", 2000, 80488, 174504898,
  "China", 1999, 212258, 1272915272,
  "China", 2000, 213766, 1280428583)
tidydata
```

```
## # A tibble: 6 × 4
##   country      year cases population
##   <chr>      <dbl> <dbl>      <dbl>
## 1 Afghanistan 1999     745  19987071
## 2 Afghanistan 2000    2666  20595360
## 3 Brazil      1999  37737  172006362
## 4 Brazil      2000  80488  174504898
## 5 China       1999 212258 1272915272
## 6 China       2000 213766 1280428583
```

```
nontidydata <- tribble(
  ~country, ~year, ~rate,
  "Afghanistan", 1999, "745/19987071",
  "Afghanistan", 2000, "2666/20595360",
  "Brazil", 1999, "37737/172006362",
  "Brazil", 2000, "80488/174504898",
  "China", 1999, "212258/1272915272",
  "China", 2000, "213766/1280428583")
nontidydata
```

```
## # A tibble: 6 × 3
##   country      year rate
##   <chr>      <dbl> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil      1999 37737/172006362
## 4 Brazil      2000 80488/174504898
## 5 China       1999 212258/1272915272
## 6 China       2000 213766/1280428583
```

```
nontidydata
```

```
## # A tibble: 6 × 3
##   country      year rate
##   <chr>      <dbl> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil      1999 37737/172006362
## 4 Brazil      2000 80488/174504898
## 5 China       1999 212258/1272915272
## 6 China       2000 213766/1280428583
```

```
tidieddata <- nontidydata %>%
  separate(rate, into = c("cases",
    "population"),
  sep = "/")
tidieddata
```

```
## # A tibble: 6 × 4
##   country      year cases population
##   <chr>      <dbl> <chr>   <chr>
## 1 Afghanistan 1999 745     19987071
## 2 Afghanistan 2000 2666    20595360
## 3 Brazil      1999 37737   172006362
## 4 Brazil      2000 80488   174504898
## 5 China       1999 212258  1272915272
## 6 China       2000 213766  1280428583
```

```
newtidieddata <- tidieddata %>%
  pivot_longer(
    cols = cases:population,
    names_to = "measurement"
  ,
  values_to = "value"
  )
newtidieddata
```

```
## # A tibble: 12 × 4
##   country      year measurement value
##   <chr>      <dbl> <chr>      <chr>
## 1 Afghanistan 1999 cases       745
## 2 Afghanistan 1999 population 19987071
## 3 Afghanistan 2000 cases       2666
## 4 Afghanistan 2000 population 20595360
## 5 Brazil       1999 cases       37737
## 6 Brazil       1999 population 172006362
## 7 Brazil       2000 cases       80488
## 8 Brazil       2000 population 174504898
## 9 China        1999 cases       212258
## 10 China       1999 population 1272915272
## 11 China       2000 cases       213766
## 12 China       2000 population 1280428583
```

```
df <- tribble(
  ~id, ~bp1, ~bp2,
  "A", 100, 120,
  "B", 140, 115,
  "C", 120, 125
)
df
```

```
## # A tibble: 3 × 3
##   id      bp1  bp2
##   <chr> <dbl> <dbl>
## 1 A      100  120
## 2 B      140  115
## 3 C      120  125
```

```
df %>%
  pivot_longer(
    cols = bp1:bp2,
    names_to = "measurement",
    values_to = "value"
  )
```

```
## # A tibble: 6 × 3
##   id      measurement value
##   <chr> <chr>      <dbl>
## 1 A      bp1          100
## 2 A      bp2          120
## 3 B      bp1          140
## 4 B      bp2          115
## 5 C      bp1          120
## 6 C      bp2          125
```

```
newtidieddata
```

```
## # A tibble: 12 × 4
##   country      year measurement value
##   <chr>      <dbl> <chr>      <chr>
## 1 Afghanistan 1999 cases       745
## 2 Afghanistan 1999 population 19987071
## 3 Afghanistan 2000 cases       2666
## 4 Afghanistan 2000 population 20595360
## 5 Brazil      1999 cases       37737
## 6 Brazil      1999 population 172006362
## 7 Brazil      2000 cases       80488
## 8 Brazil      2000 population 174504898
## 9 China       1999 cases       212258
## 10 China      1999 population 1272915272
## 11 China      2000 cases       213766
## 12 China      2000 population 1280428583
```

```
newtidieddata %>%
  pivot_wider(names_from="measurement",
    values_from="value")
```

```
## # A tibble: 6 × 4
##   country      year cases population
##   <chr>      <dbl> <chr>      <chr>
## 1 Afghanistan 1999 745      19987071
## 2 Afghanistan 2000 2666     20595360
## 3 Brazil      1999 37737    172006362
## 4 Brazil      2000 80488    174504898
## 5 China       1999 212258   1272915272
## 6 China       2000 213766   1280428583
```

```
df <- tribble(
  ~id, ~measurement, ~value,
  "A", "bp1", 100,
  "B", "bp1", 140,
  "B", "bp2", 115,
  "A", "bp2", 120,
  "A", "bp3", 105
)
df
```

```
## # A tibble: 5 × 3
##   id      measurement value
##   <chr> <chr>      <dbl>
## 1 A      bp1          100
## 2 B      bp1          140
## 3 B      bp2          115
## 4 A      bp2          120
## 5 A      bp3          105
```

```
df %>%
  pivot_wider(
    names_from = measurement,
    values_from = value
  )
```


```
## # A tibble: 2 × 4
##   id      bp1    bp2    bp3
##   <chr> <dbl> <dbl> <dbl>
## 1 A      100    120    105
## 2 B      140    115     NA
```

## Challenge

```
billboard %>%
  pivot_longer(
    cols = starts_with("wk"),
    names_to = "week",
    values_to = "rank",
    values_drop_na = TRUE,
  ) %>%
  mutate(week=parse_number(week)) %>%

  ggplot(aes(x = week, y = rank, group = track)) +
    geom_line() +
    ggtitle("Rank vs. Week")
```

Rank vs. Week



```

cms_patient_experience %>%
  pivot_wider(
    names_from = measure_cd,
    values_from = prf_rate,
    id_cols = starts_with("org")
  )

```

```

## # A tibble: 95 × 8
##   org_pac_id org_nm CAHPS_GRP_1 CAHPS_GRP_2 CAHPS_GRP_3 CAHPS_GRP_5 CAHPS_GRP_8
##   <chr>      <chr>      <dbl>      <dbl>      <dbl>      <dbl>      <dbl>
## 1 0446157747 USC C...      63        87        86        57        85
## 2 0446162697 ASSOC...      59        85        83        63        88
## 3 0547164295 BEAVE...      49        NA        75        44        73
## 4 0749333730 CAPE ...      67        84        85        65        82
## 5 0840104360 ALLIA...      66        87        87        64        87
## 6 0840109864 REX H...      73        87        84        67        91
## 7 0840513552 SCL H...      58        83        76        58        78
## 8 0941545784 GRITM...      46        86        81        54        NA
## 9 1052612785 COMMU...      65        84        80        58        87
## 10 1254237779 OUR L...      61        NA        NA        65        NA
## # i 85 more rows
## # i 1 more variable: CAHPS_GRP_12 <dbl>

```