Data Mining:

Concepts and Techniques

(3rd ed.)

Jiawei Han, Micheline Kamber, and Jian Pei

University of Illinois at Urbana-Champaign &

Simon Fraser University

©2011 Han, Kamber & Pei. All rights reserved.

Classification: Basic Concepts

- Classification: Basic Concepts
- Decision Tree Induction
- Bayes Classification Methods 
- Lazy Learners (or Learning from Your Neighbors)
- Model Evaluation and Selection
- Techniques to Improve Classification Accuracy: Ensemble Methods
- Summary

Bayesian Classification: Why?

- A statistical classifier: performs *probabilistic prediction, i.e.,* predicts class membership probabilities
- Foundation: Based on Bayes' Theorem.
- Performance: A simple Bayesian classifier, *naïve Bayesian classifier*, has comparable performance with decision tree and selected neural network classifiers
- Incremental: Each training example can incrementally increase/decrease the probability that a hypothesis is correct — prior knowledge can be combined with observed data
- Standard: Even when Bayesian methods are computationally intractable, they can provide a standard of optimal decision making against which other methods can be measured

Bayes' Theorem: Basics

- Total probability Theorem: $P(B) = \sum_{i=1}^{M} P(B|A_i)P(A_i)$
- Bayes' Theorem: $P(H|\mathbf{X}) = \frac{P(\mathbf{X}|H)P(H)}{P(\mathbf{X})} = P(\mathbf{X}|H) \times P(H) / P(\mathbf{X})$
  - Let **X** be a data sample ("*evidence*"): class label is unknown
  - Let H be a *hypothesis* that X belongs to class C
  - Classification is to determine P(H|**X**), (i.e., *posteriori probability):* the probability that the hypothesis holds given the observed data sample **X**
  - P(H) (*prior probability*): the initial probability
    - E.g., **X** will buy computer, regardless of age, income, …
  - P(**X**): probability that sample data is observed
  - P(**X**|H) (likelihood): the probability of observing the sample **X**, given that the hypothesis holds
    - E.g., Given that **X** will buy computer, the prob. that X is 31..40, or income is medium, etc.

Prediction Based on Bayes' Theorem

- Given training data **X**, *posteriori probability of a hypothesis* H, P(H|**X**), follows the Bayes' theorem

$$P(H \mid \mathbf{X}) = \frac{P(\mathbf{X} \mid H)P(H)}{P(\mathbf{X})} = P(\mathbf{X} \mid H) \times P(H) / P(\mathbf{X})$$

- Informally, this can be viewed as

  posteriori = likelihood x prior/evidence

- Predicts **X** belongs to C_i iff the probability $P(C_i|\mathbf{X})$ is the highest among all the $P(C_k|X)$ for all the *k* classes
- Practical difficulty: It requires initial knowledge of many probabilities, involving significant computational cost

Classification Is to Derive the Maximum Posteriori

- Let D be a training set of tuples and their associated class labels, and each tuple is represented by an n-D attribute vector **X** = (x_1, x_2, …, x_n)
- Suppose there are *m* classes C_1, C_2, …, C_m.
- Classification is to derive the maximum posteriori, i.e., the maximal $P(C_i|\mathbf{X})$
- This can be derived from Bayes' theorem


$$P(C_i|\mathbf{X}) = \frac{P(\mathbf{X}|C_i)P(C_i)}{P(\mathbf{X})}$$

- Since P(X) is constant for all classes, only

$$P(C_i|\mathbf{X}) = P(\mathbf{X}|C_i)P(C_i)$$

needs to be maximized

Monty Hall



Naïve Bayes Classifier

- A simplified assumption: attributes are conditionally independent (i.e., no dependence relation between attributes):

$$P(\mathbf{X}|C_i) = \prod_{k=1}^{n} P(x_k|C_i) = P(x_1|C_i) \times P(x_2|C_i) \times ... \times P(x_n|C_i)$$

$$P(C_i|\mathbf{X}) \propto P(\mathbf{X}|C_i)P(C_i)$$

- This greatly reduces the computation cost: Only counts the class distribution
- If A_k is categorical, $P(x_k|C_i)$ is the # of tuples in C_i having value x_k for A_k divided by $|C_{i,D}|$ (# of tuples of C_i in D)
- If A_k is continous-valued, $P(x_k|C_i)$ is usually computed based on Gaussian distribution with a mean μ and standard deviation σ, and $P(x_k|C_i)$ is

$$g(x, \mu, \sigma) = \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

$$P(\mathbf{X}|C_i) = g(x_k, \mu_{C_i}, \sigma_{C_i})$$

Naïve Bayes Classifier: Training Dataset

Class:

C1:buys_computer = ‘yes’

C2:buys_computer = ‘no’

Data to be classified:

X = (age <=30,

Income = medium,

Student = yes

Credit_rating = Fair)

age	income	student	credit_rating	buys_computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31…40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31…40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
>40	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31…40	medium	no	excellent	yes
31…40	high	yes	fair	yes
>40	medium	no	excellent	no

Naïve Bayes Classifier: An Example

- $P(C_i)$: P(buys_computer = "yes") = 9/14 = 0.643
  P(buys_computer = "no") = 5/14= 0.357
- Compute $P(X|C_i)$ for each class
  P(age = "<=30" | buys_computer = "yes") = 2/9 = 0.222
  P(age = "<= 30" | buys_computer = "no") = 3/5 = 0.6
  P(income = "medium" | buys_computer = "yes") = 4/9 = 0.444
  P(income = "medium" | buys_computer = "no") = 2/5 = 0.4
  P(student = "yes" | buys_computer = "yes) = 6/9 = 0.667
  P(student = "yes" | buys_computer = "no") = 1/5 = 0.2
  P(credit_rating = "fair" | buys_computer = "yes") = 6/9 = 0.667
  P(credit_rating = "fair" | buys_computer = "no") = 2/5 = 0.4
- **X_{test}= (age <= 30 , income = medium, student = yes, credit_rating = fair)**

$P(X|C_i)$: P(X|buys_computer = "yes") = 0.222 x 0.444 x 0.667 x 0.667 = 0.044
P(X|buys_computer = "no") = 0.6 x 0.4 x 0.2 x 0.4 = 0.019

$P(X|C_i)*P(C_i)$: P(X|buys_computer = "yes") * P(buys_computer = "yes") = 0.028
P(X|buys_computer = "no") * P(buys_computer = "no") = 0.007

Therefore, X belongs to class ("buys_computer = yes")

Avoiding the Zero-Probability Problem

- Naïve Bayesian prediction requires each conditional probability be **non-zero**. Otherwise, the predicted prob. will be zero

$$P(X \mid C_i) = \prod_{k=1}^{n} P(x_k \mid C_i)$$

- Ex. Suppose a dataset with 1000 tuples, income=low (0), income= medium (990), and income = high (10)
- Use **Laplacian correction** (or Laplacian estimator)
  - *Adding 1 to each case*

    Prob(income = low) = 1/1003

    Prob(income = medium) = 991/1003

    Prob(income = high) = 11/1003
  - The "corrected" probability estimates are close to their "uncorrected" counterparts, yet the zero *probability* value is avoided.

Naïve Bayes Classifier: Comments

- Advantages
  - Easy to implement
  - Good results obtained in most of the cases
- Disadvantages
  - Assumption: class conditional independence, therefore loss of accuracy
  - Practically, dependencies exist among variables
    - E.g., hospitals: patients: Profile: age, family history, etc.

      Symptoms: fever, cough etc., Disease: lung cancer, diabetes, etc.
    - Dependencies among these cannot be modeled by Naïve Bayes Classifier
- How to deal with these dependencies? Bayesian Belief Networks