
Table of Contents


.....	1
2.3.a	1
2.3.b	2
2.3.c	4
2.3.d	6
2.3 (with noise)	9
Plot func	10

```
close all;  
clear;  
clc;
```

2.3.a

Loading the audio file

```
[x, Fs] = audioread('Audio01.wav');  
  
% Plotting signal in time and freq domain  
plot_time_freq(x, Fs, 'Original audio signal', 'Signal in Time  
Domain', 'Signal in Frequency Domain');  
  
% Playing the audio  
sound(x, Fs);  
pause(length(x) * (1/ Fs));
```



2.3.b




```
load('filter.mat');


% Plotting filter in time domain
figure('Name', 'Time Domain Representation of Filter');
stem(Num, 'LineWidth', 1.5);
grid on;
xlabel('Time(Sec)') ;
ylabel('Amplitude') ;
title('Time Domain Representation of Filter');

figure('Name', 'Filter freq-phase response');
freqz(Num); % Visualising filter freq-phase response

y_0 = filter(Num,1,x); % Applying filter


% Plotting signal in time and freq domain
plot_time_freq(y_0, Fs, 'Filtered audio signal', 'Filtered Signal in Time
    Domain', 'Filtered Signal in Frequency Domain');
```






2.3.c

```
f0 = 10000;  
n = 1:length(x);  
s_n = 2*cos(2*pi*f0*n/Fs);  
  
y_1 = y_0 .* s_n';  
y_2 = filter(Num,1,y_1); % Scrambled Signal  
  
% Plotting signals in time and freq domain  
plot_time_freq(y_1, Fs, 'Signal Multiplied by Carrier', 'Signal Multiplied by  
Carrier in Time Domain', 'Signal Multiplied by Carrier in Frequency Domain');  
plot_time_freq(y_2, Fs, 'Scrmabled Audio Signal', 'Scrmabled Audio Signal in  
Time Domain', 'Scrmabled Audio Signal in Frequency Domain');  
  
% Playing the audio  
sound(y_2, Fs);  
pause(length(y_2) * (1/ Fs));
```





2.3.d

```

y_3 = filter(Num,1,y_2);
y_4 = y_3 .* s_n';
y_5 = filter(Num,1,y_4);

% Plotting signals in time and freq domain
plot_time_freq(y_4, Fs, 'Scrmabled Signal Multiplied by Carrier', 'Scrmabled
Signal Multiplied by Carrier in Time Domain', 'Scrmabled Signal Multiplied by
Carrier in Frequency Domain');
plot_time_freq(y_5, Fs, 'Descrmabled Audio Signal', 'Descrmabled Audio Signal
in Time Domain', 'Descrmabled Audio Signal in Frequency Domain');

plot_freq_freq(x, y_5, Fs, 'Frequency Spectrums', 'Frequency Spectrum Of
Original Signal', 'Frequency Spectrum Of Descrmabled Signal');

% Playing the audio
sound(y_5, Fs);

% Calculating MSE and MAE
disp('MAE and MSE:');
MAE = mean(abs(x - y_5))
MSE = mean((x - y_5) .^ 2)

pause(length(y_2) * (1/ Fs));

```


MAE and MSE:





MAE =

0.0311

MSE =

0.0017





2.3 (with noise)

```
y_2_noisy = y_2 + 0.05 * randn(1, length(y_2));

T = length(y_2) * (1/ Fs);
t = 0: 1/Fs:T-1/Fs;

figure('Name', 'Scrambled Signal VS Noisy Scrambled Signal');
subplot(2, 1, 1);
plot(t, y_2, 'LineWidth', 1.5);
grid on;
xlabel('Time(Sec)') ;
ylabel('Amplitude') ;
title('Scrambled Signal');
subplot(2,1,2) ;
plot(t, y_2_noisy, 'LineWidth',1.5) ;
grid on;
xlabel('Time(Sec)') ;
ylabel('Amplitude');
title('Noisy Scrambled Signal');

y_3 = filter(Num,1,y_2_noisy);
y_4 = y_3 .* s_n';
y_5 = filter(Num,1,y_4);


% Plotting signals in time and freq domain
plot_time_freq(y_3, Fs, 'Low-Passed Scrmabled Noisy Signal', 'Low-Passed
    Scrmabled Noisy Signal in Time Domain', 'Low-Passed Scrmabled Noisy Signal in
    Frequency Domain');
plot_time_freq(y_4, Fs, 'Noisy Scrmabled Signal Multiplied by Carrier', 'Noisy
    Scrmabled Signal Multiplied by Carrier in Time Domain', 'Noisy Scrmabled
    Signal Multiplied by Carrier in Frequency Domain');
plot_time_freq(y_5, Fs, 'Noisy Descrmabled Audio Signal', 'Noisy Descrmabled
    Audio Signal in Time Domain', 'Noisy Descrmabled Audio Signal in Frequency
    Domain');

plot_freq_freq(x, y_5, Fs, 'Frequency Spectrums (Channel with
    noise)', 'Frequency Spectrum Of Original Signal', 'Frequency Spectrum Of
    Descrambled Signal');

% When the communication channel has noise, a noise floor is added to the
% signal which remains after descrambling and is audible in the final result.
% The noise floor can also be seen in the spectrum of the descrambled signal.

% Playing the audio
sound(y_5, Fs);

% Calculating MSE and MAE
disp('MAE and MSE for noisy signal:');
MAE = mean(abs(x - y_5))
MSE = mean((x - y_5) .^ 2)
```



Plot func

```
function plot_time_freq(y, Fs, title1, title2, title3)
    T = length(y) * (1/ Fs);
    t = 0: 1/Fs:T-1/Fs;

    % Constructing the FFT spectrum of the signal
    L_y = length(y);
    f_y = (Fs/L_y) * (-L_y/2:L_y/2-1);
    fft_y = fftshift(fft(y))/L_y;

    % Plotting signal in time and freq domain
    figure('Name', title1);
    subplot(2, 1, 1);
    plot(t, y, 'LineWidth', 1.5);
    grid on;
    xlabel('Time(Sec)') ;
    ylabel('Amplitude') ;
    title(title2);
    subplot(2,1,2) ;
    plot(f_y, abs(fft_y), 'LineWidth',1.5) ;
    grid on;
    xlabel('freq (Hz)');
    ylabel('Amplitude');
    title(title3);
end
```

```
function plot_freq_freq(y1, y2, Fs, title1, title2, title3)
    % Constructing the FFT spectrum of the signals
    L_y1 = length(y1);
    f_y1 = (Fs/L_y1) * (-L_y1/2:L_y1/2-1);
    fft_y1 = fftshift(fft(y1))/L_y1;

    L_y2 = length(y2);
    f_y2 = (Fs/L_y2) * (-L_y2/2:L_y2/2-1);
    fft_y2 = fftshift(fft(y2))/L_y2;

    % Plotting signal in time and freq domain
    figure('Name', title1);
    subplot(2, 1, 1);
    plot(f_y1, abs(fft_y1), 'LineWidth', 1.5);
    grid on;
    xlabel('freq (Hz)') ;
    ylabel('Amplitude') ;
    title(title2);
    subplot(2,1,2) ;
    plot(f_y2, abs(fft_y2), 'LineWidth',1.5) ;
    grid on;
    xlabel('freq (Hz)');
    ylabel('Amplitude');
    title(title3);
end
```

Published with MATLAB® R2023a