Edit

zsh cheatsheet

Expressions

Expression	Example	Description
`!!`	`sudo !!`	Last command (`sudo !!`)
`!*`	`vim !*`	Last command's parameters (`vim !*`)
`!^`		Last command's first parameter
`!$`		Last command's last parameter
`!?ls <tab>`	`sudo !?mv <tab>`	Command and params of last `ls` command
`!?ls?:* <tab>`		Params of last `ls` command
`*(m0)`	`rm *(m0)`	Last modified today
`*(m-4)`		Last modified <4 days ago

Change default shell

```
chsh -s `which zsh`
```

Process Substitution

Expression	Example	Description
`<(COMMAND)`	`grep "needle" <(curl "https://haystack.io")`	Replace argument with named pipe/FIFO (read-only) with command output
`=(COMMAND)`	`vim =(curl "https://haystack.io")`	Replace argument with file (writable) containing command output

Also see

- Bash cheatsheet

Zsh is mostly compatible with Bash, so most everything in Bash's cheatsheet also applies.

▶ 💬 **1 Comment** for this cheatsheet. Write yours!

devhints.io / Search 357+ cheatsheets

Over 357 curated cheatsheets, by developers for developers.

Devhints home

Other CLI cheatsheets

Cron
cheatsheet ●

Homebrew
cheatsheet ●

httpie
cheatsheet ●

adb (Android Debug Bridge)
cheatsheet ●

composer
cheatsheet ●

Fish shell
cheatsheet ●

Top cheatsheets

Elixir
cheatsheet ●

ES2015+
cheatsheet ●

React.js
cheatsheet ●

Vimdiff
cheatsheet ●

Vim
cheatsheet ●

Vim scripting
cheatsheet ●

cb