Home Work #4

Ali BaniAsad 401209244

January 24, 2023

1 Question 1

We know inertia matrix is symetric so we have:

$$I_{xy} = I_{yx} = 10, \quad I_{xz} = I_{zx} = 0, \quad I_{yz} = I_{zy}$$

$$\mathbf{I} = \begin{bmatrix} 30 & -10 & 0 \\ -10 & 20 & -I_{yz} \\ 0 & -I_{yz} & 30 \end{bmatrix}$$

1.1 part a

We know that:

$$\mathbf{I} \times \boldsymbol{\omega} = \mathbf{h} \tag{1}$$

$$\boldsymbol{\omega} = \begin{bmatrix} 10 & 10 & 10 \end{bmatrix}^T_{RPS} = \begin{bmatrix} 10 \times 2\pi & 10 \times 2\pi & 10 \times 2\pi \end{bmatrix}^T_{rad/\sec}, \quad \mathbf{h} = \begin{bmatrix} 200 & 200 & 400 \end{bmatrix}^T_{kg.m^2/s}$$

If we use radian per second instead of revelotion per second $\mathbf{I} \times \boldsymbol{\omega} \neq \mathbf{h}$ would happen.

$$\mathbf{I} \times \boldsymbol{\omega} = \begin{bmatrix} 200 \\ 100 - 10I_{yz} \\ 300 - 10I_{yz} \end{bmatrix} = \begin{bmatrix} 200 \\ 200 \\ 400 \end{bmatrix} \rightarrow I_{yz} = -10 \rightarrow \mathbf{I} = \begin{bmatrix} 30 & -10 & 0 \\ -10 & 20 & 10 \\ 0 & 10 & 30 \end{bmatrix}$$

$$T_{Rotational} = \frac{1}{2}\boldsymbol{\omega}^T \times \mathbf{I} \times \boldsymbol{\omega} = \frac{1}{2}\begin{bmatrix} 10 & 10 & 10 \end{bmatrix} \times \begin{bmatrix} 30 & -10 & 0 \\ -10 & 20 & 10 \\ 0 & 10 & 30 \end{bmatrix} \times \begin{bmatrix} 10 \\ 10 \\ 10 \end{bmatrix} = 4000 \tag{2}$$

1.2 part b

$$T_{Rotational} = \frac{1}{2}\mathrm{I}_\xi \omega^2 \rightarrow \mathrm{I}_\xi = \frac{2T_{Rotational}}{\omega^2} = \frac{2 \times 4000}{300} = 26.67 \tag{3}$$

Rotation matrix calculated via eigen vector of inertia matrix (used MATLAB to calculate).

$$\mathbf{A} = \mathrm{eig}(\mathbf{I}) = \begin{bmatrix} -0.4082 & -0.7071 & -0.5774 \\ -0.8165 & -0.0000 & 0.5774 \\ 0.4082 & -0.7071 & 0.5774 \end{bmatrix} \tag{4}$$

$$\mathbf{I}' = \mathbf{A}^T \times \mathbf{I} \times \mathbf{A} = \begin{bmatrix} 10 & 0 & 0 \\ 0 & 30 & 0 \\ 0 & 0 & 40 \end{bmatrix}, \quad \boldsymbol{\omega}' = \mathbf{A}^T\boldsymbol{\omega} = \begin{bmatrix} -8.1650 \\ -14.1421 \\ 5.7735 \end{bmatrix}$$

$$h = |\mathbf{I} \times \boldsymbol{\omega}| = 489.8979$$

We know that above matrix shows the direction cosines of the principal axes with the primary body axes. Used MATLAB function (dcm2angle) to calculate euler angles between two corinate system.

$$\begin{bmatrix} \phi \\ \theta \\ \psi \end{bmatrix} = \begin{bmatrix} 45.00^{\circ} \\ 35.26^{\circ} \\ -120.00^{\circ} \end{bmatrix}$$

1.3 part c

Ellipsoid of inertia calculated as folow:

$$\frac{X^2}{\left(\sqrt{\frac{1}{\mathrm{I}_x}}\right)^2} + \frac{Y^2}{\left(\sqrt{\frac{1}{\mathrm{I}_y}}\right)^2} + \frac{Z^2}{\left(\sqrt{\frac{1}{\mathrm{I}_z}}\right)^2} = \frac{X^2}{\left(\sqrt{\frac{1}{10}}\right)^2} + \frac{Y^2}{\left(\sqrt{\frac{1}{30}}\right)^2} + \frac{Z^2}{\left(\sqrt{\frac{1}{40}}\right)^2} = 1 \tag{5}$$

Figure 1: elipsoid of inertia



Figure 2: elipsoid of inertia in zx plane



Figure 3: elipsoid of inertia zy plane



Figure 4: elipsoid of inertia in xy plane



Part I

part d

Angular momentum and rotational kinetic energy elipsoid calculated as folow:

$$\frac{\omega_x^2}{\left(\frac{h}{\mathrm{I}_x}\right)^2} + \frac{\omega_y^2}{\left(\frac{h}{\mathrm{I}_y}\right)^2} + \frac{\omega_z^2}{\left(\frac{h}{\mathrm{I}_z}\right)^2} = \frac{\omega_x^2}{\left(\frac{490}{10}\right)^2} + \frac{\omega_y^2}{\left(\frac{490}{30}\right)^2} + \frac{\omega_z^2}{\left(\frac{490}{40}\right)^2} = 1 \tag{6}$$

$$\frac{\omega_x^2}{\left(\sqrt{\frac{2T}{\mathrm{I}_x}}\right)^2} + \frac{\omega_y^2}{\left(\sqrt{\frac{2T}{\mathrm{I}_y}}\right)^2} + \frac{\omega_z^2}{\left(\sqrt{\frac{2T}{\mathrm{I}_z}}\right)^2} = \frac{\omega_x^2}{\left(\sqrt{\frac{2\times 4000}{10}}\right)^2} + \frac{\omega_y^2}{\left(\sqrt{\frac{2\times 4000}{30}}\right)^2} + \frac{\omega_z^2}{\left(\sqrt{\frac{2\times 4000}{40}}\right)^2} = 1 \tag{7}$$

Ellipsoid parameter calculated before, now, use them to draw the elipsoid.

Figure 5: Angular momentum and rotational kinetic energy elipsoid of inertia



Figure 6: Angular momentum and rotational kinetic energy elipsoid of inertia in zx plane



Figure 7: Angular momentum and rotational kinetic energy elipsoid of inertia zy plane



Figure 8: Angular momentum and rotational kinetic energy elipsoid of inertia in xy plane



2 Question 2

Data of the question:

$$\mathrm{I}_x = 8_{kg.m^2}, \quad \mathrm{I}_y = 10_{kg.m^2}, \quad \mathrm{I}_z = 14_{kg.m^2}$$

$$\mathbf{q}(0) = \begin{bmatrix}0.3 & 0.2 & 0.5 & 0.7874\end{bmatrix}^T$$

$$\boldsymbol{\omega}(0) = \begin{bmatrix}2 & 3 & -5\end{bmatrix}^T \times 10^{-3}_{rps} = \begin{bmatrix}2\times 2\pi & 3\times 2\pi & -5\times 2\pi\end{bmatrix}^T \times 10^{-3}_{rad/\sec}$$

3 part a

Used MATLAB function(quat2eul) to calculate initial euler angles.

$$\begin{bmatrix}\phi\\ \theta\\ \psi\end{bmatrix} = \begin{bmatrix}137.74^\circ\\ -0.86^\circ\\ 65.16^\circ\end{bmatrix}$$

4 part b

Equation of motion with gravity gradient:

$$I_x\dot{\omega}_x + \omega_y\omega_z(I_z - I_y) = G_x \tag{8}$$

$$I_y\dot{\omega}_y + \omega_x\omega_z(I_x - I_z) = G_y \tag{9}$$

$$I_z\dot{\omega}_z + \omega_x\omega_y(I_y - I_x) = G_z \tag{10}$$

$$\tag{11}$$

$$\dot{\omega}_x = (G_x + \omega_y\omega_z(I_y - I_z))/I_x$$

$$\dot{\omega}_y = (G_y + \omega_x\omega_z(I_z - I_x))/I_y$$

$$\dot{\omega}_z = (G_z + \omega_y\omega_x(I_x - I_y))/I_z$$

$$\begin{bmatrix}\dot{\omega}_x\\ \dot{\omega}_y\\ \dot{\omega}_z\end{bmatrix} = \begin{bmatrix}p\\ q\\ r\end{bmatrix} + \mathbf{C}_R^b\begin{bmatrix}0\\ -\omega_0\\ 0\end{bmatrix} \rightarrow \begin{bmatrix}p\\ q\\ r\end{bmatrix} = \begin{bmatrix}\dot{\omega}_x\\ \dot{\omega}_y\\ \dot{\omega}_z\end{bmatrix} + \mathbf{C}_R^b\begin{bmatrix}0\\ \omega_0\\ 0\end{bmatrix} \tag{12}$$

where $\mathbf{C}_R^b$ is transformation matrix.

$$\mathbf{C}_b^R = \begin{bmatrix}\cos(\theta)\cos(\psi) & -\cos(\phi)\sin(\psi) + \sin(\phi)\sin(\theta)\cos(\psi) & \sin(\phi)\sin(\psi) + \cos(\phi)\sin(\theta)\cos(\psi)\\ \cos(\theta)\sin(\psi) & \cos(\phi)\cos(\psi) + \sin(\phi)\sin(\theta)\sin(\psi) & -\sin(\phi)\cos(\psi) + \cos(\phi)\sin(\theta)\sin(\psi)\\ -\sin(\theta) & \sin(\phi)\cos(\theta) & \cos(\phi)\cos(\theta)\end{bmatrix} \tag{13}$$

Using euler propagation:

$$\begin{bmatrix}\dot{\phi}\\ \dot{\theta}\\ \dot{\psi}\end{bmatrix} = \begin{bmatrix}1 & \sin(\phi)\tan(\theta) & \cos(\phi)\tan(\theta)\\ 0 & \cos(\phi) & -\sin(\phi)\\ 0 & \dfrac{(\phi)}{\cos(\theta)} & \dfrac{\cos(\phi)}{\cos(\theta)}\end{bmatrix}\begin{bmatrix}p\\ q\\ r\end{bmatrix} \tag{14}$$

In linearized equation of motion we assume:

$$\mathbf{C}_b^R = \begin{bmatrix} 1 & -\psi & \theta \\ \psi & 1 & -\phi \\ -\theta & \phi & 1 \end{bmatrix}, \quad \begin{bmatrix} p \\ q \\ r \end{bmatrix} = \begin{bmatrix} \dot{\phi} \\ \dot{\theta} \\ \dot{\psi} \end{bmatrix} \tag{15}$$

For the transformation from reference to body use the transpose of the desciberd matrix above.

The equations of motions solved in MATLAB with ode45 function. Below is the figure of euler angles simulation in 50 and 1000 seconds.

Figure 9: simulation of ϕ for 50 seconds



Figure 10: simulation of θ for 50 seconds



Figure 11: simulation of ψ for 50 seconds



Figure 12: simulation of ϕ for 1000 seconds



Figure 13: simulation of θ for 1000 seconds



Figure 14: simulation of ψ for 1000 seconds



5 part d

Used above equation with different initial conditions and add initial torque disturbance.

Figure 15: simulation of ϕ with torque disturbance



Figure 16: simulation of θ with torque disturbance



Figure 17: simulation of ψ with torque disturbance



Contents

List of Figures