

Lab Assignment 3, Hopfield networks

Alice Karnsund, Elin Samuelsson & Irene Natale

KTH The Royal Institute of Technology

September 27, 2018

Sequential Update




Figure 2: Middle column represents the results of the degraded patterns p_{10} and p_{11} after 7 iterations. The network succeeds to complete p_{11} into p_2 .

The number of incorrect states in each result, compared to the attractor it aimed for, turned out to be:

$$[p_{10} \rightarrow p_1, p_{11} \rightarrow p_2, p_{11} \rightarrow p_3] = [135, 0, 728].$$




Figure 3: Units selected randomly when calculating the states for p10 and p11.

Energy

For the three different attractors p1, p2 and p3 the energies are:

$$E_{\text{attractors}} = [-1439.4, -1365.6, -1462.3]$$

And for the two distorted patterns, p10 and p11, the energies are:

$$E_{\text{distorted}} = [-415.9805, -173.5000]$$




Figure 4: Decrease in energy for the patterns p10 and p11 as they approaches attractors. The results are obtained over 10 iterations.





Figure 5: Decrease in energy for the patterns p8 and p9 when (1) W is normally distributed random numbers and (2) when W is a symmetric version of the normally distributed W . The results are obtained over 10 iterations.

Distortion Resistance




Figure 6: The fraction of restored pictures over 500 iterations when training with 3 pictures, with and without including inverted pictures.

- ▶ p2 has the best noise tolerance.
- ▶ The network can recover pictures when $< 50\%$ noise.
- ▶ The network can recover inverted pictures when $> 50\%$ noise.

Distortion Resistance - One example




Figure 7: An example of the resulting patterns for different levels of noise, when training with 3 pictures. Title = input, picture = output.

- ▶ When restoring x , the network sometimes need more than one update for convergence, but the number of restored patterns is equally good regardless of one or more updates.

Distortion Resistance - 9 attractors

The attractors




Figure 8: The attractors, when training with 3 pictures.

Capacity




Figure 9: The fraction of successfully restored pictures over 500 iterations, for picture and random data, when training with 4 patterns.

- ▶ By adding p4 to the weight matrix, the network abruptly loses its ability to restore any picture.
- ▶ When replacing the pictures with random data of the same size, the network can restore all data with noise less than 50%.

Capacity - Adding more memory




Figure 10: The effect of removing self-connections when adding more memories to the network. A 5% noise was used and the test was repeated 100 times.

Capacity - Removing self-connections

- ▶ The number of stable patterns increase with number of patterns added to the network.
- ▶ The number of successfully recovered patterns from 5% noise quickly reaches a maximum and then decreases down to zero again.
- ▶ This implies that training on a large number of patterns leads to poor generalization performance.
- ▶ By removing the self-connections, and thus the spurious patterns, the stable patterns exhibit the same behaviour.

Capacity - Biased patterns

The effect of adding more memories to a network without self-connections




Figure 11: The effect of having biased patterns when adding more memories to a network without self-connections. A 5% noise was used and the test was repeated 100 times.

Capacity - Biased patterns

- ▶ The mean maximum number of retrievable patterns is 9.42, which is not too far from the theoretical value of 13.8.
- ▶ Having biased patterns decreases the network's performance regarding both stable and retrievable patterns.
- ▶ This can explain the previous difference between picture data and random data. The pictures are biased towards one colour, and are thus harder to recover.
- ▶ p2, which was the most noise tolerant, has a more even distribution between 1 and -1 than p1 and p3.

Sparse Patterns




Figure 12: Number of stored patterns with varying bias and average activity.

- ▶ bias ≈ 17.50 best results
- ▶ more active neurons to store \rightarrow less stored patterns