

Thermal Sticker

Attribute	Details
Product Name	Thermal Sticker
Material	Direct Thermal Paper (Top-Coated / Non-Coated)
Sticker Type	Barcode / Price / Shipping Label
Technics	Thermal Printing (No Ink Required)
Thickness / GSM	60–70 GSM
Design	Standard / Customized
Logo	Optional (Pre-Printed Logo)
Color	White Base, Black Print
Printing	Direct Thermal / Thermal Transfer
Adhesive Strength	Permanent Adhesive
Finish Type	Matte Finish
Custom Shape Support	Yes
Application Method	Peel & Stick (Self-Adhesive)
Temperature Resistance	-5°C to +40°C
Water / Oil Resistance	Low (not waterproof, unless laminated)
UV / Scratch Resistance	Low (print fades with sunlight/heat)
Roll / Sheet Options	Rolls (1000 pcs/roll)
Core Size	1” or 3”
Shelf Life	6–12 months (printing fades over time)

Storage Conditions	Store in cool, dry place, away from heat & sunlight
Usage	Supermarkets, Garment Tags, Logistics, POS Systems
Packing Method	Roll (1000 pcs/roll or customized)
Country of Origin	Bangladesh
MOQ	5000 pcs
Bulk Order Discount	Available on 20,000 pcs+
Sample Order Lead Time	5 Days
Product Lead Time	5000–20,000 pcs = 3–4 Days 20,000+ pcs = 7 Days
Shipment	FOB Chittagong
Certifications	FSC Certificate, ISO 9001