TICK the lines you want (they turn yellow), then SAVE and send this file back to us.

Client name:

HIPKO
HAMMOUD INTERNATIONAL PAPER SAL.
PAPER & BOARD

AVAILABLE OFFSHORE - متوفر في الخارج

Stocklot Report

Reference: SL157-K-CKB-DPLX-27.10.2026
27 OCTOBER 2026

TOTAL AVAILABLE	SUBSTANCE RANGE	MILL (معمل)
394.34 MT	42 - 460 GSM	BILLERUD

#	QUALITY	GSM	SIZE (CM)	TONS
	REELS			389.46 MT
	CROWNBOARD PRESTIGE			306.83 MT
1	CROWNBOARD PRESTIGE	230	71 cm	7.35
2	CROWNBOARD PRESTIGE	230	76 cm	12.94
3	CROWNBOARD PRESTIGE	230	85 cm	3.36
4	CROWNBOARD PRESTIGE	230	96 cm	27.45
5	CROWNBOARD PRESTIGE	230	162.5 cm	92.76
6	CROWNBOARD PRESTIGE	230	202 cm	10.51
7	CROWNBOARD PRESTIGE	260	122.8 cm	60.81
8	CROWNBOARD PRESTIGE	285	99.2 cm	9.63
9	CROWNBOARD PRESTIGE	285	104 cm	8.82
10	CROWNBOARD PRESTIGE	285	115 cm	20.70
11	CROWNBOARD PRESTIGE	285	120 cm	1.92
12	CROWNBOARD PRESTIGE	285	129 cm	14.98
13	CROWNBOARD PRESTIGE	285	133.2 cm	4.32
14	CROWNBOARD PRESTIGE	285	140.6 cm	19.63
15	CROWNBOARD PRESTIGE	285	144.8 cm	8.74
16	CROWNBOARD PRESTIGE	285	146 cm	2.92
	CLC/C DUPLEX			35.29 MT
17	CLC/C DUPLEX	200	157.1 cm	1.82
18	CLC/C DUPLEX	278	153.6 cm	1.92
19	CLC/C DUPLEX	282	153 cm	15.67
20	CLC/C DUPLEX	282	153.5 cm	7.50
21	CLC/C DUPLEX	282	161.5 cm	8.38
	CLC/M DUPLEX			12.26 MT
22	CLC/M DUPLEX	221	144.5 cm	1.90
23	CLC/M DUPLEX	221	157.1 cm	6.26

#	QUALITY	GSM	SIZE (CM)	TONS
24	CLC/M DUPLEX	221	157.4 cm	4.09
	LIQUID LC			9.26 MT
25	LIQUID LC	240	163 cm	9.26
	CLC/C DUPLEX 290 MN			8.23 MT
26	CLC/C DUPLEX 290 MN	282	161.8 cm	8.23
	DUPLEX			7.24 MT
27	DUPLEX	135	130.6 cm	5.45
28	DUPLEX	139	129.6 cm	1.80
	CLC/C DUPLEX 150 MN			6.59 MT
29	CLC/C DUPLEX 150 MN	242	157.1 cm	6.59
	PURE BOARD			2.56 MT
30	PURE BOARD	185	97 cm	1.31
31	PURE BOARD	295	107 cm	1.25
	UNBLEACHED MG KRAFT			1.21 MT
32	UNBLEACHED MG KRAFT	42	136 cm	1.21
	SHEETS			4.88 MT
	CROWNBOARD PRESTIGE			1.83 MT
33	CROWNBOARD PRESTIGE	315	79.1 x 119.9 cm	1.44
34	CROWNBOARD PRESTIGE	400	68.1 x 92.2 cm	0.39
	CROWNBOARD CRAFT			3.05 MT
35	CROWNBOARD CRAFT	245	102.8 x 54.5 cm	0.30
36	CROWNBOARD CRAFT	265	60.7 x 75.3 cm	0.34
37	CROWNBOARD CRAFT	265	66.2 x 76.4 cm	0.39
38	CROWNBOARD CRAFT	345	82.4 x 57 cm	0.35
39	CROWNBOARD CRAFT	460	48.7 x 81.2 cm	0.53
40	CROWNBOARD CRAFT	460	82.7 x 54.7 cm	0.25
41	CROWNBOARD CRAFT	460	86.6 x 130 cm	0.88
TOTAL				**394.34**

This offer is subject to prior sale and stock confirmation. Prices and availability may change without notice.

Billerud CrownBoard Prestige

Production units: Frövi & Gruvön

Technical guideline
Imperial



Fully coated top side
Top: Bleached chemical pulp
Middle: Bleached CTMP reinforced with bleached chemical pulp
Bottom: Bleached chemical pulp
Light coated reverse side

Product description

CrownBoard Prestige® combines strength and printability in a unique way. The strong, stiff and tough board gives top performance throughout the product range. A high-white, coated surface offers outstanding print results giving the packaging a sophisticated visual appearance that enhances the contents. CrownBoard Prestige® is made out of 100% primary wood fibres. Produced in Sweden.

Certification

Our mills are certified in accordance with ISO 9001, ISO 14001, ISO 50001, FSSC 22000. PEFC CoC and FSC® CoC available. The product is in compliance with FDA and BfR regarding food contact applications, for restriction and limitations ask your Billerud sales representative. Recyclable in accordance with EN 13430:2004 and EN 13431:2004.

Property	Unit	Method							
Caliper points	**pt**		**11.4**	**12.0**	**14.0**	**15.9**	**17.9**	**19.9**	**21.9**	**23.8**
Nominal basis weight	**lb/3000 sq.ft**		**135**	**144**	**163**	**178**	**194**	**209**	**227**	**246**
Bending stiffness, taber 15º MD	mNm		8.3	10.2	14.5	20.8	26.6	31.4	40.6	51.7
Bending stiffness, taber 15º CD	mNm		4.0	4.9	7.2	11.1	14.0	17.1	22.2	28.0
Bending stiffness, taber MD	gcm		85	104	148	212	271	320	414	527
Bending stiffness, taber CD	gcm		40	50	74	113	143	175	227	286
Z-strength	psi		51	51	51	51	51	51	51	51
Tearing resistance	gf		275	316	387	433	489	561	642	744
GE Brightness TS	%	TAPPI T 452 *	92	92	92	92	92	92	92	92
GE Brightness RS	%	TAPPI T 452 *	87	87	87	87	87	87	87	87
CIE Whiteness TS	%	ISO 11475	125	125	125	125	125	125	125	125
CIE Whiteness RS	%	ISO 11475	102	102	102	102	102	102	102	102
Roughness PPS-10 TS	microns	ISO 8791-4	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Sheffield RS		TAPPI T 538 *	180	180	180	180	180	180	180	180
Moisture content	%	ISO 287	7.3	7.4	7.4	7.5	7.7	7.9	8.1	8.3

- Issued on the 17th of October 2019. Revised on the 13h of August 2024.
- Values may be subject to change without notice.
- This summary sheet reflects only nominal values. For full product information see Billerud CrownBoard Prestige Technical Data Sheet revised on the 13th of August 2024
- Billerud production units are certified according to FSC® and PEFC Chain of Custody standards, which both demonstrate traceability. Licence codes: FSC-C004906, FSC-C108771, PEFC/05-33-135 and PEFC/05-33-114
- FSC® and PEFC certified products are available on request.

*) Indicative value