













2-dimensional vertex model \Rightarrow simulating epithelial tissue

```
In[ ]:= LaunchKernels[]  
ParallelTable[$KernelID, {i, $KernelCount}]
```

```
Out[ ]:= {KernelObject[  Name: local  
KernelID: 1 ], KernelObject[  Name: local  
KernelID: 2 ],  
  
KernelObject[  Name: local  
KernelID: 3 ], KernelObject[  Name: local  
KernelID: 4 ],  
  
KernelObject[  Name: local  
KernelID: 5 ], KernelObject[  Name: local  
KernelID: 6 ]}
```

```
Out[ ]:= {6, 5, 4, 3, 2, 1}
```

geometrical f(x)s

```
In[ ]:= (*get vertex in the list by ccw order*)  
Clear[getCounterClockwise];  
getCounterClockwise[vertex_, vertices_] := Block[{pos, v},  
  pos = First@@Position[vertices, vertex];  
  If[pos == Length[vertices], pos = 1, pos += 1];  
  vertices[[pos]]  
];
```

```
In[ ]:= (*get vertex in the list by cw order*)  
Clear[getClockwise];  
getClockwise[vertex_, vertices_] := Block[{ls, pos},  
  pos = First@@Position[vertices, vertex];  
  If[pos == 1, pos = Length[vertices], pos -= 1];  
  vertices[[pos]]  
];
```

```
In[ ]:= getCounterClockwise[{xi, yi}, {{xi-1, yi-1}, {xi, yi}, {xi+1, yi+1}, d, e}]
```

```
Out[ ]:= {x1+i, y1+i}
```

```
In[ ]:= getClockwise[{xi, yi}, {{xi-1, yi-1}, {xi, yi}, {xi+1, yi+1}, d, e}]
```

```
Out[ ]:= {x-1+i, y-1+i}
```

```
In[ ]:= Clear[areaOfPolygon];  
areaOfPolygon[cells_ /; Head[cells] === Association] :=  
  Parallelize[Map[Area@*Polygon, cells]];
```

```

In[ ]:= Clear[areaPolygon];
areaPolygon[vertices_] := Block[{edges},
  edges = Partition[vertices, 2, 1, 1];
  0.5 Abs@Total[(#[[1, 1]] * #[[2, 2]]) - (#[[2, 1]] * #[[1, 2]]) & /@ edges]
]

```

```

In[ ]:= Clear[perimeterOfPolygon];
perimeterOfPolygon[cells_ /; Head[cells] === Association] :=
  Parallelize[(Perimeter@*Polygon) /@ cells];

```

```

In[ ]:= Clear[perimeterPolygon];
perimeterPolygon[vertices_] := Block[{edges},
  edges = Partition[vertices, 2, 1, 1];
  Total[Apply[EuclideanDistance] /@ edges]
]

```

```

In[ ]:= Clear[centroidPolygon];
centroidPolygon[vertices_] := Mean[vertices]

```

```

In[ ]:= (*counterclockwise polygonQ*)
Block[{signedarea = 0, j, vertlen = 5},
  Do[
    j = Mod[i, vertlen] + 1;
    signedarea += (xi yj - xj yi),
    {i, vertlen}];
  Echo[ $\frac{1}{2}$  (signedarea)]
];

$$\frac{1}{2} (-x_2 y_1 + x_5 y_1 + x_1 y_2 - x_3 y_2 + x_2 y_3 - x_4 y_3 + x_3 y_4 - x_5 y_4 - x_1 y_5 + x_4 y_5)$$


```

```

In[ ]:= Clear[polyCounterClockwiseQ];
polyCounterClockwiseQ[poly_] := Block[{area = 0, j, vertLength = Length[poly]},
  Do[
    j = Mod[i, vertLength] + 1;
    area += poly[[i, 1]] * poly[[j, 2]];
    area -= poly[[j, 1]] * poly[[i, 2]],
    {i, vertLength}
  ];
  (area / 2.) > 0
]

```

```

In[ ]:= (*Clear [sortCC];
sortCC[polyinds_, indTopts_, ptsToInds_] := Block[{cent, poly},
  poly = Lookup[indTopts, polyinds];
  Lookup[ptsToInds,
    DeleteDuplicates@
      Flatten[MeshPrimitives[ConvexHullMesh[poly], 1] /. Line -> Sequence, 1]
  ]
];*)

```

In[]:= (*sort points for a convex polygon in counter-clockwise direction*)

```

In[ ]:= Clear[sortPointsCC];
sortPointsCC[polyinds_, indTopts_, ptsToInds_] :=
  Block[{cent, ordering, polyPoints},
    polyPoints = Lookup[indTopts, polyinds];
    cent = Mean[polyPoints];
    ordering = Ordering[ArcTan[#[[1]], #[[2]]] & @ (# - cent) & /@ polyPoints];
    Lookup[ptsToInds, Part[polyPoints, ordering]]
  ]

```

```

In[ ]:= outeredges[indToPtsAssoc_, localtopology_] := Block[{k, temp, tcells, assoc},
  Reap[
    Scan[(k = #; temp = localtopology[k];
      tcells = temp[[2]];
      If[tcells != {},
        MapAt[Sow@Cases[Partition[#, 2, 1,
          1], OrderlessPatternSequence[{x : indToPtsAssoc[k], y : _}] ->
            {x, y}] &, temp[[1]], {Key[#]} & /@ tcells];
      ] &, Keys@indToPtsAssoc]
  ] [[2]] // Flatten[#, 2] &
];

```

mesh restructuring operations

simulation domain

```

In[ ]:= xLim = yLim = {-1, 1};
D = Rectangle[{First@xLim, First@yLim}, {Last@xLim, Last@yLim}];

```

local topology

```

In[ ]:= ClearAll[periodicRules, transformRules];
periodicRules::Information =
  "shift the points outside the simulation domain to inside the domain";
transformRules::Information =
  "vector that shifts the point outside the simulation domain back inside";
With[{xlim1 = xLim[[1]], xlim2 = xLim[[2]],
      ylim1 = yLim[[1]], ylim2 = yLim[[2]], dstep = 2},
  periodicRules = Dispatch[{
    {x_ /; x ≥ xlim2, y_ /; y ≤ ylim1} => SetPrecision[{x - dstep, y + dstep}, 10],
    {x_ /; x ≥ xlim2, y_ /; ylim1 < y < ylim2} => SetPrecision[{x - dstep, y}, 10],
    {x_ /; xlim1 < x < xlim2, y_ /; y ≤ ylim1} => SetPrecision[{x, y + dstep}, 10],
    {x_ /; x ≤ xlim1, y_ /; y ≤ ylim1} => SetPrecision[{x + dstep, y + dstep}, 10],
    {x_ /; x ≤ xlim1, y_ /; ylim1 < y < ylim2} => SetPrecision[{x + dstep, y}, 10],
    {x_ /; x ≤ xlim1, y_ /; y ≥ ylim2} => SetPrecision[{x + dstep, y - dstep}, 10],
    {x_ /; xlim1 < x < xlim2, y_ /; y ≥ ylim2} => SetPrecision[{x, y - dstep}, 10],
    {x_ /; x ≥ xlim2, y_ /; y ≥ ylim2} => SetPrecision[{x - dstep, y - dstep}, 10]
  }];

  transformRules = Dispatch[{
    {x_ /; x ≥ xlim2, y_ /; y ≤ ylim1} => {-dstep, dstep} ~SetPrecision~10,
    {x_ /; x ≥ xlim2, y_ /; ylim1 < y < ylim2} => {-dstep, 0} ~SetPrecision~10,
    {x_ /; xlim1 < x < xlim2, y_ /; y ≤ ylim1} => {0, dstep} ~SetPrecision~10,
    {x_ /; x ≤ xlim1, y_ /; y ≤ ylim1} => {dstep, dstep} ~SetPrecision~10,
    {x_ /; x ≤ xlim1, y_ /; ylim1 < y < ylim2} => {dstep, 0} ~SetPrecision~10,
    {x_ /; x ≤ xlim1, y_ /; y ≥ ylim2} => {dstep, -dstep} ~SetPrecision~10,
    {x_ /; xlim1 < x < xlim2, y_ /; y ≥ ylim2} => {0, -dstep} ~SetPrecision~10,
    {x_ /; x ≥ xlim2, y_ /; y ≥ ylim2} => {-dstep, -dstep} ~SetPrecision~10,
    {___Real} => {0, 0} ~SetPrecision~10}];
];

```

```

In[ ]:= Clear@getLocalTopology;
getLocalTopology[ptsToIndAssoc_, indToPtsAssoc_, vertexToCell_,
  cellVertexGrouping_, wrappedMat_, faceListCoords_] :=
  Block[{localTopology = <| |>, wrappedcellList = {}, vertcellconns,
    localcellunion, v, wrappedcellpos, vertcs = vertices, r11, r12,
    transVector, wrappedcellCoords, wrappedcells, vertOutofBounds,
    shiftedPt, transvecList = {}, $faceListCoords = faceListCoords,
    vertexQ, boundsCheck, rules, extractcellkeys, vertind,
    cellsconnected, wrappedcellsrem},
    vertexQ = MatchQ[vertices, {__?NumberQ}];
    If[vertexQ,
      (vertcellconns =
        AssociationThread[{#}, {vertexToCell[ptsToIndAssoc[#]]}] &@vertices;
        vertcs = {vertices};
        localcellunion = Flatten[Values@vertcellconns]),
      (vertcellconns = AssociationThread[#,
        Lookup[vertexToCell, Lookup[ptsToIndAssoc, #]]] &@vertices;
        localcellunion = Union@Flatten[Values@vertcellconns])
    ];
    If[localcellunion ≠ {},

```

```

AppendTo[localtopology,
  Thread[localcellunion →
    Map[Lookup[indToPtsAssoc, #] &, cellVertexGrouping /@ localcellunion, {2}]]
];
(* condition to be an internal edge: both vertices should have 3 neighbours *)
(* if a vertex has 3 cells in its local neighbourhood then the entire
  network topology about the vertex is known → no wrapping required *)
(* else we need to wrap around the vertex because other cells
  are connected to it → periodic boundary conditions *)
With[{vert = #},
  vertind = ptsToIndAssoc[vert];
  cellsconnected = vertexToCell[vertind];
  If[Length[cellsconnected] ≠ 3,
    If[(D~RegionMember~vert),
      v = vert;
      With[{x = v[[1]], y = v[[2]]}, boundsCheck =
        (x == xLim[[1]] || x == xLim[[2]] || y == yLim[[1]] || y == yLim[[2]])];
      extractcellkeys = If[boundsCheck,
        {r11, r12} = {v, v /. periodicRules};
        rules = Block[{x$},
          With[{r = r11, s = r12},
            DeleteDuplicates[
              HoldPattern[SameQ[x$, r]] || HoldPattern[SameQ[x$, s]]]
          ]
        ];
      Position@@
        With[{rule = rules}, Hold[wrappedMat, x_ /; ReleaseHold@rule, {2}]],
      Position[wrappedMat, x_ /; SameQ[x, v], {2}]
    ];
    (* find cell indices that are attached to the vertex in wrappedMat *)
    wrappedcellpos = DeleteDuplicatesBy[
      Cases[extractcellkeys,
        {Key[p : Except[Alternatives@@Join[localcellunion,
          Flatten@wrappedcellList]]], y__} ⇒ {p, y}],
      First];
    (*wrappedcellpos = wrappedcellpos/.
      {Alternatives@@Flatten[wrappedcellList],__} ⇒ Sequence[];*)
    (* if a wrapped cell has not been considered earlier (i.e. is new)
      then we translate it to the position of the vertex *)
    If[wrappedcellpos ≠ {},
      If[vertexQ,
        transVector = SetPrecision[(v - Extract[$faceListCoords,
          Replace[#, {p_, q__} ⇒ {Key[p], q}]]] & /@ wrappedcellpos, 10],
        (* call to function is enquiring an edge and not a vertex*)
        transVector = SetPrecision[(v - Extract[$faceListCoords,
          Replace[#, {p_, q__} ⇒ {Key[p], q}]]] & /@ wrappedcellpos, 10]
      ];
    wrappedcellCoords = MapThread[#1 → Map[Function[x,
      SetPrecision[x + #2, 10]], $faceListCoords[[Key@#1]], {1}] &,
      {First /@ wrappedcellpos, transVector}];
    wrappedcells = Keys@wrappedcellCoords;
    AppendTo[wrappedcellList, Flatten@wrappedcells];
    AppendTo[transvecList, transVector];
    AppendTo[localtopology, wrappedcellCoords];

```

```

],
(* the else clause: vertex is out of bounds *)
vertOutOfBounds = vert;
(* translate the vertex back into mesh *)
transVector = vertOutOfBounds /. transformRules;
shiftedPt = SetPrecision[vertOutOfBounds + transVector, 10];
(* ----- CORE B ----- *)
(* find which cells the
   shifted vertex is a part of in the wrapped matrix *)
wrappedcells = Complement[
  Union@Cases[Position[wrappedMat, x_ /; SameQ[x, shiftedPt], {2}],
    x_Key => Sequence @@ x, {2}] /.
    Alternatives @@ localcellunion -> Sequence[],
  Flatten@wrappedcellList];
(*forming local topology now that we know the wrapped cells *)
If[wrappedcells != {},
  AppendTo[wrappedcellList, Flatten@wrappedcells];
  wrappedcellCoords = AssociationThread[wrappedcells,
    Map[Lookup[indToPtsAssoc, #] &,
      cellVertexGrouping[#] & /@ wrappedcells, {1}]];
  With[{opt = (vertOutOfBounds /. periodicRules)},
    Block[{pos, vertref, transvec},
      Do[
        With[{cellcoords = wrappedcellCoords[cell]},
          pos = FirstPosition[cellcoords /. periodicRules, opt];
          vertref = Extract[cellcoords, pos];
          transvec = SetPrecision[vertOutOfBounds - vertref, 10];
          AppendTo[transvecList, transvec];
          AppendTo[localtopology,
            cell -> Map[SetPrecision[# + transvec, 10] &, cellcoords]];
        ], {cell, wrappedcells}
      ];
    ];
];
(* to detect wrapped cells not detected by CORE B*)
(* ----- CORE C ----- *)
Block[{pos, celllocs, ls, transvec, assoc, tvecLs = {}, ckey},
  ls = Union@Flatten@Join[cellsconnected, wrappedcells];
  If[Length[ls] != 3,
    pos = Position[$faceListCoords, x_ /; SameQ[x, shiftedPt], {2}];
    celllocs = DeleteDuplicatesBy[Cases[pos, Except[{Key[Alternatives @@ ls],
      __}]], First] /. {Key[x_], z__} -> {Key[x], {z}}];
  If[celllocs != {},
    celllocs = Transpose@celllocs;
    assoc = <|
      MapThread[
        (transvec = SetPrecision[vertOutOfBounds -
          Extract[$faceListCoords[Sequence @@ #1], #2], 10];
          ckey = Identity @@ #1;
          AppendTo[tvecLs, transvec];
          ckey -> Map[SetPrecision[Lookup[indToPtsAssoc, #] + transvec,
            10] &, cellVertexGrouping[Sequence @@ #1], {1}]
        ) &, celllocs]
      |>;
    AppendTo[localtopology, assoc];

```

```

        AppendTo[wrappedcellList, Keys@assoc];
        AppendTo[transvecList, tvecLs];
    ];
];
];
];
];
];
] & /@ vertcs;
transvecList = Which[
    MatchQ[transvecList, {{{__?NumberQ}}}], First[transvecList],
    MatchQ[transvecList, {{{__?NumberQ} ..}}], transvecList,
    True, transvecList /. {x___, {p : {__?NumberQ} ..}, y___} => {x, p, y}
];
{localtopology, Flatten@wrappedcellList, transvecList}
];

```

T1 transition

In[]:= (*find edge function*)

find edges

```

In[ ]:= Clear@edgesforT1;
edgesforT1[edgeLs_, indToPts_, threshLength_ : 0.0015] :=
    Block[{edges, dist, sel, filt, b, cand, sameedg2Q, del},
        edges = Lookup[indToPts, #] & /@ edgeLs;
        dist = EuclideanDistance@@# & /@ edges;
        sel = Pick[edges, Thread[dist ≤ threshLength], True];
        If[Length[sel] == 1,
            Nothing,
            filt = sel /. periodicRules;
            b = MapThread[SameQ, {filt, sel}];
            cand = Pick[filt, b, False];
            sameedg2Q = MemberQ[sel, {OrderlessPatternSequence@@#}] & /@ cand;
            del = {OrderlessPatternSequence@@@ Pick[cand, sameedg2Q]};
            If[Length[cand] > 1, del = Alternatives@@del];
            sel = DeleteCases[sel, {del}]
        ];
        sel
    ];

```

T1

In[]:= bagged = CreateDataStructure["DynamicArray"]

Out[]:= DataStructure[ Type:DynamicArray
Length:0]

```

In[ ]:= Clear@T1transitionFn;
T1transitionFn[edges_, indToPtsAssoc_, ptsToIndAssoc_, vertexToCellG_,
    cellToVertexG_, wrappedMat_, facelistCoords_, dSep_ : 0.004] :=

```

```

Block[{edgeind, connectedcellKeys, edge, newpts, cellvertices, pos, cellpolys,
  memF, keyscellP, selcellKeys, ptToCell, newptsindices, indToPts = indToPtsAssoc,
  ptsToInds = ptsToIndAssoc, PtIndToCell, keysToMap, f1, otherkeys, f2,
  bag = bagged, vertToCellG = vertexToCellG, cellToVertG = cellToVertexG, testpts,
  localtopology, translCells, transVector, edgepts, celltopo, polysharingEdge,
  ls, cs, cc, ccw, trimmedtopo, ordering, edgeordered, topotransl, newtransvert,
  findEdges, $wrappedMat = wrappedMat, $faceListCoords = faceListCoords,
  cellToVertGC, dropinds, bagopen, maxlab, mm, ll},
findEdges = edgesforT1[edges, indToPts];
(* finding all possible edges for T1 transition *)
If[findEdges != {},
  (*run if there are any edges for T1*)
  Scan[
    {edge = #;
      cellToVertGC = cellToVertG;
      edgeind = Lookup[ptsToInds, edge];
      If[ContainsAll[Keys[indToPts], edgeind],
        (* should be an edge not
           connected to an edge that has already undergone a T1 *)
        (* let us get the local network topology *)
        {localtopology, translCells, transVector} =
          getLocalTopology[ptsToInds, indToPts, vertToCellG,
            cellToVertG, $wrappedMat, $faceListCoords][#] &[edge];
        If[! DuplicateFreeQ[translCells],
          {translCells, transVector} =
            DeleteDuplicates[Transpose[{translCells, transVector}]]^T
        ];
        connectedcellKeys = Keys@localtopology;
        celltopo = Values@localtopology;
        newpts = With[{midPt = Mean@edge},
          SetPrecision[midPt + dSep Normalize[(# - midPt)], 10] & /@
            Flatten[RotationTransform[- $\frac{\pi}{2}$ , midPt] /@ {edge}, 1]
        ];
        testpts = With[{midPt = Mean@edge},
          midPt + 0.00001 Normalize[(# - midPt)] & /@ newpts];
        (*plt1=Graphics[{FaceForm[LightGray],EdgeForm[{Thick,Black}],
          Polygon/@celltopo},{Red,Line@edge,Orange,
          Point@newpts,Green,Point@testpts}},ImageSize->Tiny];
        Print@plt1;*)
        (*which cells contain both vertices*)
        pos = Position[celltopo, {OrderlessPatternSequence[
          ___, First[edge], ___, Last[edge], ___]}, {1}];
        polysharingEdge = Extract[celltopo, pos];
        (* the edge should not be part of any  $\Delta$  *)
        bagopen = Union@* Flatten@* Normal@bag;
        (*Print[Show[Graphics[{Polygon/@Values@$faceListCoords}],plt1]];*)
        mm = edge /. periodicRules;
        If[(AllTrue[polysharingEdge, Length[#] != 3 &]) &&
          ContainsNone[edgeind, bagopen] && ContainsNone[mm, bagopen],
          cellvertices = celltopo;

```



```

cellpolys = Polygon /@ cellvertices;
memF = Function[x, RegionMember@*DiscretizeRegion@x, Listable] [
  Extract[cellpolys, pos]];
keyscellP = Extract[connectedcellKeys, pos];
selcellKeys = Thread[keyscellP → memF];
ptToCell = Quiet[#, First @@ Select[selcellKeys, Function[x,
  Last[x][#]]] & /@ testpts /. HoldPattern[_ → First[]] → Nothing];
(* testpt to cell *)
ptToCell = ptToCell /. Thread[testpts → newpts];
newptsindices = Range[#+1, #+2] &[Max@Keys@indToPts];
KeyDropFrom[indToPts, edgeind];
AppendTo[indToPts, Thread[newptsindices → newpts]];

ll = Lookup[ptsToInds, mm];
If[ll ≠ edge, bag["Append", ll]];

ptsToInds = AssociationMap[Reverse, indToPts];
bag["Append", edgeind];
PtIndToCell = MapAt[ptsToInds, ptToCell, {All, 1}] /. Rule → List;
(*index to cell*)
keysToMap = Map[{Lookup[indToPts, #][1]], Key@#[2]} &, PtIndToCell];
f1 = Fold[
  MapAt[Function[x, DeleteDuplicates@Replace[x, (Alternatives @@ edge) →
    #2[1]], {1}]], #1, #2[[-1]]] &, localtopology, keysToMap];
otherkeys = List@*Key /@ Complement[connectedcellKeys, keyscellP];

ls = Lookup[localtopology, First @@ otherkeys];
cs = FirstCase[ls, Alternatives @@ edge];
cc = getClockwise[cs, ls];
ccw = getCounterClockwise[cs, ls];
trimmedtopo =
  KeyDrop[localtopology, connectedcellKeys ~ Complement ~ keyscellP];
ordering = {
  FirstCase[Position[trimmedtopo, cc],
    x : {Key[First@keyscellP], _} | {Key[Last@keyscellP], _} → First @@ x],
  FirstCase[Position[trimmedtopo, ccw],
    x : {Key[First@keyscellP], _} | {Key[Last@keyscellP], _} → First @@ x]
];
edgeordered = ordering /. Reverse[ptToCell, 2];
f2 = MapAt[Replace[#, Alternatives @@ edge → Splice[edgeordered], {1}] &,
  f1, First@otherkeys];
f2 = MapAt[Replace[#, Alternatives @@ edge → Splice[Reverse[edgeordered]],
  {1}] &, f2, Last@otherkeys];

(*plt2=Values@f2//Map[Polygon]//Graphics[
  {FaceForm[LightGray], EdgeForm[{Thin, Red}], #}, ImageSize→Tiny]&*)
(* once we make the transition, we translate the cell back and
  add the shifted vertex into the indtopts and ptstoinds *)
If[translCells ≠ {},
  f2 =
    Fold[MapAt[Function[x, Function[y, SetPrecision[y - #2[[2]], 10]] /@ x],
      #1, {#2[[1]]}] &, f2, Thread[{Key /@ translCells, transVector}]];
  newtransvert = Complement[Flatten[Values@f2, 1],
    Values@indToPts, SameTest → (#1 == #2 &)];
  If[newtransvert ≠ {},

```

```

newptsindices =
  Range[#+ 1, # + Length@newtransvert] &[Max[Keys@indToPts]];
AppendTo[indToPts, Thread[newptsindices → newtransvert]];
AppendTo[ptsToInds, Thread[newtransvert → newptsindices]];
];
];
(*plt3=Values@f2//Map[Polygon]//Graphics[
  {FaceForm[LightGray],EdgeForm[{Thin,Red}],#},ImageSize→Tiny]&*)
f2 = Lookup[ptsToInds, #] & /@ f2;
AppendTo[cellToVertG, f2];
];

cellToVertG = KeySort@cellToVertG;
dropinds =
  Flatten@Map[Complement[cellToVertGC[#], cellToVertG[#]] &, translCells];
KeyDropFrom[indToPts, dropinds];
ptsToInds = AssociationMap[Reverse, indToPts];
vertToCellG = KeySort@GroupBy[Flatten[
  (Reverse[#, 2] &) @* Thread /@ Normal@cellToVertG], First → Last];
$faceListCoords = Lookup[indToPts, #] & /@ cellToVertG;
$wrappedMat = Map[# /. periodicRules &, $faceListCoords];
(*Print@{plt1,plt2};*)
]] &, findEdges]
];
bagged["DropAll"];
{indToPts, vertToCellG, cellToVertG, $wrappedMat, $faceListCoords}
];

```

T2 transition

find cells for T2

```

In[ ]:= Clear@cellsforT2;
cellsforT2[areaAssoc_, cellVertexG_, thresh_ : 0.1] := Block[{keys, ls, inds},
  keys = Keys@Select[areaAssoc, # < thresh &];
  ls = Lookup[cellVertexG, keys];
  inds = Flatten@Position[ls, x_ /; (Length[x] == 3), {1}];
  (* cell_edges == 3 *)
  If[inds ≠ {}, keys[[inds]], {}] (*cell inds*)
];

```

T2

```

In[ ]:= Clear@T2TransitionFn;
T2TransitionFn[removeelem_, indToPtsAssoc_, ptsToIndAssoc_,
  vertexCellAssoc_, cellVertexGrouping_, wrappedMat_, faceListCoords_] :=
Block[{assoc, translC, transVec, ptsToInds = ptsToIndAssoc, indToPts = indToPtsAssoc,
  vertCellAssoc = vertexCellAssoc, cvG = cellVertexGrouping,
  $wrappedMat = wrappedMat, $faceListCoords = faceListCoords, cellkey,

```

```

res, mergedtopo, vertinds, vertpts, mean, ruletrans, changedtopo,
transtopo, ckeys, pos, newpt, maxlab, newind, vertinddrop, oldptind, re},
re = Replace[removeelem, x_Integer -> {x}];
If[removeelem != {},
Scan[
  (cellkey = #;
  {assoc, translC, transVec} =
    getLocalTopology[ptsToInds, indToPts, vertCellAssoc, cvG, $wrappedMat,
      $faceListCoords][#] & /@ Lookup[indToPts, cvG[cellkey]] // Transpose;
  res = DeleteDuplicates[Flatten[{translC, transVec}, {3, 2}] /.
    {p___, x: {}, q___} -> {p, q}];
  mergedtopo = KeySort[Join@@assoc];
  vertinds = cvG[cellkey];
  vertpts = Lookup[indToPts, vertinds];
  mean = SetPrecision[Mean@vertpts, 10];
  ruletrans = Flatten[Thread[{# -> mean}] & /@ vertpts];
  (*Print[Values@mergedtopo//Graphics[{FaceForm[LightBlue],
    EdgeForm[Black], Map[Polygon][#], ImageSize->Small]&];*)
  If[res == {}, KeyDropFrom[mergedtopo, cellkey]];
  changedtopo = (mergedtopo /. ruletrans);
  (*Print[Values@changedtopo//Graphics[{FaceForm[LightBlue],
    EdgeForm[Black], Map[Polygon][#], ImageSize->Small]&];*)
  If[res != {},
    transtopo = Fold[MapAt[Function[x, Function[y, SetPrecision[y - #2[[-1]],
      10]] /@ x], #1, Key@#2[[1]]] &, changedtopo, res];
    ckeys = res[[All, 1]];
    pos = Cases[Position[<|Thread[ckey -> Lookup[mergedtopo, ckeys]]|>,
      Alternatives@@vertpts], {Key[Alternatives@@ckey], _}];
    newpt = DeleteDuplicates@Extract[transtopo, pos];
    oldptind = Extract[<|Thread[ckey -> Lookup[cvG, ckeys]]|>, pos];
    newpt = Join[{mean}, newpt];
    maxlab = Max[Keys@indToPts];
    newind = Range[maxlab + 1, maxlab + Length[newpt]];
    vertinddrop = Join[oldptind, vertinds];
    AppendTo[indToPts, Thread[newind -> newpt]],
    newind = Max[Keys@indToPts] + 1;
    newpt = mean;
    vertinddrop = vertinds;
    AppendTo[indToPts, newind -> newpt];
  ];
ptsToInds = AssociationMap[Reverse, indToPts];
If[res != {},
  AppendTo[cvG, DeleteDuplicates@Lookup[ptsToInds, #] & /@ transtopo],
  AppendTo[cvG, DeleteDuplicates@Lookup[ptsToInds, #] & /@ changedtopo]
];
cvG = KeySort@cvG;
KeyDropFrom[indToPts, vertinddrop];
ptsToInds = AssociationMap[Reverse, indToPts];
KeyDropFrom[cvG, cellkey];
vertCellAssoc = GroupBy[Flatten[
  (Reverse[#, 2] &) @* Thread /@ Normal@cvG], First -> Last] // KeySort;
$wrappedMat = AssociationThread[Keys[cvG] -> Map[
  Lookup[indToPts, #] /. periodicRules &, Lookup[cvG, Keys[cvG]], {2}]];
$faceListCoords = Map[Lookup[indToPts, #] &, cvG, {2}]
(*$wrappedMat = Map[# /. periodicRules &, $faceListCoords] *) &, re];

```

```
];
(*Print@Graphics[{EdgeForm[Black],FaceForm[LightBlue],
  Polygon/@Values@Map[Lookup[indToPts,#]&,cvG,{2}]],ImageSize→Medium];*)
{indToPts, ptsToInds, vertCellAssoc, cvG, $wrappedMat, $faceListCoords}
];
```

cell division

Difference from Farahdifar's paper: in his article he dilates the cells before dividing them. Here I randomly select a cell and divide it into two. This does not really matter

```
In[ ]:= Clear[selectDivCells];
selectDivCells[areaPolygon_, areathresh_ : 2.2, thresh_ : 0.0025] :=
Block[{candidates, pos},
  candidates = Normal@Select[areaPolygon / Mean[areaPolygon], # > areathresh &];
  pos = Position[0.1 RandomReal[1, Length@candidates], x_ /; x < thresh];
  Keys@Extract[candidates, pos]
];
```

```
In[ ]:= (* division events more random *)
```

```
In[ ]:= Clear[pickcellsDiv];
pickcellsDiv[cellToVertG_, areaAssoc_] := Block[{pickcells, selcells, pos},
  pickcells = Keys@Select[Pick[areaAssoc,
    Thread[RandomReal[{0, 1}, Length[areaAssoc]] < 0.001], True], # > 0.005 &];
  pos = Position[Lookup[cellToVertG, pickcells], x_ /; Length[x] > 3, {1}];
  Extract[pickcells, pos]
];
```

```
In[ ]:= Clear[cellDivision, i];
cellDivision[polygonind_, indToPoints_, areaAssoc_, perimAssoc_, cellToVertG_] :=
Block[{x, y, num, matrix, xx, xy, yy, eigvals, eigVecs, maxeigpos, cent, edges, edgesL,
  intersects, intersectionPts, posIntersections, repPart, α, β, polygonPts,
  newkeys = Range[# + 1, # + 2] & [Max@Keys[indToPoints]], newPtToInds, indtoPtAssoc =
  indToPoints, ptToIndAssoc, edgeinds, contour, poly1, poly2, res, seq,
  newcells = Range[# + 1, # + 2] & [Max@Keys[areaAssoc]], CVG = cellToVertG,
  addcellsRule, polygonPtsInds, VCG, polygonptsTrans},
VCG = GroupBy[Flatten[(Reverse[# , 2] &) @* Thread /@ Normal@CVG], First → Last];
polygonPtsInds = CVG[polygonind];
num = Length@polygonPtsInds;
ptToIndAssoc = AssociationMap[Reverse, indToPoints];
polygonPts = Lookup[indToPoints, polygonPtsInds];
polygonptsTrans = TranslationTransform[-Mean[polygonPts]] @ polygonPts;
Evaluate[Table[{xi, yi}, {i, num + 1}]] =
  Append[polygonptsTrans, First@polygonptsTrans];


$$I_{xx} = \left( \frac{1}{12} \right) \sum_{i=1}^{\text{num}} (x_i y_{i+1} - x_{i+1} y_i) (y_i^2 + y_i y_{i+1} + y_{i+1}^2);$$



$$I_{yy} = \left( \frac{1}{12} \right) \sum_{i=1}^{\text{num}} (x_i y_{i+1} - x_{i+1} y_i) (x_i^2 + x_i x_{i+1} + x_{i+1}^2);$$

```

```


$$I_{xy} = \left( \frac{1}{24} \right) \sum_{i=1}^{\text{num}} (x_i y_{i+1} - x_{i+1} y_i) (x_i y_{i+1} + 2 x_i y_i + 2 x_{i+1} y_{i+1} + x_{i+1} y_i);$$

Table[{Unevaluated[Subscript[x, j]] = .,
  Unevaluated[Subscript[y, j]] = .}, {j, num + 1}];
matrix =  $\begin{pmatrix} I_{xx} & -I_{xy} \\ -I_{xy} & I_{yy} \end{pmatrix}$ ;
{eigvals, eigVecs} = Eigensystem[matrix];
maxeigpos = Position[eigvals, Max@eigvals];
{edges, edgeinds} = Partition[#, 2, 1, 1] & /@ {polygonPts, polygonPtsInds};
edgesL = Line /@ edges;
cent = centroidPolygon[polygonPts];
intersects = RegionIntersection[
  InfiniteLine[{cent, cent + Extract[eigVecs, maxeigpos][[1]]}], #] & /@ edgesL;
intersectionPts = Cases[intersects, {(_Real | _Integer) ..}, {3}];
newPtToInds = Thread[intersectionPts → newkeys];
posIntersections = Flatten@Position[intersects, _Point, {1}];
MapThread[
  (res = Complement[Intersection @@ Lookup[CVG, #2], {polygonind}];
  If[res ≠ {},
    seq = Partition[CVG[First@res], 2, 1, 1];
    AppendTo[CVG,
      First@res → DeleteDuplicates@
        Flatten@SequenceSplit[seq, {x___, p : {OrderlessPatternSequence[
          #2[[1]], #2[[-1]]}], y___} → {x, Insert[p, #1, 2], y}]]];
  ] &, {newkeys, edgeinds[[posIntersections]]}];

repPart =
  Thread[{Thread[{ReverseSort@posIntersections, 2}], Reverse[intersectionPts]}];
{α, β} = intersectionPts;
AppendTo[ptToIndAssoc, newPtToInds];
AppendTo[indToPtAssoc, Reverse[newPtToInds, 2]];
contour = DeleteDuplicates@
  Flatten[Fold[Insert[#1, #2[[2]], #2[[1]]] &, edges, repPart], 1];
poly1 = Join @@ SequenceCases[contour, {___, α} | {β, ___}];
poly2 = Join @@ SequenceCases[contour, {α, __, β}];
KeyDropFrom[CVG, polygonind];
addcellsRule = Thread[newcells → {poly1, poly2}];
AppendTo[CVG, addcellsRule /. ptToIndAssoc];
{indToPtAssoc, CVG, Append[KeyDrop[areaAssoc, polygonind],
  MapAt[Area@*Polygon, addcellsRule, {All, 2}]],
  Append[KeyDrop[perimAssoc, polygonind],
  MapAt[Perimeter@*Polygon, addcellsRule, {All, 2}]]}
];

```

computing forces

area elasticity

In[]:=

```

FAreaElasticity[indTopts_, localtopo_, areaPolygonAssoc_] :=
Block[{assoc, cellinds, force, vertKeys = Keys[indTopts],
  vertLs, vertex, gc, gcc, diffVec, grad, coeff},
First@*Last@Reap@Do[
  assoc = First@Lookup[localtopo, i];
  cellinds = Keys[assoc];
  force = {0, 0};
  vertex = indTopts[i];
  Do[
    vertLs = assoc[j];
    gcc = getCounterClockwise[vertex, vertLs];
    gc = getClockwise[vertex, vertLs];
    diffVec = SetPrecision[gcc - gc, 10];
    grad = SetPrecision[ $\frac{1}{2} \begin{pmatrix} 0 & 1 \\ -1 & 0 \end{pmatrix} \cdot \text{diffVec}$ , 10];
    coeff = SetPrecision[2 ka (areaPolygonAssoc[j] - A0), 10];
    force += SetPrecision[coeff * grad, 10], {j, cellinds}
  ];
  Sow@force, {i, vertKeys}
]

```

In[]:= $\begin{pmatrix} 0 & 1 \\ -1 & 0 \end{pmatrix} \cdot (\text{getCounterClockwise}[\{x_i, y_i\}, \{\{x_{i-1}, y_{i-1}\}, \{x_i, y_i\}, \{x_{i+1}, y_{i+1}\}\}] - \text{getClockwise}[\{x_i, y_i\}, \{\{x_{i-1}, y_{i-1}\}, \{x_i, y_i\}, \{x_{i+1}, y_{i+1}\}\}]) // \text{MatrixForm}$

Out[]//MatrixForm=

$$\begin{pmatrix} -y_{-1+i} + y_{1+i} \\ x_{-1+i} - x_{1+i} \end{pmatrix}$$

In[]:= $\text{MatrixForm}\left[\begin{pmatrix} 0 & 1 \\ -1 & 0 \end{pmatrix} \cdot (\{x_{i+1}, y_{i+1}\} - \{x_{i-1}, y_{i-1}\})\right]$

Out[]//MatrixForm=

$$\begin{pmatrix} -y_{-1+i} + y_{1+i} \\ x_{-1+i} - x_{1+i} \end{pmatrix}$$

perimeter elasticity

```
In[ ]:= FPerimeterElasticity[indTopts_, localtopo_, periPolygonAssoc_] :=
Block[{assoc, cellinds, force, vertKeys = Keys[indTopts],
  vertLs, vertex, gc, gcc, v1, v2, coeff, grad},
First@*Last@Reap@Do[
  assoc = First@Lookup[localtopo, i];
  cellinds = Keys@assoc;
  force = {0, 0};
  vertex = indTopts[i];
  Do[
    vertLs = assoc[j];
    gc = getClockwise[vertex, vertLs];
    v1 = Normalize[vertex - gc] ~SetPrecision~10;
    gcc = getCounterClockwise[vertex, vertLs];
    v2 = Normalize[gcc - vertex] ~SetPrecision~10;
    grad = SetPrecision[v1 - v2, 10];
    coeff = SetPrecision[2 γ (periPolygonAssoc[j] - P0), 10];
    force += SetPrecision[coeff * grad, 10], {j, cellinds}
  ];
  Sow@force, {i, vertKeys}]
]
```

```
In[ ]:= MatrixForm@Normalize[{xi, yi} - {xj, yj}]
```

Out[]//MatrixForm=

$$\begin{pmatrix} \frac{x_i - x_j}{\sqrt{\text{Abs}[x_i - x_j]^2 + \text{Abs}[y_i - y_j]^2}} \\ \frac{y_i - y_j}{\sqrt{\text{Abs}[x_i - x_j]^2 + \text{Abs}[y_i - y_j]^2}} \end{pmatrix}$$

line tension

```
In[ ]:= FLineTension[indTopts_, ptsToInd_, edges_] :=
Block[{vertKeys = Keys@indTopts, $v1, $v2, v1, force, uv},
  force = AssociationThread[vertKeys → 0.];
  Do[
    {$v1, $v2} = i;
    uv = Normalize[$v1 - $v2] ~SetPrecision~10;
    v1 = ptsToInd[$v1];
    force[v1] += SetPrecision[κ * uv, 10],
    {i, edges}];
  Values[force]
]
```

ΣF

```

In[ ]:= F_T[indTopts_, ptsToInds_, localTopology_,
  areaPolygonAssoc_, periPolygonAssoc_, edges_] :=
  - (F_AreaElasticity[indTopts, localTopology, areaPolygonAssoc]
    + F_PerimeterElasticity[indTopts, localTopology, periPolygonAssoc] +
    F_LineTension[indTopts, ptsToInds, edges]);

```

generating mesh

```

In[ ]:= (* ensure PBC logically integrates with the rest of the code *)

```

```

In[ ]:= SeedRandom[1];
pts = RandomReal[{-1, 1}, {200, 2}];

```

```


In[ ]:= pts2 = Flatten[Table[TranslationTransform[{2 i, 2 j}][pts], {i, -1, 1}, {j, -1, 1}], 2];
vor = VoronoiMesh[pts2, {{-3, 3}, {-3, 3}}]

```

```

Out[ ]:=

```



```

In[ ]:= vcells = Catenate[NearestMeshCells[{vor, 2}, #] & /@ pts];
pvor = MeshRegion[MeshCoordinates[vor], MeshCells[vor, vcells]];

```



```

In[ ]:= Show[Table[MeshRegion[TransformedRegion[pvor, TranslationTransform[{2 i, 2 j}]]],
  MeshCellStyle -> {1 -> Black, 2 -> ColorData[2, 7 i + j + 25]}], {i, -3, 3}, {j, -3, 3}]

```

Out[]:=



```

In[ ]:= vpts = Extract[MeshCoordinates[vor],
  Union@Flatten[MeshCells[vor, vcells] /. Polygon[x_] -> x] ~Partition~1];


```

```

In[ ]:= Show[pvor, Graphics[
  {{EdgeForm[{Thick, Dashed, Black}], FaceForm[None], Rectangle[{-1, -1}, {1, 1}]},
  Red, PointSize[0.01], Point@vpts}]]

```


Out[]:=



```

In[ ]:= len = Length[pts];
C22 = #.Transpose[#] &@vor["ConnectivityMatrix"[2, 1]];
cells = Region`Mesh`MeshMemberCellIndex[vor, pts2][[All, 2]];
C22perm = C22[[cells, cells]];
pC22 = SparseArray[Unitize[Total[Partition[Unitize[C22perm], {len, len}], 2]]];
pC22 -= IdentityMatrix[len, SparseArray];
Show[pvor, Graph[AdjacencyGraph[pC22, VertexCoordinates → pts],
  VertexStyle → Red, EdgeStyle → Black]]

```



```

In[ ]:= indToPtsAssoc = AssociationThread[
  Replace[First@MeshCells[pvor], Point[x_] => x, {1}] →
  Replace[MeshPrimitives[pvor, 0], Point → Sequence, {2}, Heads → True]
];

```

```

In[ ]:= ptsToIndAssoc = <| Reverse[Normal@indToPtsAssoc, 2] |>;

```

```

In[ ]:= cellVertexGrouping = AssociationThread[Range@Length[#] → #] &@
  Replace[MeshCells[pvor, 2], x_Polygon → Sequence@@x, {1}, Heads → True];

```

```

In[ ]:= vertexCellAssoc = KeySort@GroupBy[
  Flatten[Thread[#] & /@ Reverse[Normal@cellVertexGrouping, 2]], First → Last];

```

```

In[ ]:= wrappedMat = AssociationThread[
  Keys[cellVertexGrouping] → Map[Lookup[indToPtsAssoc, #] /. periodicRules &,
  Lookup[cellVertexGrouping, Keys[cellVertexGrouping]], {2}]];

```

```

In[ ]:= faceListCoords = AssociationThread[Keys[cellVertexGrouping] →
  Map[Lookup[indToPtsAssoc, #] &, Values@Normal@cellVertexGrouping]];

```

```

In[ ]:= ptsToIndAssoc = KeyMap[SetPrecision[#, 10] &, ptsToIndAssoc];
indToPtsAssoc = SetPrecision[#, 10] & /@ indToPtsAssoc;
wrappedMat = SetPrecision[#, 10] & /@ wrappedMat;
faceListCoords = SetPrecision[#, 10] & /@ faceListCoords;

```

Main()

(* rigid network parameter choices *)

```
In[ ]:= ka = 1000;
A0 = 0.01;
γ = 0.04 * ka * A0;
δt = 0.001;
P0 = 0;
κ = 0.025;
```

```
In[ ]:= {γ / (ka * A0), κ / (ka * A03/2)}
```

```
Out[ ]:= {0.04, 0.025}
```

```
In[ ]:= indTopts = indToptsAssoc;
ptsToInd = ptsToIndAssoc;
cellToVertexG = cellVertexGrouping;
vertexToCell = vertexCellAssoc;
$wrappedMat = wrappedMat;
$faceListCoords = faceListCoords;
areaPolygonAssoc = areaOfPolygon@faceListCoords;
periPolygonAssoc = perimeterOfPolygon@faceListCoords;
SeedRandom[1];
cj = 0;
Tmax = 4000;
t = 0;
tt = {};
Module[{cellsToRemove, edgechanged, polydiv, findEdges},
  saveres = First@Last@Reap@Monitor[
    While[t ≤ Tmax * δt,
      cj = Round[t / δt];

      (* T2 transitions *)
      cellsToRemove = cellsforT2[areaPolygonAssoc, cellToVertexG];
      If[cellsToRemove ≠ {},
        {indTopts, ptsToInd, vertexToCell, cellToVertexG, $wrappedMat,
          $faceListCoords} = T2TransitionFn[cellsToRemove, indTopts, ptsToInd,
            vertexToCell, cellToVertexG, $wrappedMat, $faceListCoords];
      ];

      (* T1 transitions *)
      edges = DeleteDuplicatesBy[
        Flatten[Map[Partition[#, 2, 1, 1] &, Values[cellToVertexG]], 1], Sort];
      {indTopts, vertexToCell, cellToVertexG, $wrappedMat, $faceListCoords} =
        T1transitionFn[edges, indTopts, ptsToInd, vertexToCell,
          cellToVertexG, $wrappedMat, $faceListCoords];
      ptsToInd = AssociationMap[Reverse, indTopts];
      areaPolygonAssoc = areaPolygon /@ $faceListCoords;
      periPolygonAssoc = perimeterPolygon /@ $faceListCoords;

      (* cell divisions *)
      polydiv = selectDivCells[areaPolygonAssoc];
      If[polydiv ≠ {},
        Scan[({indTopts, cellToVertexG, areaPolygonAssoc, periPolygonAssoc} =
          cellDivision[#, indTopts, areaPolygonAssoc,
            periPolygonAssoc, cellToVertexG]) &, polydiv];
        vertexToCell = KeySort@GroupBy[Flatten[(Reverse[#, 2] &)]@*
```

```

Thread /@Normal@cellToVertexG], First → Last];
$faceListCoords = Lookup[indTopts, #] & /@ cellToVertexG;
$wrappedMat = Map[# /. periodicRules &, $faceListCoords];
];
ptsToInd = AssociationMap[Reverse, indTopts];

(* update positions *)
localtopo = getLocalTopology[ptsToInd, indTopts, vertexToCell,
    cellToVertexG, $wrappedMat, $faceListCoords][#] & /@ indTopts;
edgeLst = SortBy[Flatten[Map[Partition[#, 2, 1, 1] &,
    Values[$faceListCoords]], 1], First];
externedges = outeredges[indTopts, localtopo];
edgeLst = Join[edgeLst, externedges];
(*capture the first and the last output for the magnitude of force*)
If[cj == 3 || (cj + 1) == Tmax, AppendTo[tt, FT[indTopts, ptsToInd,
    localtopo, areaPolygonAssoc, periPolygonAssoc, edgeLst] δt]];

indTopts = AssociationThread[
    Keys[indTopts] → SetPrecision[(Values[indTopts] + FT[indTopts, ptsToInd,
        localtopo, areaPolygonAssoc, periPolygonAssoc, edgeLst] δt), 10]];


ptsToInd = AssociationMap[Reverse, indTopts];
$faceListCoords = Lookup[indTopts, #] & /@ cellToVertexG;
areaPolygonAssoc = areaPolygon /@ $faceListCoords;
periPolygonAssoc = perimeterPolygon /@ $faceListCoords;
vertexToCell = GroupBy[Flatten[
    (Reverse[#, 2] &) * Thread /@ Normal@cellToVertexG], First → Last];
$wrappedMat = Map[# /. periodicRules &, $faceListCoords];
(*plt=
    Graphics[{ColorData[1][1], Thick, Values@Map[Line[Join[##, {First@#}]] &@
        Lookup[indTopts, #] &, cellToVertexG]}, ImageSize → Medium]; *)
plt = Graphics[{FaceForm[LightBlue], EdgeForm[{Black}], Values[
    Polygon@Lookup[indTopts, #] & /@ cellToVertexG]}, ImageSize → Medium];
(*plt=Graphics[{■, Thick, Values@Map[Line[Join[##, {First@#}]] &@
    Lookup[indTopts, #] &, cellToVertexG]}, ImageSize → Medium]; *)
If[Mod[cj, 2] == 0, Sow[plt]];
t += δt;
], {cj, plt}
]
]; // AbsoluteTiming

```


Out[*n*]= {1639.97, Null}

```
In[ ]:= plt
```

```
Out[ ]:=
```



```
In[ ]:= (ListLinePlot[#, PlotStyle → {{Thickness[0.01], Red}, {Thickness[0.01], Darker@Blue}},  
PlotLabel → "force"] &) @* Transpose /@ tt
```



```
In[ ]:= (* different parameter choices *)
```

```
In[ ]:= ka = 1000;  
A0 = 0.01;  
γ = 0.015 * ka * A0;  
P0 = 0;  
κ = -0.025;  
δt = 0.00008;
```

```
In[ ]:= {γ / (ka * A0), κ / (ka * A03/2)}
```

```
Out[ ]:= {0.015, -0.025}
```

```
In[ ]:= indTopts = indToPtsAssoc;  
ptsToInd = ptsToIndAssoc;  
cellToVertexG = cellVertexGrouping;  
vertexToCell = vertexCellAssoc;  
$wrappedMat = wrappedMat;  
$faceListCoords = faceListCoords;  
areaPolygonAssoc = areaOfPolygon@faceListCoords;  
periPolygonAssoc = perimeterOfPolygon@faceListCoords;  
SeedRandom[1];  
cj = 0;
```

```

Tmax = 4000;
t = 0;
tt = {};
Module[{cellsToRemove, edgechanged, polydiv, findEdges},
  saveres = First@Last@Reap@Monitor[
    While[t ≤ Tmax * δt,
      cj = Round[t / δt];
      (* T2 transitions *)
      cellsToRemove = cellsforT2[areaPolygonAssoc, cellToVertexG];
      If[cellsToRemove ≠ {},
        {indTopts, ptsToInd, vertexToCell, cellToVertexG, $wrappedMat,
          $faceListCoords} = T2TransitionFn[cellsToRemove, indTopts, ptsToInd,
            vertexToCell, cellToVertexG, $wrappedMat, $faceListCoords];
      ];

      (* T1 transitions *)
      edges = DeleteDuplicatesBy[
        Flatten[Map[Partition[#, 2, 1, 1] &, Values[cellToVertexG]], 1], Sort];
      {indTopts, vertexToCell, cellToVertexG, $wrappedMat, $faceListCoords} =
        T1transitionFn[edges, indTopts, ptsToInd, vertexToCell,
          cellToVertexG, $wrappedMat, $faceListCoords];
      ptsToInd = AssociationMap[Reverse, indTopts];
      areaPolygonAssoc = areaPolygon /@ $faceListCoords;
      periPolygonAssoc = perimeterPolygon /@ $faceListCoords;

      (* cell divisions *)
      polydiv = selectDivCells[areaPolygonAssoc];
      If[polydiv ≠ {},
        Scan[({indTopts, cellToVertexG, areaPolygonAssoc, periPolygonAssoc} =
          cellDivision[#, indTopts, areaPolygonAssoc,
            periPolygonAssoc, cellToVertexG]) &, polydiv];
        vertexToCell = KeySort@GroupBy[Flatten[(Reverse[#, 2] &) @*
          Thread /@ Normal@cellToVertexG], First → Last];
        $faceListCoords = Lookup[indTopts, #] & /@ cellToVertexG;
        $wrappedMat = Map[#, /. periodicRules &, $faceListCoords];
      ];
      ptsToInd = AssociationMap[Reverse, indTopts];

      (* update positions *)
      localtopo = getLocalTopology[ptsToInd, indTopts, vertexToCell,
        cellToVertexG, $wrappedMat, $faceListCoords] [ # ] & /@ indTopts;
      edgeLst = SortBy[Flatten[Map[Partition[#, 2, 1, 1] &,
        Values[$faceListCoords]], 1], First];
      externedges = outeredges[indTopts, localtopo];
      edgeLst = Join[edgeLst, externedges];
      (*capture the first and the last output for the magnitude of force*)
      If[cj == 3 || (cj + 1) == Tmax, AppendTo[tt, FT[indTopts, ptsToInd,
        localtopo, areaPolygonAssoc, periPolygonAssoc, edgeLst] δt]];

      indTopts = AssociationThread[
        Keys[indTopts] → SetPrecision[(Values[indTopts] + FT[indTopts, ptsToInd,
          localtopo, areaPolygonAssoc, periPolygonAssoc, edgeLst] δt), 10]];

      ptsToInd = AssociationMap[Reverse, indTopts];
      $faceListCoords = Lookup[indTopts, #] & /@ cellToVertexG;

```

```


areaPolygonAssoc = areaPolygon /@ $faceListCoords;
periPolygonAssoc = perimeterPolygon /@ $faceListCoords;
vertexToCell = GroupBy[Flatten[
  (Reverse[#, 2] &) @* Thread /@ Normal@cellToVertexG], First → Last];
$wrappedMat = Map[# /. periodicRules &, $faceListCoords];
(*plt=
  Graphics[{ColorData[1][1], Thick, Values@Map[Line[Join[##, {First@#}]] &@
    Lookup[indTopts, #] &, cellToVertexG]}, ImageSize → Medium];*)
plt = Graphics[{FaceForm[LightBlue], EdgeForm[{Black}], Values[
  Polygon@Lookup[indTopts, #] & /@ cellToVertexG]}, ImageSize → Medium];
(*plt=Graphics[{■, Thick, Values@Map[Line[Join[##, {First@#}]] &@
  Lookup[indTopts, #] &, cellToVertexG]}, ImageSize → Medium];*)
If[Mod[cj, 2] == 0, Sow[plt]];
t += δt;
], {cj, plt}
]
]; // AbsoluteTiming

```


Out[]:= {1709.51, Null}

In[]:= plt

Out[]:=



In[]:= (ListLinePlot[#, PlotStyle → {{Thickness[0.01], Red}, {Thickness[0.01], Darker@Blue}},
PlotLabel → "force" &) @* Transpose /@ tt



miscellaneous