# Collision Prevention in Distributed 6TiSCH Networks

#### Ali Jawad Fahs

Université Grenoble Alpes (UGA) - UFR IM<sup>2</sup>AG Laboratoire d'Informatique de Grenoble (LIG), Team Drakkar VERIMAG,Synchrone Supervised by: Olivier Alphand, Franck Rousseau Karine Altisen, Stéphane Devismes

Master thesis, 21st of June,2017









# Outline

#### Introduction

General intoduction Project Objectives

## Background

IEEE802.15.4e & 6top Collisions in Dedicated cells

# Proposed Mechanism

Criteria

Using 6top Transactions Collect neighbor's cells

Avoid Table

Adding the Cell Buffer

#### Simulator and Results

Simulator

Results

# Outline

#### Introduction

#### General intoduction

Project Objectives

## Background

IEEE802.15.4e & 6top

## Proposed Mechanism

Criteria

Using 6top Transactions Collect neighbor's cells

Avoid Table

Adding the Cell Buffer

#### Simulator and Results

Simulator

Results

IoT & Wireless Sensor Networks

## ΙoΤ

Historically networks were a connection of high performance expensive computers.

IoT & Wireless Sensor Networks

## **IoT**

- Historically networks were a connection of high performance expensive computers.
- Nowadays network is a connection of entities with limited processing capabilities called Things.

IoT & Wireless Sensor Networks

#### **IoT**

- Historically networks were a connection of high performance expensive computers.
- Nowadays network is a connection of entities with limited processing capabilities called Things.
- ▶ led us to the idea of Internet of Things (IoT)

IoT & Wireless Sensor Networks

#### **IoT**

- Historically networks were a connection of high performance expensive computers.
- Nowadays network is a connection of entities with limited processing capabilities called Things.
- ▶ led us to the idea of *Internet of Things (IoT)*

#### Wireless Sensor Networks

▶ A source of communication between the IoT nodes.

IoT & Wireless Sensor Networks

#### lo<sub>T</sub>

- Historically networks were a connection of high performance expensive computers.
- Nowadays network is a connection of entities with limited processing capabilities called Things.
- ▶ led us to the idea of *Internet of Things (IoT)*

#### Wireless Sensor Networks

- A source of communication between the IoT nodes.
- Main contributions are : low power, low cost.

IoT & Wireless Sensor Networks

#### **IoT**

- Historically networks were a connection of high performance expensive computers.
- Nowadays network is a connection of entities with limited processing capabilities called Things.
- ▶ led us to the idea of *Internet of Things (IoT)*

#### Wireless Sensor Networks

- A source of communication between the IoT nodes.
- Main contributions are : low power, low cost.
- ▶ IEEE802.15.4 one of the main standard for those Networks

IEEE802.15.4


#### IEEE802.15.4

 The low layers of the network (i.e., PHY and MAC)

IEEE802.15.4


- The low layers of the network (i.e., PHY and MAC)
- The Physical Layer and Medium Access Control Layer.

- The low layers of the network (i.e., PHY and MAC)
- The Physical Layer and Medium Access Control Layer.
- Uses RPL to set-up A DODAG.




IEEE802.15.4

- The low layers of the network (i.e., PHY and MAC)
- The Physical Layer and Medium Access Control Layer.
- Uses RPL to set-up A DODAG.
- A converge cast towards a sink.



IEEE802.15.4


- The low layers of the network (i.e., PHY and MAC)
- The Physical Layer and Medium Access Control Layer.
- Uses RPL to set-up A DODAG.
- A converge cast towards a sink.



IEEE802.15.4


#### IEEE802.15.4e TSCH

▶ Extension of the Medium Access Control (MAC) Layer.




IEEE802.15.4

- Extension of the Medium Access Control (MAC) Layer.
- Time-slotted Channel Hopping (TSCH) is based on time frequency multiplexing.




IEEE802.15.4

- Extension of the Medium Access Control (MAC) Layer.
- Time-slotted Channel Hopping (TSCH) is based on time frequency multiplexing.
- Two types of cells: dedicated and shared.



IEEE802.15.4


- Extension of the Medium Access Control (MAC) Layer.
- Time-slotted Channel Hopping (TSCH) is based on time frequency multiplexing.
- Two types of cells: dedicated and shared.
- Managed in centralized or distributed way.



Collision in the Dedicated Cells

#### IEEE802.15.4e TSCH


► Collision free dedicated cells.



◆ロト ◆部 ト ◆ 恵 ト ◆ 恵 ・ 夕 Q ②


Collision in the Dedicated Cells

- Collision free dedicated cells.
- Collisions in distributed approach .




Collision in the Dedicated Cells

- Collision free dedicated cells.
- Collisions in distributed approach .
- ▶ Lack of central entity.



Collision in the Dedicated Cells

- Collision free dedicated cells.
- Collisions in distributed approach .
- ▶ Lack of central entity.
- Collision are very expensive in Wireless sensor Networks.



# Outline

#### Introduction

General intoduction

**Project Objectives** 

## Background

IEEE802.15.4e & 6top

## Proposed Mechanism

Criteria

Using 6top Transactions Collect neighbor's cells

Avoid Table

Adding the Cell Buffer

#### Simulator and Results

Simulator

Results

# **Project Objectives**

Reducing the collisions in TSCH dedicated cells.

# **Project Objectives**

- Reducing the collisions in TSCH dedicated cells.
- Modifying the Cell reserving process without introducing new overhead on the network

# **Project Objectives**

- Reducing the collisions in TSCH dedicated cells.
- Modifying the Cell reserving process without introducing new overhead on the network
- Creating a flexible mechanism, compatible with all scheduling functions

# Outline

#### Introduction

General intoduction Project Objectives

# Background

IEEE802.15.4e & 6top

Collisions in Dedicated cells

## Proposed Mechanism

Criteria

Using 6top Transactions Collect neighbor's cells

Avoid Table

Adding the Cell Buffer

#### Simulator and Results

Simulator

Results

#### 6TiSCH

► The standard have defined TSCH schedule but the control of this schedule was left for other protocols for flexibility and optimization.

- ► The standard have defined TSCH schedule but the control of this schedule was left for other protocols for flexibility and optimization.
- ▶ 6TiSCH purpose is the Integration of IPv6 and TSCH.

- The standard have defined TSCH schedule but the control of this schedule was left for other protocols for flexibility and optimization.
- ▶ 6TiSCH purpose is the Integration of IPv6 and TSCH.
- ▶ 6TiSCH operation (6top) is a sublayer of 6TiSCH.

- The standard have defined TSCH schedule but the control of this schedule was left for other protocols for flexibility and optimization.
- ▶ 6TiSCH purpose is the Integration of IPv6 and TSCH.
- 6TiSCH operation (6top) is a sublayer of 6TiSCH.
- 6top contains the scheduling function.

- ► The standard have defined TSCH schedule but the control of this schedule was left for other protocols for flexibility and optimization.
- ▶ 6TiSCH purpose is the Integration of IPv6 and TSCH.
- 6TiSCH operation (6top) is a sublayer of 6TiSCH.
- 6top contains the scheduling function.
- 6top is responsible for the cell addition and deletion.

# 6top

 Orchestrates all communications using the TSCH schedule.

| PCEP<br>PCC        | CoAP<br>DTLS | PANA | 6LoWPAN<br>ND | RPL |      |  |
|--------------------|--------------|------|---------------|-----|------|--|
| TCP                | UDP          |      | ICMP          |     | RSVP |  |
| IPV6               |              |      |               |     |      |  |
| 6LoWPAN HC         |              |      |               |     |      |  |
| 6top               |              |      |               |     |      |  |
| IEEE802.15.4e TSCH |              |      |               |     |      |  |
| IEEE802.15.4 PHY   |              |      |               |     |      |  |

# 6top

- Orchestrates all communications using the TSCH schedule.
- Allows the nodes to request for new TSCH cells.

| PCEP<br>PCC        | CoAP<br>DTLS | PANA | 6LoWPAN<br>ND | RPL |      |  |
|--------------------|--------------|------|---------------|-----|------|--|
| TCP                | UDP          |      | ICMP          |     | RSVP |  |
| IPV6               |              |      |               |     |      |  |
| 6LoWPAN HC         |              |      |               |     |      |  |
| 6top               |              |      |               |     |      |  |
| IEEE802.15.4e TSCH |              |      |               |     |      |  |
| IEEE802.15.4 PHY   |              |      |               |     |      |  |

# 6top

- Orchestrates all communications using the TSCH schedule.
- Allows the nodes to request for new TSCH cells.
- 6top enables the distributed scheduling in 6TiSCH network.

| PCEP<br>PCC        | CoAP<br>DTLS | PANA | 6LoWPAN<br>ND | RPL |      |  |
|--------------------|--------------|------|---------------|-----|------|--|
| TCP                | UDP          |      | ICMP          |     | RSVP |  |
| IPV6               |              |      |               |     |      |  |
| 6LoWPAN HC         |              |      |               |     |      |  |
| 6top               |              |      |               |     |      |  |
| IEEE802.15.4e TSCH |              |      |               |     |      |  |
| IEEE802.15.4 PHY   |              |      |               |     |      |  |


# IEEE802.15.4e & 6top

▶ 6top transactions: negotiation to Add/Delete/Relocate cells.

## IEEE802.15.4e and 6top

### IEEE802.15.4e & 6top


- ▶ 6top transactions: negotiation to Add/Delete/Relocate cells.
- ► Two types: 2-step and 3-step.



## IEEE802.15.4e and 6top

### IEEE802.15.4e & 6top


- ▶ 6top transactions: negotiation to Add/Delete/Relocate cells.
- ► Two types: 2-step and 3-step.
- ▶ The transaction is done in the shared slot.



## IEEE802.15.4e and 6top

### IEEE802.15.4e & 6top

- ▶ 6top transactions: negotiation to Add/Delete/Relocate cells.
- ► Two types: 2-step and 3-step.
- ▶ The transaction is done in the shared slot.
- The transaction will be received by the neighbor nodes by dropped due too MAC filtering of the messages.



### Outline

#### Introduction

General intoduction Project Objectives

### Background

IEEE802.15.4e & 6top

Collisions in Dedicated cells

### Proposed Mechanism

Criteria

Using 6top Transactions Collect neighbor's cells

Avoid Table

Adding the Cell Buffer

#### Simulator and Results

Simulator


Results

### 6top

▶ Nodes have no information about the neighbors.


### 6top

- Nodes have no information about the neighbors.
- Scheduling function cell selection does not consider the neighbor's cells.




### 6top

- Nodes have no information about the neighbors.
- Scheduling function cell selection does not consider the neighbor's cells.
- If another neighbor node is using the same cell a collision will occur.



### 6top

- ▶ Nodes have no information about the neighbors.
- Scheduling function cell selection does not consider the neighbor's cells.
- If another neighbor node is using the same cell a collision will occur.
- Collisions are expensive.



### Outline

#### Introduction

General intoduction Project Objectives

### Background

IEEE802.15.4e & 6top Collisions in Dedicated cells

### Proposed Mechanism

#### Criteria

Using 6top Transactions Collect neighbor's cells Avoid Table Adding the Cell Buffer

#### Simulator and Results

Simulator

Our objective is to Reduce the collisions in the dedicated cells.

- Our objective is to Reduce the collisions in the dedicated cells.
- Using local mutual exclusion we can prevent collisions.

- Our objective is to Reduce the collisions in the dedicated cells.
- Using local mutual exclusion we can prevent collisions.
- Since we are working with distributed system, then all the information is local for each node.

- Our objective is to Reduce the collisions in the dedicated cells.
- Using local mutual exclusion we can prevent collisions.
- Since we are working with distributed system, then all the information is local for each node.
- Using the 6top transaction we can collect information about neighbors.

- Our objective is to Reduce the collisions in the dedicated cells.
- Using local mutual exclusion we can prevent collisions.
- Since we are working with distributed system, then all the information is local for each node.
- Using the 6top transaction we can collect information about neighbors.
- ► From the collected information we can prevent the nodes selecting the same cell.

- Our objective is to Reduce the collisions in the dedicated cells.
- Using local mutual exclusion we can prevent collisions.
- Since we are working with distributed system, then all the information is local for each node.
- Using the 6top transaction we can collect information about neighbors.
- ► From the collected information we can prevent the nodes selecting the same cell.

### Outline

#### Introduction

General intoduction Project Objectives

### Background

IEEE802.15.4e & 6top Collisions in Dedicated cells

### Proposed Mechanism

Criteria

### Using 6top Transactions Collect neighbor's cells

Avoid Table

Adding the Cell Buffer


#### Simulator and Results

Simulator

Results


## Using 6top Transactions Collect neighbor's cells

D will transmit an Add request to B.




## Using 6top Transactions Collect neighbor's cells

- D will transmit an Add request to B.
- ▶ B will reply with the Add Response that will contain the cells.



## Using 6top Transactions Collect neighbor's cells

- D will transmit an Add request to B.
- ▶ B will reply with the Add Response that will contain the cells.
- ► The Add Response is transmitted in the shared cell, E & F will receive and extract the cells.



### Outline

#### Introduction

General intoduction Project Objectives

### Background

IEEE802.15.4e & 6top Collisions in Dedicated cells

### Proposed Mechanism

Criteria

Using 6top Transactions Collect neighbor's cells

Avoid Table

Adding the Cell Buffer


#### Simulator and Results

Simulator

Results


### Avoid Table

► The cells reserved by neighbors will be saved by a structure similar to TSCH table.




### Avoid Table

- ► The cells reserved by neighbors will be saved by a structure similar to TSCH table.
- Scheduling function will avoid selecting cells found in this structure.



### Avoid Table

- ► The cells reserved by neighbors will be saved by a structure similar to TSCH table.
- Scheduling function will avoid selecting cells found in this structure.
- 6top will manage this table.



### Outline

#### Introduction

General intoduction Project Objectives

### Background

IEEE802.15.4e & 6top Collisions in Dedicated cells

### Proposed Mechanism

Criteria

Using 6top Transactions Collect neighbor's cells


Adding the Cell Buffer

#### Simulator and Results


Simulator

Results


▶ The assumption of 100% successful dilevery is not realistic.




- ▶ The assumption of 100% successful dilevery is not realistic.
- ▶ The 6top Transaction maybe lost due too environment effects.



- ▶ The assumption of 100% successful dilevery is not realistic.
- The 6top Transaction maybe lost due too environment effects.
- The loss of the transaction increase the probability of collisions.



- ▶ The assumption of 100% successful dilevery is not realistic.
- ▶ The 6top Transaction maybe lost due too environment effects.
- ► The loss of the transaction increase the probability of collisions.
- By saving the reserved cells in a buffer, and sending the buffer this probability can be reduced.



▶ We have created a probablistic model to calaculate the optimal length of the buffer.

- We have created a probablistic model to calaculate the optimal length of the buffer.
- ▶ *p* is the probability of successful transmission.

- We have created a probablistic model to calaculate the optimal length of the buffer.
- ▶ *p* is the probability of successful transmission.
- we are confidence with a probability P<sub>o</sub> that one of the transmission is successful.

- We have created a probablistic model to calaculate the optimal length of the buffer.
- p is the probability of successful transmission.
- we are confidence with a probability P<sub>o</sub> that one of the transmission is successful.
- ▶ *k* is the number of retransmission (the optimal length of the buffer).

- We have created a probablistic model to calaculate the optimal length of the buffer.
- p is the probability of successful transmission.
- ▶ we are confidence with a probability P<sub>o</sub> that one of the transmission is successful.
- ▶ *k* is the number of retransmission (the optimal length of the buffer).
- we end up with the following equation using binomial distribution:

$$\left\lceil \frac{\log(1 - P_0)}{\log(1 - p)} \right\rceil$$

- We have created a probablistic model to calaculate the optimal length of the buffer.
- ▶ *p* is the probability of successful transmission.
- ▶ we are confidence with a probability P<sub>o</sub> that one of the transmission is successful.
- ▶ *k* is the number of retransmission (the optimal length of the buffer).
- we end up with the following equation using binomial distribution:

$$\left\lceil \frac{\log(1 - P_0)}{\log(1 - p)} \right\rceil$$

► According to this equation, and by taking the worst case scenario a buffer of length 10 can assure us 95% of success

### Outline

#### Introduction

General intoduction Project Objectives

### Background

IEEE802.15.4e & 6top Collisions in Dedicated cells

### Proposed Mechanism

Criteria

Using 6top Transactions Collect neighbor's cells

Avoid Table

Adding the Cell Buffer

### Simulator and Results

Simulator

Results

### Simulator Architecture




Figure: Simulator Architecture

### Outline

#### Introduction

General intoduction Project Objectives

### Background

IEEE802.15.4e & 6top Collisions in Dedicated cells

### Proposed Mechanism

Criteria

Using 6top Transactions Collect neighbor's cells

Avoid Table

Adding the Cell Buffer

#### Simulator and Results

Simulator

Results

### Results





Figure: Simulation of the Number of Collided Tx Cells as Function of Cycle Number (Time)

► The lost 6top transactions.

- ▶ The lost 6top transactions.
- Special Case That Induce Collisions.



## Comparison with Housekeeping




Figure: Simulation of the Number of Collided Tx Cells as Function of Cycle Number (Time) - comparison with the housekeeping approach

## Comparison with Housekeeping





Figure: Simulation of the Number of Collided Packets as Function of Cycle Number (Time) - comparison with the housekeeping approach

## Summary

- Our implementation introduce no overhead in the network.
- ► The implementation achieved 60% reduction in the number of collided Tx cells and 70% reduction of the Collided Packets.
- ► The Combination of Our approach and Housekeeping accomplish an almost collision free dedicated cells.
- Outlook
  - Our goal is to reach a place were we have collision free network, using more complex methods.
  - Our prespective in this project was work on 6top, but our next steps is to study the effects of traffic in the protocols performances.



# Thanks for your attention! Questions?