```
CA4 tols.m -- dhpham -- 12 feb 2019
% Run CA4_nm.m and CA4_fzero.m for every value in 'tols', a vector of
% convergence tolerances.
% For each tolerance value, record the:
       1) mean # of function evals per root found. for each
procedure,
       2) rms of the residual error given by J_m(x), at every root
found
       3) maximum abs. value of the res error when solving the DE in
્ટ
응
           CA4 BesselMovie for 0
   Create a log-plot of the residual errors, and a plot of the mean
9
  Nevals.
clear
% vector of convergence tolerances to test
tols = [3:15];
    mean Nevals: mean # of function evals per iter. of procedure
     bsl_reserr: take rms of J_m(x) evaluated at all roots found
% diffeq_reserr: max abs val of res err; given by CA4_BesselMovie
fzero_data = struct( 'mean_Nevals', zeros(size(tols)), ...
                    'bsl_reserr', zeros(size(tols)), ...
                    'diffeq_reserr', zeros(size(tols)) );
nm_data = struct( 'mean_Nevals',
                                  zeros(size(tols)), ...
                 'bsl_reserr',
                                  zeros(size(tols)), ...
                 'diffeq_reserr',
                                     zeros(size(tols)) );
% Run CA4_nm.m for each value in 'tols'
for toli = tols(1):tols(end)
    % i-th iteration
   ix = toli - tols(1) + 1;
   % Set tol for CA4_nm.m
   tolnm = 1 * 10^(-toli);
   % Run NM
   CA4 nm submsn;
    % Store data produced by NM
   nm_data.mean_Nevals(ix) = mean_Nevals;
   nm_data.bsl_reserr(ix) = bsl_reserr;
   Zmk = Amk;
                       % Prepare Zmk for CA4 BesselMovie
   CA4_BesselMovie_submsn;
```

```
% Store data produced by CA4 BesselMovie.m
    nm_data.diffeq_reserr(ix) = max(abs(real(test(:,end))/mP));
end
% Run CA4 fzero.m for each value in 'tols'
for toli = tols(1):tols(end)
    % i-th iteration
    ix = toli - tols(1) + 1;
    % Set tol for CA4_fzero.m
    tolfz = 1 * 10^(-toli);
    % Run fzero
    CA4 fzero submsn;
    % Store data produced by NM
    fzero_data.mean_Nevals(ix) = mean_Nevals;
    fzero_data.bsl_reserr(ix) = bsl_reserr;
                        % Prepare Zmk for CA4_BesselMovie
    Zmk = Amk;
    nofigs = true;
                         % skip creating the gif
    CA4_BesselMovie_submsn;
    % Store data produced by CA4 BesselMovie.m
    fzero_data.diffeq_reserr(ix) = max(abs(real(test(:,end))/mP));
end
% Create log-plot figure of error results for NM and fzero
figure(4000); clf
% Set figure parameters
ax1 = gca;
title('Log-plot of Residual Errors vs. Tol. (NM and fzero)')
           grid on;
hold on;
xlabel('log_{10}(\epsilon = convg. tol)')
ax1.XAxisLocation = 'top';
ax1.XLim = [min(tols-1) max(tols+1)];
ax1.XTick = [ax1.XLim(1):ax1.XLim(end)];
ylabel('log_{10}(res err)')
ax1.YLim = [-18 0];
ax1.YTick = [ax1.YLim(1):ax1.YLim(end)];
% Create legend using dummy varaibles
invis = [NaN NaN];
dum(1,1) = plot(invis,'.k');
                                 lbl(1,1) = "rms(res err) of J_{m}
(x)";
dum(2,1) = plot(invis,'xk');
                                 lbl(2,1) = max(abs(res err)) of DE";
                                 1b1(3,1) = "NM";
dum(3,1) = plot(invis,'--r');
dum(4,1) = plot(invis,'--b');
                                 lbl(4,1) = "fzero";
```

```
legend(ax1,dum(:,1),lbl(:,1),'AutoUpdate','off','Location','best')
% plot NM res errs
plot(tols,log10(nm_data.bsl_reserr),'.r')
plot(tols,log10(nm_data.diffeq_reserr),'xr')
% plot fzero res errs
plot(tols,log10(fzero_data.bsl_reserr),'.b')
plot(tols,log10(fzero_data.diffeq_reserr),'xb')
% Create figure of mean function evals. at each 'tol' for NM and
fzero
figure(4001); clf
title('Mean # of Function Evals/root found (NM and fzero)')
ax2 = gca;
legend(ax2, 'Location', 'northwest')
hold on;
           grid on;
% Set axis parameters
xlabel('log_{10}(\epsilon = convg. tol)')
ax2.XAxisLocation = 'bottom';
ax2.XLim = [min(tols-1) max(tols+1)];
ax2.XTick = [ax2.XLim(1):ax2.XLim(end)];
ylabel('# of func. evals. per iter')
ax2.YLim = [0 nm_data.mean_Nevals(end)+1];
ax2.YTick = [ax2.YLim(1):ax2.YLim(end)];
% Plot mean func. evals to find each root
plot(tols,nm_data.mean_Nevals,'*r', ...
        'DisplayName','NM')
plot(tols,fzero_data.mean_Nevals,'*b', ...
        'DisplayName', 'fzero')
```

Published with MATLAB® R2018a