

---

```

%
% ca2_demo.m -- timing exercise (macm316, hl -- 13 jan 2019)
%
% Purpose:      This script serves as a demo for students to build on
%               in
%               completing computing assignment 2. This script builds
%               three types
%               of NxN matrices: dense, upper triangular, and
%               permuted upper
%               triangular. It then performs a matrix solve with each,
%               Nex number
%               of times. The time it takes for Nex number of solves
%               is used to
%               estimate the time of one solve .
%
% Instructions: Start by running the script once, and see the
%               output for the esimated times. Note: the choice of
%               Nex here may
%               not give accurate results for all three matrix types.
%               Next, copy
%               and paste this code into your own Matlab
%               file. Follow the assignment sheet for further
%               instructions to
%               complete your report.

% experimental parameters

n = 3;
N = zeros(2*n-1, 1);

dense_Nex = ones(2*n-1, 1);
avg_dense_time = zeros(2*n-1, 1);

tri_Nex = ones(2*n-1, 1);
avg_tri_time = zeros(2*n-1, 1);

perm_Nex = ones(2*n-1, 1);
avg_perm_time = zeros(2*n-1, 1);

tridiag_Nex = ones(2*n-1, 1);
avg_tridiag_time = zeros(2*n-1, 1);

sparse_tridiag_Nex = ones(2*n-1, 1);
avg_sparse_tridiag_time = zeros(2*n-1, 1);

i=1;
for k = 1:0.5:n
    % Fill N with values of 10^1, 10^1.5, ... 10^3.5, 10^4
    N(i) = ceil(10^k);

    % size exists only for convenient terminal output
    size = N(i)

```

---

---

```
% three matrix types

% dense matrix (no zeros)
Md = randn(N(i),N(i));

% upper triangular
Mt = triu(Md);

% randomly row-exchanged upper triangular (these are tricky array
commands,
% but if you run a small sample, it is clear they do the right
thing)
idx=randperm(N(i));
Mp = Mt(idx,:);

%Tri-diagonal and sparse tri-diagonal
M3 = diag(diag(Md))+diag(diag(Md,-1),-1)+diag(diag(Md,1),1);
M3s=sparse(M3);

% exact solution of all ones
x = ones(N(i),1);

% right-side vectors
bd = Md*x;
bt = Mt*x;
bp = bt(idx);
b3dg = M3*x;
b3dgs = M3s*x;

% define # of experiments per matrix type
dense_Nex(i) = 4440*ceil(10^(n-k));
tri_Nex(i) = 100000*ceil(10^(n-k));
perm_Nex(i) = 20000*ceil(10^(n-k));
tridiag_Nex(i) = 5600*ceil(10^(n-k));
sparse_tridiag_Nex(i) = 100000*ceil(10^(n-k));

% dense test
tic
for jj = 1:dense_Nex(i)
    xd = Md\bd;
end
dense_time=toc;

% upper tri test
tic
for jj = 1:tri_Nex(i)
    xt = Mt\bt;
end
tri_time=toc;

% permuted upper tri test
tic
for jj = 1:perm_Nex(i)
```

---

---

```

        xp = Mp\bp;
    end
    perm_tri_time=toc;

    % tridiagonal test
    tic
    for jj = 1:tridiag_Nex(i)
        x3dg = M3\b3dg;
    end
    tridiag_time=toc;

    % sparse tridiagonal test
    tic
    for jj = 1:sparse_tridiag_Nex(i)
        x3dgs = M3s\b3dgs;
    end
    sparse_tridiag_time=toc;

    %Computing avgerage solve times
    avg_dense_time(i) = dense_time/dense_Nex(i);

    avg_tri_time(i) = tri_time/tri_Nex(i);

    avg_perm_time(i) = perm_tri_time/perm_Nex(i);

    avg_tridiag_time(i) = tridiag_time/tridiag_Nex(i);

    avg_sparse_tridiag_time(i) = sparse_tridiag_time/
    sparse_tridiag_Nex(i);

    % You may find the following code helpful for displaying the
    results
    % of this demo.
    type_times = {'Dense',avg_dense_time(i), ...
        'Upper Triangular', avg_tri_time(i), ...
        'permuted Upper Triangular', avg_perm_time(i), ...
        'Tridiagonal', avg_tridiag_time(i), ...
        'sparse Tridiagonal', avg_sparse_tridiag_time(i)};

    fprintf(' \n')
    fprintf('Estimated time for a %s matrix is %f seconds.
    \n',type_times{:})

    fprintf('=====
    \n')
    i = i+1;
end

% Begin plotting log-log graph of results

% to be used as x axis
logN = log10(N);
% (2*n)-1 x 3 sized matrix, each column a diff. matrix type
logTimes = log10([ avg_dense_time, avg_tri_time, avg_perm_time, ...
    avg_tridiag_time, avg_sparse_tridiag_time]);

```

---

---

```

% hold the log slope for each matrix type
p = ones(5,2);

% hold appropriately ordered ylabel labels for log-log plot
logylabel = ["log_{10}(avg time to solve dense) (in s)", ...
             "log_{10}(avg time to solve upp. tri.) (in s)", ...
             "log_{10}(avg time to solve perm. upp.) (in s)", ...
             "log_{10}(avg time to solve tridiag.) (in s)", ...
             "log_{10}(avg time to solve sparse tridiag.) (in s)"];

% colours for plot of each matrix type
plotopts = ["r*", "g^", "bp", "cs", "ms"];

x1 = [logN(1):0.01:logN(end)];

% Output
for j = 1:5
    p(j,:) = polyfit(logN, logTimes(:,j), 1);
    display(['Slope of best fit line is : ', num2str(p(j,1))])

    % Plotting
    figure(1)

    % Plot of log data
    subplot(1,5,j)
    % plot discrete points
    plot(logN, logTimes(:,j), plotopts(j))
    hold on;
    % plot bestfit line
    y1 = polyval(p(j,:), x1);
    plotcolour = char(plotopts(j));
    plot(x1,y1,plotcolour(1))

    grid on
    xlabel('log_{10}(N)')
    ylabel(logylabel(j))
    title(['Log-log plot, with slope ', num2str(p(j,1))])
end

```

*Published with MATLAB® R2018a*