

You submitted this quiz on **Tue 22 Sep 2015 4:10 PM PDT**. You got a score of **10.00** out of **10.00**.

Question 1


Suppose I define the following function in R

```
cube <- function(x, n) {  
  x^3  
}
```

What is the result of running

```
cube(3)
```

in R after defining this function?

Your Answer	Score	Explanation
<input checked="" type="radio"/> The number 27 is returned	 1.00	Because 'n' is not evaluated, it is not needed even though it is a formal argument.
<input type="radio"/> An error is returned because 'n' is not specified in the call to 'cube'		
<input type="radio"/> The users is prompted to specify the value of 'n'.		
<input type="radio"/> A warning is given with no value returned.		
Total	1.00 / 1.00	

Question 2

The following code will produce a warning in R.

```
x <- 1:10
if(x > 5) {
  x <- 0
}
```

Why?

Your Answer	Score	Explanation
<input type="radio"/> The expression uses curly braces.		
<input type="radio"/> There are no elements in 'x' that are greater than 5		
<input type="radio"/> You cannot set 'x' to be 0 because 'x' is a vector and 0 is a scalar.		
<input checked="" type="radio"/> 'x' is a vector of length 10 and 'if' can only test a single logical statement.	✓ 1.00	
<input type="radio"/> The syntax of this R expression is incorrect.		
Total	1.00 / 1.00	

Question 3

Consider the following function

```
f <- function(x) {
  g <- function(y) {
    y + z
  }
  z <- 4
  x + g(x)
}
```

If I then run in R

```
z <- 10  
f(3)
```

What value is returned?

Your Answer	Score	Explanation
<input type="radio"/> 7		
<input type="radio"/> 16		
<input checked="" type="radio"/> 10	✓ 1.00	
<input type="radio"/> 4		
Total	1.00 / 1.00	

Question 4

Consider the following expression:

```
x <- 5  
y <- if(x < 3) {  
      NA  
} else {  
      10  
}
```

What is the value of 'y' after evaluating this expression?

Your Answer	Score	Explanation
<input type="radio"/> 5		
<input type="radio"/> 3		
<input checked="" type="radio"/> 10	✓ 1.00	
<input type="radio"/> NA		

Total

1.00 / 1.00

Question 5

Consider the following R function

```
h <- function(x, y = NULL, d = 3L) {  
  z <- cbind(x, d)  
  if(!is.null(y))  
    z <- z + y  
  else  
    z <- z + f  
  g <- x + y / z  
  if(d == 3L)  
    return(g)  
  g <- g + 10  
  g  
}
```

Which symbol in the above function is a free variable?

Your Answer	Score	Explanation
<input checked="" type="radio"/> f	✓ 1.00	
<input type="radio"/> z		
<input type="radio"/> d		
<input type="radio"/> L		
<input type="radio"/> g		
Total	1.00 / 1.00	

Question 6

What is an environment in R?

Your Answer	Score	Explanation
<input type="radio"/> a list whose elements are all functions		
<input checked="" type="radio"/> a collection of symbol/value pairs	✓ 1.00	
<input type="radio"/> a special type of function		
<input type="radio"/> an R package that only contains data		
Total	1.00 / 1.00	

Question 7

The R language uses what type of scoping rule for resolving free variables?

Your Answer	Score	Explanation
<input checked="" type="radio"/> lexical scoping	✓ 1.00	
<input type="radio"/> compilation scoping		
<input type="radio"/> global scoping		
<input type="radio"/> dynamic scoping		
Total	1.00 / 1.00	

Question 8

How are free variables in R functions resolved?

Your Answer	Score	Explanation
<input checked="" type="radio"/> The values of free variables are searched for in the environment in which the function was defined	✓ 1.00	

☐ The values of free variables are searched for in the working directory

☐ The values of free variables are searched for in the environment in which the function was called


☐ The values of free variables are searched for in the global environment

Total	1.00 / 1.00
-------	-------------

Question 9

What is one of the consequences of the scoping rules used in R?

Your Answer	Score	Explanation
-------------	-------	-------------

<input checked="" type="radio"/> All objects must be stored in memory	 1.00	
---	--	--

☐ Functions cannot be nested

☐ R objects cannot be larger than 100 MB

☐ All objects can be stored on the disk

Total	1.00 / 1.00
-------	-------------

Question 10

In R, what is the parent frame?

Your Answer	Score	Explanation
-------------	-------	-------------

☐ It is always the global environment

<input checked="" type="radio"/> It is the environment in which a function was called	 1.00	
---	--	--

☐ It is the package search list

☐ It is the environment in which a function was defined

Total

1.00 / 1.00