



Create resource groups and attach policies

SnapCenter Software

Nirupama Sriram, Archana, Soumik Das
June 17, 2021

This PDF was generated from https://docs.netapp.com/us-en/snapcenter/protect-hana/task_create_resource_groups_and_attach_policies.html on June 18, 2021. Always check docs.netapp.com for the latest.

Table of Contents


Create resource groups and attach policies. 1

Create resource groups and attach policies

A resource group is the container to which you must add resources that you want to back up and protect. A resource group enables you to back up all the data that is associated with a given application simultaneously. A resource group is required for any data protection job. You must also attach one or more policies to the resource group to define the type of data protection job that you want to perform.

Steps

1. In the left navigation pane, click **Resources**, and then select the appropriate plug-in from the list.
2. On the **Resources** page, click **New Resource Group**.
3. On the **Name** page, perform the following actions:

For this field...	Do this...
Name	<p>Enter a name for the resource group.</p> <div> The resource group name should not exceed 250 characters.</div>
Tags	<p>Enter one or more labels that will help you later search for the resource group.</p> <p>For example, if you add HR as a tag to multiple resource groups, you can later find all resource groups associated with the HR tag.</p>
Use custom name format for Snapshot copy	<p>Select this check box, and enter a custom name format that you want to use for the Snapshot copy name.</p> <p>For example, customtext_resource group_policy_hostname or resource group_hostname. By default, a timestamp is appended to the Snapshot copy name.</p>

4. On the **Resources** page, select a host name from the **Host** drop-down list and resource type from the **Resource Type** drop-down list.

This helps to filter information on the screen.

5. Select the resources from the **Available Resources** section, and then click the right arrow to move them to the **Selected Resources** section.
6. On the **Application Settings** page, do the following:
 - a. Click the **Backups** arrow to set additional backup options:

Enable consistency group backup and perform the following tasks:

For this field...	Do this...
Afford time to wait for Consistency Group Snapshot operation to complete	<p>Select Urgent, Medium, or Relaxed to specify the wait time for Snapshot copy operation to complete.</p> <p>Urgent = 5 seconds, Medium = 7 seconds, and Relaxed = 20 seconds.</p>
Disable WAFL Sync	Select this to avoid forcing a WAFL consistency point.

- Click the **Scripts** arrow and enter the pre and post commands for quiesce, Snapshot copy, and unquiesce operations. You can also enter the pre commands to be executed before exiting in the event of a failure.
- Click the **Custom Configurations** arrow and enter the custom key-value pairs required for all data protection operations using this resource.

Parameter	Setting	Description
ARCHIVE_LOG_ENABLE	(Y/N)	Enables the archive log management to delete the archive logs.
ARCHIVE_LOG_RETENTION	number_of_days	<p>Specifies the number of days the archive logs are retained.</p> <p>This setting must be equal to or greater than NTAP_SNAPSHOT_RETENTIONS.</p>

Parameter	Setting	Description
ARCHIVE_LOG_DIR	change_info_directory/logs	Specifies the path to the directory that contains the archive logs.
ARCHIVE_LOG_EXT	file_extension	Specifies the archive log file extension length. For example, if the archive log is log_backup_0_0_0_0.161518551942 9 and if the file_extension value is 5, then the extension of the log will retain 5 digits, which is 16151.
ARCHIVE_LOG_RECURSIVE_SE ARCH	(Y/N)	Enables the management of archive logs within subdirectories. You should use this parameter if the archive logs are located under subdirectories.



The custom key-value pairs are supported for SAP HANA Linux plug-in systems and not supported for SAP HANA database registered as a centralized windows plug-in.

- d. Click the **Snapshot Copy Tool** arrow to select the tool to create Snapshot copies:

If you want...	Then...
SnapCenter to use the plug-in for Windows and put the file system into a consistent state before creating a Snapshot copy. For Linux resources, this option is not applicable.	Select SnapCenter with File System Consistency . This option is not applicable for SnapCenter Plug-in for SAP HANA Database.
SnapCenter to create a storage level Snapshot copy	Select SnapCenter without File System Consistency .
To enter the command to be executed on the host to create Snapshot copies.	Select Other , and then enter the command to be executed on the host to create a Snapshot copy.


7. On the **Policies** page, perform the following steps:

- a. Select one or more policies from the drop-down list.



You can also create a policy by clicking .

The policies are listed in the Configure schedules for selected policies section.

- b. In the Configure Schedules column, click  for the policy you want to configure.
- c. In the Add schedules for policy *policy_name* dialog box, configure the schedule, and then click **OK**.

Where, *policy_name* is the name of the policy that you have selected.

The configured schedules are listed in the **Applied Schedules** column.

Third party backup schedules are not supported when they overlap with SnapCenter backup schedules.

- 8. On the **Notification** page, from the **Email preference** drop-down list, select the scenarios in which you want to send the emails.

You must also specify the sender and receiver email addresses, and the subject of the email. The SMTP server must be configured in **Settings > Global Settings**.

- 9. Review the summary, and then click **Finish**.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.