



Create an ONTAP cluster role with minimum privileges

SnapCenter Software

Soumik Das, Archana
June 10, 2021

This PDF was generated from https://docs.netapp.com/us-en/snapcenter/install/task_create_an_ontap_cluster_role_with_minimum_privileges.html on June 18, 2021. Always check docs.netapp.com for the latest.

Table of Contents

- Create an ONTAP cluster role with minimum privileges. 1
 - ONTAP CLI commands for creating roles and assigning permissions. 1

Create an ONTAP cluster role with minimum privileges

You should create an ONTAP cluster role with minimum privileges so that you do not have to use the ONTAP admin role to perform operations in SnapCenter. You can run several ONTAP CLI commands to create the ONTAP cluster role and assign minimum privileges.

Steps

1. On the storage system, create a role and assign all the permissions to the role.

```
security login role create -vserver <cluster_name\>- role <role_name\>  
-cmddirname <permission\>
```



You should repeat this command for each permission.

2. Create a user and assign the role to that user.

```
security login create -user <user_name\> -vserver <cluster_name\> -application  
ontapi -authmethod password -role <role_name\>
```

3. Unlock the user.

```
security login unlock -user <user_name\> -vserver <cluster_name\>
```

ONTAP CLI commands for creating roles and assigning permissions

There are several ONTAP CLI commands you should run to create a role and assign permissions.

- `security login role create -role Role_Name -cmddirname "cluster identity modify" -vserver SVM_name or Cluster_name or cluster_name -access all`
- `security login role create -role Role_Name -cmddirname "cluster identity show" -vserver SVM_name or Cluster_name -access all`
- `security login role create -role Role_Name -cmddirname "cluster modify" -vserver SVM_name or Cluster_name -access all`
- `security login role create -role Role_Name -cmddirname "cluster peer show" -vserver SVM_name or Cluster_name -access all`
- `security login role create -role Role_Name -cmddirname "cluster show" -vserver SVM_name or Cluster_name -access all`
- `security login role create -role Role_Name -cmddirname "event generate-autosupport-log" -vserver SVM_name or Cluster_name -access all`
- `security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "job history show" -access all`

- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "job stop" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun delete" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun igroup add" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun igroup create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun igroup delete" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun igroup modify" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun igroup rename" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun igroup show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun mapping add-reporting-nodes" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun mapping create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun mapping delete" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun mapping remove-reporting-nodes" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun mapping show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun modify" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun move-in-volume" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun offline" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun online" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun persistent-reservation clear" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name

```
-cmddirname "lun resize" -access all
```

- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun serial" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "lun show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "network interface create" -access readonly
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "network interface delete" -access readonly
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "network interface modify" -access readonly
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "network interface show" -access readonly
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "security login" -access readonly
- security login role create -role Role_Name -cmddirname "snapmirror create" -vserver SVM_name or Cluster_name -access all
- security login role create -role Role_Name -cmddirname "snapmirror list-destinations" -vserver SVM_name or Cluster_name -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror policy add-rule" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror policy create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror policy delete" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror policy modify" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror policy modify-rule" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror policy remove-rule" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror policy show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror restore" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror show-history" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror update" -access all

- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "snapmirror update-ls-set" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "version" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume clone create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume clone show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume clone split start" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume clone split stop" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume clone split status" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume destroy" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume file clone create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume file show-disk-usage" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume modify" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume offline" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume online" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume qtree create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume qtree delete" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume qtree modify" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume qtree show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume restrict" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "volume show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name

```
-cmddirname "volume snapshot create" -access all
```

- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "volume snapshot delete" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "volume snapshot modify" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "volume snapshot promote" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "volume snapshot rename" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "volume snapshot restore" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "volume snapshot restore-file" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "volume snapshot show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "volume unmount" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver cifs create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver cifs delete" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver cifs share modify" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver cifs share create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver cifs share delete" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver cifs share modify" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver cifs share show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver cifs show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver export-policy create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name
-cmddirname "vserver export-policy delete" -access all

- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver export-policy rule create" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver export-policy rule delete" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver export-policy rule modify" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver export-policy rule show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver export-policy show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver iscsi connection show" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver" -access readonly
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver modify" -access readonly
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver show" -access readonly
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver export-policy" -access all
- security login role create -vserver SVM_name or Cluster_name -role Role_Name -cmddirname "vserver iscsi" -access all

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.