



Configure Disaster recovery

SnapCenter Software 4.6

NetApp
March 07, 2022

This PDF was generated from https://docs.netapp.com/us-en/snapcenter/protect-scsql/task_disaster_recovery_scsql.html on March 07, 2022. Always check docs.netapp.com for the latest.

Table of Contents

- Configure Disaster recovery 1
 - Disaster recovery of SnapCenter Plug-in for SQL Server 1
 - Storage disaster recovery (DR) for SnapCenter Plug-in for SQL Server 1
 - Failback from SnapCenter Plug-in for SQL Server secondary storage to primary storage 2

Configure Disaster recovery

Disaster recovery of SnapCenter Plug-in for SQL Server

When the SnapCenter Plug-in for SQL Server is down, switch to a different SQL host and recover the data by performing few steps.

What you will need

- The secondary host should have the same operating system, application, and host name as the primary host.
- Push the SnapCenter Plug-in for SQL Server to an alternative host using **Add host** or **Modify host** page.

[Manage hosts](#)

Steps

1. Select the host from the **Hosts** page to modify and install the SnapCenter Plug-in for SQL Server.
2. (Optional) Replace the SnapCenter Plug-in for SQL Server configuration files from disaster recovery (DR) backup to the new machine.
3. Import Windows and SQL schedules from the SnapCenter Plug-in for SQL Server folder from the DR backup.

For more information, see the [Disaster Recovery APIs](#) video.

Storage disaster recovery (DR) for SnapCenter Plug-in for SQL Server

You can recover the SnapCenter Plug-in for SQL Server storage by enabling the DR Mode for Storage in the **Global Settings** page.

What you will need

- Ensure that the plug-ins are in maintenance mode.
- Break the SnapMirror/SnapVault relationship. [Breaking SnapMirror relationships](#)
- Attach the LUN from secondary to the host machine with same drive letter.
- Ensure that all the disks are connected using the same drive letters that were used prior to DR.
- Restart MSSQL server service.
- Ensure that the SQL resources are back online.

About this task

Disaster recovery (DR) is not supported on VMDK and RDM configurations.

Steps

1. In the **Settings** page, navigate to **Settings > Global Settings > Disaster Recovery**.

2. Select **Enable Disaster Recovery**.
3. Click **Apply**.
4. Verify whether the DR job is enabled or not by clicking **Monitor > Jobs**.

After you finish

- If new databases are created after the failover, the databases will be in non-DR mode.

The new databases will continue to operate like they did before the failover.

- The new backups that were created in DR mode will be listed under SnapMirror or SnapVault (secondary) in the **Topology** page.

An "i" icon is displayed next to the new backups to indicate that these backups were created during DR mode.

- You can delete the SnapCenter Plug-in for SQL Server backups that were created during failover either by using the UI or the following cmdlet: `Remove-SmBackup`
- After failover, if you want some of the resources to be in non-DR mode, use the following cmdlet: `Remove-SmResourceDRMode`

For more information refer [SnapCenter Software Cmdlet Reference Guide](#).

- SnapCenter Server will manage the individual storage resources(SQL databases) that are in DR or non-DR mode but not the resource group with storage resources that are in DR mode or non-DR mode.

Failback from SnapCenter Plug-in for SQL Server secondary storage to primary storage

After the SnapCenter Plug-in for SQL Server primary storage is back online, you should failback to the primary storage.

What you will need

- Place the SnapCenter Plug-in for SQL Server in **Maintenance** mode from the **Managed Hosts** page.
- Disconnect the secondary storage from the host and connect from the primary storage.
- To failback to the primary storage, ensure that the relationship direction remains the same as it was before the failover by performing the reverse resync operation.

To retain the roles of primary and secondary storage after the reverse resync operation, perform the reverse resync operation once again.

For more information see [Reverse resynchronizing mirror relationships](#)

- Restart MSSQL server service.
- Ensure that the SQL resources are back online.

Steps

1. In the **Settings** page, navigate to **Settings > Global Settings > Disaster Recovery**.

2. Unselect **Enable Disaster Recovery**.
3. Click **Apply**.
4. Verify whether the DR job is enabled or not by clicking **Monitor > Jobs**.

After you finish

- You can delete the SnapCenter Plug-in for SQL Server backups that were created during failover either by using the UI or the following cmdlet: `Remove-SmDRFailoverBackups`

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.