# EE-559 - Deep learning

# 8.1. Looking at parameters

François Fleuret
https://fleuret.org/ee559/
Mon Feb 18 13:36:00 UTC 2019





Understanding a network's behavior

Understanding what is happening in a deep architectures after training is complex and the tools we have at our disposal are limited.

In the case of convolutional feed-forward networks, we can look at

- the network's parameters, filters as images,
- internal activations on a single sample as images,
- distributions of activations on a population of samples,
- derivatives of the response(s) wrt the input,
- maximum-response synthetic samples,
- adversarial samples.

François Fleuret

EE-559 – Deep learning / 8.1. Looking at parameters

2 / 9

Given a one-hidden layer fully connected network  $\mathbb{R}^2 o \mathbb{R}^2$ 

```
nb_hidden = 20
model = nn.Sequential(
    nn.Linear(2, nb_hidden),
    nn.ReLU(),
    nn.Linear(nb_hidden, 2)
)
```

we can visit the parameters (w, b) of each hidden units with


```
for k in range(model[0].weight.size(0)):
    w = model[0].weight[k]
    b = model[0].bias[k]
```

and draw for each the line

```
\{x: w \cdot x + b = 0\}.
```


During training, these separations get organized so that their combination partitions properly the signal space.

François Fleuret



François Fleuret

EE-559 – Deep learning / 8.1. Looking at parameters



3 / 9

### Convnet filters

François Fleuret

EE-559 – Deep learning / 8.1. Looking at parameters

4 / 9

A similar analysis is complicated to conduct with real-life networks given the high dimension of the signal.

The simplest approach for convnets consists of looking at the filters as images.

While it is quite reasonable in the first layer, since the filters are indeed consistent with the image input, it is far less so in the subsequent layers.

LeNet's first convolutional layer (1  $\rightarrow$  32), all filters

#### 媥娺悜襧敓椺剓豖缿鄵馸甋銊膌眗鄸詽獔閵齖笭缿覢輺鄵傶鴔磆扟濥琞籣

François Fleuret

EE-559 - Deep learning / 8.1. Looking at parameters

6 / 9

LeNet's second convolutional layer (32  $\rightarrow$  64), first 32 filters out of 64

François Fleuret

### AlexNet's first convolutional layer (3 $\rightarrow$ 64), first 20 filters out of 64



or as RGB images



François Fleuret

EE-559 - Deep learning / 8.1. Looking at parameters

8 / 9

AlexNet's second convolutional layer (64  $\rightarrow$  192). First 15 channels (out of 64) of the first 20 filters (out of 192).

